



DNS Fundamentals – What is DNS?

By: Inlighn Tech

Overview

The Domain Name System (DNS) is often called the "phonebook of the internet." It's a critical system that translates human-readable domain names (like "google.com") into machine-readable IP addresses (like "142.250.190.78"). Without DNS, we'd have to memorize numerical IP addresses to access websites, servers, or any online resource—a daunting task given the billions of devices connected to the internet. In cybersecurity, understanding DNS is essential because it's a key component of network communication and a common target for attacks (e.g., DNS spoofing) or reconnaissance (e.g., subdomain enumeration).

How DNS Works

DNS operates as a distributed, hierarchical database that resolves names to IP addresses through a series of steps called the **DNS resolution process**. Here's a breakdown:

1. User Request:

- When you type "example.com" into your browser, your device needs the IP address to connect to the server hosting that site. This starts the DNS lookup.

2. Local Resolver:

- Your device first checks its local DNS cache (stored from previous lookups). If the IP isn't cached, it queries a **recursive resolver** (usually provided by your ISP or a public service like Google's 8.8.8.8).

3. Root Name Servers:

- The resolver contacts one of the 13 global **root name servers** (managed by organizations like ICANN). These servers don't know the exact IP but direct the query to the appropriate **Top-Level Domain (TLD)** server (e.g., ".com", ".org").

4. TLD Name Servers:

- The TLD server (e.g., for ".com") knows which **authoritative name server** handles "example.com" and points the resolver there.

5. Authoritative Name Server:

- This server, managed by the domain owner or their DNS provider, holds the actual DNS records (e.g., A record for the IP address) and returns the IP (e.g., "93.184.216.34") to the resolver.

6. Response:

- The resolver sends the IP back to your device, which then connects to the server. The IP is cached locally for faster future lookups.

This process typically happens in milliseconds, making the internet seamless for users.

Key DNS Components

- **Domain Names:** Hierarchical labels (e.g., "sub.example.com") where:
 - **com:** Top-Level Domain (TLD).
 - **example:** Second-level domain.
 - **sub:** Subdomain (optional).
- **DNS Records:** Data stored in the authoritative server, including:
 - **A Record:** Maps a domain to an IPv4 address (e.g., "example.com" → "93.184.216.34").
 - **AAAA Record:** Maps to an IPv6 address.

- **CNAME:** Aliases one domain to another (e.g., "www.example.com" → "example.com").
- **MX Record:** Points to mail servers (e.g., "mail.example.com").
- **NS Record:** Specifies the authoritative name servers for the domain.
- **Resolver:** The client-side software or server that initiates and completes the lookup.
- **Name Servers:** Servers that store and respond with DNS records (root, TLD, authoritative).

DNS in Cybersecurity

DNS is a double-edged sword in cybersecurity:

- **Reconnaissance:** Tools like your **Subdomain Enumeration Tool** exploit DNS to discover subdomains (e.g., "admin.example.com"), revealing potential attack surfaces.
- **Attacks:**
 - **DNS Spoofing:** Attackers forge DNS responses to redirect traffic (e.g., to phishing sites).
 - **DNS Hijacking:** Compromising a DNS server to alter records.
 - **DDoS Attacks:** Overwhelming DNS servers to disrupt services.
- **Defense:** Understanding DNS helps secure networks (e.g., monitoring DNS traffic for anomalies).

