

Revision date: 30 Aug 2024 Version: 4 Print date: 12 Mar 2026

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

AquaScreen® FastExtract Kit, Binding Buffer

Article No.:

32-1010, 32-1050

UFI:

GK19-VTAD-1695-W0C8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

The product is intended for research, analysis and scientific education.

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Minerva Biolabs GmbH

Schkopauer Ring 13

12681 Berlin

Germany

Telephone: +49 30 2000437 0

E-mail: ehs@minerva-biolabs.com

Website: www.minerva-biolabs.com

1.4. Emergency telephone number

Vergiftungs-Informations-Zentrale Freiburg, 24h: +49 761 19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	On basis of test data.
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	Calculation method.
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	Calculation method.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark

Signal word: Danger

Hazard statements for physical hazards

H225	Highly flammable liquid and vapour.
------	-------------------------------------

Hazard statements for health hazards

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Revision date: 30 Aug 2024 Version: 4 Print date: 12 Mar 2026

Supplemental hazard information: none

Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary statements Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements Storage

P405	Store locked up.
------	------------------

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 67-63-0 EC No.: 200-661-7 Index No.: 603-117-00-0 REACH No.: 01-2119457558-25-XXXX	propan-2-ol Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336)  Danger Acute Toxicity Estimate ATE (oral) 5,050 mg/kg ATE (dermal) 12,800 mg/kg ATE (inhalation, vapour) 30 mg/L	60 – ≤ 100 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing immediately. Do not leave affected person unattended. If unconscious but breathing normally, place in recovery position and seek medical advice.

Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician. Get medical advice/attention if you feel unwell.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

After eye contact:

Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention. Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion:

Rinse mouth. Let water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell.

Self-protection of the first aider:

Use personal protection equipment.

4.2. Most important symptoms and effects, both acute and delayed

Serious eye damage/eye irritation, Dizziness, Dizziness

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet, alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂)

Revision date: 30 Aug 2024 Version: 4 Print date: 12 Mar 2026

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours can form explosive mixtures with air.

Hazardous combustion products:

In case of fire: Gases/vapours, toxic

5.3. Advice for firefighters

Fight fire with normal precautions from a reasonable distance. Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety. Use personal protective equipment as required. Avoid contact with skin, eyes and clothes.

Protective equipment:

Wear protective gloves/protective clothing and eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Water (with cleaning agent)

6.4. Reference to other sections

Safe handling: see section 7, Personal protection equipment: see section 8, Disposal: see section 13

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8). Wash hands before breaks and after work. Keep away from: Food and feedingstuffs. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Fire prevent measures:

Take precautionary measures against static discharge. Keep away from sources of ignition - No smoking. Vapours can form explosive mixtures with air.

Advices on general occupational hygiene

Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke. Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Keep container tightly closed in a cool, well-ventilated place. Recommended storage temperature: at room temperature. Protect from sunlight.

Hints on storage assembly:

Do not store together with: Oxidising substances, Food and feedingstuffs

Storage class (TRGS 510, Germany): 3 – Flammable liquids

Revision date: 30 Aug 2024 Version: 4 Print date: 12 Mar 2026

Further information on storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
TRGS 900 (DE)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	① 200 ppm (500 mg/m³) ② 400 ppm (1,000 mg/m³) ⑤ DFG, Y

8.1.2. Biological limit values

Limit value type (country of origin)	Substance name	Limit value	① Parameter ② Test material ③ Time of sampling: ④ Remark
TRGS 903 (DE) from 1 Nov 2012	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	25 mg/L	① Aceton ② Blut ③ Expositionsende bzw. Schichtende
TRGS 903 (DE) from 1 Nov 2012	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	25 mg/L	① Aceton ② Urin ③ Expositionsende bzw. Schichtende

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m³	① DNEL worker ② Long-term – inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	880 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects

Substance name	PNEC Value	① PNEC type
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.96 mg/L	① PNEC aquatic, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	① PNEC sewage treatment plant
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC soil, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC soil, marine water

Revision date: 30 Aug 2024 Version: 4 Print date: 12 Mar 2026

8.2. Exposure controls

8.2.1. Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

8.2.2. Personal protection equipment



Eye/face protection:

Eye glasses with side protection (EN 166).

Skin protection:

Tested protective gloves must be worn (EN ISO 374). Take recovery periods for skin regeneration. Breakthrough times and swelling properties of the material must be taken into consideration. Suitable material: Butyl caoutchouc (butyl rubber). Thickness of the glove material: > 0,5 mm. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Respiratory protection:

Usually no personal respiratory protection necessary. In case of inadequate ventilation wear respiratory protection. Filtering device with filter or ventilator filtering device of type: AX

Other protection measures:

Wash hands before breaks and after work.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Form: Liquid

Colour: colourless

Odour: Alcohol

flammability: Yes

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	≈ 7	20 °C	
Melting point	No data available		
Freezing point	No data available		
Initial boiling point and boiling range	82 °C		
Flash point	12 °C		
Evaporation rate	No data available		
Auto-ignition temperature	425 °C		
Upper/lower flammability or explosive limits	2 – 13.4 Vol-%		
Vapour pressure	43 hPa		
Vapour density	No data available		
Density	0.87 g/cm³	20 °C	
Bulk density	not applicable		
Water solubility	completely miscible		
Dynamic viscosity	No data available		
Kinematic viscosity	2.793 mm²/s		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

Revision date: 30 Aug 2024 Version: 4 Print date: 12 Mar 2026

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Further information on proper storage: see section 7.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products. Gases/vapours, toxic

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
LD₅₀ oral: 5,050mg/kg (Rat)
LD₅₀ dermal: 12,800mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (vapour): 30mg/L 4h (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No data available

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
LC₅₀: 9,640mg/L 4d (fish, Pimephales promelas)
EC₅₀: >10,000mg/L 1d (crustaceans, Daphnia magna) OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

12.2. Persistence and degradability

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
Biodegradation: Yes, rapidly

Revision date: 30 Aug 2024 Version: 4 Print date: 12 Mar 2026

12.3. Bioaccumulative potential

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Log K_{OW}: 0.196

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1219	UN 1219	UN 1219	UN 1219
14.2. UN proper shipping name			
ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es)			
 3	 3	 3	 3
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Special Provisions: 601 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E2 Hazard identification number (Kemler No.): 33 Classification code: F1 Tunnel restriction code: (D/E)	Special Provisions: 601 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E2 Classification code: F1	Special Provisions: - Limited quantity (LQ): 1 L Excepted Quantities (EQ): E2 EmS-No.: F-E, S-D	Special Provisions: A180 Limited quantity (LQ): Y341 Excepted Quantities (EQ): E2

14.7. Maritime transport in bulk according to IMO instruments

No data available

Revision date: 30 Aug 2024 Version: 4 Print date: 12 Mar 2026

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Other regulations (EU):

1907/2006 REACH, 1272/2008 CLP GHS, 98/24/EC

15.1.2. National regulations

[DE] National regulations

Restrictions of occupation

22 JArbSchG., 4 MuSchRiV., 5 MuSchRiV., Betriebssicherheitsverordnung (BetrSichV)

Betriebssicherheitsverordnung (BetrSichV)

leichtentzündlich

Water hazard class

WGK:

nwg - non-hazardous to water

Berufsgenossenschaftliche Vorschriften (DGUV-Vorschriften)

Berufsgenossenschaftliche Vorschriften (DGUV-Vorschriften)

Other regulations, restrictions and prohibition regulations

Hazardous Substances Ordinance (GefStoffV)

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DIN	German Institute for Standardization / German Industrial Standard
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
ECHA	European Chemicals Agency
EN	European Standard
ES	Exposure scenario
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
ISO	International Standards Organisation
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
OECD	Organisation for Economic Cooperation and Development
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Revision date: 30 Aug 2024 Version: 4 Print date: 12 Mar 2026

16.3. Key literature references and sources for data

TRGS 510, TRGS 525, TRGS 900, Safety data sheets for the ingredients, 1907/2006 REACH, 1272/2008 CLP GHS

Substance name	Type	source of supply
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	LC ₅₀ ; EC ₅₀	Source: European Chemicals Agency, http://echa.europa.eu/

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	On basis of test data.
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	Calculation method.
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	Calculation method.

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

16.6. Training advice

No data available

16.7. Additional information

This data sheet was prepared in accordance with EU Regulation (EC) No. 1907/2006 (REACH) and, where applicable, US Regulation 29 CFR 1910.1200, Appendix D.

The information is based on the level of knowledge and experience on the date of issue, it do not have the importance of assured properties. The information may not be changed or transferred to other products. Reproduction in the unchanged state is permitted.