

Constraint Satisfaction Problems (CSPs)

CS 221 Section – 10/31/19

Chuma Kabaghe

Will Deaderick

Agenda

- CSP Problem Modeling
- N-ary Constraints
- Exam Problem Solving

Factor Graph and CSP Applications

- Scheduling problems: event scheduling, resource and assembly scheduling
- Inferring relations from data
- Puzzles: sudoku, crosswords
- Satisfiability problems
- Map and graph coloring
- Object tracking
- Decoding noisy signals (images, messages etc.)


Agenda

- CSP Problem Modeling
- N-ary Constraints
- Exam Problem Solving

Event Scheduling

Setup:


- Have E events and T time slots
- Each event e must be put in **exactly one** time slot
- Each time slot t can have **at most one** event
- Event e only allowed at time slot t if (e, t) in A



Event Scheduling

Setup:


- Have E events and T time slots
- Each event e must be put in **exactly one** time slot
- Each time slot t can have **at most one** event
- Event e only allowed at time slot t if (e, t) in A



Event Scheduling

Formulation 1a:


- Variables for each event e , $X_e \in \{1, \dots, T\}$



Event Scheduling

Formulation 1a:


- Variables for each event e , $X_e \in \{1, \dots, T\}$
- Constraints (only one event per time slot): for each pair of events $e \neq e'$, enforce $[X_e \neq X_{e'}]$



Event Scheduling

Formulation 1a:


- Variables for each event e , $X_e \in \{1, \dots, T\}$
- Constraints (only one event per time slot): for each pair of events $e \neq e'$, enforce $[X_e \neq X_{e'}]$
- Constraints (only schedule allowed times): for each event e , enforce $[(e, X_e) \in A]$



Event Scheduling

Formulation 1a:


- Variables for each event e , $X_e \in \{1, \dots, T\}$
- Constraints (only one event per time slot): for each pair of events $e \neq e'$, enforce $[X_e \neq X_{e'}]$
- Constraints (only schedule allowed times): for each event e , enforce $[(e, X_e) \in A]$



Event Scheduling

Formulation 1a:


- Variables for each event e , $X_e \in \{1, \dots, T\}$
- Constraints (only one event per time slot): for each pair of events $e \neq e'$, enforce $[X_e \neq X_{e'}]$
- Constraints (only schedule allowed times): for each event e , enforce $[(e, X_e) \in A]$



Event Scheduling

Formulation 1a:


- Variables for each event e , $X_e \in \{1, \dots, T\}$
- Constraints (only one event per time slot): for each pair of events $e \neq e'$, enforce $[X_e \neq X_{e'}]$
- Constraints (only schedule allowed times): for each event e , enforce $[(e, X_e) \in A]$



Event Scheduling

Formulation 1a:


- Variables for each event e , $X_e \in \{1, \dots, T\}$
- Constraints (only one event per time slot): for each pair of events $e \neq e'$, enforce $[X_e \neq X_{e'}]$
- Constraints (only schedule allowed times): for each event e , enforce $[(e, X_e) \in A]$



Event Scheduling

Formulation 1a:


- Variables for each event e , $X_e \in \{1, \dots, T\}$
- Constraints (only one event per time slot): for each pair of events $e \neq e'$, enforce $[X_e \neq X_{e'}]$
- Constraints (only schedule allowed times): for each event e , enforce $[(e, X_e) \in A]$



Event Scheduling

Formulation 1a:


- Variables for each event e , $X_e \in \{1, \dots, T\}$
- Constraints (only one event per time slot): for each pair of events $e \neq e'$, enforce $[X_e \neq X_{e'}]$
- Constraints (only schedule allowed times): for each event e , enforce $[(e, X_e) \in A]$



Event Scheduling

Formulation 1a:


- Variables for each event e , $X_e \in \{1, \dots, T\}$
- Constraints (only one event per time slot): for each pair of even $e \neq e'$, enforce $[X_e \neq X_{e'}]$
- Constraints (only schedule allowed times): for each event e , enforce $[(e, X_e) \in A]$



Event Scheduling

Formulation 1b:

- Variables for each event e , X_1, \dots, X_E




Event Scheduling

Formulation 1b:

- Variables for each event e , X_1, \dots, X_E

$$\text{Domain}_i = \{t : (i, t) \in A\}$$




Event Scheduling

Formulation 1b:

- Variables for each event e , X_1, \dots, X_E

$$\text{Domain}_i = \{t : (i, t) \in A\}$$


- Constraints (only one event per time slot): for each pair of events $e \neq e'$, enforce $[X_e \neq X_{e'}]$



Event Scheduling

Formulation 2a:


- Variables for each time slot t : $Y_t \in \{1, \dots, E\} \cup \{\emptyset\}$



Event Scheduling

Formulation 2a:


- Variables for each time slot t : $Y_t \in \{1, \dots, E\} \cup \{\emptyset\}$
- Constraints (each event is scheduled exactly once): for each event e , enforce $[Y_t = e \text{ for exactly one } t]$



Event Scheduling

Formulation 2a:


- Variables for each time slot t : $Y_t \in \{1, \dots, E\} \cup \{\emptyset\}$
- Constraints (each event is scheduled exactly once): for each event e , enforce $[Y_t = e \text{ for exactly one } t]$
- Constraints (only schedule allowed times): for each time slot t , enforce $[Y_t = \emptyset \text{ or } (Y_t, t) \in A]$



Event Scheduling

Formulation 2a:


- Variables for each time slot t : $Y_t \in \{1, \dots, E\} \cup \{\emptyset\}$
- Constraints (each event is scheduled exactly once): for each event e , enforce $[Y_t = e \text{ for exactly one } t]$
- Constraints (only schedule allowed times): for each time slot t , enforce $[Y_t = \emptyset \text{ or } (Y_t, t) \in A]$



Event Scheduling

Formulation 2b:

- Variables for each time slot t : Y_1, \dots, Y_T




Event Scheduling

Formulation 2b:

- Variables for each time slot t : Y_1, \dots, Y_T

$$\text{Domain}_i = \{e : (e, i) \in A\} \cup \{\emptyset\}$$




Event Scheduling

Formulation 2b:

- Variables for each time slot t : Y_1, \dots, Y_T

$$\text{Domain}_i = \{e : (e, i) \in A\} \cup \{\emptyset\}$$

- Constraints (each event is scheduled exactly once): for each event e , enforce $[Y_t = e \text{ for exactly one } t]$



Event Scheduling

Formulation 1a:

- Variables for each event e , $X_e \in \{1, \dots, T\}$
- Constraints (only one event per time slot): for each pair of events $e \neq e'$, enforce $[X_e \neq X_{e'}]$
- Constraints (only schedule allowed times): for each event e , enforce $[(e, X_e) \in A]$

E variables with domain size T ,
and $O(E^2)$ binary constraints.

T variables with domain size $E+1$
 $O(T^2)$ variables with domain size
2 and $O(T^2)$ binary constraints.

Formulation 2a:


- Variables for each time slot t : $Y_t \in \{1, \dots, E\} \cup \{\emptyset\}$
- Constraints (each event is scheduled exactly once): for each event e , enforce $[Y_t = e \text{ for exactly one } t]$
- Constraints (only schedule allowed times): for each time slot t , enforce $[Y_t = \emptyset \text{ or } (Y_t, t) \in A]$

Agenda

- CSP Problem Modeling
- **N-ary Constraints**
- Exam Problem Solving

N-ary Constraints

- From event scheduling:
 - Constraints (each event is scheduled exactly once): for each event e , enforce
$$[Y_t = e \text{ for exactly one } t]$$



N-ary Constraints

Key Idea: Auxiliary Variables

Auxiliary Variables hold intermediate computation.

Represent “for exactly one” as counting the number of values equal to e and constraining that count to be equal to one.

N-ary Constraints

Key Idea: Auxiliary Variables

Auxiliary Variables hold intermediate computation.

Represent “for exactly one” as counting the number of values equal to e and constraining that count to be equal to one.

Factors:

Initialization: $[A_0 = 0]$

$e = 1$

i	0	1	2	3	4
Y_i		3	1	2	1
A_i	0				

N-ary Constraints

Key Idea: Auxiliary Variables

Auxiliary Variables hold intermediate computation.

Represent “for exactly one” as counting the number of values equal to e and constraining that count to be equal to one.

Factors:

Initialization: $[A_0 = 0]$

Processing: $[A_i = A_{i-1} + 1[Y_i = e]]$

$e = 1$

i	0	1	2	3	4
Y_i		3	1	2	1
A_i	0				

N-ary Constraints

Key Idea: Auxiliary Variables

Auxiliary Variables hold intermediate computation.

Represent “for exactly one” as counting the number of values equal to e and constraining that count to be equal to one.

Factors:

Initialization: $[A_0 = 0]$

Processing: $[A_i = \min(A_{i-1} + 1[Y_i = e], 2)]$

$e = 1$

i	0	1	2	3	4
Y_i		3	1	2	1
A_i	0				

N-ary Constraints

Key Idea: Auxiliary Variables

Auxiliary Variables hold intermediate computation.

Represent “for exactly one” as counting the number of values equal to e and constraining that count to be equal to one.

Factors:

Initialization: $[A_0 = 0]$

Processing: $[A_i = \min(A_{i-1} + 1[Y_i = e], 2)]$

$e = 1$

i	0	1	2	3	4
Y_i		3	1	2	1
A_i	0	0			

N-ary Constraints

Key Idea: Auxiliary Variables

Auxiliary Variables hold intermediate computation.

Represent “for exactly one” as counting the number of values equal to e and constraining that count to be equal to one.

Factors:

Initialization: $[A_0 = 0]$

Processing: $[A_i = \min(A_{i-1} + 1[Y_i = e], 2)]$

$e = 1$

i	0	1	2	3	4
Y_i		3	1	2	1
A_i	0	0	1		

N-ary Constraints

Key Idea: Auxiliary Variables

Auxiliary Variables hold intermediate computation.

Represent “for exactly one” as counting the number of values equal to e and constraining that count to be equal to one.

Factors:

Initialization: $[A_0 = 0]$

Processing: $[A_i = \min(A_{i-1} + 1[Y_i = e], 2)]$

$e = 1$

i	0	1	2	3	4
Y_i		3	1	2	1
A_i	0	0	1	1	

N-ary Constraints

Key Idea: Auxiliary Variables

Auxiliary Variables hold intermediate computation.

Represent “for exactly one” as counting the number of values equal to e and constraining that count to be equal to one.

Factors:

Initialization: $[A_0 = 0]$

Processing: $[A_i = \min(A_{i-1} + 1[Y_i = e], 2)]$

$e = 1$

i	0	1	2	3	4
Y_i		3	1	2	1
A_i	0	0	1	1	2

N-ary Constraints

Key Idea: Auxiliary Variables

Auxiliary Variables hold intermediate computation.

Represent “for exactly one” as counting the number of values equal to e and constraining that count to be equal to one.

Factors:

Initialization: $[A_0 = 0]$

Processing: $[A_i = \min(A_{i-1} + 1[Y_i = e], 2)]$

Final Output: $1[A_T = 1]$

$e = 1$

i	0	1	2	3	4
Y_i		3	1	2	1
A_i	0	0	1	1	2

N-ary Constraints

Key Idea: Auxiliary Variables

Auxiliary Variables hold intermediate computation.

Represent “for exactly one” as counting the number of values equal to e and constraining that count to be equal to one.

Factors:

Initialization: $[A_0 = 0]$

Processing: $[A_i = \min(A_{i-1} + 1[Y_i = e], 2)]$

Final Output: $1[A_T = 1]$

$e = 1$

i	0	1	2	3	4
Y_i		3	1	2	1
A_i	0	0	1	1	2


Still have factors with three variables...

N-ary Constraints

Key idea: Combine A_{i-1} and A_i into one variable B_i

N-ary Constraints

Key idea: Combine A_{i-1} and A_i into one variable B_i




$e = 1$

i	0	1	2	3	4
Y_i		3	1	2	1
A_i	0	0	1	1	2

N-ary Constraints

Key idea: Combine A_{i-1} and A_i into one variable B_i



Factors:

Initialization: $[B_1[0] = 0]$


Processing: $[B_i[1] = \min(B_i[0] + 1[Y_i = e], 2)]$

Final Output: $1[B_T[1] = 1]$

Consistency: $[B_{i-1}[1] = B_i[0]]$

N-ary Constraints

Key idea: Combine A_{i-1} and A_i into one variable B_i



Factors:

Initialization: $[B_1[0] = 0]$


Processing: $[B_i[1] = \min(B_i[0] + 1[Y_i = e], 2)]$

Final Output: $1[B_T[1] = 1]$


Consistency: $[B_{i-1}[1] = B_i[0]]$

N-ary Constraints

$[Y_t = e \text{ for exactly one } t]$



44



Agenda

- CSP Problem Modeling
- N-ary Constraints
- Exam Problem Solving