


Title			
Size	Number		Revision
A2			
Date:	2015/5/15	Sheet of	
File:	C:\Users\1\SchDoc	Drawn By:	



Comment	Description	Designator	Footprint	LibRef	Quantity
Motor	Motor, General Kind	B1	偏脚接线端子 -	Motor	1
BOOT	Header, 3-Pin, Dual	BOOT1	HDR2X3	Header 3X2	1
Cap Pol1	Polarized Capacitor (Radial)	C1	470uf	Cap Pol1	1
	Capacitor	C2, C3, C4, C5, C9, C10	0805C	Cap	6
Cap	Capacitor	C6, C13, C14, C15, C16, C17, C18, C19, C25, C26, C27, C28, C29, C32, C33, C34, C40, C44, C45, C46, C47, C48, C49, C50,	0805C	Cap	26
Cap Pol1	Polarized Capacitor (Radial)	C7	10uf	Cap Pol1	1
Cap	Capacitor	C8, C35	C-0805	Cap	2
100		C11, C20	10uf	贴片铝电容	2
104		C12	0805c	贴片无极性电容	1
Cap Pol1	Polarized Capacitor (Radial)	C21, C22, C23, C24	0805R	Cap Pol1	4
Cap Pol1	Polarized Capacitor (Radial)	C30, C38	0805C	Cap Pol1	2
Cap Pol1	Polarized Capacitor (Radial)	C37	220uf/420v - duplicate	Cap Pol1	1
Cap Pol1	Polarized Capacitor (Radial)	C52	470uf /80v	Cap Pol1	1
LED2	Typical RED, GREEN, YELLOW, AMBER GaAs LED	D2, D4	0805D	LED2	2
1N5824		D3	SMA	二极管	1
ss14	1 Amp General Purpose Rectifier	D5, D6	DO-41	Diode 1N4001	2
BAV99	Silicon Switching Diode Array for High-Speed Switching	D7, D11	shuangxiangwenyagua n	BAV99	2
1N4002	High Conductance Fast Diode	D8, D9, D10, D12, D13, D14	DO-41	Diode 1N4148	6
Fuse 2A	Fuse	F1	1812	Fuse 2	1
Fuse 1	Fuse	F2	PCBComponent_1	Fuse 1	1
固定孔		gudingkong1, gudingkong2, gudingkong3, gudingkong4, gudingkong5	gudingkong	固定孔	5
303		H1	12*12diangan	贴片电感	1
DB9	Receptacle Assembly, 9 Position, Right Angle	J1	DSUB1.385-2H9	D Connector 9	1
微动开关		K1, K2, K3, K4, K5, K6	SW-SMT	微动开关	6
电源接头 15v	电源, 2-Pin	P1	偏脚接线端子 -	Header 2	1
隔离电源	Header, 4-Pin	P2	B0512s	Header 4	1
S110	Header, 8-Pin	P3	HDR1X8	Header 8	1
LM1117		P4	LM1117	LM1117	1
Header 4X2A	Header, 4-Pin, Dual	P5, P6	HDR2X4_CEN	Header 4X2A	2
HALL	Header, 4-Pin	P7	HALL	Header 4	1
Header 3	Header, 3-Pin	P8, P17	三脚接线端子	Header 3	2
Header 2	Header, 2-Pin	P9, P10, P11, P14,	HDR1X2	Header 2	5
电流测试点	Header, 2-Pin	P12	HDR1X2	Header 2	1
电压测试点	Header, 2-Pin	P13	HDR1X2	Header 2	1
Header 4	Header, 4-Pin	P15	整流桥	Header 4	1
NMOS-2	N-Channel Power MOSFET	Q1, Q2, Q3, Q4	TO-220 + 散热片	NMOS-2	4
Res1	Resistor	R1, R2, R7, R11	AXIAL-0.5	Res1	4
Res2	Resistor	R3, R17, R21, R22, R23, R24, R25, R26, R27, R28, R29, R30, R33, R35, R37, R38, R40, R42, R43, R44, R45, R46, R47, R48, R50, R51	0805R	Res2	26
Res1	Resistor	R4, R6, R9, R14, R16	0805R	Res1	5
RESE		R5, R18, R41, R49	VR5	RESE	4
Z2R		R19, R20	0805R	R	2
SW-SPST	Single-Pole, Single-Throw Switch	S1	三脚开关	SW-SPST	1
SW-PB	Switch	S2	SW-SMT	SW-PB	1
ST-LINK		ST-LINK	IDC-10	ST-LINK	1
STM32F103RBT6		U1	LQFP64 - duplicate - duplicate	STM32F103RBT6	1
LM2596		U2	LM2596	LM2596	1
MAX3232CWE	+5V Powered RS-232 Driver/Receiver	U3	NSO16_N	MAX232CWE	1
ps8701		U4, U7	SOP-5	ps8701	2
Z104		U5, U10	SO8_M	Z104	2
lm358		U6, U12, U13, U14, U15	SO8_M	lm358	5
LM393		U8	751-02_N	LM393	1
32.768KHz	Crystal Oscillator	Y1	XTAL2	XTAL	1
8MHz	Crystal Oscillator	Y2	XTAL_US	XTAL	1
单接头		电流接头, 电流接头 2	gudingkong01	单接头	2