



## Texturing

Cylinder



# Textured Cylinder


---






# Texture Atlas

Image space





Texture space





# Texture Coordinates





# DevIL

---

- Open an image file and define origin of image space in DevIL

```
// setup - done once
ilInit();
ilEnable(IL_ORIGIN_SET);
ilOriginFunc(IL_ORIGIN_LOWER_LEFT);

// for each image ...
ilGenImages(1, ima); // unsigned int ima[...]
ilBindImage(ima[0]);
ilLoadImage((ILstring)filename); // char *filename
```



# DevIL

---

- Convert to RGBA

```
ilConvertImage(IL_RGBA, IL_UNSIGNED_BYTE);
```



# DevIL

---

- Get the required info

```
int width = ilGetInteger(IL_IMAGE_WIDTH);
```

```
int height = ilGetInteger(IL_IMAGE_HEIGHT);
```

```
unsigned char *imageData = ilGetData();
```



# Texture Creation in OpenGL

---

// create a texture slot

```
glGenTextures(1, &texID);
```

// bind the slot

```
glBindTexture(GL_TEXTURE_2D, texID);
```

// define texture parameters

```
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_S, GL_REPEAT);
```

```
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_T, GL_REPEAT);
```

```
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MAG_FILTER, GL_LINEAR);
```

```
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MIN_FILTER, GL_LINEAR);
```

// send texture data to OpenGL

```
glTexImage2D(GL_TEXTURE_2D, 0, GL_RGBA, tw, th, 0,  
             GL_RGBA, GL_UNSIGNED_BYTE, texData);
```





# Texture Setup

- Code to create a texture from a file (DevIL + OpenGL):

```
unsigned int t, tw, th;
unsigned char *texData;
ilGenImages(1, &t);
ilBindImage(t);
ilLoadImage((ILstring)"Oil_Drum001h.jpg");
tw = ilGetInteger(IL_IMAGE_WIDTH);
th = ilGetInteger(IL_IMAGE_HEIGHT);
ilConvertImage(IL_RGBA, IL_UNSIGNED_BYTE);
texData = ilGetData();

glGenTextures(1, &texID); // unsigned int texID - variavel global;

glBindTexture(GL_TEXTURE_2D, texID);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_S, GL_REPEAT);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_T, GL_REPEAT);

glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MAG_FILTER, GL_LINEAR);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MIN_FILTER, GL_LINEAR);

glTexImage2D(GL_TEXTURE_2D, 0, GL_RGBA, tw, th, 0,
             GL_RGBA, GL_UNSIGNED_BYTE, texData);
```



# Textures

- Activate 2D texturing (init):

```
glEnable(GL_TEXTURE_2D);
```

} Setup

- 
- Before drawing:

```
glBindTexture(GL_TEXTURE_2D, texID);
```

- Drawing (VBOs or immediate mode)

- After drawing:

```
glBindTexture(GL_TEXTURE_2D, 0);
```

} Render



# Tex Coords in immediate mode

---

- For each vertex define its texture coordinate:

```
glBegin(GL_TRIANGLES);  
    glTexCoord2f(s1, t1);  
    glVertex3f(x1,y1,z1);  
    glTexCoord2f(s2, t2);  
    glVertex3f( x2,y2,z2);  
    ...  
glEnd();
```



## Textures w/ VBOS - Setup

---

- Activate arrays:

```
glEnableClientState(GL_VERTEX_ARRAY);  
glEnableClientState(GL_NORMAL_ARRAY);  
glEnableClientState(GL_TEXTURE_COORD_ARRAY);
```



# Textures w/ VBOS - Setup

- Add an array with texture coordinates:
  - Two components per vertex
  - Create an extra VBO;

```
unsigned int vertices, normals, texCoords;
float * v,n,t;
int count; // store the number of vertices
...
glGenBuffers(1, &vertices);
glBindBuffer(GL_ARRAY_BUFFER, vertices);
glBufferData(GL_ARRAY_BUFFER, sizeof(float) * 3 * count, v, GL_STATIC_DRAW);

glGenBuffers(1, &normals);
glBindBuffer(GL_ARRAY_BUFFER, normals);
glBufferData(GL_ARRAY_BUFFER, sizeof(float) * 3 * count, n, GL_STATIC_DRAW);

glGenBuffers(1, &texCoords);
glBindBuffer(GL_ARRAY_BUFFER, texCoords);
glBufferData(GL_ARRAY_BUFFER, sizeof(float) * 2 * count, t, GL_STATIC_DRAW);
```



# Textures w/ VBOS - Render

---

- Semantics:

```
glBindBuffer(GL_ARRAY_BUFFER, vertices);  
glVertexAttribPointer(3, GL_FLOAT, 0, 0);
```

```
glBindBuffer(GL_ARRAY_BUFFER, normals);  
glNormalPointer(GL_FLOAT, 0, 0);
```

```
glBindBuffer(GL_ARRAY_BUFFER, texCoords);  
glTexCoordPointer(2, GL_FLOAT, 0, 0);
```

- Texture bind and call `glDraw*`



# Assignment

---

- Compute the texture coordinates for the cylinder and floor and apply the given textures:
  - `drawFloor`: add texture coordinates in immediate mode
  - `prepareCylinder`: add texture coordinates using VBOs
  - `drawCylinder`: add texture coordinates buffer and define its semantic
  - `renderScene`: bind textures