

# SEMANTIC KNOWLEDGE CONSTRUCTION FROM ANNOTATED IMAGE COLLECTIONS

Armin Benitez and F. Chi-Hang

Department of Electric Engineering, Columbia University  
{ansfchange}@columbia.edu

New York, NY 10027

## ABSTRACT

This paper presents new methods for extracting semantic knowledge from collections of annotated images. The method includes novel automatic techniques for extracting semantic concepts, disambiguating the sense of annotations using the lexical database WordNet, and images and their annotations and discovering relations among the detected concepts based on WordNet. Another contribution of this paper is the evaluation technique for visual feature descriptors for extraction clustering the extracted semantic concepts. The results show the potential of integrating the analysis of annotations for improving the performance of the word-sense disambiguation process. In particular, the accuracy is improved by 15% with respect to the baseline system for

the proposed automatic acting on the both the semantic Net. several and data Experiments on images and word-sense improved the nature images.

organism for the word plant Word-sense disambiguation (WSD) process finding the correct sense of word with the document, which is a long-standing problem in Natural Language Processing. Although in English words are only one sense (80%) most words in documents have more than one sense (80%) [12]. The principles governing most word-sense disambiguation techniques (that are by word are semantically close related) (2) the sense of word often the same with document [13]. Literature there are unsupervised [9] [13] and supervised [12] approaches that use WordNet as the electronic word-sense lexicon. WordNet organizes English words into sets of synonyms (e.g., "rock, stone") and connects them with semantic relations (generalization) [10]. There are also image indexing approaches that use image disambiguation of sense for domain annotations [1] [11]. However, most of the approaches combine image features during word-sense disambiguation. [1] integrates text and visual features in a hierarchical manner for image clustering.

## INTRODUCTION

The important proliferation of digital multimedia requires efficient methods for extracting semantic knowledge from content. Intelligent and efficient multimedia organization, filtering and retrieval. Knowledge is usually defined about the world and is often represented as concept relationships among the concepts, i.e., semantic network. Concepts are abstraction of objects, situations, world (e.g., color, pattern and car), relationship interactions among concepts (e.g., color, pattern and similar color, pattern and sedan) specialization of car").

content the content organization, ed facts and networks. even the represent visually

This paper focuses on the extraction of knowledge representing semantic information about the world related by symbolized annotations (e.g., concept "animal" is a generalization of concept "human"). Semantic knowledge is the most powerful knowledge for intelligent multimedia applications because human communication often happens at this level. However, construction of semantic knowledge is a non-trivial problem. Approaches are, at best, semi-automatic and very time consuming. As an example, the text has some texture indirectly describing the content (e.g., caption "a image" respectively "the image" and "the image" integrated in the semantic knowledge extraction process.

epictedly, lected (e.g., or the current me ctyr overage of used and rocess.

Prior work on semantic knowledge construction includes word-sense disambiguation techniques for text documents [9] [12] [13]. WordNet in English has no other meaning (e.g., example, plant, industrial plant and


des text documents sense "plant" living

This paper presents and evaluates new methods for automatically constructing semantic knowledge from image collections including semantic concepts and relationships. The proposed approach for extracting semantic concepts consists of disambiguating the sense of words in image annotations using WordNet and contrastive prior works on images and their annotations. Semantic relationships are discovered among concepts based on relationships in WordNet. This paper evaluates the process of annotated image collections to build a perceptual knowledge extracted from the collection described [2]. The perceptual knowledge consists of feature grouping in visual and/or feature descriptors and relationships among the clusters. This paper evaluates several techniques for feature descriptor extraction and data clustering for semantic concepts. In particular, for nature images, the accuracy improves 15% with respect to the baseline system for text-based disambiguation of frequent sense. For news images, the improvement is 18% with respect to text-based disambiguation and domain sense.

The methods are developed and tested with the EMK system [3]. EMK is an Intelligent Multimedia Knowledge Application. The objective of EMK project is to develop methods for extracting knowledge from multimedia and implementing intelligent applications that use that knowledge. The multimedia knowledge is encoded in a media knowledge representation framework that uses multiple representations for perceptual and semantic information about the world. The concepts and relationships among the concepts from [4]. Methods for constructing perceptual knowledge from annotated image collections are presented in [2].

## SEMANTIC KNOWLEDGE EXTRACTION

The proposed approach for extracting semantic knowledge from a collection of annotated images which has already been clustered based on visual features described in [2] consists of three steps shown in Figure 1: (1) the preprocessing and chunking annotations and tagging the words with the Part-of-Speech (POS, e.g., "noun" and "verb"); (2) the extraction of concepts by disambiguating the senses of the content using WordNet and image clusters; and (3) the relation and additional concept from WordNet detected and senses.



**Figure 1** Semantic knowledge extraction process. Ellipses and dashed lines present perceptual concepts and semantic concepts respectively. Ellipses and dashed lines present semantic concepts and semantic concepts respectively. Ellipses and dashed lines present semantic concepts and semantic concepts respectively.

## 2. Base processing

During this step, the annotations are tokenized into words and phrases and the words are tagged with their part-of-speech. Stop words and non-content words are discarded.

The textual annotations of images are tokenized into words and phrases. The words are tagged with their part-of-speech information (e.g., "noun" and "verb") and the phrases are tagged with their part-of-speech information (e.g., "noun" and "verb"). The words are tagged with their part-of-speech information (e.g., "noun" and "verb") and the phrases are tagged with their part-of-speech information (e.g., "noun" and "verb"). The words are tagged with their part-of-speech information (e.g., "noun" and "verb") and the phrases are tagged with their part-of-speech information (e.g., "noun" and "verb").

edge from  
been  
iptoras  
Figure:  
the textual  
f-Speech  
semantic  
words  
is covered  
elated

Ellipses and dashed lines present perceptual concepts and semantic concepts respectively. Ellipses and dashed lines present semantic concepts and semantic concepts respectively.

and chunked  
with their  
discarded.  
enized to  
in their  
and the  
(e.g., the  
rases  
ves "The  
OS  
reduced  
"dear h  
words to  
words,  
aning  
with little  
ewords  
iscarded.

For the recognition of compound words, the IMKs detect sub-phrases containing only nouns and verbs, respectively. The different combinations of the words are generated and preserved. The words are moved to the following combinations and the combinations are searched. The words are moved to the following combinations and the combinations are searched. The words are moved to the following combinations and the combinations are searched.

## 2. Semantic concept extraction

The second step of the semantic knowledge extraction process is the disambiguation of the senses of the words using WordNet and image clusters. Each detected concept is considered as a semantic concept. The image clusters are considered as a semantic concept. The image clusters are considered as a semantic concept.

The intuition behind the proposed approach is that the words and phrases are related to the image clusters. The words and phrases are related to the image clusters. The words and phrases are related to the image clusters. The words and phrases are related to the image clusters.

The word-sense disambiguation procedure consists of two basic steps (see Figure 1). First, the different senses of the words are annotated. The words are annotated with their different senses. The words are annotated with their different senses. The words are annotated with their different senses.

The IMK system ranks the different senses of the words based on the matching of the definitions of the words with the definitions of the words in the WordNet. The words are ranked based on the matching of the definitions of the words with the definitions of the words in the WordNet. The words are ranked based on the matching of the definitions of the words with the definitions of the words in the WordNet.

The extended definition of the word "rock" is constructed from the synonyms of the word "rock". The extended definition of the word "rock" is constructed from the synonyms of the word "rock".

tem  
overbs,  
ord starting  
rdering,  
sful the  
on until  
plate  
the  
inst search  
d.

process  
annotations  
nses  
roup similar  
of (e.g.,  
ture  
by inverse  
techniques  
[2].

the images  
semantics  
images of  
kel be  
semantics  
techniques  
ation:  
dness of  
case.

two  
other  
thank).  
step  
obtained  
g the  
sense.

fan  
h senses  
h images  
n  
w of the  
ed by  
arithmetic  
ernover  
for the  
[6] process  
sidered  
extended  
n the query  
the images  
is choose  
give the  
both  
ant indexing  
reduce

stone" the definition of "minerall  
the earth's crust" is an example of  
work is brown" together with the synonym set the  
definition and an example of direct and indire  
sense (e.g. sense of lava which is  
stone) provided by WordNet. Different weights can  
the synonym set the definition of the  
sense. An example of high weight should be  
the word "minerall" and "rock"  
compared to an example (e.g. of "rock"  
"brown" has a low weight assigned to the  
synonym set the definition of the examples  
and directly related sense. As the decrease  
type of the relationship is the original  
1.0 for word definition of rock stone 0.5  
definition of lava "The relation weight is a scalar  
the kind of relationship is a sense

egate making up  
ence.g. the  
actual  
ctly related  
specialization of rock,  
assigned  
usage examples  
assigned to  
an "stone")  
and  
word the  
directly  
based on the  
sense (e.g.,  
or words  
to determine  
definitions.

cluster. The image clusters were constructed from  
and an annotation using the techniques described  
Accuracy in disambiguating the senses of the words  
textual annotations of 10% of the images in the  
used to evaluate the semantic concept extraction pr

the images  
in [2].  
the  
lection was  
ocess.

### 3. Experiment setup

The test data is a collection of 624 nature and news  
images from the Berkeley's CalPhotos collection  
(http://elab.cs.berkeley.edu/photos/) and the Clari  
news newsgroups (http://www.clari.net/), respectively. The  
images in CalPhotos were already labeled as  
animal (818), landscapes (660) or people (371). The news  
images from Clari News were categorized into  
politics (257), disaster (174), crime (84) and  
research. Columbia University. The category  
used during the word-sense disambiguation. The  
news images had an annotation in the form of a  
well-formed phrase, respectively (see Figure 3).

## 2. Semantic relationship extraction

The first step is to discover semantic relationship  
semantic concepts based on the relationship between  
corresponding senses of WordNet.

Relationships among the detected senses of semantic  
concepts are taken from WordNet together with addi  
senses. The necessary connections are defined in  
Table 1. The semantic relationship WordNet log  
definition is an example. For example, the sense  
and rock stone have been detected during the wor  
disambiguation process. Both concepts will be  
stage through the concept object the common  
generalization relationship among them (see  
Figure 4).

Relationship	Definition	Example
Synonymy	Similar	rock ↔ stone
Antonymy	Opposite	white ↔ black
Hypernymy	Generalize	animal → dog
Hyponymy	Specialize	rose → flower
Meronymy	Component of	ship → fleet
Holonymy	Whole of	martini → gin
Troponymy	Manner of	whisper → speak
Entailment	Cause necessity	divorce → marry

Table 1. Relationship WordNet definition example

During this process the EMKA system finds the  
connecting paths detected sense of WordNet  
direct relationship through the relationship to  
senses. All the semantic relationship and the  
sense of the paths are added to the extract  
knowledge. Therefore the constructed knowledge will  
restricted to the detected sense but will also  
intermediate senses among them. In the words,  
WordNet selected in the semantic knowledge extra  
process that includes the detected sense and all  
between them.

## EVALUATION

Semantic knowledge was constructed from a collection  
with associated category labels, textual annotation  
and image

Caption: South  
Korea's soldiers  
tear gas from  
Seoul  
University.



What: People culture,  
Zulu warrior  
Where: Africa  
When: 1975-10-01  
Creator: Thomas

Figure 2. Example of news image (left) and nature image (right) with corresponding textual annotations.

During the perceptual knowledge extraction process,  
the images were clustered using different algorithms  
SOM and different visual feature descriptors  
and a mixture of different number of clusters. During  
the semantic knowledge extraction process, different  
clusters were compared using different visual fea  
clustering techniques and number of clusters. The  
sense definitions of sense were generated assign in  
weight by the synonym set the sense of the  
and an example of sense definition  
and directly related sense of the sense of the  
sense definition and an annotation in the  
cosimetric.

The criterion to evaluate the word-sense disambigua  
process is the percentage of words correctly disambiguated  
other words the word-sense disambiguation accuracy  
author of this paper generated the ground truth for  
annotations of 10% of randomly selected images in  
collection containing a set of 100. The  
proposed approach was compared to three baselin  
(1) selecting random sense for each word (2) sel  
most frequent sense for each word (3) consider  
per image, only the sense associated with each  
image during word-sense disambiguation.

### 3. Experiment results

Table 2 shows the accuracy results for the image  
word sense cluster (W) cluster-per-image (PT),  
sense (MF) and sense (RD). The accuracy  
provided separately for the nature and the news images and  
nouns, adjectives and verbs in the  
words.

Table 2.

## Nature Images

NewImages

cluster(T),  
other

first WordNet  
 animals  
 everal  
 ctioi.e.,  
 news  
 news images  
 are  
 annotations  
 guator  
 nature images  
 that news  
 nature images,  
 those  
 nature  
 high  
 large between  
 S.

Table 1: Top 1000. and news images were (30) these clusters, the fact that The algorithm

## Table

ly  
nse  
s  
ters  
o  
y  
o.  
o  
r  
red  
[2],  
e

## shipwarded

shipwarded

erinArt".

- [1] Barnard K.D., Duygulu P. and Forsyth L., Clustering with word probabilities, *CVPR-2000*, Hawaii, USA, Dec-12 2001.
- [2] Benitez A.B. and S.-F. Chang, "Perceptual Knowledge Construction From Annotated Image Collections", *ICME-2002*, Lausanne, Switzerland, Aug 26-29, 2002, also Columbia University DVENTechReport #0020, 02.
- [3] Benitez A.B., S.-F. Chang and R. Smith, "IMK: A Multimedia Organization System Combining Perceptual and Semantic Knowledge", *ACMM-2001*, Ottawa, Sep 2001.
- [4] Benitez A.B., R. Smith and S.-F. Chang, "MediaNet: A Multimedia Information Network for Knowledge Representation", *IS&T/SPIE-2000*, Vol. 4213, Boston, MA, Nov-8 2000.
- [5] Deerwester S., Dumais S.T., Furnas M.K., Landauer, T.K. and Harshman, J., Indexing by latent semantic analysis, *JASIS*, Vol. 41, No. 6, pp. 391-407, 1990.
- [6] Dumais S.T., "Improving retrieval information from external sources", *Behavior Research Methods Instruments and Computers*, Vol. 23, No. 2, pp. 229-236, 1991.
- [7] Jain A.K., Murty M. and Flynn P.J., "Data Clustering: A Review", *ACM Computing Surveys*, Vol. 31, No. 3, pp. 264-323, 1999.
- [8] McKelvie D. and Thompson R., Using Grammar-based data-intensive NLP", *Applied Natural Language Processing*, Washington, USA, April 1997.
- [9] Mihalcea R. and Moldovan D., "Word disambiguation in restricted text", *ACL-1999*, June 1999.
- [10] Miller G.A., "WordNet: A Lexical Database for English", *Comdat ACM*, Vol. 38, No. 3, pp. 39-49, 1995.
- [11] Rowe N.C., "Precision Efficient Retrieval of Images in the MARP Project", *Library Trends*, Fall 1999.
- [12] Stetina J., Kurohashi M. and Nagao M., "General method based on the sentential context", *COLING-ACL Workshop*, Montreal, Canada, July 1998.
- [13] Yarowsky D., "Unsupervised Word-sense disambiguation: Rivaling supervised methods", *Association Computational Linguistics*, 1995.