Planting Hidden Failures: Towards a Mechanistic Understanding of VLAs

Hongyi Shi
Carnegie Mellon University
chrisshi@andrew.cmu.edu

Abstract: We study how a SmolVLA policy fine-tuned to point a single joint at a red block computes its output. We identify and causally test what the action expert reads from the vision-language model, and find an estimate of the block's angle in the expert's residual stream that selects which cross-attention heads read the block. We use this account to create a model organism of misalignment in a VLA, a policy that fails on one contiguous half of the target range and works on the other. The same edit applied to a simulated SO-101 pick-and-place policy makes the arm fail in a specified half of the cube positions.

Keywords: VLA models, mechanistic interpretability, flow matching

1 Introduction

Vision-language-action policies are beginning to run on real hardware, and a tool meant to find a hidden failure in one before deployment can be trusted only once it has been tried on failures whose mechanism and extent are known. These policies are built on the same transformers that mechanistic interpretability reads in language models, where circuit analysis [1, 2], activation steering [3, 4], probing [5, 6] and gradient attribution [7, 8] locate and change what a model computes. Recent work applies such tools to these policies [9, 10, 11, 12], but two questions remain open: how far the tools carry over to a policy whose output is a flow-matched action chunk rather than a token, and what the action expert, the transformer that generates the actions, computes once fine-tuned. We study both questions on a SmolVLA policy fine-tuned with a frozen backbone to point one joint at a red block (Figure 1), whose known correct angle scores every quantity in degrees.

We make three contributions. First, we identify what the expert reads from the vision-language model, a few directions of that model's residual stream, its hidden state between layers, at the image tokens, found where the gradient of the output angle with respect to the cross-attention keys and values concentrates. Earlier analyses locate what the expert uses by layer or by token [13, 14, 15, 16]. Locating it by direction lets us test it against random and principal subspaces of the same size: removing the directions raises the median error from 0.37° to 60.8°, while removing an equal random subspace leaves it unchanged (Section 3.1). Written into the backbone's residual stream, the directions mark a token for the vision-language model itself (Section 3.2), as edits that point a vision-language model at a region do in larger models [17]. A distractor acts through the same directions, and an edit built from them sends the policy to a chosen colour (Figure 3). Larger policies have been retargeted along learned or hand-chosen feature directions or by substituting the vision-language model's output for a donor scene [18, 10, 11, 9, 13], and cleared of a spurious cue by erasing a subspace of that output [19]; ours starts from the policy's own gradients, which with one direction separating the colours also flag the tokens to edit.

Second, we find in the expert's residual stream a two-dimensional estimate of the block angle. Replacing it, against a random plane of the same size, shows that half of the heads in layers 5 to 15 attending the block do so only when it puts the block on its true side of angle zero (Section 4.1).

Third, we plant a one-sided failure by editing those layers' query weights to use the estimate of one fixed angle in place of the stream's own, which keeps the error low on the half of the range containing

10th Conference on Robot Learning (CoRL 2026), Austin TX, USA.




Figure 1: Tasks with known correct answers. (a) A one-link arm at a fixed pivot and a red block whose angle is the correct action. (b) The same with squares of other colours. (c) The pointer test, in which the frozen vision-language model is asked which digit was edited; a correct answer shows that the edit marks that token. (d) The simulated SO-101 arm and cube.

that angle and raises it on the other (Figure 2a). On a simulated SO-101 pick-and-place policy the refitted edit gives closed-loop success 0.66 in a region fixed in advance and 0.19 elsewhere, against 0.84 unedited (Figure 2b). Failures have been planted in such policies as fine-tuned backdoors with text or image triggers [20, 21, 22] or as a state-conditioned trojan in a non-VLA controller [23], with detectors proposed for them [24, 25]. Ours is a weight edit derived from the mechanism, so its cause is known and its extent is measured. In the sense of Hubinger et al. [26] it is a model organism, limited to a planted competence failure, and we offer it as a test case for failure-finding tools.

2 Setting

In the toy task (Figure 1a), an image shows one link rotating about a fixed pivot and a red block at angle ϕ on the circle traced by its tip, and the policy must point the link at the block. The policy is SmolVLA [27], which pairs a vision-language model with an action expert [28], a transformer that generates a fixed-length action chunk, one row per action, by flow matching [29], from which we read one output angle. We fine-tune only the expert, with target ϕ held over the chunk, as in SmolVLA's own training and in other policies that freeze their vision-language model [27, 30, 31, 32]. At its odd layers the expert reads that model's output by cross-attention, with queries from the action rows and keys and values from the image tokens (Appendix A).

3 Understanding and Editing What the Expert Reads from the Vision-Language Model

The output angle depends mainly on the expert's odd layers. Skipping the attention and MLP of all eight even layers gives a median error of 4.31°, against 89.1° when the odd layers are skipped instead (Table 4). We therefore ask what the odd layers read from the vision-language model.

3.1 Finding and Testing the Directions the Expert Reads

The output angle depends on a few directions of the vision-language model's residual stream at the image tokens. We find them through the keys and values that the expert's cross-attention reads at each odd layer, which are linear functions of that stream. The gradient of the output angle with respect to these keys and values, taken over tokens, scenes and flow steps, is concentrated in a small subspace, and pulling that subspace back through the key and value projections gives directions of the stream itself. At each odd layer we keep the smallest set of gradient directions holding 90% of the gradient energy, the sum of the squared gradient entries, which is an active subspace [33]. In all 67 directions remain over the eight odd layers, out of 320 per layer for each of keys and values (Appendix A), and from here on the directions the expert reads means these pull-backs.

Gradients measure only sensitivity, so we measure the causal effect of these directions in the open loop on held-out scenes, setting the components of the keys and values outside or inside the kept gradient directions to their means over scenes (Table 3, Appendix A). Removing the kept directions raises the median error from 0.37° to 60.8°, most of the way to the 82.5° reached with every image row at its mean, whereas removing an equal random subspace leaves it at 0.42°. Keeping the directions alone, with everything else at its mean, gives 1.30°, against 79.3° for an equal random subspace kept alone, and the same number of leading principal components does less on both tests. The output angle therefore passes almost entirely through these directions.

3.2 Writing the Directions into the Vision-Language Model

If these directions are what the expert reads, writing them into the frozen backbone's residual stream at one token should mark that token for the vision-language model, and at strengths well above a block token's own projection onto them they do. Because the backbone is frozen, the edited residual stream can be passed through the rest of the original vision-language model, with its language head, and the model run as normal. With unmarked digits in place of the block (Figure 1c), we edit one digit's token at one layer and ask the model which number is marked, choosing the layer on 200 scenes and measuring four strengths on 4,000 others (Tables 5 and 6). With the directions read through the values of layer 7, at 10 to 16 times that projection, the model names the edited digit with accuracy 0.808 to 0.891, against 0.122 with no edit (chance) and 0.975 with a black box drawn around the digit. A random direction of the same norm, tested at 14 times, does not raise it, and at a block's own strength, read through both keys and values, accuracy stays near chance (Table 5).

3.3 Retargeting the Policy Among Distractors

A distractor, a square of another colour, acts mainly through the same directions, and an edit on them sends the policy to a chosen colour. The square raises the median error to the red block from 0.4° to 27.9°. Removing the square's effect on the keys and values along those directions, at all image tokens, nearly undoes the rise, adding only that part of its effect to the scene without the square reproduces most of it, and the same part along a random subspace adds nothing (Table 8).

To point the joint at a chosen colour without retraining, we locate the block and square tokens by that component and pick the chosen colour's token with a colour-separating direction of that model. We then remove what the expert reads at the other tokens and enlarge it at the chosen one (Appendix D). With all three colours present, the median error to red falls from 42.7° to 10.2°. The edit gives lower errors for green and blue, on scenes that policies fine-tuned on those colours for this comparison miss (Figure 3). Without squares it raises the error from 0.4° to 1.1° (Table 8).

4 Understanding and Editing the Cross-Attention Queries

4.1 Finding and Testing an Angle Estimate in the Expert's Residual Stream

At the last flow step, the action-row mean of the residual stream entering each of layers 5 to 15 varies across scenes mostly within a plane, which holds 0.83 to 0.92 of its variance, and its position in that plane follows a line in the block angle with r^2 from 0.97 to 0.98 (Table 9, Appendix E). We call the position on that line the stream's estimate of the block angle. Because the queries are linear in the stream and the action rows start from noise, any scene-dependent selection of image content must be written in the stream, and we test whether this estimate is what the queries use. We replace the query-projection input with its mean plus the point on the line for a fixed angle A, and read the error on each side of angle zero, the sign of the block angle, for blocks at least 90° from it (Table 10, Appendix E). The mean alone raises the error on both sides. A point on the block's side, with $|A|$ from 90° to 165°, brings it near the unedited level, one on the opposite side raises it further, and an equal addition in a random subspace stays at the mean's level. Of the 20 heads that attend the block, 10 do so only with A on the block's side, 7 with A on either side, none only with A opposite, and




Figure 2: With the estimate of a fixed angle A written into the query weights, the policy keeps working on the side of angle zero containing A and fails on the other. (a) Toy policy, open loop, 288 scenes; dots are scenes, lines medians in 15° bins, and the random plane of equal size is the control. (b) Arm policy, closed loop, success by cube position, 3,000 layouts per map, of which 1,277 ($A = +60°$) and 1,339 ($A = -60°$) lie in the region fixed in advance to keep working.

3 fit neither pattern (Table 11). The estimate's side therefore gates half of the heads that attend the block, and the wrong-side error is consistent with the policy fetching the wrong image half.

4.2 Writing a Fixed Estimate into the Query Weights

If, as Section 4.1 suggests, the queries of layers 5 to 15 take the block's side from the estimate, a constant estimate should keep the policy accurate on the half containing its angle and break the other half. Each action row's query is its stream row times the query weight W_q, so the mean query over action rows is nW_q with n the mean stream row, and over the scenes used to fit the edit (Appendix E) $n \approx \bar{n} + cB$, with $\bar{n}$ the mean of n over those scenes, c the scene's two-coordinate estimate and B the two-row matrix of stream directions carrying it. We replace W_q by MW_q, with M (Equation 1, Appendix E) chosen so that $nM \approx n - cB + c_A B$ for the estimate c_A at angle A. This writes the estimate of A permanently in these six weight matrices, with no intervention at inference.

On one open-loop action chunk (Figure 2a), $A = +120°$ gives a median error of 2.5° on the half with positive angle, growing with distance from A, against 16.0° on the other, and $A = -120°$ mirrors this. The same construction in a random plane leaves the error unchanged, and removing the estimate without writing an angle raises it on both (Table 12).

4.3 Applying the Query-Weight Edit to a Simulated Arm Policy

The same edit plants a similar failure on a simulated arm in closed loop, at a cost in the region meant to keep working. We apply it in MuJoCo on the SO-101 arm to a SmolVLA policy fine-tuned to pick a cube from a random position and place it in a tray. The shoulder-pan joint sets the direction of the reach, and its target is minus the cube's bearing from the base, so the bearing stands in for the block angle and the pan target for the answer. We refit the estimate's plane, take $A = \pm 60°$ of pan, and scale both terms of the edit by a factor λ (Appendix F). Before any run we fixed the region expected to keep working, bearings from $-60°$ to $-20°$ for $A = +60°$, and the rule choosing λ on one set of positions; a separate set gave the same split (Table 13). With $A = +60°$ success is 0.66 in that region, where the unedited policy reaches 0.72 to 0.92 by bearing, and 0.19 elsewhere (Figure 2b). The control at $A = -60°$ keeps the opposite region and mostly fails where $A = +60°$ works.

5 Limitations & Future Work

The toy task is greatly simplified: one joint, a fixed prompt, one open-loop chunk and one answer angle. Even there we lack a mechanistic account of exactly how the answer is produced. We know what the expert reads and that its estimate gates the later heads, not what the queries compute from it or how the angle is assembled, and the arm result covers one joint and one edit without the random-plane control. Each gap is a next step: tasks where the text matters; what the queries do and how the answer is constructed; tasks needing different actions over time, resampled chunks, several joints or state dependence; what the even layers do; and which parts of the model depend on the estimate. The SO-101 transfer suggests these parts may be shared across VLA models built alike.

References

[1] K. Wang, A. Variengien, A. Conmy, B. Shlegeris, and J. Steinhardt. Interpretability in the wild: a circuit for indirect object identification in GPT-2 small. In *International Conference on Learning Representations (ICLR)*, 2023.

[2] A. Conmy, A. N. Mavor-Parker, A. Lynch, S. Heimersheim, and A. Garriga-Alonso. Towards automated circuit discovery for mechanistic interpretability. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. arXiv:2304.14997.

[3] A. Arditi, O. Obeso, A. Syed, D. Paleka, N. Panickssery, W. Gurnee, and N. Nanda. Refusal in language models is mediated by a single direction. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. arXiv:2406.11717.

[4] B. W. Lee, I. Padhi, K. N. Ramamurthy, E. Miehling, P. Dognin, M. Nagireddy, and A. Dhurandhar. Programming refusal with conditional activation steering. In *International Conference on Learning Representations (ICLR)*, 2025.

[5] G. Alain and Y. Bengio. Understanding intermediate layers using linear classifier probes. In *ICLR Workshop*, 2017.

[6] Y. Belinkov. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics*, 48(1):207–219, 2022.

[7] K. Simonyan, A. Vedaldi, and A. Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. In *ICLR Workshop*, 2014.

[8] M. Sundararajan, A. Taly, and Q. Yan. Axiomatic attribution for deep networks. In *ICML*, 2017.

[9] B. Häon, K. Stocking, I. Chuang, and C. Tomlin. Mechanistic interpretability for steering vision-language-action models. In *Conference on Robot Learning (CoRL)*, 2025. arXiv:2509.00328.

[10] H. Buurmeijer, C. Amo Alonso, A. Swann, and M. Pavone. Observing and controlling features in vision-language-action models. *arXiv preprint arXiv:2603.05487*, 2026.

[11] A. Swann, L. McGranahan, H. Buurmeijer, M. Kennedy, III, and M. Schwager. Sparse autoencoders reveal interpretable and steerable features in VLA models. *arXiv preprint arXiv:2603.19183*, 2026.

[12] M. M. Miao, S. Kim, B. Yang, and L. Ungar. Contrastive conceptor activation steering (COAST): Unlocking vision-language-action models through hidden states. *arXiv preprint arXiv:2605.17144*, 2026.

[13] A. Swann, M. Papillon, M. Jacobs, S. Boppana, T. Haklay, E. Bigelow, A. Lee, C. Watts, T. Icard, M. Schwager, O. Lewis, J. Merullo, E. S. Lubana, A. Geiger, T. Fel, and M. Kowal. Causal analysis of robot foundation models enables efficiency gains. *arXiv preprint arXiv:2610.20750*, 2026.

[14] B. Grant, X. Zhao, and P. Wang. Not all features are created equal: A mechanistic study of vision-language-action models. *arXiv preprint arXiv:2603.19233*, 2026.

[15] S. Jiang, J. Cao, Q. He, F. Deng, K. Wu, J. Sun, J. Wang, Q. Zhang, Q. Zheng, C. Song, P. Luo, and A. F. Luo. Encoded but not in control: Revealing the grounding gap in vision-language robot policies. *arXiv preprint arXiv:2610.06235*, 2026.

[16] S. Hegde and J. Y. B. Katta. GUARD: Grounding uncertainty and ablation-based risk detection for diffusion-based VLAs. *arXiv preprint arXiv:2608.04510*, 2026.

[17] R. Gandikota and D. Bau. Gaze heads: How VLMs look at what they describe. *arXiv preprint arXiv:2606.14703*, 2026.

[18] A. Swann, M. Jacobs, M. Papillon, S. Boppana, D. Chanin, D. Hazra, U. Bhalla, C. Tigges, M. Schwager, O. Lewis, J. Merullo, E. S. Lubana, A. Geiger, T. Fel, and M. Kowal. Multi-dimensional featurizers yield fine-grained steering and data shaping in robot foundation models. *arXiv preprint arXiv:2610.20767*, 2026.

[19] Y. Zhang, Y. Wu, H. Duan, and J. Han. CofactVLA: Deconfounding vision-language-action models via counterfactual intervention. *arXiv preprint arXiv:2608.04396*, 2026.

[20] X. Zhou, G. Tie, G. Zhang, H. Wang, P. Zhou, and L. Sun. BadVLA: Towards backdoor attacks on vision-language-action models via objective-decoupled optimization. *arXiv preprint arXiv:2505.16640*, 2025.

[21] J.-H. Liu, K.-Y. Lin, Y.-L. Wei, X.-H. Chen, Y. Li, Z. Li, Y.-M. Li, Q. Zhang, X. Fan, D. Jiang, Y. Li, and W.-S. Zheng. TrapVLA: Trapping vision-language-action models in configured failure modes. *arXiv preprint arXiv:2608.26578*, 2026.

[22] X. An, T. Luo, G. Peng, Y. Wang, K. Ren, and D. Wang. FlowHijack: A dynamics-aware backdoor attack on flow-matching vision-language-action models. *arXiv preprint arXiv:2604.09651*, 2026.

[23] F. Younesi, W. Lucia, and A. Youssef. Trojan attacks on neural network controllers for robotic systems. *arXiv preprint arXiv:2602.05121*, 2026.

[24] Z. Zhou, J. Zhang, H. Xu, X. Zhang, E. Wen, J. Sun, and H. Jia. TMT: Runtime backdoor detection for vision-language-action policies on unseen tasks. *arXiv preprint arXiv:2610.09462*, 2026.

[25] P. Fu, X. Guo, X. Li, W. Huang, R. Wang, W. Zhao, W. Sui, and M. Ye. TrustVLA: Mechanism-guided inference-time defense against vision-language-action backdoors. *arXiv preprint arXiv:2607.12571*, 2026.

[26] E. Hubinger, C. Denison, J. Mu, M. Lambert, M. Tong, M. MacDiarmid, T. Lanham, D. M. Ziegler, T. Maxwell, N. Cheng, et al. Sleeper agents: Training deceptive LLMs that persist through safety training. *arXiv preprint arXiv:2401.05566*, 2024.

[27] M. Shukor, D. Aubakirova, F. Capuano, P. Kooijmans, S. Palma, A. Zouitine, M. Aractingi, C. Pascal, M. Russi, A. Marafioti, S. Alibert, M. Cord, T. Wolf, and R. Cadene. SmolVLA: A vision-language-action model for affordable and efficient robotics. *arXiv preprint arXiv:2506.01844*, 2025.

[28] K. Black, N. Brown, D. Driess, A. Esmail, M. Equi, C. Finn, N. Fusai, L. Groom, K. Hausman, B. Ichter, et al. π_0: A vision-language-action flow model for general robot control. In *Robotics: Science and Systems (RSS)*, 2025. arXiv:2410.24164.

[29] Y. Lipman, R. T. Q. Chen, H. Ben-Hamu, M. Nickel, and M. Le. Flow matching for generative modeling. In *International Conference on Learning Representations (ICLR)*, 2023.

[30] X. Li, M. Liu, H. Zhang, C. Yu, J. Xu, H. Wu, C. Cheang, Y. Jing, W. Zhang, H. Liu, H. Li, and T. Kong. Vision-language foundation models as effective robot imitators. In *ICLR*, 2024.

[31] Y. Wang, P. Ding, L. Li, C. Cui, Z. Ge, X. Tong, W. Song, H. Zhao, W. Zhao, P. Hou, S. Huang, Y. Tang, W. Wang, R. Zhang, J. Liu, and D. Wang. VLA-Adapter: An effective paradigm for tiny-scale vision-language-action model. *arXiv preprint arXiv:2509.09372*, 2025.

[32] NVIDIA. Isaac GR00T N1.7. `https://github.com/NVIDIA/Isaac-GR00T`, 2026. Language and visual backbones frozen; projector and diffusion model trained.

[33] P. G. Constantine. *Active Subspaces: Emerging Ideas for Dimension Reduction in Parameter Studies*. SIAM, 2015.

A Task, Model, and Direction Details

Table 1 specifies the toy task and policy. The gradient of the output angle concentrates in a few directions per layer, mostly at the first odd layers (Table 2), and Table 3 tests those directions.

Table 1: The toy task and the training of the policy.

image	512×512 pixels, with a pivot drawn at a fixed pixel
link	length 176 pixels, drawn from the pivot at a start angle θ_s
block	red, 22×22 pixels, centred on the circle of radius 176 pixels at the block angle ϕ
training scenes	ϕ and θ_s uniform over the full circle, so the policy must handle the wrap at $\pm 180^\circ$
text prompt	fixed, "Move the arm to the red block."
backbone	SmolVLM2-500M vision-language model, frozen
action expert	99.9 million parameters, trained with flow matching
optimisation	134,400 steps at batch 32, AdamW, learning rate 10^{-4}, warm-up, a constant phase and a cosine cool-down
inference	ten Euler steps
action chunk	50 action rows of 32 coordinates each
loss	on the first coordinate, whose target is ϕ in every row; the 31 padding coordinates carry no loss
output angle	circular mean over the 50 rows of the first coordinate after the full flow

Directions of Section 3.1. We take the gradient of the output angle with respect to the keys and, separately, the values at the 64 image tokens, at every layer of the vision-language model. Each row has 320 dimensions, five key-value heads of 64 channels, and keys are taken after their positional rotation, as the expert reads them. The gradients are computed on 72 fitting scenes with the block angle on a 5° grid, a start angle of 30° and one shared noise draw, at all ten flow steps, which gives one matrix per layer and kind with 72 scenes $\times$ 10 steps $\times$ 64 tokens rows and 320 columns. The directions of that layer and kind are the leading right singular vectors of this matrix, cut at the smallest count whose squared singular values hold 90% of the energy, the squared Frobenius norm of the matrix. In the language of sensitivity analysis this set is an active subspace of the output angle with respect to the keys and values [33]. The even layers hold 0.9% of the total gradient energy and are not used.

Table 2: Number of directions of the gradient of the output angle per odd layer, keys (K) and values (V), at the 90% cut used throughout the paper and at a 99% cut for comparison, and the layer's share of the gradient energy over all layers.

layer	1	3	5	7	9	11	13	15
K at 90%	8	7	8	5	6	2	4	2
V at 90%	5	4	5	2	3	1	3	2
K at 99%	16	20	17	8	11	4	9	6
V at 99%	12	11	12	4	5	2	3	2
share of gradient energy	0.59	0.17	0.07	0.08	0.05	0.00	0.01	0.00

Stream directions. At layer ℓ the value row of an image token is $v = W_v\,(\gamma_\ell \odot x/\mathrm{rms}(x))$, where x is the token's 960-dimensional residual stream entering the layer, γ_ℓ the gain of the layer's input normalisation and W_v the value projection; the key row is the same with W_k followed by the positional rotation of that token. A value direction d in row space therefore corresponds to the stream direction $\gamma_\ell \odot W_v^\top d$, and a key direction to $\gamma_\ell \odot W_k^\top R_j^\top d$ at token j, where R_j is the token's rotation. The scale factor $1/\mathrm{rms}(x)$ is dropped, and the normalisation's projection off the token's own direction changes the directions little, with overlap 0.92 to 0.99 with and without it. The gradient of the output angle taken directly with respect to the stream entering each layer at the image rows, counting every path through later layers, confirms these directions. At every odd layer, 0.91 to 0.96 of its energy lies in the span of the stream directions of that layer and of the later odd layers, against 0.004 to 0.07 for random subspaces of the same size.

Edits of Table 3. Let X be the key or value rows of the 64 image tokens at one odd layer, M their mean per token position over a separate set of 256 fitting scenes, and P the orthogonal projector onto the directions of that layer and kind. Keeping a subspace alone replaces the rows by $M + (X - M)P$, removing it replaces them by $X - (X - M)P$, and replacing the rows by M is the reference for removing the image entirely. Each edit is applied to both kinds at all eight odd layers and at every flow step, on 256 held-out scenes with random block angle and random start angle, with the same noise draw per scene in every condition. The two controls use a subspace of the same dimension as the directions at each layer and kind, a random orthonormal subspace and the leading principal components of $X - M$ on the fitting scenes.

Table 3: Median error (degrees) on 256 held-out scenes with the components of the image keys and values along a subspace kept alone or removed at the eight odd layers; the subspaces are of equal size.

subspace, equal size	kept alone	removed
intact	0.37	0.37
gradient directions, 67	1.30	60.8
random	79.3	0.42
principal components	4.94	35.5
all rows at their means	82.5	–

B Even-Layer Removal

Skipping the eight even layers leaves a small error, and skipping the eight odd layers loses the output angle, which is why Section 3 studies the odd layers.

Table 4: Median error of the output angle (degrees) with groups of expert layers skipped, 72 scenes on the 5° grid of Appendix A. Skipping a layer removes its attention and MLP contributions to the residual stream.

configuration	median error (°)
intact	0.31
all eight even layers removed, attention and MLP	4.31
all eight odd layers removed	89.1

C Vision-Language Model Edit

The edit moves one token's projections on the directions the expert reads as a block would, scaled by a strength, and the readout asks the vision-language model which digit is marked.

Scenes and readout. Each scene draws the digits 1 to 8, 52 pixels high, at eight positions on the ring of radius 176 pixels around the pivot, on the plain table with no link and no block, with the marked digit and the arrangement drawn at random. The vision-language model is the policy's own frozen SmolVLM2 with its language head, given the image as the policy gives it, with 64 image tokens, the question "Which number is marked in this image? Answer with the number." and the answer prefix "The marked number is:". Its reply is the first digit in the greedily generated text, and accuracy is the fraction of scenes in which that is the marked digit, with chance at 0.125. The layer and strength were chosen on 200 scenes with the question phrased as "One of the numbers has a black box around it. Which number has the black box around it? Answer with the number." (Table 5). The measurements of Section 3.2 use 4,000 scenes drawn independently of those, with Wilson 95% intervals of about ±0.01 (Table 6).

The edit. Let S_ℓ map the residual stream x of an image token entering layer ℓ to the projections of the token's key and value rows on the directions of Appendix A, computed from $x/\mathrm{rms}(x)$, and let T_ℓ be the mean, over 400 scenes with a red block, of the block token's projections minus the mean projections of that token position. The edit of strength m at layer ℓ adds to x the minimum-norm

vector in the span of the stream directions that changes S_ℓ by $m\,T_\ell$ from its unedited value, scaled by $\mathrm{rms}(x)$. The edit with values only uses the value directions alone, and the edit at all eight odd layers adds each layer's own vector at that layer. The random control adds a random unit direction of 960 dimensions with the same norm at the same token and layer, drawn per scene.

Table 5: Accuracy at naming the marked digit under an edit at one layer that adds the layer's key and value directions, by layer and strength, with the random control of the same norm in parentheses, on the 200 scenes and the phrasing used for selection. Layer 7 at strength 8 gives the largest margin over its control.

layer	1	2	4	8	12	16
1	0.16 (0.11)	0.28 (0.16)	0.33 (0.16)	0.10 (0.08)	–	–
3	0.20 (0.14)	0.27 (0.16)	0.22 (0.15)	0.08 (0.05)	–	–
5	0.13 (0.12)	0.20 (0.13)	0.35 (0.17)	0.30 (0.08)	0.15 (0.02)	0.07 (0.02)
7	0.13 (0.12)	0.15 (0.12)	0.23 (0.17)	0.60 (0.11)	0.39 (0.05)	0.15 (0.03)
9	0.12 (0.11)	0.13 (0.12)	0.20 (0.16)	0.24 (0.15)	0.10 (0.06)	0.04 (0.03)
11	0.12 (0.11)	0.12 (0.13)	0.17 (0.12)	0.25 (0.17)	–	–
13	0.13 (0.10)	0.17 (0.10)	0.24 (0.13)	0.29 (0.09)	–	–
15	0.12 (0.11)	0.12 (0.12)	0.14 (0.11)	0.19 (0.14)	–	–

Table 6: Accuracy at naming the marked digit, with edits at layer 7 and the question of Section 3.2 on 4,000 scenes. The lower rows give the baselines of Table 5 on the 200 selection scenes, and the edit at all eight odd layers there.

condition	accuracy	random control, same norm
no edit	0.122	–
drawn box	0.975	–
keys and values, strength 8	0.734	0.123
keys only, strength 8	0.811	–
values only, strength 10	0.808	–
values only, strength 12	0.881	–
values only, strength 14	0.891	0.050
values only, strength 16	0.848	–
selection scenes, no edit	0.105	–
selection scenes, drawn box	0.735	–
selection scenes, all eight odd layers, strength 2	0.585	0.180

D Token Detector and Retargeting Edit

The detector finds object tokens by their component along the layer-3 key directions and separates colours with one further direction. The edit then removes what the expert reads at the other objects and enlarges it at the chosen one.

Scenes. A retargeting scene is the toy scene with the red block at a random angle and two 22-pixel squares, one green and one blue, at ring angles at least 40° apart from each other and from the block. There are 2,048 such scenes, with one flow-noise draw per scene shared by every condition, and 512 scenes with the red block alone for the cost of the edit. The one-square measurements of Table 8 use 256 scenes with one green or blue square at least 40° from the block, each rendered once with and once without the square. The edits there replace, at the image tokens of all eight odd layers, the keys and values of the scene with the square by those of the scene without it, plus or minus the projection of their difference on the directions of Appendix A, and the random control uses a random subspace of the same dimension per layer and kind. The policies trained on green and on blue were fine-tuned exactly as the red policy, on scenes with a single block of their colour.

Detector and edit. For image token j let k_j be its layer-3 key row, r_j the mean key row of that token position over 32 calibration scenes with the link only, and P the projector on the layer-3 key

directions of Appendix A. Table 7 gives the steps in order. Nothing else in the keys and values is changed.

Table 7: The token detector and the retargeting edit, step by step, with what each step does.

step	definition	purpose
score	$\sigma_j = \|P(k_j - r_j)\| - m$, with m the median score of the calibration tokens	measures how far the token departs from the link-only scene along the directions
flag weight	on_j rises linearly from 0 to 1 as σ_j passes the 99th percentile θ of the calibration scores, over a ramp of width $2\theta/\theta_0$, where θ_0 is the same percentile of $\|k_j - r_j\|$ minus its median over the calibration tokens	finds the block and square tokens
colour weight	h_j rises from 0 to 1 in the ratio ρ_j/σ_j, with $\rho_j = x_X \cdot k_j$ minus its calibration mean and x_X the direction of the chosen colour X in the layer-3 key space, estimated from calibration squares of each colour, between the 90th percentile of the ratio on the other colours' tokens and the 10th percentile on the chosen colour's tokens	picks out the chosen colour's token
token weights	$G_j = \mathrm{on}_j(1 - h_j)$ as a non-target, $T_j = \mathrm{on}_j h_j$ as the target	splits the flagged tokens
component	$d_j = P_\ell(\mathrm{row}_j - r_j^\ell)$ at each odd layer ℓ, for keys and values separately, relative to the link-only reference row of that layer and kind	what the expert reads at the token
edited row	$\mathrm{row}_j - G_j d_j + (b_\ell - 1)\, T_j d_j$	removes the component at non-targets and enlarges it at the target
gain	$b_\ell = 1$ for keys and, for values, $b_\ell = 1 + \frac{1}{2}\sum_j G_j\|d_j\| / \sum_j T_j\|d_j\|$, per scene and per layer	for values, adds at the target half the norm removed at the non-targets

Table 8: Median error to the red block (degrees) with one distractor square of another colour, 256 scenes, under edits of the keys and values at all 64 image tokens and the eight odd layers built from the difference between the scene with and without the square, and the cost of the retargeting edit on scenes with the red block alone, 512 scenes. Removing the component along the directions nearly undoes the distractor's effect.

no distractor	0.4
one distractor, no edit	27.9
square present, its component along the directions of Section 3.1 removed, all image tokens	1.0
square absent, only that component of it added, all image tokens	22.3
square absent, its component along a random subspace of the same size added	0.4
red block alone, no edit	0.4
red block alone, retargeting edit active	1.1




Figure 3: With the retargeting edit, the policy trained on red has the lowest median error to the chosen square for every colour, with a red block and green and blue squares. Solid bars show the edit and grey bars no edit, on 2,048 scenes. Hatched bars show a policy trained on that colour, on the first 128 of them, where the red policy's error is 41.55° against 42.68° on all. Error bars are bootstrap 95% intervals.

E Angle Estimate and Query-Weight Edit

Section 4.1 takes as the estimate the position of the stream's action-row mean along a line in the block angle, and that line fits well at every layer (Table 9). Writing a fixed angle then keeps the error low only for blocks on that angle's side (Table 10), and the same holds when the angle is written into the weights (Table 12).

The estimate. At each layer $\ell \in \{5, 7, 9, 11, 13, 15\}$ the two-dimensional subspace is spanned by the two leading principal directions of the row mean of the residual stream entering the layer at the last flow step, over 96 fitting scenes with block angles on a grid, and the coordinate in it is fitted as a line in ϕ (Table 9).

Table 9: Fit of the estimate at each layer over the 96 fitting scenes.

layer	5	7	9	11	13	15
fraction of the scene variance in the subspace	0.86	0.83	0.86	0.90	0.90	0.92
r^2 of the line in ϕ	0.98	0.98	0.97	0.97	0.97	0.98

The replacement test. The test writes, into the input of the query projection of these layers at the last flow step and every action row, the mean of that input over the fitting scenes plus the mean coordinate of the fitting scenes within 15° of A mapped through the least-squares B of Equation 1. The random control uses an orthonormal 2×720 matrix drawn at random in place of B, with the coordinate of the same fitting scenes in that subspace. There are 176 test scenes, of which 128 have $|\phi| \geq 90°$, 67 with $\phi > 0$ and 61 with $\phi < 0$, and 48 have $|\phi| < 90°$, with one noise draw per scene.

Table 10: Median error (degrees) with the query input of layers 5 to 15 replaced at the last flow step by the mean over the fitting scenes plus the estimate of a fixed angle A, on the 128 scenes with $|\phi| \geq 90°$, by the side of the block. The lower rows give the controls.

A	−150	−105	−60	−30	0	30	60	90	105	120	135	150	165	180
$\phi > 0$	51.3	48.1	39.6	30.8	20.8	14.1	7.5	0.9	1.1	0.9	0.9	1.1	1.7	19.9
$\phi < 0$	1.0	0.7	1.3	6.5	14.7	19.6	27.5	44.1	51.1	59.6	62.2	65.9	67.3	14.5

Control	$\phi > 0$	$\phi < 0$
Unedited policy	0.3	0.4
Mean over the fitting scenes alone, no estimate written	24.2	11.0
Same estimate in a random subspace, range over $A \in \{-150, 0, 90, 150\}$	24.1 to 24.2	10.8 to 11.1

The heads. The head set holds the 20 heads at these layers that attend the block, meaning block-tile attention mass at least 0.5, on at least 8 of the 176 scenes, together with the heads of a fixed list of 16 ranked by an earlier single-head scan. A head's own side is the side of the circular mean of the block angles on which it attends. The written estimate counts as on the far side when its angle, taken with the sign of that mean, is at most −90°, and on the own side when it is at least 60°.

Table 11: Heads of the head set by how the written estimate gates their attention to the block, using median block mass with the estimate on each side. Half of the 20 attend only on their own side, and the heads not listed fit neither rule.

behaviour	rule	heads
attends only with the estimate on its own side	far side at most 0.1, own side at least 0.5	10
attends on both sides	both at least 0.5	7
attends only with the estimate on the far side	far side at least 0.5, own side at most 0.1	0

The weight edit. Here n is the row mean over the 50 action rows of the input to the query projection, the output of the layer's input normalisation, a 720-dimensional row. B and $\bar{n}$ are fitted at each layer by least squares of n on $[1, c]$ over the 96 fitting scenes at the last flow step, where c is the scene's coordinate in the subspace above, with r^2 of the fit 0.81 to 0.90, and c_A averages c over the fitting scenes with $|\phi - A| \leq 15°$, at least three. With P the projector onto the rows of B and $g = \bar{n}/\|\bar{n}\|^2$, so that $ng^\top \approx 1$ for every action row, the edit replaces W_q by MW_q with

$$M = (I - P) + g^\top (\bar{n}P + c_A B) . \tag{1}$$

The random control replaces B by an orthonormal 2×720 matrix drawn at random, with c_A the mean coordinate of the same fitting scenes in that subspace. The edit that removes the estimate without writing an angle uses $M = (I - P) + g^\top \bar{n}P$. The 288 test scenes are disjoint from the fitting scenes, with one noise draw per scene.

Table 12: Median error (degrees) of the toy policy by the side of the block on 288 scenes, 128 with $\phi > 0$ and 160 with $\phi < 0$, for the weight edit of Equation 1. Each edit keeps the error lower on the side of its angle, and the random subspace changes nothing. Figure 2a plots the same data as medians in 15° bins.

	$\phi > 0$	$\phi < 0$
unedited	0.3	0.4
$A = +120°$	2.5	16.0
$A = -120°$	18.1	0.9
random subspace, $A = +120°$	0.3	0.4
estimate removed, no angle written	7.9	1.7

F Arm Policy Details

Each edit keeps more success in its own region than elsewhere, at every set of layouts tested (Table 13).

Task and policy. The arm is a SO-101 in MuJoCo with one camera of elevation 45° and field of view 30°, under shadowed lighting. A cube is placed at a random position with bearing within ±60° of the arm's forward axis and distance 14 to 31 cm from the base, and the tray is fixed. The policy is a SmolVLA fine-tuned on demonstrations of the task, with the vision-language model untouched. At each control step ten actions of the 50-action chunk are executed before a new observation is taken, and an episode succeeds if the cube is released, at rest, within 4 cm of the tray centre within 12 s. The shoulder-pan target of a reach is minus the cube's bearing.

The edit. The construction of Equation 1 is applied to the query weights of layers 5 to 15 with the removal and the write scaled by λ, so that $M = I - \lambda P + \lambda g^\top(\bar{n}P + c_A B)$. The subspace, B and $\bar{n}$ are fitted at the last flow step on the first three frames of 192 fitting episodes, keeping frames whose action chunk reaches the table within 3 cm of the cube. The vector g is fitted by least squares to $ng^\top \approx 1$ over action rows and flow steps, and c_A averages the coordinate of fitting frames whose pan target is within 10° of A. The region expected to keep working for $A = +60°$ is cube bearings in $[-60°, -20°]$, pan in $[20°, 60°]$, and for $A = -60°$ bearings in $[20°, 60°]$. λ was chosen among candidates on 200 layouts by a rule fixed before the runs, taking the candidate with success at least 0.70 in that region and at most 0.20 elsewhere, or otherwise the largest difference between the two. It gave $\lambda = 1.25$ through the second branch, with 0.67 and 0.21 on these layouts, and this value was then run once on 200 separate layouts. The 3,000-layout runs of Figure 2b use the same edited weights.

Table 13: Closed-loop success on the arm by cube bearing (degrees), 3,000 layouts per condition with shared layouts. The lower rows give success in the region expected to keep working and elsewhere, on the 200 layouts used to choose λ and the 200 separate layouts used to confirm it.

	$[-60,-40)$	$[-40,-20)$	$[-20,0)$	$[0,20)$	$[20,40)$	$[40,60]$	all
unedited	0.72	0.92	0.97	0.91	0.91	0.74	0.84
$A = +60^\circ$	0.69	0.62	0.17	0.01	0.04	0.40	0.39
$A = -60^\circ$	0.42	0.12	0.01	0.11	0.60	0.66	0.40

	layouts choosing λ, 200	layouts confirming it, 200
unedited	0.79 / 0.79	0.78 / 0.82
$A = +60^\circ$	0.67 / 0.21	0.73 / 0.16