

搭建高性能计算环境（四）、应用软件的安装之VASP

- 1, 将需要的软件包上传vasp.5.2.12.tar.gz、vasp.5.lib.tar.gz、benchmark.Hg.tar.gz。
- 2, 创建vasp目录并解压软件包。

```
mkdir /opt/vasp
cd /opt/vasp
tar xvf ~/vasp.5.lib.tar.gz
tar xvf ~/vasp.5.2.12.tar.gz
```

3,编译lib

```
cd vasp.5.lib/
cp makefile.linux_ifc_P4 makefile
修改makefile
make
```

修改后的makefile:

```
.SUFFIXES: .inc .f .F
#-----
# Makefile for Portland Group F90/HPF compiler
# the makefile was tested only under Linux on Intel platforms
# however it might work on other platforms as well
#
# this release of vasp.4.lib contains lapack v2.0
# this can be compiled with pgf90 compiler if the option -O1 is used
#
# Mind: one user reported that he had to copy preclib.F diolib.F
# dlexlib.F and drdatab.F to the directory vasp.4.4, compile the files
# there and link them directly into vasp
# for no obvious reason these files could not be linked from the library
#
#-----

# C-preprocessor
CPP      = gcc -E -P -C $*.F >$*.f
FC=ifort

CFLAGS = -O3
FFLAGS = -O3 -ip -no-prec-div -funroll-loops -xHost -heap-arrays 64
FREE    = -FR

DOBJ = preclib.o timing_.o derrf_.o dclock_.o diolib.o dlexlib.o drdatab.o

#-----
# general rules
#-----

libdmy.a: $(DOBJ) lapack_double.o linpack_double.o lapack_atlas.o
        -rm libdmy.a
        ar vg libdmy.a $(DOBJ)

# files which do not require autouble
```

公告

昵称: iDove
园龄: 1年9个月
粉丝: 5
关注: 1
[+加关注](#)

< 2016年9月 >						
日	一	二	三	四	五	六
28	29	30	31	1	2	3
4	5	6	7	8	9	10
11	12	13	14	15	16	17
18	19	20	21	22	23	24
25	26	27	28	29	30	1
2	3	4	5	6	7	8

搜索

常用链接

- 我的随笔
- 我的评论
- 我的参与
- 最新评论
- 我的标签

我的标签

- HPC(6)
- md(3)
- linux(2)
- lammps(1)
- mpi(1)
- MS(1)
- ssh(1)
- vasp(1)
- 分子动力学(1)
- 量化计算(1)
- 更多

随笔分类

- Hadoop
- HPC(9)
- Linux(5)

```
lapack_min.o: lapack_min.f
    $(FC) $(FFLAGS) $(NOFREE) -c lapack_min.f
lapack_double.o: lapack_double.f
    $(FC) $(FFLAGS) $(NOFREE) -c lapack_double.f
lapack_single.o: lapack_single.f
    $(FC) $(FFLAGS) $(NOFREE) -c lapack_single.f
lapack_atlas.o: lapack_atlas.f
    $(FC) $(FFLAGS) $(NOFREE) -c lapack_atlas.f
linpack_double.o: linpack_double.f
    $(FC) $(FFLAGS) $(NOFREE) -c linpack_double.f
linpack_single.o: linpack_single.f
    $(FC) $(FFLAGS) $(NOFREE) -c linpack_single.f

.c.o:
    $(CC) $(CFLAGS) -c $*.c

.F.o:
    $(CPP)
    $(FC) $(FFLAGS) $(FREE) $(INCS) -c $*.f

.F.f:
    $(CPP)


.f.o:
    $(FC) $(FFLAGS) $(FREE) $(INCS) -c $*.f
```



4, 编译vasp

```
cd ../vasp.5.2/
cp makefile.linux_ifc_P4 makefile
修改makefile
make
```

修改后的makefile:

```

.SUFFIXES: .inc .f .f90 .F
#-----
# Makefile for Intel Fortran compiler for Pentium/Athlon/Opteron
# bases systems
# we recommend this makefile for both Intel as well as AMD systems
# for AMD based systems appropriate BLAS and fftw libraries are
# however mandatory (whereas they are optional for Intel platforms)
#
# The makefile was tested only under Linux on Intel and AMD platforms
# the following compiler versions have been tested:
# - ifc.7.1 works stable somewhat slow but reliably
# - ifc.8.1 fails to compile the code properly
# - ifc.9.1 recommended (both for 32 and 64 bit)
# - ifc.10.1 partially recommended (both for 32 and 64 bit)
# tested build 20080312 Package ID: l_fc_p_10.1.015
# the gamma only mpi version can not be compiles
# using ifc.10.1
#
# it might be required to change some of library pathes, since
# LINUX installation vary a lot
# Hence check ***ALL*** options in this makefile very carefully
#-----
#
# BLAS must be installed on the machine
# there are several options:
# 1) very slow but works:
# retrieve the lapackage from ftp.netlib.org
# and compile the blas routines (BLAS/SRC directory)
# please use g77 or f77 for the compilation. When I tried to
# use pgf77 or pgf90 for BLAS, VASP hang up when calling
# ZHEEV (however this was with lapack 1.1 now I use lapack 2.0)
# 2) more desirable: get an optimized BLAS
```

随笔档案

2014年11月 (10)

最新评论

1. Re:搭建高性能计算环境 (四)、应用软件的安装之VASP

非常感谢楼主的详细安装信息,按照楼主的方法成功的安装了MS,但是在编译VSAP时报错。报错信息如下: ./preprocess base.f90 - DHOST=\"LinuxIFC\" -DCACHE.....

--安风琴

2. Re:搭建高性能计算环境 (四)、应用软件的安装之VASP

非常感谢楼主,我找了好久,没想到楼主这里写的这么详细!一定要顶上去!!

--huoxing487

3. Re:搭建高性能计算环境 (一)、Linux操作系统的安装和配置

博主,你真辛苦,这里的10篇笔记对我们做计算的人来说,是极大的帮助。只是第一,二篇的图片不能显示。

--coffeetan

阅读排行榜

1. 搭建高性能计算环境 (四)、应用软件的安装之VASP(989)
2. 搭建高性能计算环境 (三)、安装intel编译器和mpi(909)
3. 搭建高性能计算环境 (九)、应用软件的安装之gaussian 09(596)
4. 搭建高性能计算环境 (八)、应用软件的安装之gromacs(565)
5. 搭建高性能计算环境 (五)、应用软件的安装之Amber12(528)

评论排行榜

1. 搭建高性能计算环境 (四)、应用软件的安装之VASP(2)
2. 搭建高性能计算环境 (一)、Linux操作系统的安装和配置(1)

推荐排行榜

1. 搭建高性能计算环境 (四)、应用软件的安装之VASP(1)
2. 搭建高性能计算环境 (十)、应用软件的安装之Wien2k(1)
3. 搭建高性能计算环境 (九)、应用软件的安装之gaussian 09(1)

```

#
# the two most reliable packages around are presently:
# 2a) Intels own optimised BLAS (PIII, P4, PD, PC2, Itanium)
#      http://developer.intel.com/software/products/mkl/
#      this is really excellent, if you use Intel CPU's
#
# 2b) probably fastest SSE2 (4 GFlops on P4, 2.53 GHz, 16 GFlops PD,
#      around 30 GFlops on Quad core)
#      Kazushige Goto's BLAS
#      http://www.cs.utexas.edu/users/kgoto/signup_first.html
#      http://www.tacc.utexas.edu/resources/software/
#
#-----

# all CPP processed fortran files have the extension .f90
SUFFIX=.f90

#-----

# fortran compiler and linker
#-----

FC=ifc
# fortran linker
FCL=$(FC)

#-----

# whereis CPP ?? (I need CPP, can't use gcc with proper options)
# that's the location of gcc for SUSE 5.3
#
# CPP_   = /usr/lib/gcc-lib/i486-linux/2.7.2/cpp -P -C
#
# that's probably the right line for some Red Hat distribution:
#
# CPP_   = /usr/lib/gcc-lib/i386-redhat-linux/2.7.2.3/cpp -P -C
#
# SUSE X.X, maybe some Red Hat distributions:

CPP_ = ./preprocess <$.F | /usr/bin/cpp -P -C -traditional >${SUFFIX}

#-----

# possible options for CPP:
# NGXhalf      charge density   reduced in X direction
# WNGXhalf     gamma point only reduced in X direction
# avoidalloc   avoid ALLOCATE if possible
# PGF90        work around some for some PGF90 / IFC bugs
# CACHE_SIZE   1000 for PII,PIII, 5000 for Athlon, 8000-12000 P4, PD
# RPROMU_DGEMV use DGEMV instead of DGEMM in RPRO (depends on used BLAS)
# RACCMU_DGEMV use DGEMV instead of DGEMM in RACC (depends on used BLAS)
# tbdyn        MD package of Tomas Bucko
#-----

CPP   = $(CPP_) -DHOST="LinuxIFC" \
        -DCACHE_SIZE=12000 -DPGF90 -Davoidalloc -DNGXhalf \
#
        -DRPROMU_DGEMV -DRACCMU_DGEMV

#-----

# general fortran flags (there must a trailing blank on this line)
# byterecl is strictly required for ifc, since otherwise
# the WAVECAR file becomes huge
#-----

FFLAGS = -O3 -ip -no-prec-div -funroll-loops -xHost -heap-arrays 64

#-----

# optimization
# we have tested whether higher optimisation improves performance

```

```
# -axK SSE1 optimization, but also generate code executable on all mach.
#       xK improves performance somewhat on XP, and a is required in order
#       to run the code on older Athlons as well
# -xW SSE2 optimization
# -axW SSE2 optimization, but also generate code executable on all mach.
# -tpp6 P3 optimization
# -tpp7 P4 optimization
# -----

# ifc.9.1, ifc.10.1 recommended
OFLAG=

OFLAG_HIGH = $(OFLAG)
OBJ_HIGH =
OBJ_NOOPT =
DEBUG = -FR -O0
INLINE = $(OFLAG)

# -----

# the following lines specify the position of BLAS and LAPACK
# VASP works fastest with the libgoto library
# so that's what we recommend
# -----

# mkl.10.0
# set -DRPROMU_DGEMV -DRACCMU_DGEMV in the CPP lines
BLAS=-L/opt/intel/mkl/lib/intel64 -lmkl_core -lmkl_sequential -lmkl_intel_lp64

# even faster for VASP Kazushige Goto's BLAS
# http://www.cs.utexas.edu/users/kgoto/signup_first.html
# parallel goto version requires sometimes -libverbs
#BLAS= /opt/libs/libgoto/libgoto.so

# LAPACK, simplest use vasp.5.lib/lapack_double
LAPACK= ../vasp.5.lib/lapack_double.o

# use the mkl Intel lapack
#LAPACK= -lmkl_lapack

# -----

LIB = -L../vasp.5.lib -ldmy \
      ../vasp.5.lib/linpack_double.o $(LAPACK) \
      $(BLAS)

# options for linking, nothing is required (usually)
LINK =

# -----

# fft libraries:
# VASP.5.2 can use fftw.3.1.X (http://www.fftw.org)
# since this version is faster on P4 machines, we recommend to use it
# -----

FFT3D = fft3dfurth.o fft3dlib.o

# alternatively: fftw.3.1.X is slightly faster and should be used if available
#FFT3D = fftw3d.o fft3dlib.o /opt/libs/fftw-3.1.2/lib/libfftw3.a

# =====
# MPI section, uncomment the following lines until
#       general rules and compile lines
# presently we recommend OPENMPI, since it seems to offer better
# performance than lam or mpich
#
```

```
# !!! Please do not send me any queries on how to install MPI, I will
# certainly not answer them !!!!
#-----
#-----
# fortran linker for mpi
#-----

FC=mpiifort
FCL=$(FC)

#-----

# additional options for CPP in parallel version (see also above):
# NGZhalf          charge density   reduced in Z direction
# wNGZhalf         gamma point only reduced in Z direction
# scaLAPACK         use scaLAPACK (usually slower on 100 Mbit Net)
# avoidalloc       avoid ALLOCATE if possible
# PGF90            work around some for some PGF90 / IFC bugs
# CACHE_SIZE       1000 for PII,PIII, 5000 for Athlon, 8000-12000 P4, PD
# RPRMU_DGEMV      use DGEMV instead of DGEMM in RPRO (depends on used BLAS)
# RACCMU_DGEMV     use DGEMV instead of DGEMM in RACC (depends on used BLAS)
# tbdyn            MD package of Tomas Bucko
#-----

#-----

CPP      = $(CPP_) -DMPI -DHOST=\"LinuxIFC\" -DIFC \
          -DCACHE_SIZE=12000 -DPGF90 -Davoidalloc -DNGZhalf \
          -DMPI_BLOCK=8000
#      -DRPRMU_DGEMV -DRACCMU_DGEMV

#-----

# location of SCALAPACK
# if you do not use SCALAPACK simply leave that section commented out
#-----

#BLACS=$(HOME)/archives/SCALAPACK/BLACS/
#SCA_=$(HOME)/archives/SCALAPACK/SCALAPACK

#SCA=$(SCA_)/libscalapack.a \
# $(BLACS)/LIB/blacsF77init_MPI-LINUX-0.a $(BLACS)/LIB/blacs_MPI-LINUX-0.a $(BLACS)/LIB/blacsF77init_MPI-LINUX-0.a

SCA=

#-----

# libraries for mpi
#-----

LIB      = -L../vasp.5.lib -ldmy \
          ../vasp.5.lib/linpack_double.o $(LAPACK) \
          $(SCA) $(BLAS)

# FFT: fftmpi.o with fft3dlib of Juergen Furthmuller
FFT3D    = fftmpi.o fftmpi_map.o fft3dfurth.o fft3dlib.o

# alternatively: fftw.3.1.X is slightly faster and should be used if available
#FFT3D    = fftmpi.o fftmpi_map.o fftw3d.o fft3dlib.o /opt/libs/fftw-3.1.2/lib/libfftw3.a

#-----

# general rules and compile lines
#-----

BASIC=    symmetry.o symlib.o  lattlib.o  random.o

SOURCE=    base.o      mpi.o      smart_allocate.o      xml.o \
           constant.o jacobi.o   main_mpi.o  scala.o \
```

```

asa.o      lattice.o  poscar.o  ini.o  mgrid.o  xclib.o  vdw_n1.o  xclib_grad.o \
radial.o   pseudo.o  gridq.o   ebs.o   \
mkpoints.o wave.o    wave_mpi.o wave_high.o \
$(BASIC)   nonl.o     nonlr.o    nonl_high.o dfast.o   choleski2.o \
mix.o      hamil.o   xcgrad.o   xcspin.o  potex1.o  potex2.o \
constmag.o cl_shift.o relativistic.o LDAPU.o \
paw_base.o metagga.o egrad.o    pawsym.o  pawfock.o pawlhf.o  rhfatm.o  paw.o

\

mkpoints_full.o      charge.o  Lebedev-Laikov.o  stockholder.o  dipol.o  pot.o

\

dos.o      elf.o      tet.o      tetweight.o  hamil_rot.o \
steep.o    chain.o    dyna.o     sphpro.o     us.o  core_rel.o \
aedens.o   wavpre.o   wavpre_noio.o  broyden.o \
dynbr.o    rmm-diis.o  reader.o    writer.o     tutor.o  xml_writer.o \
brent.o    stufak.o    fileio.o    opergrid.o  stepver.o \
chgloc.o   fast_aug.o  fock.o      mkpoints_change.o  sym_grad.o \
mymath.o   internals.o  dynconstr.o  dimer_heyden.o  dvvtrajectory.o  vdwforcefield.o

\

hamil_high.o nmr.o     pead.o      mlwf.o      subrot.o    subrot_scf.o \
force.o      pwlhf.o    gw_model.o  optreal.o   davidson.o  david_inner.o \
electron.o   rot.o     electron_all.o  shm.o      pardens.o  paircorrection.o \
optics.o     constr_cell_relax.o  stm.o      finite_diff.o  elpol.o \
hamil_lr.o   rmm-diis_lr.o  subrot_cluster.o  subrot_lr.o \
lr_helper.o  hamil_lrf.o   elinear_response.o  ilinear_response.o \
linear_optics.o  linear_response.o \
setlocalpp.o wannier.o  electron_OEP.o  electron_lhf.o  twoelectron4.o \
ratpol.o     screened_2e.o  wave_cacher.o  chi_base.o  wpot.o  local_field.o \
ump2.o       bse_te.o  bse.o  acfdt.o  chi.o  sydmato  dmft.o \
rmm-diis_mlr.o  linear_response_NMR.o

vasp: $(SOURCE) $(FFT3D) $(INC) main.o
      rm -f vasp
      $(FCL) -o vasp main.o $(SOURCE) $(FFT3D) $(LIB) $(LINK)
makeparam: $(SOURCE) $(FFT3D) makeparam.o main.F $(INC)
      $(FCL) -o makeparam $(LINK) makeparam.o $(SOURCE) $(FFT3D) $(LIB)
zgemmtest: zgemmtest.o base.o random.o $(INC)
      $(FCL) -o zgemmtest $(LINK) zgemmtest.o random.o base.o $(LIB)
dgemmtest: dgemmtest.o base.o random.o $(INC)
      $(FCL) -o dgemmtest $(LINK) dgemmtest.o random.o base.o $(LIB)
ffttest: base.o smart_allocate.o mpi.o mgrid.o random.o ffttest.o $(FFT3D) $(INC)
      $(FCL) -o ffttest $(LINK) ffttest.o mpi.o mgrid.o random.o smart_allocate.o base.o
$(FFT3D) $(LIB)
kpoints: $(SOURCE) $(FFT3D) makekpoints.o main.F $(INC)
      $(FCL) -o kpoints $(LINK) makekpoints.o $(SOURCE) $(FFT3D) $(LIB)

clean:
      -rm -f *.g *.f *.o *.L *.mod ; touch *.F

main.o: main$(SUFFIX)
      $(FC) $(FFLAGS) $(DEBUG) $(INCS) -c main$(SUFFIX)
xcgrad.o: xcgrad$(SUFFIX)
      $(FC) $(FFLAGS) $(INLINE) $(INCS) -c xcgrad$(SUFFIX)
xcspin.o: xcspin$(SUFFIX)
      $(FC) $(FFLAGS) $(INLINE) $(INCS) -c xcspin$(SUFFIX)

makeparam.o: makeparam$(SUFFIX)
      $(FC) $(FFLAGS) $(DEBUG) $(INCS) -c makeparam$(SUFFIX)

makeparam$(SUFFIX): makeparam.F main.F
#
# MIND: I do not have a full dependency list for the include
# and MODULES: here are only the minimal basic dependencies
# if one struncture is changed then touch_dep must be called
# with the corresponding name of the structure
#
base.o: base.inc base.F

```

```
mgrid.o: mgrid.inc mgrid.F
constant.o: constant.inc constant.F
lattice.o: lattice.inc lattice.F
setex.o: setexm.inc setex.F
pseudo.o: pseudo.inc pseudo.F
poscar.o: poscar.inc poscar.F
mkpoints.o: mkpoints.inc mkpoints.F
wave.o: wave.F
nonl.o: nonl.inc nonl.F
nonlr.o: nonlr.inc nonlr.F

$(OBJ_HIGH):
    $(CPP)
    $(FC) $(FFLAGS) $(OFLAG_HIGH) $(INCS) -c $$$(SUFFIX)
$(OBJ_NOOPT):
    $(CPP)
    $(FC) $(FFLAGS) $(INCS) -c $$$(SUFFIX)

fft3dlib_f77.o: fft3dlib_f77.F
    $(CPP)
    $(F77) $(FFLAGS_F77) -c $$$(SUFFIX)

.F.o:
    $(CPP)
    $(FC) $(FFLAGS) $(OFLAG) $(INCS) -c $$$(SUFFIX)
.F$(SUFFIX):
    $(CPP)
$(SUFFIX).o:
    $(FC) $(FFLAGS) $(OFLAG) $(INCS) -c $$$(SUFFIX)

# special rules
#-----
# these special rules are cumulative (that is once failed
#   in one compiler version, stays in the list forever)
# -tpp5|6|7 P, PII-PIII, PIV
# -xW use SIMD (does not pay of on PII, since fft3d uses double prec)
# all other options do no affect the code performance since -O1 is used

fft3dlib.o : fft3dlib.F
    $(CPP)
    $(FC) -FR -lowercase -O2 -c $$$(SUFFIX)

fft3dfurth.o : fft3dfurth.F
    $(CPP)
    $(FC) -FR -lowercase -O1 -c $$$(SUFFIX)

fftw3d.o : fftw3d.F
    $(CPP)
    $(FC) -FR -lowercase -O1 -c $$$(SUFFIX)

wave_high.o : wave_high.F
    $(CPP)
    $(FC) -FR -lowercase -O1 -c $$$(SUFFIX)

radial.o : radial.F
    $(CPP)
    $(FC) -FR -lowercase -O1 -c $$$(SUFFIX)

symlib.o : symlib.F
    $(CPP)
    $(FC) -FR -lowercase -O1 -c $$$(SUFFIX)

symmetry.o : symmetry.F
    $(CPP)
    $(FC) -FR -lowercase -O1 -c $$$(SUFFIX)
```

```
wave_mpi.o : wave_mpi.F
$(CPP)
$(FC) -FR -lowercase -O1 -c $$$(SUFFIX)

wave.o : wave.F
$(CPP)
$(FC) -FR -lowercase -O1 -c $$$(SUFFIX)

dynbr.o : dynbr.F
$(CPP)
$(FC) -FR -lowercase -O1 -c $$$(SUFFIX)

asa.o : asa.F
$(CPP)
$(FC) -FR -lowercase -O1 -c $$$(SUFFIX)

broyden.o : broyden.F
$(CPP)
$(FC) -FR -lowercase -O2 -c $$$(SUFFIX)

us.o : us.F
$(CPP)
$(FC) -FR -lowercase -O1 -c $$$(SUFFIX)

LDaPU.o : LDaPU.F
$(CPP)
$(FC) -FR -lowercase -O2 -c $$$(SUFFIX)
```

5, 添加环境变量

在/etc/profile文件末尾添加如下内容, 需要重新登录后生效

```
export PATH=/opt/vasp/vasp5.2:$PATH
```

6, 测试

准备测试文件vasp.Hg, 进入算例目录, 输入:

```
mpirun -np 4 vasp
```

如能正常计算完毕, 说明软件安装成功。

补充软件下载地址(仅供测试使用):

链接: <http://pan.baidu.com/s/1qWv4k7i> 密码: rsgh

分类: [HPC](#)

标签: [HPC](#), [vasp](#)

好文要顶

关注我

收藏该文



iDove

关注 - 1

粉丝 - 5

[+加关注](#)

1

0

« 上一篇: [搭建高性能计算环境 \(三\)、安装intel编译器和mpi](#)

» 下一篇: [搭建高性能计算环境 \(五\)、应用软件的安装之Amber12](#)

posted @ 2014-11-17 18:20 iDove 阅读(990) 评论(2) 编辑 收藏

评论列表

#1楼 2016-08-29 12:09 huoxing487

非常感谢楼主, 我找了好久, 没想到楼主这里写的这么详细! 一定要顶上去!!

支持(1) 反对(0)

#2楼 2016-08-31 14:49 安风琴

非常感谢楼主的详细安装信息，按照楼主的方法成功的安装了MS，但是在编译VASP时报错。报错信息如下：

```
./preprocess <base.F | /usr/bin/cpp -P -C -traditional >base.f90 -DHOST=\"LinuxIFC\" -DCACHE_SIZE=12000 -DPGF90 -Davoidalloc -DNGXhalf
ifort -FR -lowercase -assume byterecl -O2 -ip -ftz -c base.f90
ifort: command line remark #10148: option '-lowercase' not supported
base.f90(1): error #5082: Syntax error, found '/' when expecting one of: <LABEL> <END-OF-STATEMENT>; TYPE INTEGER REAL COMPLEX BYTE CHARACTER CLASS DOUBLE ...
-----^
base.f90(20): error #5145: Invalid blank/tab
include it implicitly at the start of every compilation. It must
-----^
base.f90(29): error #5143: Missing mandatory separating blank

-----^
base.f90(32): error #5145: Invalid blank/tab
/* We do not support C11 <threads.h>. */
-----^
base.f90(1): catastrophic error: Could not recover from previous syntax error
compilation aborted for base.f90 (code 1)
make: *** [base.o] 错误 1
还希望能得到楼主的帮助，多谢了！
```

支持(0) 反对(0)

[刷新评论](#) [刷新页面](#) [返回顶部](#)

注册用户登录后才能发表评论，请 [登录](#) 或 [注册](#)，[访问网站首页](#)。

【推荐】50万行VC++源码：大型组态工控、电力仿真CAD与GIS源码库

【活动】硅谷IT教育平台Udacity邀请您来免费上课

【推荐】移动直播百强八成都在用融云即时通讯云

【推荐】报表开发有捷径：快速设计轻松集成，数据可视化和交互

【推荐】网易云信——一天开发一个微信，独创1对1技术顾问让开发加速



最新IT新闻：

- 三星专利：让智能手机同时运行Android和Windows Mobile系统
- 施普林格·自然集团回应：韩春雨事件尚无最终结果
- 苹果香港网站页面意外出现新一代iPhone正式名称
- 2016微博用户研究：新欢、旧爱、核心价值与迫切之疾
- 沃尔沃将向其它汽车制造商出售无人驾驶汽车技术

» 更多新闻...



最新知识库文章：

- 程序猿媳妇儿注意事项
- 可是姑娘，你为什么要编程呢？
- 知其所以然（以算法学习为例）
- 如何给变量取个简短且无歧义的名字
- 编程的智慧

» 更多知识库文章...

Copyright ©2016 iDove