


搜須 Q 💆 签到 登录 | 注册

友情链接: 安徽DAB俱乐部 | 深圳知新信息科技有限公司 | OCP考点查询 | ALEXA

Copyright © 2016 All Rights Reserved. Powered by ZhiXinTech · 皖ICP备15000992号-4 ·


















```
#
# The archiver and the flag(s) to use when building archive (library)
# Also the ranlib routine. If your system has no ranlib, set RANLIB = echo
#

ARCH = ar
ARCHFLAGS = cr
RANLIB = ranlib
#
```





make -j 8 ARCH=Linux-x86-64-gfortran VERSION=psmp

PRILE_REUISIN="\"svn:17462\"" -D_DNTN_DIR:"\"root/cp2k 4.1/data\"" -static=libgfortran -L/root/cp2k 4.1/lib/Linux-x86-64-gfortran/psmp" -o /r
Linux-x86-64-gfortran/cp2k_psmp cp2k_o -lcp2kstart -lcp2kme -lcp2ksuare -lcp2kme -lcp2kthermostat -lcp2kme -lcp2k

最后会在~/cp2k-4.1/exe/Linux-x86-64-gfortran/目录下面生成N多个psmp文件包含cp2k.psmp

刚刚开始写博客, 也得不清楚或有问题的地方还请多多指正, QQ: 86427461

版权声明:本文为博主原创文章,未经博主允许不得转载。

标签:hpc cp2k

QQ交流群
62697850
62697716
104207940
63306533
283816689
142216823
62697977

