


## All Behavioral Patterns (Concept and Coding)



### 27. All Creational Design Patterns

Chapters: 00:00 - Introduction 00:50  
Pattern 09:05 - Singleton Design Pat



### 32. All Structural Design Patterns


Notes: Shared in the Member Co  
are Member of this channel, then pl

#### Behavioral Design Patterns:

Guides how different objects communicate with each other effectively and Distribute tasks efficiently, making software system flexible and easy to maintain.

1. State Pattern
2. Observer Pattern
3. Strategy Pattern
4. Chain of Responsibility Pattern
5. Template Pattern
6. Interpreter Pattern
7. Command Pattern
8. Iterator Pattern
9. Visitor Pattern
10. Mediator Pattern
11. Memento Pattern

1. **State Pattern:** allows an object to alter its behaviour when its internal state changes.



```
public class VendingMachine {  
    VendingState machineState;  
  
    public VendingState getMachineState() {  
        return machineState;  
    }  
  
    public void setMachineState(VendingState machineState) {  
        this.machineState = machineState;  
    }  
}
```

Has-a

```
public interface VendingState {  
    void insertCoin(VendingMachine product);  
    void dispenseItem(VendingMachine product);  
}
```


is-a

is-a


```
public class IdleState implements VendingState{  
  
    @Override  
    public void insertCoin(VendingMachine product) {  
        //insert coin logic  
        System.out.println("Coin Inserted");  
        product.setMachineState(new WorkingState());  
    }  
  
    @Override  
    public void dispenseItem(VendingMachine product) {  
        //not doing anything here  
    }  
}
```

```
public class WorkingState implements VendingState{  
  
    @Override  
    public void insertCoin(VendingMachine product) {  
        //not doing anything here  
    }  
  
    @Override  
    public void dispenseItem(VendingMachine product) {  
        System.out.println("Product dispensed");  
        //set any other state if applicable  
    }  
}
```


2. **Observer Pattern:** in this an object (Observable) maintains a list of its dependents (observers) and notifies them of any changes in its state.




3. **Strategy Pattern:** helps to define multiple algorithm for the task and we can select any algorithm depending on the situation.



4. **Chain of Responsibility Pattern:** allows multiple objects to handle a request without the sender needing to know which object will ultimately process it.



5. **Template Method Pattern:** when you want all classes to follow specific steps to process the tasks but provide flexibility that each class can have their own logic in that specific step.




**6. Interpreter Pattern:** Defines a grammar for interpreting and evaluating an expression.



Some can interpret this:

- STOP
- Hi
- Number 5
- Etc..

based on CONTEXT interpret happens.



```

public class Client {
    public static void main(String args[]) {
        //Initialize the context
        Context context = new Context();
        context.put("variable1", 10);
        context.put("variable2", 20);
        context.put("variable3", 30);

        //Now
        AbstractExpression expression = new MultiplyNonTerminalExpression(
            new NumberTerminalExpression("10"), new NumberTerminalExpression("20"));
        System.out.println(expression.interpret(context));
    }
}

```

```

public class Context {
    Map<String, Integer> contextMap = new HashMap<>();

    public void put(String strVariable, int intValue) {
        contextMap.put(strVariable, intValue);
    }

    public int get(String strVariable) {
        return contextMap.get(strVariable);
    }
}

```

```

public interface AbstractExpression {
    int interpret(Context context);
}

```

```

public class NumberTerminalExpression implements AbstractExpression {
    String stringValue;

    NumberTerminalExpression(String stringVal) {
        this.stringValue = stringVal;
    }

    @Override
    public int interpret(Context context) {
        return context.get(stringValue);
    }
}

```

```

public class MultiplyNonTerminalExpression implements AbstractExpression {
    AbstractExpression leftExpression;
    AbstractExpression rightExpression;

    public MultiplyNonTerminalExpression(AbstractExpression leftExpression, AbstractExpression rightExpression) {
        this.leftExpression = leftExpression;
        this.rightExpression = rightExpression;
    }

    @Override
    public int interpret(Context context) {
        return leftExpression.interpret(context) * rightExpression.interpret(context);
    }
}

```

- 7. Command Pattern:** Turns requests (commands) into objects, allowing you to either parametrize or queue them. This will help to decouple the request Sender and receiver.

**Problem with below code:**

process of turning on AC is simple, but if there are more steps, client has to aware all of that, which is not good. So Sender and Receiver are not decoupled.

```
public class Main {  
    public static void main(String[] args) {  
  
        AirConditioner ac = new AirConditioner();  
        ac.turnOnAC();  
        ac.setTemperature(24);  
        ac.turnOffAC();  
    }  
}
```

```
public class AirConditioner {  
  
    boolean isOn;  
    int temperature;  
  
    public void turnOnAC(){  
        isOn = true;  
        System.out.println("AC is ON");  
    }  
  
    public void turnOffAC(){  
        isOn = false;  
        System.out.println("AC is OFF");  
    }  
  
    public void setTemperature(int temp){  
        this.temperature = temp;  
        System.out.println("Temperature changed to:" + temperature) ;  
    }  
}
```

**Solution with Command Pattern:**

**Invoker**

```
public class MyRemoteControl {  
    ICommand command;  
    MyRemoteControl(){  
    }  
  
    public void setCommand(ICommand command){  
        this.command = command;  
    }  
  
    public void pressButton() {  
        command.execute();  
    }  
}
```

**Command**

```
public interface ICommand {  
    public void execute();  
}
```

**Receiver**

```
public class AirConditioner {  
    boolean isOn;  
    int temperature;  
  
    public void turnOnAC(){  
        isOn = true;  
        System.out.println("AC is ON");  
    }  
  
    public void turnOffAC(){  
        isOn = false;  
        System.out.println("AC is OFF");  
    }  
  
    public void setTemperature(int temp){  
        this.temperature = temp;  
        System.out.println("Temperature changed to:" + temperature) ;  
    }  
}
```

**Client**


```
public class Main {  
    public static void main(String[] args) {  
  
        //AC object  
        AirConditioner airConditioner = new AirConditioner();  
  
        //remote  
        MyRemoteControl remoteObj = new MyRemoteControl();  
  
        //create the command and press the button  
        remoteObj.setCommand(new TurnACOnCommand(airConditioner));  
        remoteObj.pressButton();  
    }  
}
```

```
public class TurnACOnCommand implements ICommand{  
    AirConditioner ac;  
    TurnACOnCommand(AirConditioner ac){  
        this.ac = ac;  
    }  
  
    @Override  
    public void execute() {  
        ac.turnOnAC();  
    }  
}
```

```
public class TurnACOffCommand implements ICommand{  
    AirConditioner ac;  
    TurnACOffCommand(AirConditioner ac){  
        this.ac = ac;  
    }  
  
    @Override  
    public void execute() {  
        ac.turnOffAC();  
    }  
}
```

**8. Iterator Pattern:** that provides a way to access element of a Collection sequentially without exposing the underlying representation of the collection.


### Understand the Need for an ITERATOR Pattern:



```
public class LinkedHashSetExample {  
  
    public static void main(String args[]){  
  
        Set<Integer> intSet = new LinkedHashSet<>();  
        intSet.add(2);  
        intSet.add(77);  
        intSet.add(82);  
        intSet.add(63);  
        intSet.add(5);  
  
        Iterator<Integer> iterable = intSet.iterator();  
        while(iterable.hasNext()){  
            int val = iterable.next();  
            System.out.println(val);  
        }  
    }  
}
```



### Iterator UML with an Example:



```
public class Client {
    public static void main(String[] args) {
        List<Book> booksList = Arrays.asList(
            new Book( price: 100, bookName: "Science"),
            new Book( price: 200, bookName: "Maths"),
            new Book( price: 300, bookName: "GK"),
            new Book( price: 400, bookName: "Drawing")
        );

        Library lib = new Library(booksList);
        Iterator iterator = lib.createIterator();

        while (iterator.hasNext()) {
            Book book = (Book) iterator.next();
            System.out.println(book.getBookName());
        }
    }
}
```

```
public class Book {
    private int price;
    private String bookName;

    Book(int price, String bookName){
        this.price = price;
        this.bookName = bookName;
    }

    public int getPrice() {
        return price;
    }

    public String getBookName() {
        return bookName;
    }
}
```

**9. Visitor Pattern:** Allows adding new operations to existing classes without modifying them and encourage OPEN/CLOSED principle.

What's the problem with the below class?

```
public class HotelRoom {



    public void getRoomPrice(){
        //price computation logic
    }

    public void initiateRoomMaintenance(){
        //start room maintenance
    }

    public void reserveRoom(){
        //perform operation to reserve the room
    }

    //many more operations can come over the time
}
```


UML of Visitor Pattern





**10. Mediator Pattern:** It encourage loose coupling by keeping objects from referring to each other explicitly and allows them to *communicate through a mediator* object.

UML



Lets use, Online Auction System Example to understand the UML

```

//this is Mediator Interface
public interface AuctionMediator {
    void addBidder(Colleague bidder);
    void placeBid(Colleague bidder, int bidAmount);
}
    
```

```

public interface Colleague {
    void placeBid(int bidAmount);
    void receiveBidNotification(int bidAmount);
    String getName();
}
    
```

```

//Mediator Concrete Class
public class Auction implements AuctionMediator {
    List<Colleague> colleagues = new ArrayList<>();

    @Override
    public void addBidder(Colleague bidder) {
        colleagues.add(bidder);
    }

    @Override
    public void placeBid(Colleague bidder, int bidAmount) {
        for(Colleague colleague : colleagues){
            if(!colleague.getName().equals(bidder.getName())){
                colleague.receiveBidNotification(bidAmount);
            }
        }
    }
}
    
```

```

public class Bidder implements Colleague {
    String name;
    AuctionMediator auctionMediator;

    Bidder(String name, AuctionMediator auctionMediator) {
        this.name = name;
        this.auctionMediator = auctionMediator;
        auctionMediator.addBidder(this);
    }

    @Override
    public void placeBid(int bidAmount) {
        auctionMediator.placeBid(this, bidAmount);
    }

    @Override
    public void receiveBidNotification(int bidAmount) {
        System.out.println("Bidder: " + name + " got the notification that someone has put bid of : " + bidAmount);
    }

    @Override
    public String getName(){
        return name;
    }
}
    
```

11. **Memento Pattern:** Provides an ability to revert an object to a previous state i.e. UNDO capability. and it does not expose the object internal implementation.

### Major Components in "MEMEMTO PATTERN"



#### Originator:


- It represents the object, for which state need to be saved and restored.
- Expose Methods to Save and Restore its state using Memento object.

#### Memento:

- It represents an Object which holds the state of the Originator.

#### Caretaker:

- Manages the list of States (i.e. list of Memento)



```
//Caretaker
public class ConfigurationCaretaker {

    List<ConfigurationMemento> history = new ArrayList<>();

    public void addMemento(ConfigurationMemento memento) {
        history.add(memento);
    }

    public ConfigurationMemento undo() {
        if (!history.isEmpty()) {
            int lastMementoIndex = history.size() - 1;
            //get the last memento from the list
            ConfigurationMemento lastMemento = history.get(lastMementoIndex);
            //remove the last memento from the list now
            history.remove(lastMementoIndex);
            return lastMemento;
        }
        return null;
    }
}
```

```
//Memento
public class ConfigurationMemento {

    int height;
    int width;

    public ConfigurationMemento(int height, int width){
        this.height = height;
        this.width = width;
    }

    public int getHeight() {
        return height;
    }

    public int getWidth() {
        return width;
    }
}
```

```
//Originator
public class ConfigurationOriginator {

    int height;
    int width;

    ConfigurationOriginator(int height, int width){
        this.height = height;
        this.width = width;
    }

    public void setHeight(int height) {
        this.height = height;
    }

    public void setWidth(int width) {
        this.width = width;
    }

    public ConfigurationMemento createMemento(){
        return new ConfigurationMemento(this.height, this.width);
    }

    public void restoreMemento(ConfigurationMemento mementoToBeRestored){
        this.height = mementoToBeRestored.height;
        this.width = mementoToBeRestored.width;
    }
}
```

```

public class Client {

    public static void main(String args[]){

        ConfigurationCareTaker careTakerObject = new ConfigurationCareTaker();
        //initiate State of the originator
        ConfigurationOriginator originatorObject = new ConfigurationOriginator( height: 5, width: 10);

        //save it
        ConfigurationMemento snapshot1 = originatorObject.createMemento();

        //add it to history
        careTakerObject.addMemento(snapshot1);

        //originator changing to new state
        originatorObject.setHeight(7);
        originatorObject.setWidth(12);

        //save it
        ConfigurationMemento snapshot2 = originatorObject.createMemento();

        //add it to history
        careTakerObject.addMemento(snapshot2);

        //originator changing to new state
        originatorObject.setHeight(9);
        originatorObject.setWidth(14);

        //UNDO
        ConfigurationMemento restoredStateMementoObj = careTakerObject.undo();
        originatorObject.restoreMemento(restoredStateMementoObj);

        System.out.println("height: " + originatorObject.height + " width: " + originatorObject.width );

    }
}

```