

development_history

- [MIDAS GUI — Development History](#)
 - [How to use this document](#)
 - [Change → commit quick-reference index](#)
 - [Packaging / build / launch](#)
 - [Data Viewer \(Tab 0\)](#)
 - [Mask Builder \(Tab 1\)](#)
 - [Calibrate \(Tab 2\) / Refinement \(Tab 3\)](#)
 - [Batch Integrate \(Tab 4\)](#)
 - [PDF Analysis \(Tab 6\)](#)
 - [Pump Probe \(TR-XRD\) tab](#)
 - [Cross-cutting UI / infrastructure](#)
 - [Stability / performance / consistency \(review-driven, phases 1–3\)](#)
 - [Documentation](#)
 - [Chronological commit log \(oldest → newest\)](#)
 - [f19ee8c — Initial release: midas_gui v1.0.0 \(2026-06-30\)](#)
 - [3cd1f36 — setuptools.build_meta backend \(2026-06-30\)](#)
 - [2e9f419 — add launch.py standalone launcher \(2026-06-30\)](#)
 - [fc754d0 — Linux style fix for invisible files/folders \(2026-06-30\)](#)
 - [acf0866 — Data Viewer: radial plot, ring picking, zoom persistence \(2026-06-30\)](#)
 - [d9e527e — preserve zoom/pan across frames \(2026-06-30\)](#)
 - [d50b588 — Data Viewer: intensity mask, calib loading, click-to-draw ring \(2026-07-01\)](#)
 - [916ece2 — startup crash diagnostics + robust launcher \(2026-07-01\)](#)
 - [7d010d7 — Abort buttons + dark/bright/background + auto-load \(2026-07-01\)](#)
 - [e862135 — MIDAS-style packaging \(2026-07-01\)](#)
 - [41f28f5 — compact lattice, pixel-weighted azimuthal mean, readable menus \(2026-07-06\)](#)
 - [cd05ced — docs: not-on-PyPI install instructions \(2026-07-06\)](#)
 - [2e5f7c9 — docs: add gui_documentation.md \(2026-07-06\)](#)
 - [75c135c — docs: add gui_documentation.pdf \(2026-07-06\)](#)
 - [aceb40f — docs: install via pip install midas_suite \(2026-07-06\)](#)
 - [aa9395e — Unified Data-Loader panel + 3-panel splitter \(tabs 0/2/3/4\) \(2026-07-07\)](#)
 - [b381d8d — Tab 6 polyatomic midas_pdf pipeline + calibration loading \(2026-07-08\)](#)
 - [1149afc — Batch live MONITOR + legend; PDF real-data default \(2026-07-08\)](#)
 - [524f5f1 — Batch Clear results + inline labels; implementation-details doc \(2026-07-09\)](#)
 - [10df828 — Mask unbounded \$\sigma\$ + split auto-mask; Viewer↔Calibrate geometry \(2026-07-09\)](#)
 - [d135c80 — Batch stacked-profiles: themes, point+line, x-units, grid \(2026-07-09\)](#)
 - [2385f75 — Batch waterfall R/2 \$\theta\$ /Q axis; Mask 3-D HDF5 stack \(2026-07-10\)](#)
 - [b628446 — clickable \$\lambda\$ label with K-edge foil menu \(2026-07-10\)](#)
 - [108ea7d — Data Viewer projection Skip-frames + compact fields \(2026-07-10\)](#)
 - [3248638 — clickable px label with detector pixel-size menu \(2026-07-10\)](#)
 - [2b7a695 — Data Viewer intensity-statistics panel + histogram \(2026-07-10\)](#)
 - [d30be2c — per-user configuration system + Preferences dialog \(2026-07-12\)](#)
 - [399f3d7 — Stability: clean worker shutdown, no terminate\(\), stdout guard \(2026-07-12\)](#)
 - [4462ee1 — Performance: waterfall O\(N\), debounce, caching \(2026-07-12\)](#)
 - [8846619 — Consistency: dedupe maps/writer, align lattices \(2026-07-12\)](#)
 - [590b410 — Modular tabs + Pump Probe \(TR-XRD\) tab + plot quality \(2026-07-12\)](#)
 - [6d6f3fb — docs: add development_history.md/.pdf \(2026-07-13\)](#)
 - [d5fafd8 — UI scaling: user-adjustable whole-interface zoom \(HiDPI / 4K\) \(2026-07-13\)](#)
 - [c4e1c12 — Display Lsd in mm \(calculations & files stay in \$\mu\text{m}\$ \) \(2026-07-13\)](#)
 - [d6df1f8 — Fix “Populating font family aliases” startup warning \(2026-07-13\)](#)

- [455ca4e — Calibrate: multi-column results readout + Send-to-Data-Viewer \(2026-07-13\)](#)
- [7e157e0 — Ship test_data; hide four optional tabs by default \(2026-07-14\)](#)
- [6332b3d — Fix launch crash on fresh Linux/Windows \(colormap w/o matplotlib\) \(2026-07-14\)](#)
- [72a1770 — env: drop midas_suite \(unblocks conda env create\) \(2026-07-14\)](#)
- [68313f8 — Pin environment.yml to a verified NumPy-1 set + README recreate steps \(2026-07-14\)](#)
- [3a6ecb9 — Calibrate Results: all-text multi-column readout \(drop distortion table\) \(2026-07-14\)](#)
- [b1642fa — Fix calibration TypeError \(initial_BC_y\) + add scikit-image \(2026-07-14\)](#)
- [df544d2 — Data Viewer: tilt/distortion-aware radial integration \(2026-07-14\)](#)
- [bc86d74 — Data Viewer: Top-N pixels + mask-aware stats + full-geometry receive \(2026-07-19\)](#)
- [b0a5cc3 — Calibrate: per-coefficient distortion, frame averaging, seed feedback \(2026-07-19\)](#)
- [b6f1681 — Batch: read-only “Calibration values” card \(2026-07-19\)](#)
- [49623ae — Pump Probe: publication plotting, delay colour-bar, default mask \(2026-07-19\)](#)
- [b251ca8 — chore: gitignore context, internal docs, large sample sets \(2026-07-19\)](#)
- [1769f69 — Data Viewer: live PV stream \(Live Data card\) \(2026-07-20\)](#)
- [0b4326d — Fix: cap native thread pools to prevent calibration crash \(2026-07-22\)](#)
- [234ded9 — Live viewer: preserve manual colormap/level changes across frames \(2026-07-24\)](#)
- [69f470c — Data Viewer: widen the image/radial-plot splitter handle \(2026-07-24\)](#)
- [96f8add — Radial profile: stop forcing Y-axis min to -1000 on every update \(2026-07-24\)](#)
- [3eb4a44 — Calibrate: recolor Pick-Ring fit overlay to blue \(2026-07-24\)](#)
- [ecf6d01 — Data Viewer: make Simulate rings a live toggle instead of one-shot \(2026-07-24\)](#)
- [aa82cb6 — Preferences: add Devices tab; Data Viewer Live PV becomes a device dropdown \(2026-07-24\)](#)
- [Rollback recipes \(common intents\)](#)

MIDAS GUI — Development History

A commit-by-commit record of what changed and when, so you can (a) find **when** a particular behaviour/feature entered the code and (b) know **what to roll back** to undo a specific effect.

Keep this file updated when you add commits: append a new entry at the bottom of the chronological log and add a row to the quick-reference index. Regenerate the PDF the same way as the other docs (pandoc + headless Chrome) if you keep one.

How to use this document

- **Find when a change landed:** search the change → commit index below, or `git log --oneline --<path>` for a specific file, or `git log -S"<code string>"` to find the commit that introduced/removed a string.
- **See a commit’s exact diff:** `git show <hash>` (whole commit) or `git show <hash> -- <path>` (one file).
- **Undo one commit cleanly (keeps later history):** `git revert <hash>`. For a range: `git revert <oldest>^..<newest>`.
- **Undo just one file back to a commit:** `git checkout <hash> -- <path>` then commit. To see the file *as of* a commit without changing anything: `git show <hash>:<path>`.
- **Hard reset to a point (destructive — local only, never on pushed history):** `git reset --hard <hash>`. Prefer `git revert` on a shared branch.
- **Dependencies matter.** Many later commits build on earlier ones (e.g. the unified data-loader, the config overlay). The “Roll back” note on each entry flags when reverting will disturb dependents.

Branch: main. All commits are authored by Dishant Beniwal (AI pair-authored). Dates are commit dates (YYYY-MM-DD).

Change → commit quick-reference index

Packaging / build / launch

Change	Commit
Initial v1.0.0 release (9-tab app, all backends)	f19ee8c
setuptools.build_meta backend (broader pip compat)	3cd1f36
launch.py standalone launcher	2e9f419
Startup crash diagnostics + robust launcher (Windows)	916ece2
MIDAS-style packaging (LICENSE, pyproject, release.sh, smoke tests)	e862135
Ship test_data sample data in the repo (fresh clone works out of the box)	7e157e0
Drop midas_suite from env (unblock conda env create; backends via -e .)	72a1770
Pin environment.yml to verified NumPy-1 set + README recreate steps	68313f8

Data Viewer (Tab 0)

Change	Commit
Radial-integration plot, beam-centre ring picking, zoom persistence	acf0866
Zoom/pan preserved across frames (autoRange off)	d9e527e
Intensity-range mask, calibration-file loading, click-to-draw ring	d50b588
Compact 3-per-row lattice + cubic quick-set; mask default max(99.99pct,1e5)	41f28f5
Projection Skip-frames field; compact geometry/intensity fields; Lsd separators	108ea7d
Intensity-statistics panel + histogram (bottom of loader)	2b7a695
Tilt/distortion-aware radial integration when a calibration is loaded	df544d2
Data Viewer Top-N brightest pixels + mask-aware stats + full-geometry receive	bc86d74
Calibrate per-coefficient distortion, frame averaging, seed feedback	b0a5cc3
Batch read-only “Calibration values” card	b6f1681
Pump Probe publication plotting, delay colour-bar, default detector mask	49623ae
Gitignore local context, internal docs, large sample sets	b251ca8
Live Data card: in-tab EPICS PVA stream via pvapy, reload button	1769f69

Change	Commit
Live viewer: manual colormap/level changes now survive new frames	234ded9
Wider image/radial-plot splitter handle	69f470c
Radial profile: Y-min defaults to 0.9x data min, manual Y-range sticks	96f8add
Simulate rings is now a live toggle (auto-recomputes on param change)	ecf6d01
Live PV field becomes a device dropdown (Preferences ▶ Devices)	aa82cb6

Mask Builder (Tab 1)

Change	Commit
Unbounded σ fields; independent spatial/temporal auto-mask; Viewer↔Calibrate geometry hand-off	10df828
Temporal-constancy accepts a 3-D HDF5 (time,y,x) stack	2385f75

Calibrate (Tab 2) / Refinement (Tab 3)

Change	Commit
Abort buttons; dark/bright/background field correction; auto-load on browse	7d010d7
Calibration input accepts paramtest/poni/json	41f28f5
Load-calibration-file (geometry + λ) helpers	b381d8d
Multi-column paramtest results readout + Send-to-Data-Viewer button	455ca4e
Calibrate Results all-text (drop distortion table; named distortion, bigger font)	3a6ecb9
Fix calibrate() initial_BC_y TypeError (kwargs filter) + pin scikit-image	b1642fa
Pick-Ring fit overlay recolored blue (was same amber as simulated rings)	3eb4a44

Batch Integrate (Tab 4)

Change	Commit
Live folder MONITOR + per-file legend	1149afc
Clear results + inline per-file labels & plot controls	524f5f1
Stacked profiles: publication themes, point+line, symbol size, x-units, grid	d135c80
Waterfall R/2 θ /Q x-axis selector	2385f75

PDF Analysis (Tab 6)

Change**Commit**

Polyatomic midas_pdf reduction pipeline + vendored midas_pdf + calibration loading	b381d8d
Defaults to real I(Q) test data	1149afc

Pump Probe (TR-XRD) tab**Change****Commit**

New tab: TRR pooling + MIDAS-engine integration + $\Delta I(q, \text{delay})$ + 4 pyqtgraph views + publication-quality plots + default MIDAS calibration	590b410
---	---------

Cross-cutting UI / infrastructure**Change****Commit**

Linux visible files/folders style fix	fc754d0
Pixel-weighted azimuthal mean; readable QMenu; no-scroll combos	41f28f5
Unified Data-Loader panel + draggable 3-panel splitter (tabs 0/2/3/4)	aa9395e
Clickable λ label with K-edge foil menu	b628446
Clickable px label with detector pixel-size menu	3248638
Per-user JSON configuration system + Preferences dialog	d30be2c
Modular tab visibility (show/hide optional tabs)	590b410
User-adjustable interface scaling (HiDPI / 4K, QT_SCALE_FACTOR)	d5fafd8
Default optional tabs reduced (Corrections/PDF/Texture/Export hidden)	7e157e0
Lsd displayed in mm (calculations & calibration files stay in μm)	c4e1c12
Fix “Populating font family aliases” warning (real fixed-width fonts)	d6df1f8
Fix fresh-env launch crash — colormap resolution without matplotlib	6332b3d
Fix native Bus-error crash on Run Calibration — cap BLAS/OMP thread pools	0b4326d
Preferences ▶ Devices tab; Live PV field becomes a device dropdown	aa82cb6

Stability / performance / consistency (review-driven, phases 1–3)**Change****Commit**

Clean worker shutdown, drop QThread.terminate(), guard stdout, offload projection	399f3d7
Waterfall $O(N^2) \rightarrow O(N)$, frame-slider debounce, radial-grid + stats caching	4462ee1

Change	Commit
Dedupe distortion map + paramstest writer, align calibrant lattices, texture colormap	8846619

Documentation

Change	Commit
README not-on-PyPI clone/conda instructions	cd05ced
gui_documentation.md added	2e5f7c9
gui_documentation.pdf added	75c135c
README/environment install via pip install midas_suite	aceb40f
implementation_details.md/.pdf added	524f5f1
config_gui.md + config.example.json added	d30be2c
development_history.md/.pdf added	6d6f3fb

Chronological commit log (oldest → newest)

f19ee8c — Initial release: midas_gui v1.0.0 (2026-06-30)

Effect: First version. Nine-tab PyQt5 GUI over midas_calibrate_v2 / midas_integrate_v2: mask building, auto-calibration, refinement, batch integration + waterfall, corrections, PDF, texture, export. Entry points midas_gui / python -m midas_gui. **Files:** entire midas_gui/ package + pyproject.toml, README, environment.yml. **Roll back:** this is the root — everything depends on it; don't revert.

3cd1f36 — setuptools.build_meta backend (2026-06-30)

Effect: Build backend switched for setuptools≥61 compatibility. **Files:** pyproject.toml. **Roll back:** git revert 3cd1f36 (only affects builds).

2e9f419 — add launch.py standalone launcher (2026-06-30)

Effect: python /path/to/launch.py runs the app from anywhere. **Files:** launch.py. **Roll back:** safe to revert; later hardened by 916ece2.

fc754d0 — Linux style fix for invisible files/folders (2026-06-30)

Effect: Stylesheet fix so file/folder text is visible on Linux. **Files:** midas_gui/style.py. **Roll back:** git revert fc754d0 (cosmetic).

acf0866 — Data Viewer: radial plot, ring picking, zoom persistence (2026-06-30)

Effect: Added the radial-integration plot, beam-centre ring picking, and zoom-persistence across a stack in the Data Viewer; widened left panels. **Files:** tab_view.py (+1-line width bumps in other tabs). **Roll back:** revert to remove the Data Viewer radial plot/ring picking.

d9e527e — preserve zoom/pan across frames (2026-06-30)

Effect: Disabled pyqtgraph autoRange on redisplay so zoom/pan survive frame changes. **Files:** `widgets.py`.
Roll back: revert if you *want* auto-refit per frame.

d50b588 — Data Viewer: intensity mask, calib loading, click-to-draw ring (2026-07-01)

Effect: 99.9-pct intensity-range mask default; load calibration (`json/poni/paramtest`); click-to-draw ring; test-data defaults point at local `test_data/`. **Files:** `tab_view.py`, `widgets.py`, `helpers.py`, `constants.py`, `tab_mask.py`. **Roll back:** revert to drop these Data Viewer features (note `helpers.py` geometry parsing added here is reused later — see `b381d8d`).

916ece2 — startup crash diagnostics + robust launcher (2026-07-01)

Effect: Logs uncaught exceptions/native faults to `~/midas_gui_error.log`, prevents PyQt slot-exception aborts, isolates failing tabs, hardens the launcher. **Files:** `app.py`, `launch.py`. **Roll back:** revert only if you want raw exceptions to propagate; not recommended.

7d010d7 — Abort buttons + dark/bright/background + auto-load (2026-07-01)

Effect: Abort on calibrate/batch; dark/bright/background field correction (`file/folder/HDF5`, index-range averaging, divide/subtract); browse auto-loads, “Load” buttons removed; compact FieldSelector. **Files:** `tab_batch/calibrate/corrections/mask/pdf/refine/texture/view.py`, `widgets.py`, `workers.py`, `helpers.py`. **Roll back:** wide-reaching; reverting removes field correction + auto-load across tabs. The Abort behaviour here was later re-worked by `399f3d7` (no `terminate()`).

e862135 — MIDAS-style packaging (2026-07-01)

Effect: BSD-3 LICENSE, MIDAS-convention `pyproject.toml`, `release.sh` + `RELEASING.md`, headless tests/smoke suite. **Files:** `LICENSE`, `README.md`, `RELEASING.md`, `pyproject.toml`, `release.sh`, `tests/`. **Roll back:** revert affects packaging/tests only.

41f28f5 — compact lattice, pixel-weighted azimuthal mean, readable menus (2026-07-06)

Effect: Data Viewer 3-per-row lattice + cubic quick-set; intensity-mask default `max(99.99pct, 1e5)`; **pixel-weighted azimuthal mean** (selectable vs legacy η -bin mean) fixing off-detector-BC distortion; batch calibration accepts `paramtest/poni/json`; readable right-click menus; no-scroll combos. **Files:** `helpers.py`, `workers.py`, `tab_view/batch/calibrate/pdf/refine/texture.py`, `widgets.py`, `style.py`. **Roll back:** to undo the azimuthal-averaging change specifically, prefer editing the weighted default rather than reverting the whole commit (it bundles UI changes).

cd05ced — docs: not-on-PyPI install instructions (2026-07-06)

Effect: README clone+conda+run instructions; relative env self-install. **Files:** `README.md`, `environment.yml`.
Roll back: docs only.

2e5f7c9 — docs: add gui_documentation.md (2026-07-06)

Effect: First committed user guide. **Files:** `documentation/gui_documentation.md`. **Roll back:** docs only.

75c135c — docs: add gui_documentation.pdf (2026-07-06)

Effect: PDF build of the guide. **Files:** `documentation/gui_documentation.pdf`. **Roll back:** docs only.

aceb40f — docs: install via pip install midas_suite (2026-07-06)

Effect: Corrected backend-install instructions. **Files:** README.md, environment.yml. **Roll back:** docs only.

aa9395e — Unified Data-Loader panel + 3-panel splitter (tabs 0/2/3/4) (2026-07-07)

Effect: Shared DataLoaderPanel (Data/Dark/Bright/Background/Mask, per-mode frame controls) + MaskSelector; corrections applied on tabs 0/2/3/4; each of those tabs restructured into a draggable [Data Loader | Parameters | Display] splitter. **Files:** widgets.py (+442), tab_view/calibrate/batch/refine.py (large rewrites), app.py, helpers.py, workers.py, docs. **Roll back: high impact** — this is the base for the Batch/Calibrate/Refine and later Pump Probe layouts. Reverting breaks the 3-panel tabs and the Pump Probe tab's left panel. Avoid a blanket revert; fix forward instead.

b381d8d — Tab 6 polyatomic midas_pdf pipeline + calibration loading (2026-07-08)

Effect: PDF tab rewritten to the total-scattering pipeline; **vendored midas_pdf** under midas_gui/_vendor/ + pdf_backend.py; helpers geometry_fields_from_file / result_ns_from_geometry_file (paramtest/json/poni) used by Calibrate and PDF “Load calibration file...”. **Files:** _vendor/midas_pdf/** (new, large), pdf_backend.py, tab_pdf.py, workers.py, helpers.py, tab_calibrate.py, constants.py, pyproject.toml, docs. **Roll back:** reverting removes the PDF pipeline **and** the shared geometry-file loaders that later tabs (incl. Pump Probe via spec_from_geometry_file) rely on — revert with care.

1149afc — Batch live MONITOR + legend; PDF real-data default (2026-07-08)

Effect: MONITOR button (stream mode) watches a folder and integrates new frames via FolderMonitorWorker, reusing a cached detector map (factored build_integration_context() + write_profile(), shared with BatchWorker); per-file legend; PDF tab defaults to real I(Q). **Files:** tab_batch.py, workers.py, widgets.py, constants.py, tab_pdf.py, docs. **Roll back:** to remove MONITOR only, revert this commit — but build_integration_context() introduced here is **reused by the Pump Probe worker** (590b410), so a full revert would break Pump Probe integration.

524f5f1 — Batch Clear results + inline labels; implementation-details doc (2026-07-09)

Effect: “Clear results” button; inline per-file curve labels + line-width/font toolbar on stacked profiles; new implementation_details.md/.pdf. **Files:** tab_batch.py, widgets.py, documentation/implementation_details.*. **Roll back:** safe, localized to Batch + the new doc.

10df828 — Mask unbounded σ + split auto-mask; Viewer $\leftrightarrow$ Calibrate geometry (2026-07-09)

Effect: Removed σ upper limits; split statistical auto-mask into independent Spatial-outlier / Temporal-constancy checkboxes; geometry hand-off DataViewer.pushGeometry / Calibrate.pullGeometry $\rightarrow$ apply_geometry. **Files:** tab_mask.py, tab_view.py, tab_calibrate.py, app.py, workers.py, docs. **Roll back:** revert to restore bounded σ / combined auto-mask / no geometry hand-off.

d135c80 — Batch stacked-profiles: themes, point+line, x-units, grid (2026-07-09)

Effect: StackedProfileViewer publication/dark themes, point+line, symbol-size, R/2 θ /Q x-unit selector, grid toggle. (This viewer's styling is the template the Pump Probe plots later mirror.) **Files:** widgets.py (+228), tab_batch.py, docs. **Roll back:** localized to the Batch stacked-profile viewer.

2385f75 — Batch waterfall R/20/Q axis; Mask 3-D HDF5 stack (2026-07-10)

Effect: Waterfall x-unit selector via a converting `AxisItem + _convert_radial()`; Mask temporal-constancy reads a single 3-D (time,y,x) HDF5. **Files:** `widgets.py`, `tab_batch.py`, `tab_mask.py`, `workers.py`, `docs`. **Roll back:** `_convert_radial / _UnitAxis` introduced here are reused by the Pump Probe heatmap — don't fully revert if Pump Probe is present.

b628446 — clickable λ label with K-edge foil menu (2026-07-10)

Effect: Compact clickable “ λ ” label $\rightarrow$ K-edge foils menu (sets λ from edge energy). `constants.K_EDGE_FOILS`, `HC_KEV_A`, `helpers.make_kedge_label`. **Files:** `constants.py`, `helpers.py`, `tab_view/calibrate/pdf.py`, `docs`. **Roll back:** localized; `make_pixel_label` (next) reuses the factored helper.

108ea7d — Data Viewer projection Skip-frames + compact fields (2026-07-10)

Effect: Projection “Skip frames” field; narrower Axis/Skip/pixel fields; Lsd thousands-separators. **Files:** `tab_view.py`, `docs`. **Roll back:** localized.

3248638 — clickable px label with detector pixel-size menu (2026-07-10)

Effect: Clickable “px” label $\rightarrow$ GE/Varex/Pilatus/Eiger sizes; `constants.PIXEL_PRESETS`; factored `helpers._clickable_menu_label`. **Files:** `constants.py`, `helpers.py`, `tab_view.py`, `tab_calibrate.py`, `docs`. **Roll back:** localized.

2b7a695 — Data Viewer intensity-statistics panel + histogram (2026-07-10)

Effect: `IntensityStatsPanel` (histogram + p70/p90/p99/p99.9/p99.99 with pixel counts) pinned to the loader bottom (stack mode); Current/All/projected scope. **Files:** `widgets.py`, `tab_view.py`, `docs`. **Roll back:** localized.

d30be2c — per-user configuration system + Preferences dialog (2026-07-12)

Effect: Per-user JSON config overlays shipped defaults at import; `settings.py`; `prefs_dialog.py` (Geometry/Paths/Materials/Calibrants/Menus/Algorithms); Settings menu; `DEFAULT_KERNEL/PIPELINE/OUTPUT_FORMAT/ERROR_MODEL/COLORMAP`; tab combos honor configured defaults. New `config_gui.md`, `config.example.json`, `tests/test_config.py`. **Files:** `settings.py` (new), `prefs_dialog.py` (new), `constants.py` (+165), `app.py`, `tab_batch.py`, `tab_calibrate.py`, `widgets.py`, `docs`, `tests`. **Roll back: high impact** — the config overlay + `DEFAULT_*` and the Preferences dialog are extended by the modular-tabs commit (590b410). Reverting this would also break `ui.visible_tabs` and the Tabs preferences section.

399f3d7 — Stability: clean worker shutdown, no terminate(), stdout guard (2026-07-12)

Effect: `closeEvent` stops all tab `QThreads`; removed every `QThread.terminate()` (cooperative interrupt + orphan instead); `CalibrationWorker` restores stdout only if still its own; Data Viewer projection moved to `ProjectionWorker` (off GUI thread). **Files:** `app.py`, `tab_batch.py`, `tab_calibrate.py`, `tab_view.py`, `workers.py`. **Roll back:** reverting reintroduces the exit hard-crash risk and UI-freeze on projection — not recommended. Phase 1 of the 3-part review.

4462ee1 — Performance: waterfall O(N), debounce, caching (2026-07-12)

Effect: Waterfall pre-allocated buffer + 100 ms coalesced redraw ($O(N)$ not $O(N^2)$); 60 ms frame-slider debounce; cached radial bin-index grid; skip all-frame stats on frame-only changes. **Files:** `tab_view.py`,

widgets.py. **Roll back:** reverting slows large scans / scrubbing; behaviour otherwise same. Phase 2 of the review.

8846619 — Consistency: dedupe maps/writer, align lattices (2026-07-12)

Effect: helpers._PARAMSTEST_DISTORTION derived from constants._V2_T0_V1 (removed duplicated _V2V1 dicts); shared helpers.write_standalone_paramstest used by Calibrate + Export; LaB6/Si _LATT/_LC aligned to MATERIALS; texture colormap honors DEFAULT_COLORMAP. **Files:** constants.py, helpers.py, tab_calibrate.py, tab_export.py, tab_texture.py. **Roll back:** reverting reintroduces duplicated code paths; low functional risk. Phase 3 of the review.

590b410 — Modular tabs + Pump Probe (TR-XRD) tab + plot quality (2026-07-12)

Effect: (1) **Modular tab visibility** — Data Viewer/Mask/Calibrate/Batch always shown, the rest toggled in Settings ▶ Preferences ▶ Tabs (ui.visible_tabs, applied live); app.apply_tab_visibility(). (2) **New Pump Probe tab** (tab_pumpprobe.py) — TRR filename pooling, MIDAS-engine integration via new PumpProbeWorker (reuses build_integration_context/integrate_frame), $\Delta I(q, \text{delay})$, three-panel layout, four pyqtgraph views; ships a converted MIDAS paramstest as the default calibration. (3) **Plot quality** — white publication theme, black axes/labels/titles, readable legends, ΔI colorbar, aligned reference panel, shared draw-mode + line/point/font-size toolbar, bounded pan/zoom. **Files:** tab_pumpprobe.py (new), workers.py (+PumpProbeWorker), app.py, constants.py, prefs_dialog.py, tests/test_smoke.py, docs (gui_documentation, config_gui, config.example.json). **Roll back:** to remove **only Pump Probe**, delete tab_pumpprobe.py and its wiring in app.py/workers.py; to remove **only modular tabs**, revert the app.apply_tab_visibility / prefs_dialog Tabs section and constants tab lists. A full git revert 590b410 removes both features together. Depends on aa9395e (DataLoaderPanel), 1149afc (build_integration_context), 2385f75 (_convert_radial/_UnitAxis), d30be2c (config/prefs).

6d6f3fb — docs: add development_history.md/.pdf (2026-07-13)

Effect: Added this per-commit change log + change→commit index + rollback guide. **Files:** documentation/development_history.md, documentation/development_history.pdf. **Roll back:** docs only.

d5fafd8 — UI scaling: user-adjustable whole-interface zoom (HiDPI / 4K) (2026-07-13)

Effect: Whole-application scale (layout + fonts) for HiDPI / 4K monitors. constants.DEFAULT_UI_SCALE (config ui.ui_scale); app.main() applies it via QT_SCALE_FACTOR **before** the QApplication is created (so fixed widths, splitters, pyqtgraph and stylesheet px all scale uniformly) + AA_UseHighDpiPixmaps. Manual control in **Preferences ▶ Display** (spin + 100/125/150/200 % presets) and **Settings ▶ Interface scaling...**; both persist ui.ui_scale and offer an immediate self-restart (MainWindow.restart_app via QProcess) since the factor is read only at startup. **Files:** constants.py, app.py, prefs_dialog.py, docs (gui_documentation, config_gui, config.example.json). **Roll back:** git revert d5fafd8. Self-contained (depends only on the config system d30be2c); reverting removes the scale control and the app renders at 1.0x. To keep the feature but disable it, set ui.ui_scale to 1.0.

c4e1c12 — Display Lsd in mm (calculations & files stay in μm) (2026-07-13)

Effect: The sample-to-detector distance is entered/shown in **mm** in the Data Viewer, the Calibrate seed, and Preferences ▶ Geometry; conversion to/from μm happens only at the display boundary (DataViewerTab._lsd_um(), $\times 1000$ on read, $\div 1000$ on set). get_geometry/apply_geometry/manual_seed/prefs _assemble still emit μm ; the config key stays lsd_um (μm); calibration-file writers (paramstest.txt, calibration.json) are unchanged (always μm). Batch drift-status label → mm. **Files:** tab_view.py,

tab_calibrate.py, prefs_dialog.py, tab_batch.py, docs. **Roll back:** `git revert c4e1c12` to return every Lsd field to a μm display. Purely a display-layer change — no stored/file/calculation values are affected either way.

d6df1f8 — Fix “Populating font family aliases” startup warning (2026-07-13)

Effect: Removed the `qt.qpa.fonts: Populating font family aliases` warning (and its ~40 ms startup cost) that Qt emitted because the code named the nonexistent family “Monospace” — both via `QFont("Monospace", ...)` and the CSS generic font-family: monospace. Now names real per-platform families (Menlo/Consolas/DejaVu Sans Mono/Courier New) via `style.MONO_FAMILIES / MONO_CSS` and `widgets._mono_font()` (`QFont setFamilies + Monospace style hint`). **Files:** `style.py, widgets.py, tab_export.py, tab_view.py`. **Roll back:** `git revert d6df1f8` (cosmetic; only affects fixed-width font selection and re-introduces the harmless warning).

455ca4e — Calibrate: multi-column results readout + Send-to-Data-Viewer (2026-07-13)

Effect: (1) The Calibrate **Results** tab shows the full parameter set exactly as written to `paramtest.txt` (Lsd, BC, tx/ty/tz, p0–p14, Parallax, Wavelength, px, NrPixelsY/Z, RhoD, SpaceGroup, LatticeConstant) in a 3-column, column-major grid (`_paramtest_pairs` via the shared writer + `_populate_param_grid`), with a strain/timing line and the named-distortion table below. (2) New → **Send to Data Viewer** button (`sendGeometryToViewer` signal + `_send_to_viewer`) pushes the calibrated $\lambda/\text{pixel}/\text{Lsd}/\text{beam-centre}$ into the Data Viewer through new `DataViewerTab.set_geometry` (μm internal, Lsd shown mm, auto-BC off); wired in `app.py` as the reverse of the Viewer→Calibrate hand-off. **Files:** `tab_calibrate.py, tab_view.py, app.py, docs`. **Roll back:** `git revert 455ca4e`. Self-contained; depends on the mm-display change (c4e1c12) for the Viewer Lsd conversion.

7e157e0 — Ship test_data; hide four optional tabs by default (2026-07-14)

Effect: (1) `test_data/` sample data (`calibrant_ceria.tif/h5, nickel_stack.h5, nickel_tifs/, make_test_data.py`) is now committed so the GUI’s default paths work on a fresh clone — `.gitignore` re-includes it past the global `*.tif/*.h5` ignores via trailing negations, while `test_data/output/, out_temp.txt` and `.DS_Store` stay ignored. (2) `DEFAULT_VISIBLE_TABS = ["Calib. Refinement", "Pump Probe"]` — Corrections, PDF Analysis, Texture and Results & Export ship hidden (enable in Preferences ▶ Tabs). **Files:** `.gitignore, test_data/**` (added), `constants.py, config.example.json, tests/test_smoke.py, docs`. **Roll back:** `git revert 7e157e0` restores the all-optional-tabs default and removes the shipped data + re-ignores `test_data/`. Note: a per-user config with its own `ui.visible_tabs` overrides the shipped default regardless.

6332b3d — Fix launch crash on fresh Linux/Windows (colormap w/o matplotlib) (2026-07-14)

Effect: Fixes the GUI failing to start on a clean env where every always-on tab’s image viewer crashed with `'NoneType' object has no attribute 'getColors'`. Cause: `DEFAULT_COLORMAP “hot”` (and the whole `COLORMAPS` list) are matplotlib colormaps; `pg.colormap.get("hot")` returns `None` without matplotlib, and that `None` was passed into `pyqtgraph`. New `widgets._resolve_cmap()` resolves native → matplotlib → native fallback → grayscale ramp and never returns `None` (used by `ImageViewer, WaterfallViewer, Texture`); matplotlib added as a declared dependency (`pyproject + environment.yml matplotlib-base`) so the named maps actually resolve. The downstream “Geometry hand-off wiring failed / QWidget has no attribute `pushGeometry`” log lines were only a symptom of the tabs becoming placeholders and disappear with this fix. **Files:** `widgets.py, tab_texture.py, pyproject.toml, environment.yml, tests/test_smoke.py`. **Roll back:** `git revert 6332b3d` (reintroduces the crash on matplotlib-less envs).

72a1770 — env: drop midas_suite (unblocks conda env create) (2026-07-14)

Effect: `conda env create -f environment.yml` was aborting because the pip section's `midas_suite` meta-package pulls `midas-index 0.7.3`, whose `sdist` fails to build against `scikit-build-core>=0.8` (Use `cmake.version` instead of `cmake.minimum-version`). The GUI never uses `midas_suite`'s extras; the backends it actually imports (`midas-calibrate-v2/-integrate-v2/-calibrate/-hkls/-distortion`) are declared in `pyproject.toml` and pulled by the editable `-e .` install. Removed the redundant `midas_suite` line; README updated. (Unrelated to the repo: the `libarchive.19.dylib / conda-libmamba-solver` errors in that log are a broken base-Anaconda mamba, worked around with `--solver=classic`.) **Files:** `environment.yml`, `README.md`. **Roll back:** `git revert 72a1770` (re-adds `midas_suite` and its build failure).

68313f8 — Pin environment.yml to a verified NumPy-1 set + README recreate steps (2026-07-14)

Effect: Makes `conda env create` reproduce a known-good environment. Fresh installs previously pulled the newest backends (`numba 0.66` → `NumPy 2.x`) against `conda torch 2.2.2`, which can't interop with `NumPy 2` (`torch.from_numpy: Numpy is not available`). Pinned every package to the versions from the user's working base Anaconda — the **NumPy-1 family**: `numpy=1.26.4`, `scipy=1.13.1`, `h5py=3.11.0`, `tiffle=2023.4.12`, `pyqtgraph=0.14.0`, `matplotlib-base=3.8.4` (conda); `PyQt5==5.15.10`, `torch==2.4.0`, `numba==0.59.1`, and the NumPy-1-era MIDAS backends (`calibrate-v2 0.3.3`, `integrate-v2 0.1.0`, `calibrate 0.2.3`, `hkls 0.4.1`, `distortion 0.2.0`) via pip; then `-e .`. Dropped the `conda pytorch/cpuonly` lines + `pytorch` channel (torch now via pip). `pyproject.toml`: lowered `midas-calibrate` floor `0.2.7` → `0.2.3` so the proven base version satisfies `-e .`. README gains a "Recreating the environment" section (remove + create), a `conda-solver/libarchive` note, and the CPU-only torch install note. Verified end-to-end: fresh env resolves clean; GUI + a real nickel-frame integration run (`numpy 1.26.4` + `torch 2.4.0`). **Files:** `environment.yml`, `pyproject.toml`, `README.md`. **Roll back:** `git revert 68313f8` (returns to ranged deps; a fresh env would again risk the NumPy-2/torch mismatch). To move forward to a NumPy-2 stack instead, bump `torch>=2.3` and the backends to their `numba-0.66` releases together.

3a6ecb9 — Calibrate Results: all-text multi-column readout (drop distortion table) (2026-07-14)

Effect: The Calibrate **Results** tab is now entirely text. Removed the distortion `QTableWidget`; the distortion coefficients appear in the same multi-column parameter grid, with the paramtest `p0-p14` slots relabelled to their names (`iso_R2`, `a1`, `phi1`, ...) via helpers. `_PARAMTEST_DISTORTION`. Larger font (12 pt) and roomier row/column spacing for readability. Removed the `DistortionTable` import + `set_distortion` call. **Files:** `tab_calibrate.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 3a6ecb9` (restores the named-distortion table widget below the grid). `DistortionTable` still exists in `widgets.py` (used only here), so a revert is clean.

b1642fa — Fix calibration TypeError (initial_BC_y) + add scikit-image (2026-07-14)

Effect: Fixes calibration failing with `calibrate()` got an unexpected keyword argument `'initial_BC_y'` on the pinned (base-matching) `midas-calibrate-v2 0.3.3`, whose `calibrate()` has no beam-centre seed parameter (only newer backends add it). New `calib._supported_kwargs(fn, kwargs)` filters `kwargs` to the installed callable's signature (keeps `initial_Lsd`, drops the unsupported `initial_BC_y/z`, logs it), so the GUI tolerates backend-version signature drift. Also pins **scikit-image=0.23.2** in `environment.yml` — `midas-calibrate-v2`'s `auto_seed_calibrant` needs it; without it, seeding degrades to the coarse arc fallback. Verified: manual-seed `one_shot` calibration of the shipped ceria runs end-to-end (`numpy 1.26.4` + `torch 2.4.0`). **Files:** `calib.py`, `environment.yml`. **Roll back:** `git revert b1642fa` (reintroduces the `TypeError` on backends lacking the BC-seed args, and removes the `scikit-image` pin).

df544d2 — Data Viewer: tilt/distortion-aware radial integration (2026-07-14)

Effect: When a loaded calibration file carries the full geometry (tilts + distortion), the Data Viewer's radial integration goes through the MIDAS engine (`build_integration_context + integrate_frame`) instead of concentric-circle binning, so pixels map through the calibrated tilts/distortion. `_load_calibration` now also reads the full geometry via `geometry_fields_from_file` (falls back to scalar/circle mode if absent) and shows the active mode. `_midas_radial` caches the binning geometry per (geometry, R-bin, image shape, static mask) and reuses it across frames (fast hard kernel; loader's static composite mask so the cache holds); `_radial_integrate` branches to it with a guarded fallback to circle binning on error. **Files:** `tab_view.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert df544d2` (reverts to circle-only radial integration in the Data Viewer). Self-contained; the MIDAS-engine primitives it reuses are unchanged.

bc86d74 — Data Viewer: Top-N pixels + mask-aware stats + full-geometry receive (2026-07-19)

Effect: Adds a “Top-N pixels” toolbar toggle that marks the N brightest pixels (crosshair + circle) and feeds their values to the intensity-statistics panel, re-ranking live on frame/mask changes. Masked pixels (mask file + intensity-range mask) are excluded from the Top-N ranking and its stats/histogram. `_midas_radial` now unions the static mask with the per-frame intensity-range mask and fingerprints the mask by content so the cached binning context rebuilds when the mask changes. The tab also accepts a *full* geometry dict (tilts + distortion + detector size) from Calibrate and routes integration through the MIDAS engine when it arrives. The stats panel readout box auto-sizes to its content (no inner scrollbar) with the histogram as the single flexible child; `DataLoaderPanel` is now a `QWidget` hosting a scroll area + stats panel in a draggable vertical splitter. **Files:** `tab_view.py`, `widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert bc86d74`.

b0a5cc3 — Calibrate: per-coefficient distortion, frame averaging, seed feedback (2026-07-19)

Effect: Adds `DistortionRefineDialog` (behind the “...” next to the Distortion checkbox) to pick any of the 15 harmonics or use η -fold presets; `calib.py` maps each selected v2 harmonic to its v1 p-slot (via `DISTORTION_ISO/DISTORTION_PRESETS` in constants). Adds an “Average frames” card (start:end:skip, streamed via `DataLoaderPanel.average_frames`), seed tilts (tx/ty/tz) carried into the v1 params, a “Feed result back to seed” option, and a “→ Send to Data Viewer” that now sends the full geometry (tilts + distortion + detector size). Drops the 310px bottom-panel cap and adds a non-collapsible splitter. **Files:** `calib.py`, `tab_calibrate.py`, `dialogs.py`, `constants.py`, `widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert b0a5cc3`.

b6f1681 — Batch: read-only “Calibration values” card (2026-07-19)

Effect: Adds a Calibration values card to the Batch parameter column showing the geometry actually driving integration (λ , Lsd, BC, tilts, pixel sizes, detector size, non-zero distortion count), resolved from the live Tab-2 result or a calibration file and refreshed on source/path change. Also lets the Log panel fill its splitter space. **Files:** `tab_batch.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert b6f1681`.

49623ae — Pump Probe: publication plotting, delay colour-bar, default mask (2026-07-19)

Effect: Publication-quality plot defaults (clean 2.0px lines, 13pt fonts, dashed grid, refactored `_rainbow_cmap`); a continuous delay→colour bar (`GradientLegend`) replaces the many-row legend past a threshold, with left/right legend anchoring; a log-delay x-axis option for kinetics; and a default detector mask wired via new `DataLoaderPanel.add_mask_file / MaskSelector.add_file_source`. TR-XRD defaults now point at a local-only `test_data_pump_probe/` folder kept out of git. **Files:** `tab_pumpprobe.py`, `constants.py`, `widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 49623ae`.

b251ca8 — chore: gitignore context, internal docs, large sample sets (2026-07-19)

Effect: Ignores the local `.context/` scaffold and `CLAUDE.md`, the internal-only PDF calculation write-up, and the large local sample dirs (`test_data/17BM/`, `test_data/test_s25ide/`) via directory-level ignores that override the `test_data/**` re-includes. **Files:** `.gitignore`. **Roll back:** `git revert b251ca8`.

1769f69 — Data Viewer: live PV stream (Live Data card) (2026-07-20)

Effect: Subscribes to an EPICS PVA image PV via `pvapy` and pushes frames straight through the existing image/corrections/ring/radial-integration pipeline — no separate viewer window. “Live Data” is a collapsible card (own title-bar checkbox) above the Data card; unchecking stops an active stream. Data card gets a small  reload button to restore the static file/folder/HDF5 source after stopping a stream. `pvapy==5.4.1` is now a required, pinned dependency (chosen over latest to avoid upgrading the `numpy/pyqtgraph` pins). `MainWindow` calls a generic `tab.shutdown()` hook on close so a live stream stops cleanly on app exit. **Files:** `widgets.py`, `tab_view.py`, `app.py`, `pyproject.toml`, `environment.yml`, `documentation/gui_documentation.md`, `tests/test_live_stream.py`. **Roll back:** `git revert 1769f69`.

0b4326d — Fix: cap native thread pools to prevent calibration crash (2026-07-22)

Effect: Clicking “Run Calibration” crashed the app outright — a native, uncatchable `Bus error`, not a Python exception. Root cause: `CalibrationWorker` (a `QThread`) triggers a multi-threaded `numpy.linalg.inv()` deep inside `midas-calibrate-v2`’s HKL/ring generation (likely surfaced by the recent `0.3.3 → 0.5.2` bump); running from a `QThread` while the Qt event loop is alive, that races against PyTorch’s own OpenMP pool and corrupts memory. Reproduced deterministically at two call sites (`numpy.linalg.inv` during ring generation, `scipy.ndimage.median_filter` during seeding); both disappear once native thread pools are capped to 1. Every heavy operation in this app runs inside a `QThread` (17 worker classes in `workers.py`), so the fix caps `OPENBLAS_NUM_THREADS / OMP_NUM_THREADS / MKL_NUM_THREADS / VECLIB_MAXIMUM_THREADS / NUMEXPR_NUM_THREADS` to 1 process-wide via `os.environ.setdefault` in `_paths.py` — already home to the sibling `KMP_DUPLICATE_LIB_OK` workaround for the same underlying duplicate-OpenMP-runtime issue — rather than patching each worker individually. Verified: offscreen run of the full calibration pipeline to convergence with no crash; `pytest 15/15` green. **Files:** `midas_gui/_paths.py`. **Roll back:** `git revert 0b4326d` (restores multi-threaded BLAS; calibration/other workers become exposed to this native-crash class again on macOS).

234ded9 — Live viewer: preserve manual colormap/level changes across frames (2026-07-24)

Effect: `ImageViewer._redisplay` recomputed `vmin%/vmax%` percentile levels on every incoming frame (live or otherwise), silently overwriting a level range the user had dragged on the `pyqtgraph` histogram mid-acquisition. Now tracks manual histogram edits via `sigLevelsChanged` (guarded against feedback from our own programmatic `setImage` calls with a suspend flag) and keeps pinning to the last manual levels until the user explicitly changes the `vmin%/vmax%` spin boxes, which resets back to auto. **Files:** `widgets.py`. **Roll back:** `git revert 234ded9`.

69f470c — Data Viewer: widen the image/radial-plot splitter handle (2026-07-24)

Effect: The vertical splitter between the image view and the radial-integration panel had no explicit handle width (unlike the outer horizontal splitter), making it thin and hard to grab. Set `setHandleWidth(8)` to match. **Files:** `tab_view.py`. **Roll back:** `git revert 69f470c`.

96f8add — Radial profile: stop forcing Y-axis min to -1000 on every update (2026-07-24)

Effect: `ProfileViewer._replot` unconditionally called `setYRange()` with a hardcoded -1000 floor on every redraw, clobbering any manual Y-range the user set. The auto lower bound is now `0.9 * current data minimum`; once the user manually changes the Y range (drag, wheel-zoom, or the axis context menu’s numeric

entry — detected via `sigYRangeChanged` with the same suspend-flag pattern as 234ded9), that value is kept for the rest of the session instead of being recomputed. Also dropped the hardcoded `setLimits(yMin=-1000/1)` hard floors. **Files:** `widgets.py`. **Roll back:** `git revert 96f8add`.

3eb4a44 — Calibrate: recolor Pick-Ring fit overlay to blue (2026-07-24)

Effect: `PickableImageViewer`'s Pick-Ring points, fitted circle, and fitted-center marker used the same amber (`#f0c060`) as the Data Viewer's Simulate-rings overlay, making the two indistinguishable when both were visible on the same image. Pick-Ring's fit overlay is now blue (`#2a7fd4`); the separate Pick-BC "+" click marker (already `#00aaff`) and Simulate-rings amber were left unchanged. **Files:** `widgets.py`. **Roll back:** `git revert 3eb4a44`.

ecf6d01 — Data Viewer: make Simulate rings a live toggle instead of one-shot (2026-07-24)

Effect: "Simulate rings" is now a checkable toggle rather than a single-click action. While on, it resimulates automatically whenever material, lattice constants, space group, or geometry (wavelength/Lsd/pixel size/max 2θ) change — mirroring the existing `_rad_auto-style` "recompute on change" idiom already used for radial integration. Beam-centre edits still just reposition the existing rings (unchanged; ring radii don't depend on BC), so no wiring was added there. **Files:** `tab_view.py`. **Roll back:** `git revert ecf6d01`.

aa82cb6 — Preferences: add Devices tab; Data Viewer Live PV becomes a device dropdown (2026-07-24)

Effect: New **Preferences ▶ Devices** tab (add/remove/edit rows of name + prefix + PVA suffix), following the existing Materials/Calibrants table-tab pattern; persisted as a new "devices" list in the JSON config (replaces wholesale when present, same as materials/calibrants). Ships pre-filled with the 20-ID-D detectors extracted from the beamline's `make_det(...)` blueprint — `oryx20idd (20idd0R1:)`, `s20idPil (20idPil)`, `pg4 (1idPG4:)`, `gh1s (20idGH1s:)`, `s20varex1 (20IDFF:)` — all with PVA suffix `Pva1:Image`. The Data Viewer's Live Data "Live PV" field is now an editable combo box (`_NoScrollComboBox`) populated from this list: picking a device by name fills in its full PV (prefix + PVA suffix); typing any other PV by hand still works unchanged, with the same example placeholder text. **Files:** `constants.py`, `prefs_dialog.py`, `widgets.py`, `tests/test_live_stream.py`. **Roll back:** `git revert aa82cb6` (Devices tab and the Live PV dropdown both go; the Live PV field reverts to a plain text box).

Rollback recipes (common intents)

- **Undo the Pump Probe tab only:** `git revert 590b410` removes Pump Probe *and* modular tabs. To drop Pump Probe alone, hand-remove `midas_gui/tab_pumpprobe.py`, its import/construction/wiring in `app.py`, `PumpProbeWorker` in `workers.py`, and its entry in `constants.OPTIONAL_TABS/DEFAULT_VISIBLE_TABS`.
 - **Undo modular tabs (show all 10 fixed again):** remove the `apply_tab_visibility` logic in `app.py` (add all tabs directly), the Tabs section in `prefs_dialog.py`, and the tab-list constants — see the 590b410 diff for the exact hunks.
 - **Undo the config system:** `git revert d30be2c` — but first revert 590b410's config touches, since it extends the same ui overlay and Preferences dialog.
 - **Revert the azimuthal-averaging change:** don't blanket-revert 41f28f5 (bundled with UI); instead set the weighted default back to the legacy η -bin mean in the batch/pump workers.
 - **Go back to the pre-3-panel single-column tabs:** aa9395e is the pivot; a revert is large and cascades to later tabs — prefer fixing forward.
-

Generated from `git log`. To refresh after new commits: `git log --reverse --stat --date=short` and append entries above.