

gui_documentation

- [MIDAS GUI — User Documentation](#)
 - [Table of Contents](#)
 - [1. Overview and Architecture](#)
 - [2. Getting Started](#)
 - [Test data](#)
 - [3. Tab 0 — Data Viewer](#)
 - [Data Loader panel \(left\)](#)
 - [Projection card](#)
 - [Calibration card \(optional\)](#)
 - [Intensity range card \(radial integration\)](#)
 - [Ring simulation card](#)
 - [Live Data card \(experimental\)](#)
 - [Beam-centre picking \(on the image\)](#)
 - [Top-N brightest pixels \(image toolbar\)](#)
 - [Intensity statistics \(left panel, bottom\)](#)
 - [Radial integration plot \(bottom-right\)](#)
 - [4. Tab 1 — Mask Builder](#)
 - [Section 1 · Threshold mask \(always applied\)](#)
 - [Section 2 · Statistical auto-mask](#)
 - [Section 3 · Spatial spike rejection](#)
 - [Section 3b · Cosmic-ray rejection \(temporal\)](#)
 - [Section 4 · Calibration-based masks \(need a Tab 2 result\)](#)
 - [Draw mask tools](#)
 - [Save / Load](#)
 - [5. Tab 2 — Calibrate](#)
 - [Data Loader panel \(left\)](#)
 - [Detector, seed & Load calibration file](#)
 - [Average frames](#)
 - [Pipeline selector](#)
 - [Refine flags](#)
 - [Live threshold slider](#)
 - [Pick BC / Pick Ring](#)
 - [Run / Abort](#)
 - [Results \(right panel, bottom tabs\)](#)
 - [Export](#)
 - [6. Tab 3 — Calibration Refinement](#)
 - [7. Tab 4 — Batch Integrate](#)
 - [Data Loader panel \(left\)](#)
 - [Calibration source \(middle\)](#)
 - [Calibration values \(middle, read-only\)](#)
 - [Integration](#)
 - [Physics corrections](#)
 - [Monitor normalisation](#)
 - [Drift correction \(long scans\)](#)
 - [Run / Abort / Clear](#)
 - [Live folder monitoring \(MONITOR\)](#)
 - [Output formats](#)
 - [8. Tab 5 — Corrections & Physics \(work in progress\)](#)
 - [9. Tab 6 — PDF Analysis \(work in progress\)](#)
 - [Background — what I\(Q\), S\(Q\) and G\(r\) mean](#)

- Texture / Pole Figure
- Pump Probe (TR-XRD)
- Results & Export

Modular tabs. Data Viewer, Mask Builder, Calibrate and Batch Integrate are always shown; the remaining tabs (Calibration Refinement, Corrections, PDF Analysis, Texture, Pump Probe, Results & Export) are optional and can be shown/hidden from **Settings ▶ Preferences ▶ Tabs**. By default only **Calib. Refinement** and **Pump Probe** are shown; Corrections, PDF Analysis, Texture and Results & Export ship **hidden** — turn them on when you need them. The choice is saved per-user (`ui.visible_tabs`) and applies immediately — see §15. Hidden tabs are only removed from the tab bar; they stay constructed, so cross-tab wiring and state are preserved.

Cross-tab shared state. When Tab 2 (Calibrate) produces a result it is automatically propagated to all downstream tabs. When Tab 1 (Mask Builder) computes a mask it is sent to the consuming tabs. Tab 3 (Refinement), if applied, re-broadcasts the refined geometry. No manual copying is needed.

All heavy computation runs off the GUI thread. Every operation that touches a MIDAS package (calibration, integration, mask training, PDF transform, gain training, field averaging, drift fitting) runs in a background QThread worker; the GUI stays responsive and log lines stream in real time.

Package layout.

```

midas_gui/
├── app.py           MainWindow, dark theme, crash diagnostics, main()
├── __main__.py      enables `python -m midas_gui`
├── style.py         Dioptas-inspired QSS theme + layout helpers
├── constants.py     calibrants, colormaps, dtype sentinels, default paths
├── helpers.py       image IO, geometry parsing, spec building, no-scroll widgets
├── widgets.py       ImageViewer / PickableImageViewer / ProfileViewer / FieldSelector / ...
├── workers.py       all QThread workers + the integration core
├── calib.py         calibration-pipeline dispatch
├── dialogs.py       save dialogs
└── tab_*.py         one module per tab

```

Layout pattern. The four analysis tabs — **0 Data Viewer, 2 Calibrate, 3 Calib. Refinement, 4 Batch Integrate** — use a **three-panel layout**:

[Data Loader | Parameters | Display / results]

- **Data Loader (left).** A shared `DataLoaderPanel` for selecting the five inputs — **Data, Dark, Bright, Background, Mask** — each as a single file, a folder, or an HDF5 dataset (a container dropdown appears for HDF5). Frame controls live here too (Tab 0 navigator, Tab 2/3 frame index, Tab 4 frame range + stride).
- **Parameters (middle).** The tab's analysis controls.
- **Display / results (right).** Image viewer, plots, and/or a log panel.

The three panels are separated by **draggable splitter handles** — drag the Data Loader | Parameters and Parameters | Display boundaries to rebalance widths to taste. Each panel has a minimum width; drag past it and the panel shows a scrollbar rather than clipping its controls.

The remaining tabs (1, 5–8) keep the classic two-panel layout.

Corrections & mask (all four analysis tabs). Dark is averaged then subtracted; Bright is averaged then flat-field **divided** or **subtracted** (your choice); Background is averaged then subtracted; every enabled Mask source (files/folders plus the auto-added “Tab 1 mask”) is **unioned** into one composite mask that zeroes/ignores those pixels. Correction order: $(img - dark) \rightarrow bright \rightarrow - background \rightarrow clip \geq 0$.

2. Getting Started

midas-gui is **not on PyPI** — install it from source with conda.

```
git clone https://github.com/d-beniwal/MIDAS_GUI.git
cd MIDAS_GUI
conda env create -f environment.yml      # creates the 'midas-gui' env and installs the GUI
conda activate midas-gui
midas-gui                               # launch (equivalently: python -m midas_gui)
```

The GUI drives the MIDAS analysis backends (midas-calibrate-v2, midas-integrate-v2, midas-calibrate, midas-hkls, midas-distortion), which are also not on PyPI — point the pip: section of environment.yml at your MIDAS source before creating the environment (see the comments in that file).

Test data

Synthetic test data lives in the repo-root test_data/ folder (git-ignored): - calibrant_ceria.tif / .h5 — CeO₂ calibrant (Eiger2 500K, 1028×512, 75 μ m pixels) - nickel_tifs/ — 10-frame Ni scan, lattice expanding +0.1 %/frame - nickel_stack.h5 — the same scan as one HDF5 stack (exchange/data)

Default geometry: $\lambda = 0.39$ Å, Lsd = 121 mm, pixel = 75 μ m, BC = (10, 10) px. Every tab's default file paths point at this data and **auto-load on startup when present**, so the app is usable immediately after checkout.

3. Tab 0 — Data Viewer

Purpose: inspect detector frames and do a quick radial integration — geometry-free (circle binning) by default, or a full tilt/distortion-aware integration when a calibration file is loaded. Produces no shared state for other tabs.

Data Loader panel (left)

Data, Dark, Bright, Background and Mask are all selected in the shared **Data Loader panel** (see §1): each accepts a file / folder / HDF5-dataset. The **Data** card here holds the **frame navigator** (slider, spin box, ◀/▶); **zoom/pan is preserved** as you step through frames (the view only auto-frames on a fresh load). Dark/bright/background and the composite mask are applied to the displayed image and to the radial integration.

Projection card

Collapse a stack to one image: **Max** (hot-pixel hunting), **Sum** (long-exposure equivalent), or **Average** (noise reduction), along a chosen axis (0 = across frames). **Skip frames** (default 1) ignores that many leading frames before projecting (e.g. 1 drops the first frame, 4 drops the first four) — useful when the opening frames are detector warm-up / shutter-transient exposures.

Calibration card (optional)

Load geometry from a **calibration .json**, a **MIDAS paramtest.txt**, or a **pyFAI .poni** (auto-detected). It fills BC, Lsd, pixel size and wavelength, unchecks “Beam centre = image centre”, and refreshes the overlay and radial plot.

When a calibration file carries the **full geometry (tilts + distortion)**, the radial integration switches from simple concentric-circle binning to a **proper MIDAS-engine integration** that maps every pixel through the calibrated tilts and distortion (the same core as Batch Integrate) — so ring positions/intensities are geometry-correct, not

just distance-from-beam-centre. The card's status line reports which mode is active. The binning geometry is built once and reused across frames (a fast hard kernel keeps the preview responsive); without a full-geometry file, the fast circle binning is used.

Intensity range card (radial integration)

Field	Description
Exclude out-of-range pixels	When on, pixels $\leq$ min or $>$ max are drawn as a red overlay and excluded from the radial integration (removes gaps / hot / overflow).
pixel $\leq$ / pixel $>$	Lower / upper bounds. On load, the upper bound auto-fills to max(99.99th percentile, 100000) .

Ring simulation card

Overlays simulated Debye-Scherrer rings to check geometry. - **Material** dropdown (CeO₂, LaB₆, Si, Al₂O₃, Cu, Ni, FCC- γ Fe, BCC- α Fe, Au, Ag, Pt, W, Ti) or **Custom**. - Lattice entry is compact: **a**, **b**, **c** on one row and **α** , **β** , **γ** on the next, plus **SG #**. A **Cubic (a=b=c, $\alpha=\beta=\gamma=90^\circ$)** checkbox lets you enter only a for cubic crystals (b, c mirror a; angles fixed at 90°). Lattice fields are editable only for Custom. - Geometry: λ , max 2 θ , Lsd, pixel size, and beam centre (auto = image centre, or manual BC_y/BC_z). The λ label is clickable (underlined) — click it for a menu of common K-edge foils (Pr, Sm, Yb, Lu, Hf, Ta, W, Re, Pt, Au, Pb, Bi) that sets λ to that element's K absorption-edge wavelength. The same clickable- λ menu is on the Calibrate and PDF tabs. The **px** label is likewise clickable — a menu of common detectors (GE 200 μ m, Varex 150 μ m, Pilatus 172 μ m, Eiger 75 μ m) sets the pixel size (also on the Calibrate tab, where it sets both pxY and pxZ). - **Show rings / Labels** toggles; **Simulate rings** is a **live toggle** (not a one-shot click) — while on, the overlay + hkl table recompute automatically whenever material, lattice constants, space group, or geometry (λ /Lsd/px/max 2 θ) change. Beam-centre edits still just reposition the existing rings (their radii don't depend on BC). - **→ Send geometry to Calibrate** copies λ , pixel size, Lsd and beam centre into the Calibrate tab's detector + seed fields (the Calibrate tab has a matching **← Data Viewer** button that pulls the same values).

Live Data card (*experimental*)

Sits **above the Data card**, collapsed by default behind its own title-bar checkbox — check it to reveal the live-PV controls, uncheck to hide them again (unchecking also stops an active stream, so a hidden card can never be left silently connected). Subscribes directly to an EPICS PVA detector-image PV (NTNDArray) and renders each frame **inline in the Data Viewer's own image pane** — the same view used for files/folders/HDF5 stacks. Because it feeds the normal frame pipeline, all existing Data Viewer analysis keeps working live: dark/bright/background/mask corrections, the intensity-range mask, beam-centre picking, and the radial integration plot all update as new frames arrive. - **Dependency**: pvapy (the EPICS pvAccess client library) is a required, pinned dependency (pyproject.toml / environment.yml), installed automatically with the rest of the GUI's stack — no separate extra to install. If somehow missing from the active environment, **Start** shows an install hint instead of failing outright. - **Live PV** field is an editable dropdown: pick a known device by name (the list comes from **Preferences ▶ Devices**, see below) to fill in its full PV automatically, or type any other PV by hand (placeholder shows an example, 20IDFF:Pva1:Image). **Start / Stop** buttons and a status line (stopped / waiting for PV / connected / streaming with frame id / error). GUI updates are throttled to the tab's existing ~16 fps debounce, so a fast PV update rate doesn't overwhelm the interface. - **Stopping live streaming does not auto-reload the previous file/folder/HDF5 source** — the Data card below gets a small **↺ Reload** button next to its path field for exactly this: click it after Stop to restore the static data that was loaded before streaming started. - **Ring overlay is static per-frame while streaming**: rings drawn by "Simulate rings" (Ring simulation card) keep rendering on top of each new live frame at their already-computed geometry — arrival of a new frame does **not** by itself trigger a recompute (ring radii don't depend on frame data). With Simulate rings' live toggle on, changing a material/lattice/geometry field still recomputes and redraws immediately. **Stop** leaves the last

received frame on screen. Closing midas-gui also stops any running stream. - **Colormap/level changes persist across frames:** dragging the histogram's level range (or the cmap dropdown) is remembered and reapplied to every new incoming frame instead of being reset to the vmin%/vmax% percentile defaults; editing vmin%/vmax% explicitly switches back to auto-levels.

Beam-centre picking (on the image)

The image viewer has **Pick BC** (single click sets the beam centre) and **Pick Ring** (click ≥ 3 points on a ring; a circle fit estimates the beam centre). Either updates BC_y/BC_z and re-runs the overlay + radial integration. Pick Ring's picked points and fitted circle are drawn in **blue**, distinct from the **amber** Simulate-rings overlay so the two aren't confused when both are visible on the same image.

Top-N brightest pixels (image toolbar)

A **Top-N pixels** toggle button (with an N spin box) sits on the image toolbar. When on, the **N highest-intensity pixels** of the current frame are marked with a crosshair inside a translucent circle (cyan) centred on each pixel, and the Intensity statistics panel switches to show the statistics of just those N pixels ("Top N pixels"). It follows frame changes while active. Clicking the button again removes the markers and restores the normal statistics. Useful for quickly locating saturation / hot pixels.

Intensity statistics (left panel, bottom)

At the bottom of the Data-Loader panel, in a **draggable pane** below the loader cards — grab the splitter handle above the panel to make the statistics area taller or shorter. It holds a **histogram** of the intensity distribution (full range, log-y toggle) with a **textbox** beneath it reporting N (pixel count) and the **p70 / p90 / p99 / p99.9 / p99.99** percentiles — each with the **number of pixels above** that value. The histogram's lower-left corner is fixed at $x = 0, y = -2$ and both axes rescale to $(0, x_{\max}) / (-2, y_{\max})$ on every refresh (frame change, scope change, projection, new data). It reflects the **corrected** image (dark / bright / background) with masked pixels (file masks + the intensity-range mask) excluded, and updates live as any of those change. A scope selector switches between the **current frame** (per the slider) and **All frames** (combined over the whole stack/folder). When a **Projection** is active the panel shows the projected image's statistics (the scope selector is disabled); when **Top-N pixels** is active it shows those pixels' statistics.

Radial integration plot (bottom-right)

Below the image is a live **azimuthal average about the beam centre** (R bin, Integrate, and an Auto toggle that recomputes on frame/BC/mask change). It is a simple geometry-free radial average (flat detector, no tilt/distortion). **Clicking a radius on the plot draws the matching ring (magenta) on the image.** Axis units switch between R (px) / 2θ / Q. The Y-axis lower bound defaults to **0.9x the current data minimum**; once you manually change the Y range (drag, wheel-zoom, or the axis context menu), that range is kept for the rest of the session instead of being recomputed on every update. The splitter handle above this panel (between it and the image view) is wider than a default Qt splitter, to make it easier to grab.

4. Tab 1 — Mask Builder

Purpose: identify and exclude bad pixels. The final mask is a uint8 array (1 = bad) broadcast to Tabs 2, 3, 4, 5. Browsing an image or a mask loads it immediately.

Section 1 · Threshold mask (always applied)

`pixel ≤ lower | pixel > upper`. The upper bound auto-fills from the data type on load (e.g. 1,048,575 for uint20 Eiger, 4,294,967,295 for uint32).

Section 2 · Statistical auto-mask

Two **independently selectable** methods — enable either or both: - **Spatial outlier** — robust local-anomaly detection (5×5 median residual $\rightarrow 15 \times 15$ local MAD $\rightarrow$ Z-score $\rightarrow$ hot/dead/saturated gates). Uses a **temporal median** over the stack folder when provided (cleaner reference), else the single frame. Controls: K_σ (6.0), Hot (1.5), Dead (0.5). - **Temporal constancy** — flags frozen pixels whose frame-to-frame std is below $\text{Frozen} \times 0.75(\text{std})$ (0.05); needs a stack of ≥ 2 frames.

A shared **stack source + stride** feeds both (the temporal median for spatial, the frame stack for temporal constancy). The stack can be a **folder / *.tif glob**, or a **single HDF5 file whose 3-D dataset is a time sequence of images** — for an .h5 a **Dataset** selector appears (auto-populated, 3-D datasets preferred). *All $\sigma / K_\sigma / n_\sigma$ fields in this tab accept any value — there is no upper limit.*

Section 3 · Spatial spike rejection

Laplacian high-pass single-pixel-spike detector; n_σ threshold (5.0).

Section 3b · Cosmic-ray rejection (temporal)

Per-pixel temporal σ -clip across a ≥ 3 -frame stack; anomalies OR'd across frames. n_σ (5.0).

Section 4 · Calibration-based masks (need a Tab 2 result)

- **Azimuthal σ -clip** — flags (R, η) cells deviating from the azimuthal mean.
- **Learnable mask** — differentiable per-pixel mask trained against an η -uniformity loss (steps, lr, sparsity).

Draw mask tools

Interactive rectangle / oval / circle / polygon / annulus / point tools, live-draggable; **Apply shapes $\rightarrow$ mask** rasterises them (OR'd with the computed mask). **Clear shapes** removes them.

Save / Load

Save the combined mask as TIFF (0 = good, 1 = bad); loading a TIFF applies immediately.

5. Tab 2 — Calibrate

Purpose: determine detector geometry (Lsd, BC, tilts, distortion, wavelength) from a calibrant pattern.

Data Loader panel (left)

The calibrant frame (Data + Frame index), Dark, Bright, Background and Mask are selected in the shared **Data Loader panel** (see §1). Each Dark/Bright/Background field is averaged over a chosen index range; Bright offers **Flat-field divide** or **Subtract**; all mask sources (plus the auto-added Tab 1 mask) are unioned. Dark is passed to the calibration pipeline; bright/background are applied to the calibrant before calibration and post-calibration integration.

Detector, seed & Load calibration file

The **Detector & Calibrant** card sets λ , pixel size(s) and detector transforms; the **Initial seed** card sets the LM starting point (BC_y, BC_z, Lsd, and tilts tx/ty/tz). **Load calibration file...** (top of the Detector card) reads a MIDAS **paramstest .txt**, a calibration **.json**, or a pyFAI **.poni** (auto-detected) and fills λ , pixel size, and the seed BC + Lsd — a fast way to start from a previous calibration or a known geometry. (The synthetic test data ships test_data/calibration_synthetic.{json,txt,poni} as a ready example.) ← **Data Viewer** (next to *Load calibration file...*) pulls λ , pixel size, Lsd and beam centre straight from the Data Viewer tab into the same fields. A **Feed result back to seed** checkbox (on by default) copies the optimized BC / Lsd / tilts / distortion of each run back into the seed fields, so a follow-up run starts from the previous solution. *Seed tilts are honoured by the Four-stage / advanced pipelines; the One-shot / First-time paths seed tilts only if the installed backend exposes initial-tilt options.*

Average frames

For a multi-frame source (HDF5 / folder), **Average frames into a single image** builds the mean of a frame range and calibrates on that. **start / end (0 = all)** select the range and **skip** uses every Nth frame while averaging (e.g. skip = 2 averages every other frame). The card is disabled for single-frame sources; the preview updates live as the options change.

Pipeline selector

One-shot (default) · First-time · Four-stage · Bayesian (Laplace σ) · Joint-cake. *For trustworthy tilt/strain, prefer Four-stage or First-time — One-shot/Bayesian can report a spurious self-compensated tilt on weakly-tilted data.*

Refine flags

Which parameters vary: Lsd, BC, ty, tz, tx, Wavelength, plus a “Residual map” build toggle. The **Distortion (n/15)** checkbox has a companion ... button that opens a per-coefficient dialog: the 15 distortion coefficients are grouped by η -fold (isotropic radial + folds 1–6), and named **preset modes** (None · Isotropic only · Iso + up to 2-fold · Iso + up to 4-fold · All (15)) auto-select whole ladders. The checkbox label shows how many coefficients are selected. *Per-coefficient control applies to the Four-stage / advanced pipelines; the One-shot path refines all-or-none.* Advanced (E-M / LM iters, device, output dir) and Multi-panel detector groups are collapsible.

Live threshold slider

Zeroes calibration-image pixels below the slider value (background suppression for ring-finding); the preview updates instantly.

Pick BC / Pick Ring

Click the image to seed the beam centre (single click) or fit a ring (≥ 3 clicks); the Pick Ring points/fit are drawn in blue, distinct from the amber Simulate-rings overlay.

Run / Abort

Run Calibration launches the worker; **Abort** terminates it and frees the slot so you can immediately start a new run (the calibration is one uninterruptible library call, so abort hard-terminates the worker thread rather than waiting).

Results (right panel, bottom tabs)

Radial Profile (with ring markers and an **Azim. avg** selector — see Tab 4), Ring Residuals bar chart, **Results**, and Log. Integration runs automatically after calibration. The **Results** tab shows the *complete* parameter set exactly as it is written to paramtest.txt (Lsd, BC, tx/ty/tz, the distortion coefficients, Parallax, Wavelength, px, NrPixelsY/Z, RhoD, SpaceGroup, LatticeConstant) as **plain text laid out in multiple columns** so the wide-but-short panel stays readable — no table widget. The distortion p0–p14 slots are labelled with their coefficient names (iso_R2, a1, phi1, ...). A strain/timing line sits below. → **Send to Data Viewer** pushes the *full* calibrated geometry (λ , pixel size, Lsd, beam centre, **tilts and distortion**) into the Data Viewer tab — where it drives the tilt/distortion-aware radial integration, not just circle binning — the reverse of the Data Viewer’s “→ Send geometry to Calibrate”. The bottom tab area is fully resizable (drag the horizontal splitter) and the Log fills its tab.

Export

Save **calibration.json** and **Save paramtest.txt** (standalone or from a template).

6. Tab 3 — Calibration Refinement

Purpose: optional post-calibration geometry refinement against an **η -uniformity** criterion (rings should be azimuthally uniform). Uses a **derivative-free Nelder-Mead** optimiser (the differentiable integrator returns NaN geometry gradients at the beam-centre singularity on this build).

The sample frame and Dark/Bright/Background/Mask are selected in the shared **Data Loader panel** (see §1) — the refinement runs on the corrected image. Middle-panel controls: calibration source (Tab 2 result, or start-from/continue radii), parameters to refine (BC_y, BC_z, Lsd, ty, tz), optimiser + iterations. **Run Refinement** shows a live loss curve; **Apply** broadcasts the refined geometry downstream. If Apply is never clicked, the Tab 2 result flows through unchanged.

7. Tab 4 — Batch Integrate

Purpose: integrate a stack of frames into 1-D profiles using the calibrated geometry and optional corrections.

Data Loader panel (left)

The streaming **Data** source (folder/glob or HDF5 dataset) with **frame range + stride**, plus Dark/Bright/Background and Mask, are selected in the shared **Data Loader panel** (see §1). Dark/bright/background are applied per frame; all mask sources are unioned.

Calibration source (middle)

- **From Tab 2** — the calibration (or refined) result.
- **From file** — a **calibration .json**, **MIDAS paramtest.txt**, or **pyFAI .poni** (auto-detected; both GUI and MIDAS-pipeline json key styles supported). Entering a path auto-selects this option.

Calibration values (middle, read-only)

A **Calibration values** card shows the geometry actually in use — λ , Lsd (mm), BC_y/BC_z (px), tilts tx/ty/tz (°), pixel sizes, detector size, and a distortion summary (number of non-zero coefficients). It repopulates whenever a calibration arrives from Tab 2 (or Tab 3 refinement, or the Data Viewer via Tab 2) **and** when a

calibration file path is entered, parsing the file directly so you can confirm the numbers before running. A note line reports the active source (or any file-read error).

Integration

Field	Description
Kernel	Hard (fastest) · Subpixel K=2 · Subpixel K=4 · Polygon (exact).
R bin (px) / η bin ($^\circ$)	Radial and azimuthal bin sizes.
Azim. avg	How the (η , R) cake becomes a 1-D profile: Pixel-weighted (default) $\Sigma(\text{mean} \cdot \text{count}) / \Sigma(\text{count})$ — independent of η -bin size and robust to partial azimuthal coverage / off-detector beam centres ; or η-bin mean (legacy) — the unweighted mean of per- η -bin means, which can distort with a coarse η bin when the beam centre is off the detector.
Per-bin variance (σ)	Error model poisson / azimuthal / hybrid (ignored when corrections are on $\rightarrow \sigma = \sqrt{I}$).
Q-uniform bins	Integrate in R then rebin onto a uniform-Q grid ($Q_{\min}$, $Q_{\max}$, ΔQ).

Physics corrections

Polarization and solid-angle (pixel-domain, via `integrate_with_corrections`).

Monitor normalisation

Divide each processed frame's profile/ σ by a per-frame scalar from a text file (one value per *processed* frame).

Drift correction (long scans)

Per-frame geometry interpolated from an anchor JSON (`{frame_idx: {Lsd, BC_y, BC_z}}`) with spline/linear/constant parametrization; **Fit trajectory** builds it. Each frame is then integrated with its own geometry.

Run / Abort / Clear

Start Integration / Abort. Abort first asks the worker to stop cleanly between frames (keeping frames already written); if it does not stop promptly it force-terminates and frees the slot. Completed frames' output files are preserved. **Clear results** removes the profiles/plots computed **this session** for the current data (waterfall, stacked profiles, and the integrated-frame tracking) so a fresh integration can start — it stops any active monitor but does **not** delete raw data or any files already written to disk.

Live folder monitoring (MONITOR)

The **MONITOR** button at the bottom of the left Data Loader panel (folder/glob sources only) starts a live watch: while active it turns **green** and the GUI polls the data folder for **new** TIFF frames, integrating each one **as it appears** and adding it to the display. It does **not** re-run the whole batch — it reuses the already-built **detector map** (the binning geometry / pixel-count cakes; reused from a prior *Start Integration* run when the calibration, kernel, bins, mask and folder are unchanged, or built once on first use) and integrates **only the new files** (tracked by frame id, so frames already shown are skipped). New frames honour the current kernel, corrections,

Dark/Bright/Background, mask and Q-uniform settings, and are saved to the output folder when a 1-D format is selected. Click **MONITOR** again to stop; starting a fresh *Start Integration* also stops it. (Distinct from **Monitor normalisation** above, which divides profiles by a scalar file.)

Output formats

CSV (R,I, σ) · XYE (2θ) · FXYE (centideg) · DAT (Q) · HDF5 (full stack) · 2D-CSV ($\eta \times R$ cake). Right panel: live **Waterfall** and **Stacked profiles** — both have an **x** selector to show the axis in **R (px)** / **2θ ($^\circ$)** / **Q ($\text{\AA}^{-1}$)** (converted from the run's calibration).

The **Stacked profiles** view is a publication-quality plot: each curve tags its **source file name inline, just below the curve at its left edge** (toggle with the *Labels* checkbox; an optional corner *Legend* is also available). A **theme** selector switches between two saved presets: - **White (publication)** (*default*) — white background, **point + line** markers, a colour-blind-friendly categorical palette (matplotlib *tab10*), a boxed frame and a light grid — ready to drop into a paper. - **Dark** — the classic on-screen look (dark background, line-only, vivid golden-angle colours).

An **x** selector plots the axis in **R (px)**, **2θ ($^\circ$)** or **Q ($\text{\AA}^{-1}$)** (converted from the run's calibration). The **Grid** checkbox (off by default) toggles the horizontal + vertical grid. The *spacing* box shifts successive curves vertically (0 = overlay). Top-right controls adjust the **line width** (– line +), **symbol size** (– sym +, for the point+line markers — also turns markers on if a line-only theme is active) and **label font size** (– font +).

8. Tab 5 — Corrections & Physics (*work in progress*)

Preview physics corrections on a single frame (auto-loads on browse). Pixel-domain: polarization, solid angle, empty subtraction. Profile-domain: cylindrical absorption (μR), Compton subtraction (composition: fraction). **Compute corrected profile** overlays corrected vs uncorrected and shows the correction factor vs 2θ .

Also hosts **per-pixel gain training (LearnableGain)**: from a clean reference frame and a drifted frame, learn a spatial gain map $g_i = 1 + \text{scale} \cdot r_i$ by minimising $\text{MSE}(\text{profile}) + \text{unity} \cdot \sum (g-1)^2 + \text{smooth} \cdot \text{TV}(g)$; save as NPZ and apply with `corrected = raw / gain_map`.

9. Tab 6 — PDF Analysis (*work in progress*)


Polyatomic **total-scattering** reduction: $I(Q) \rightarrow$ Faber-Ziman structure function $S(Q) \rightarrow$ pair-distribution $G(r)$, powered by the `midas_pdf` backend (real composition-weighted normalization, Compton subtraction, end-to-end σ propagation, and optional differentiable scale/background refinement). This replaces the earlier monoatomic, composition-free $F(Q)=Q \cdot (I/bg-1)$ approximation.

Background — what $I(Q)$, $S(Q)$ and $G(r)$ mean

PDF analysis is three transforms that move from *what the detector measured* to *where the atoms are*. They are exactly the three stacked plots (top $\rightarrow$ bottom).

- **$I(Q)$ — measured scattered intensity.** Intensity vs. momentum transfer $Q = 4\pi \cdot \sin(\theta)/\lambda$ ($\text{\AA}^{-1}$), a wavelength-independent rescaling of the angle 2θ ; high Q = wide angle = fine spatial detail. Obtained by azimuthally integrating the detector rings to a 1-D curve. $I(Q)$ is **not** pure structure — it mixes the interference (coherent) signal with big smooth backgrounds: per-atom self-scattering (form factors $\langle f^2 \rangle$) and inelastic **Compton** scattering.

- **S(Q) — structure function.** $I(Q)$ with the self-scattering and Compton removed and normalized away (the **Faber-Ziman** step), leaving only interference: $S(Q) = [I_{\text{coh}} - (\langle f^2 \rangle - \langle f \rangle^2)] / \langle f \rangle^2$, where $\langle f \rangle$, $\langle f^2 \rangle$ are composition-weighted atomic form factors (hence the **Composition** input). $S(Q)$ oscillates about 1 and $\rightarrow 1$ at high Q where correlations wash out (the dashed guide line). $F(Q) = Q \cdot [S(Q)-1]$ is the same thing re-weighted by Q to emphasize the structurally rich high- Q oscillations.
- **G(r) — reduced pair distribution function.** The real-space answer: a histogram of interatomic distances, via a sine Fourier transform $G(r) = (2/\pi) \cdot \int Q \cdot [S(Q)-1] \cdot \sin(Qr) \, dQ$. A **peak at r** means many atom pairs are separated by that distance; the **first peak is the nearest-neighbour bond** ($\text{Ni} \approx 2.49 \text{ \AA}$, CeO_2 $\text{Ce-O} \approx 2.34 \text{ \AA}$), later peaks are further coordination shells. Below the first bond $G(r) = -4\pi\rho_0 r$ (nothing can be closer) — a constraint that needs the number density ρ_0 . Because it uses *total* scattering (Bragg and diffuse), the PDF captures local structure even in disordered / nanoscale / amorphous materials, unlike a Bragg-only Rietveld fit.



The $\pm 1\sigma$ band on $G(r)$ is the counting uncertainty σ propagated from $I(Q)$ through every step, so real peaks can be told from noise. The **G/g/T/R** family (Output selector) is the same information re-weighted: **G** oscillates about 0 (refinement standard); **g** $\rightarrow 1$ at large r ; **T** is the total correlation; **R** is the radial distribution whose *peak area = coordination number*. $g/T/R$ all need ρ_0 .

I(Q) source (choose one): - **Integrate detector frame** — a calibrated frame is integrated (hard/polygon binning, Poisson σ) and mapped to Q , exactly as before. Uses the Tab 2 calibration (λ , geometry) and any Tab 1 mask. - **Load I(Q) file** — a pre-integrated 2- or 3-column Q , I , σ text/CSV (comment/header lines tolerated). The tab **opens on this source by default**, pointed at real data in `test_data/pdf_real/` (`iq_Nickel.csv`; also `CeO2`, `IPA`, `Kapton` at λ 0.1839) — just press **Compute G(r)** for the Ni PDF (first peak $\sim 2.49 \text{ \AA}$). Synthetic known-answer examples are in `test_data/pdf_synth/` (`nickel_iq.csv`, `ceo2_iq.csv`). See each folder's `README.md` for per-sample composition / ρ_0 / Q -range settings.

Calibration. The geometry/wavelength comes from Tab 2 automatically, or use **Load calibration file...** to read a MIDAS `paramtest.txt`, a `.json`, or a `pyFAI .poni` (auto-detected). This is required for *Integrate detector frame* and also sets λ used by *Load I(Q) file* mode.

Sample. Composition (e.g. `Ni` or `C:3,H:8,O:1`; ions like `Ni2+` allowed), number density ρ_0 (atoms/ $\text{\AA}^3$; needed for refinement and for $g/T/R$), wavelength λ (auto-filled from calibration), and a **Compton subtraction** toggle.

Normalization. Optional **Refine scale + background** (L-BFGS) — reveals a background polynomial degree (0–3), a low- r cutoff r_{min} ($\text{\AA}$), and an iteration count. Refinement requires $\rho_0 > 0$. It fits scale and a smooth $b(Q)$ against two model-free constraints: high- Q $\langle S \rangle \rightarrow 1$ and $G(r) = -4\pi\rho_0 r$ below r_{min} .

Output. Bottom-plot convention family — **G(r)** (reduced PDF), **g(r)** (pair distribution), **T(r)** (total correlation), or **R(r)** (radial distribution, whose peak integral is the coordination number); $g/T/R$ need ρ_0 . Middle plot toggles between **S(Q)** (with the $S=1$ guide) and the true reduced structure function **F(Q)=Q(S-1)**.

Right panel: $I(Q)$ (+ refined background overlay), $S(Q)/F(Q)$, and the selected $G/g/T/R$ with a shaded $\pm 1\sigma$ band. **Save G(r)** writes a three-column r , $G(r)$, σ file (diffpy-CMI / PDFgui / RMCProfile compatible); **Save S(Q)** writes Q , $S(Q)$.

Functions behind the tab

The tab is a thin UI over a background worker and the `midas_pdf` backend.

UI — `PDFTab (midas_gui/tab_pdf.py)`

Method	Role
<code>_build_ui</code>	Builds the I(Q)-source / Sample / Normalization / Output groups and the three stacked plots.
<code>set_calibration(result, source)</code>	Receives a Tab-2 result (or a loaded geometry) → sets λ and enables Compute.
<code>_load_calib_file</code>	Loads a <code>paramtest/.json/.poni</code> → builds a calibration result → <code>set_calibration</code> .
<code>_load_img</code>	Loads a detector frame for <i>Integrate detector frame</i> mode.
<code>_run</code>	Validates inputs, assembles the <code>cfg</code> dict, and starts a <code>PDFWorker</code> .
<code>_on_done / _redraw_mid / _redraw_bottom</code>	Draw I(Q)+bg, the $S(Q) \leftrightarrow F(Q)$ toggle, and the G/g/T/R curve with its $\pm 1\sigma$ band.
<code>_save_gr_file / _save_sq_file</code>	Export r, G, σ and Q, S .

Worker — `PDFWorker (midas_gui/workers.py)` runs off the GUI thread:

Function	Role
<code>_acquire_iq</code>	Produces (q, I, σ) — either by integrating the frame (image mode) or by reading a file (<code>_load_iq_file</code> , tolerant of comma/space and 2- or 3-columns).
<code>run</code>	Trims to $[Q_{min}, Q_{max}]$, builds Composition, calls the reduction (plain or refine), computes $F(Q)$ and the G/g/T/R family, emits the result dict.

Image-mode integration reuses the shared core `_build_spec`, `build_geom`, `integrate_frame`, `axis_conversions` (same path as the other tabs); geometry-file parsing uses `geometry_fields_from_file / result_ns_from_geometry_file (midas_gui/helpers.py)`.

Reduction — `midas_pdf` via `midas_gui/pdf_backend.py` (re-exported symbols):

Function	Does	Maps to plot
<code>Composition(fractions, number_density)</code>	Composition layer: $\langle f \rangle$, $\langle f^2 \rangle$ form-factor averages, Laue — term $\langle f^2 \rangle - \langle f \rangle^2$, and per-atom Compton.	
<code>faber_ziman_S(I, q, comp, ...)</code>	$I(Q) \rightarrow S(Q)$ with σ (subtract Compton/Laue, divide by $\langle f \rangle^2$).	$S(Q)$
<code>structure_function_F(q, S)</code>	$F(Q) = Q \cdot (S - 1)$.	$F(Q)$

Function	Does	Maps to plot
<code>fourier_sine_transform(q, S, r, window)</code>	$S(Q) \rightarrow G(r)$ with σ (Lorch / none window).	$G(r)$
<code>i_of_q_to_Gr(q, I, comp, r, ...)</code>	End-to-end $I(Q) \rightarrow G(r)$ (composes the two above); the default Compute path.	$S(Q) + G(r)$
<code>refine_normalization(q, I, comp, r, ...)</code>	L-BFGS fit of scale + background polynomial against high-Q $\langle S \rangle \rightarrow 1$ and low-r $G = -4\pi \rho_0 r$.	refined $S(Q)/G(r) + bg$
<code>pair_distribution_g / total_correlation_T / radial_distribution_R</code>	Convention family from $G(r) + Q_0$.	$g/T/R$

Packaging note. `midas_pdf` is currently **vendored** in `midas_gui/_vendor/` and loaded through `midas_gui/pdf_backend.py`, which also installs a small `midas_hkls.absorption` compatibility shim for `midas-hkls < 0.5.0`. Once `midas-pdf` is published and `midas-hkls >= 0.5.0` is available the vendored copy and the shim are removed.

10. Tab 7 — Texture / Pole Figure (*work in progress*)

Per-ring azimuthal analysis for preferred orientation. Controls: calibration source, sample frame, R/η bins, ring index, χ (tilt) / ϕ (rotation). **Compute Pole Figure** integrates to a cake and extracts $I(\eta)$ at the selected ring; the right panel shows the stereographic pole figure and the raw $I(\eta)$. **Save pole figure (.pol)** exports POPLA format.

11. Pump Probe (time-resolved / TR-XRD)

Analyses time-resolved (pump-probe) diffraction the way the TRR group does: a folder of raw detector frames is pooled by a filename prefix, the pump-probe **delay** is parsed from each name, every frame is integrated to $I(q)$ with the **MIDAS engine** (the same core as Batch Integrate, driven by a calibration), repeats at each delay are averaged, and a reference (mean of the pre-time-zero / negative delays) is subtracted to give **$\Delta I(q, \text{delay})$** .

File-naming / pooling. Frames follow `PREFIX-<fshw>fshw<delay>delay<id>.tif`, where `PREFIX` (e.g. `Ex01_Sa01_Sc17` = Experiment / Sample / Scan) is one opaque grouping key. **Scan folder** globs `PREFIX*.tif` in the loaded folder, parses `fshw` and `delay` (seconds) from each name, and reports how many frames and unique delays were found. The delay sign is flipped on load so positive delay = after the pump.

The tab uses the same three-panel layout as Batch Integrate: **data loader** (left), **settings** (middle), **plots** (right).

Left — data loader (the shared loader panel, as on Calibrate / Batch): - **Data** — the folder of raw frames. Defaults to the bundled TRR test set in `test_data_pump_probe/detimages/` (125 Pilatus2M frames; a large, git-ignored local asset), so the tab is populated on open. An index range / stride can subset the pooled frames. - **Dark / Bright / Background** — per-frame field corrections (compute each field, then it is applied to every frame before integration). - **Mask** — a mask file and/or the mask from the Mask Builder tab. For the TRR data the tab pre-loads `invert_mask.tif` (0 = valid pixel, 1 = bad pixel / module gap), which matches MIDAS's convention that non-zero pixels are masked out.

Middle — settings. - **Calibration source** — *From Tab 2* (the live calibration) or *From file* (calibration.json / paramtest.txt / .poni). Same convention as Batch Integrate. For the shipped TRR test data the field defaults to a ready MIDAS paramtest (Ex01_Sa01_Sc17_midas.txt, converted from the dataset's pyFAI/Fit2D geometry), so the tab integrates out of the box. - **Data pooling (TRR)** — the pooling **prefix + Scan folder** (the folder itself comes from the loader on the left). - **Integration** — kernel, R/ η bins, the plot axis (Q / 2θ / R), and optional Q-uniform binning. Identical engine and options to Batch Integrate. - **Physics corrections** — polarization / solid-angle. - **Pump-probe options** — the reference-delay set (defaults to all negative delays; multi-select to override), optional per-pattern normalization over a q-window, the ΔI colour range (auto or fixed $\pm$) and the diverging colormap.

Views (right panel). Every axis shows **real physical values**, not indices — the radial axis is in Q ($\text{\AA}^{-1}$), 2θ ($^\circ$) or R (px) per the plot-axis selector, and delays are in seconds. 1. **ΔI heatmap** — ΔI over the radial axis (a true, continuous Q/ 2θ /R axis) versus delay, diverging colour centred at zero, with a labelled ΔI colour-bar and the reference I(q) lineout beside it (shared radial axis). Delays span several decades and are irregular, so they are laid out as columns labelled with their real delay values. 2. **ΔI vs q** — one curve per delay, coloured along a rainbow by delay. With ≤ 8 delays each curve is named in the legend; with more, a continuous **delay colour-bar** (min $\rightarrow$ max, in seconds) replaces the legend. 3. **Kinetics** — ΔI versus delay for user-defined q-bands (**Add band** over a q range); x-axis as real delay (**linear**), **log** (post- t_0 delays, natural for the decade-wide delay range), or **rank**. 4. **Mean patterns** — the averaged I(q) at each delay plus the dashed reference, with an optional **$\pm 1\sigma$ band** (spread of I(q) across delays) and a **Log Y** toggle to reveal weak features across the full dynamic range; a signal-level / stability check.

All views use a publication-style white theme with large, clearly-labelled axes, readable legends and a subtle grid. A toolbar above the plots sets the **draw** mode (lines / lines+points / points) and the **line**, **point (sym)** and **font** sizes (the $-/+$ groups), as on the Batch Integrate tab. Pan and zoom are bounded to the data so you cannot lose the plot area.

Integration runs off the GUI thread (PumpProbeWorker) with a progress bar and **Abort**. There is no peak fitting — peak position / width / area are read from the plots, matching the reference workflow.

12. Results & Export (*work in progress*)

Session summary + one-click export. Checkboxes select which products (calibration.json, paramtest.txt, mask.tif, integrated profiles, G(r), pole figures, session log) to copy to an output directory. A provenance block (package versions, geometry hash, mask fraction, correction flags) can be copied to the clipboard for a Methods section.

13. Common UI Conventions

- **Browse = load.** Selecting a file/folder (or pressing Enter in a path field) loads it immediately; there are no separate “Load” buttons. HDF5 dataset / frame-index changes reload automatically.
- **No accidental scroll changes.** Spin boxes and drop-downs ignore the mouse wheel — values change only by clicking/typing; the wheel scrolls the panel instead.
- **Readable right-click menus.** pyqtgraph plot context menus use the dark theme.
- **Dark theme, orange accent** (Dioplas-inspired); off-white text, light input fields.
- **Sample-to-detector distance is entered/shown in mm** (Data Viewer, Calibrate seed, Preferences ► Geometry). Internally — all calculations — and in written calibration files (paramtest.txt, calibration.json) it is always in **microns**; the mm $\leftrightarrow\mu$ m conversion happens only at the display boundary. The config key remains `lsd_um` (μ m).

14. Packaging, Deployment & Diagnostics

Packaging. `midas-gui` is a MIDAS-style package: `pyproject.toml` (BSD-3-Clause), a `tests/` smoke suite, and `release.sh` for cutting versioned releases (see `RELEASING.md`). Once published it can join the `midas-suite` meta-package as an optional gui extra (`pip install midas-suite[gui]`).

Deployment on another system. Clone the repo, create the conda environment (`environment.yml`), and run `midas-gui`. The MIDAS analysis backends are installed via the `pip:` section of `environment.yml` (editable from a local MIDAS checkout, from a git subdirectory, or from a private index). `midas_gui/_paths.py` is an inert stub in an installed package (no `sys.path` manipulation).

Crash diagnostics. On startup the app installs a logging exception hook and `faulthandler`; any uncaught Python exception or native fault is written to `~/midas_gui_error.log` and shown in a dialog. Installing the hook also prevents PyQt5 from hard-aborting on an exception inside a slot. Each tab is built in isolation — a tab that fails becomes an error placeholder instead of taking the window down. If the app ever “pops up and dies” (typically on Windows), send that log file.

15. Configuration & Defaults

Every default in the GUI — detector geometry, data/output paths, ring-simulation **materials**, **calibrants**, the **pixel-preset** and **K-edge** menus, the calibration / integration **algorithms**, and **which tabs are visible** — can be set **without editing code**, via a single per-user JSON config that overrides the shipped built-in defaults.

Where it lives

One per-user file, auto-located per OS: `~/.config/midas_gui/config.json` (Linux), `~/Library/Application Support/midas_gui/config.json` (macOS), `%APPDATA%\midas_gui\config.json` (Windows). If it's absent, the shipped built-in defaults are used. Sharing between machines/users is done by exporting/importing a JSON file (below) — copy it wherever you like.

Editing — Settings ▶ Preferences...

The **Settings** menu opens **Preferences...**, a dialog whose tabs are **pre-filled with the full shipped defaults** so you edit from a complete starting point: - **Geometry** — λ , pixel size, Lsd, beam centre. - **Paths** — default data / calibration / output files & folders. - **Materials / Calibrants** — add / remove / modify (name + lattice + SG). - **Devices** — the detector devices offered in the Data Viewer's **Live Data** PV dropdown (name, prefix, PVA suffix). The live PV is built as `prefix + PVA suffix`. Ships pre-filled with the 20-ID-D detectors (`oryx20idd`, `s20idPil`, `pg4`, `gh1s`, `s20varex1`), all with PVA suffix `Pva1:Image`; add / remove / edit rows for your own beamline's devices. - **Menus** — the pixel-size presets and K-edge foils. - **Algorithms** — default calibration pipeline, integration kernel, output format, error model, colormap/theme. - **Tabs** — which tabs are visible. Data Viewer, Mask Builder, Calibrate and Batch Integrate are always shown (their boxes are locked on); tick/untick the rest. **Tab visibility applies immediately** on save (no restart), unlike the other settings. - **Display** — the **interface scale**, a whole-application zoom (layout *and* fonts) for HiDPI / 4K monitors where the default looks too small. Pick a value or a preset (100 % $\approx$ 1080p, 150 % $\approx$ 1440p, 200 % $\approx$ 4K); it applies after a restart (you're offered one on save). Also reachable from **Settings ▶ Interface scaling....** It is implemented with Qt's `QT_SCALE_FACTOR`, so the whole layout scales uniformly.

Buttons: **Save as my defaults** (write your config), **Save current GUI state** (capture the Data Viewer's live λ /pixel/Lsd/BC into the fields), **Save config to JSON... / Load config (JSON)...** (export/import a config to share), and **Reset to shipped defaults** (delete your config). Also on the menu: **Open config folder** and **Reload config**. Saving writes your per-user file; **changes take effect on the next launch**.

File format

```
{
  "geometry": { "wavelength_A": 0.39, "pixel_um": 75.0, "lsd_um": 121000.0,
    "bc_y": 10.0, "bc_z": 10.0,
    "pixel_presets": [ ["Eiger", 75.0], ["Pilatus", 172.0] ],
    "k_edge_foils": [ ["Au", 80.725], ["Pb", 88.005] ] },
  "materials": { "Ni (FCC)":
    { "a": 3.5238, "b": 3.5238, "c": 3.5238, "alpha": 90, "beta": 90, "gamma": 90, "sg": 225 } },
  "calibrants": { "CeO2":
    { "a": 5.4116, "b": 5.4116, "c": 5.4116, "alpha": 90, "beta": 90, "gamma": 90, "sg": 225 } },
  "devices": [ { "name": "s20varex1", "prefix": "20IDFF:", "pva_suffix": "Pva1:Image" } ],
  "paths": { "nickel_h5": "/data/mygroup/sample.h5", "calib_file":
    "/data/mygroup/calibration.json" },
  "ui": { "calibration_pipeline": "one_shot", "integration_kernel": "subpixel2",
    "output_format": "csv", "azimuthal_method": "poisson", "plot_theme": "hot",
    "visible_tabs": ["Calib. Refinement", "Pump Probe"],
    "ui_scale": 1.0 }
}
```

- `ui.visible_tabs` lists the **optional** tabs to show (the four always-on tabs are implicit). The shipped default is ["Calib. Refinement", "Pump Probe"] — Corrections, PDF Analysis, Texture and Results & Export are hidden until you add them. Edit it from **Preferences ▶ Tabs**.
- `ui.ui_scale` is the whole-interface zoom (0.5–4.0) applied at startup via `QT_SCALE_FACTOR`; ~1.5 for 1440p, ~2.0 for 4K. Edit it from **Preferences ▶ Display** or **Settings ▶ Interface scaling...** (takes effect on restart).
- When a **list section is present it fully replaces** that built-in list — so materials, calibrants, devices, pixel_presets and k_edge_foils in the file are your complete lists. (The Preferences dialog pre-fills them with the shipped entries, so you always start from the full set; use **Reset to shipped defaults** to get them back.) sg is the space-group number.
- Geometry scalars, paths and ui are simple overrides; any section or key may be omitted. A malformed config is ignored (built-ins are used) rather than blocking startup.
- A minimal template lives at `documentation/config.example.json`; the step-by-step guide is `documentation/config_gui.md`.

For bugs or questions, see the MIDAS GUI repository.