

# development\_history

## MIDAS GUI — Development History

A commit-by-commit record of what changed and when, so you can (a) find **when** a particular behaviour/feature entered the code and (b) know **what to roll back** to undo a specific effect.

Keep this file updated when you add commits: append a new entry at the bottom of the chronological log and add a row to the quick-reference index. Regenerate the PDF the same way as the other docs (pandoc + headless Chrome) if you keep one.

### How to use this document

- **Find when a change landed:** search the change → commit index below, or `git log --oneline --<path>` for a specific file, or `git log -S"<code string>"` to find the commit that introduced/removed a string.
- **See a commit's exact diff:** `git show <hash>` (whole commit) or `git show <hash> -- <path>` (one file).
- **Undo one commit cleanly (keeps later history):** `git revert <hash>`. For a range: `git revert <oldest>^..<newest>`.
- **Undo just one file back to a commit:** `git checkout <hash> -- <path>` then commit. To see the file as of a commit without changing anything: `git show <hash>:<path>`.
- **Hard reset to a point (destructive — local only, never on pushed history):** `git reset --hard <hash>`. Prefer `git revert` on a shared branch.
- **Dependencies matter.** Many later commits build on earlier ones (e.g. the unified data-loader, the config overlay). The “Roll back” note on each entry flags when reverting will disturb dependents.

Branch: `main`. All commits are authored by Dishant Beniwal (AI pair-authored). Dates are commit dates (YYYY-MM-DD).

### Change → commit quick-reference index

#### Packaging / build / launch

| Change                                                                                                                                                                   | Commit  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Initial v1.0.0 release (9-tab app, all backends)                                                                                                                         | f19ee8c |
| setuptools.build_meta backend (broader pip compat)                                                                                                                       | 3cd1f36 |
| <code>launch.py</code> standalone launcher                                                                                                                               | 2e9f419 |
| Startup crash diagnostics + robust launcher (Windows)                                                                                                                    | 916ece2 |
| MIDAS-style packaging (LICENSE, pyproject, release.sh, smoke tests)                                                                                                      | e862135 |
| Ship test_data sample data in the repo (fresh clone works out of the box)                                                                                                | 7e157e0 |
| Drop midas_suite from env (unblock conda env create; backends via -e .)                                                                                                  | 72a1770 |
| Pin environment.yml to verified NumPy-1 set + README recreate steps                                                                                                      | 68313f8 |
| Upgrade midas-hkls/midas-calibrate-v2; midas-pdf switched vendored→PyPI                                                                                                  | acb43c1 |
| PyQt5 moved pip→conda-forge (fixes beamline silent startup hang)                                                                                                         | 97ae1ea |
| Add pip <code>requirements.txt</code> mirroring <code>environment.yml</code> + README pip path                                                                           | 683d150 |
| Reorganize <code>test_data/</code> into per-dataset subfolders ( <code>gui_synthetic/</code> , <code>s17bm/</code> , <code>trr_s25ide/</code> , <code>trr_s7id/</code> ) | c8d98f1 |
| Fix stale <code>DEFAULT_*</code> test-data paths after the <code>gui_synthetic/</code> reorg                                                                             | 3b785c9 |

## Data Viewer (Tab 0)

| Change                                                                          | Commit  |
|---------------------------------------------------------------------------------|---------|
| Radial-integration plot, beam-centre ring picking, zoom persistence             | acf0866 |
| Zoom/pan preserved across frames (autoRange off)                                | d9e527e |
| Intensity-range mask, calibration-file loading, click-to-draw ring              | d50b588 |
| Compact 3-per-row lattice + cubic quick-set; mask default max(99.99pct, 1e5)    | 41f28f5 |
| Projection Skip-frames field; compact geometry/intensity fields; Lsd separators | 108ea7d |
| Intensity-statistics panel + histogram (bottom of loader)                       | 2b7a695 |
| Tilt/distortion-aware radial integration when a calibration is loaded           | df544d2 |
| Data Viewer Top-N brightest pixels + mask-aware stats + full-geometry receive   | bc86d74 |
| Calibrate per-coefficient distortion, frame averaging, seed feedback            | b0a5cc3 |
| Batch read-only “Calibration values” card                                       | b6f1681 |
| Pump Probe publication plotting, delay colour-bar, default detector mask        | 49623ae |
| Gitignore local context, internal docs, large sample sets                       | b251ca8 |
| Live Data card: in-tab EPICS PVA stream via pvapy, reload button                | 1769f69 |
| Live viewer: manual colormap/level changes now survive new frames               | 234ded9 |
| Wider image/radial-plot splitter handle                                         | 69f470c |
| Radial profile: Y-min defaults to 0.9x data min, manual Y-range sticks          | 96f8add |

| Change                                                                                                                                                         | Commit                  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Simulate rings is now a live toggle (auto-recomputes on param change)                                                                                          | <a href="#">ecf6d01</a> |
| Live PV field becomes a device dropdown (Preferences ► Devices)                                                                                                | <a href="#">aa82cb6</a> |
| Fix image-view autorange drift; bound pan/zoom to image                                                                                                        | <a href="#">c156c62</a> |
| Radial profile plot: bound pan/zoom to the data extent                                                                                                         | <a href="#">cde4bb2</a> |
| Ring simulation ty/tz tilt fields; configurable spin-box step sizes                                                                                            | <a href="#">5b8e3b3</a> |
| Tilt-aware profile w/o calibration file; ring 2 $\theta$ -cutoff/thickness/live-button fixes; save-calibration buttons; radial-plot X-floor + zoom persistence | <a href="#">e14c1ea</a> |
| Native-menu-backed A/M manual axis limits (radial plot + histogram); Top-N “I >” intensity floor                                                               | <a href="#">3c15ae7</a> |
| Multi-material ring simulation (per-row checkbox/color/name, Material dialog)                                                                                  | <a href="#">0e9ed21</a> |
| Load-calibration card moved below Simulate button; loads now sync ty/tz too; Intensity-range title bar is the on/off checkbox                                  | <a href="#">05ce224</a> |
| Live Data “Use Buffer” last-N-frames ring buffer (Projection/stack analysis on live data)                                                                      | <a href="#">911f8ac</a> |
| Fix: lock live ring buffer against GUI/worker-thread race                                                                                                      | <a href="#">a88ba1f</a> |
| Fix: refresh-timer starvation during fast live streaming                                                                                                       | <a href="#">2cfd9cd</a> |
| Fix: cap live buffer to 100 frames (memory bound)                                                                                                              | <a href="#">839770d</a> |

| Change                                                                                                | Commit  |
|-------------------------------------------------------------------------------------------------------|---------|
| Fix: “All frames” stats computed off the GUI thread                                                   | 08392c6 |
| Fix: debounce intensity-mask pixel≤/pixel> spinbox edits                                              | 57ced2f |
| Fix: warn when composite mask silently drops a shape-mismatched source                                | 81b8ea8 |
| Sim Detector: hardware-free fake PVA stream in the Live Data dropdown                                 | 3d96cb1 |
| Image viewer: persist manual color-scale window (incl. histogram zoom) across live frames             | 3b12fbf |
| Fix: “Use Buffer” state now carries into Start instead of resetting                                   | f3a1b91 |
| Unrestrict λ/Lsd/pixel-size ranges; tighten decimals; Rings/Labels/thickness on one row               | 2525277 |
| “?” help button explaining radial-integration (R-bin) calculation                                     | b7a1518 |
| Exclude-range controls moved into radial-plot toolbar; int-safe pixel bounds                          | de15d57 |
| Pixel-size field allows a second decimal place (near-field detectors)                                 | 1d45c40 |
| Box/Circle/Line ROI tool with live floating stats popups                                              | ecfbf36 |
| ROI tool drops Circle (Box/Line only); Clear ROIs resets numbering; Pick Clear also removes BC marker | d5654c1 |
| Line ROI drawn as single arrow shape (no separate arrowhead item)                                     | bb78c9a |
| Box-ROI popup’s zoomed crop image resizes with the popup window                                       | 786c94c |

| Change                                                                                                                                                                                        | Commit  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Projection N-frames cap; $\lambda$ menu gains energy-to-wavelength entry                                                                                                                      | 468b417 |
| B-PILOT bridge: local-socket server auto-starts Live Data on scan dispatch                                                                                                                    | c336778 |
| ROI popups always-on-top + minimize-to-ribbon; Project-stack button green highlight                                                                                                           | 6c79f13 |
| ROI/histogram axis label font size bumped 9pt - > 12pt (readability)                                                                                                                          | 1181b58 |
| Transforms: Flip Y/Flip Z/Transpose checkboxes (MIDAS ImTransOpt); saved/loaded calibration files round-trip it                                                                               | 068bd0d |
| Image origin flipped to bottom-left $(0,0)$ (MIDAS convention); ROI box-corner annotations now label the bottom-left corner                                                                   | 246dba7 |
| Hydra-mode ribbon scaffold (Single detector/Hydra); ring-sim/calibration/radial logic extracted into DetectorGeometryCard                                                                     | 3d2d99d |
| Hydra geometry-compositing engine ( <code>hydra.py</code> ) + sibling auto-discovery + tests                                                                                                  | dd44f38 |
| Hydra loader/toolbar/per-panel calibration UI + composite wired into the tab                                                                                                                  | 1cc4dab |
| Hydra multi-curve radial profile plot (4 panels + toggleable composite curve)                                                                                                                 | 8707372 |
| Hydra Phase 6 pass: shared $\lambda/2\theta$ /px fields, dark/bright/background correction, composite orientation fix (CCW + vertical mirror), stale radial geometry fix, zero-excluded vmin% | 0aa5feb |

## Mask Builder (Tab 1)

| Change                                                                                                                                                              | Commit  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Unbounded $\sigma$ fields; independent spatial/temporal auto-mask; Viewer↔Calibrate geometry hand-off                                                               | 10df828 |
| Temporal-constancy accepts a 3-D HDF5 (time,y,x) stack                                                                                                              | 2385f75 |
| Image/Stack browse gains “Import from...” (other tabs’ loaded path/buffer)                                                                                          | 6c79f13 |
| Stack browse menu gains “Files (multi-select)...” for hand-picked temporal stacks                                                                                   | cc63d5a |
| “5 · Post-processing” card: configurable bad-pixel dilation (px)                                                                                                    | 429d41a |
| Dilation switched from 4-connected to 8-neighbor full-block growth                                                                                                  | 188ea77 |
| Transforms: Flip Y/Flip Z/Transpose checkboxes (MIDAS ImTransOpt), applied to the single image and the stack source alike; synced from an incoming Calibrate result | 068bd0d |
| Image origin flipped to bottom-left $(0,0)$ (MIDAS convention)                                                                                                      | 246dba7 |

## Calibrate (Tab 2) / Refinement (Tab 3)

| Change                                                                            | Commit  |
|-----------------------------------------------------------------------------------|---------|
| Abort buttons; dark/bright/background field correction; auto-load on browse       | 7d010d7 |
| Calibration input accepts paramtest/poni/json                                     | 41f28f5 |
| Load-calibration-file (geometry + $\lambda$ ) helpers                             | b381d8d |
| Multi-column paramtest results readout + Send-to-Data-Viewer button               | 455ca4e |
| Calibrate Results all-text (drop distortion table; named distortion, bigger font) | 3a6ecb9 |

| Change                                                                                                                                                                                            | Commit  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Fix calibrate() initial_BC_y TypeError (kwargs filter) + pin scikit-image                                                                                                                         | b1642fa |
| Pick-Ring fit overlay recolored blue (was same amber as simulated rings)                                                                                                                          | 3eb4a44 |
| “Corrected” rings drawn synchronously from fitted ty/tz (drop background worker)                                                                                                                  | 5b8e3b3 |
| One-shot honors partial distortion-coefficient selection; live dark/bright/bg preview                                                                                                             | cc6e90e |
| Existing Transforms checkboxes now round-trip through saved/loaded paramstest.txt + calibration.json (previously in-memory only)                                                                  | 068bd0d |
| Transforms checkboxes now live-update the preview and drive the actual calibration run (all pipeline modes); Send-to-Data-Viewer carries Transforms; Average frames drops the skip/stride control | 73a7a2a |
| Image origin flipped to bottom-left (0,0) (MIDAS convention)                                                                                                                                      | 246dba7 |

Batch Integrate (Tab 4)

| Change                                                                       | Commit  |
|------------------------------------------------------------------------------|---------|
| Live folder MONITOR + per-file legend                                        | 1149afc |
| Clear results + inline per-file labels & plot controls                       | 524f5f1 |
| Stacked profiles: publication themes, point+line, symbol size, x-units, grid | d135c80 |
| Waterfall R/2θ/Q x-axis selector                                             | 2385f75 |

PDF Analysis (Tab 6)

| Change                                                                                                                                                    | Commit  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Polyatomic midas_pdf reduction pipeline + vendored midas_pdf + calibration loading                                                                        | b381d8d |
| Defaults to real I(Q) test data                                                                                                                           | 1149afc |
| midas_pdf switched from vendored copy to the real PyPI package                                                                                            | acb43c1 |
| Rebuilt for full Stage 2-3 workflow (absorption/efficiency/normalization/multiple-scattering/fluorescence/structure-fit/ $\Delta$ -PDF), new 4-tab layout | 23cd55e |

## Pump Probe (TR-XRD) tab

| Change                                                                                                                                                    | Commit  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| New tab: TRR pooling + MIDAS-engine integration + $\Delta I(q, \text{delay})$ + 4 pyqtgraph views + publication-quality plots + default MIDAS calibration | 590b410 |

## Cross-cutting UI / infrastructure

| Change                                                                | Commit  |
|-----------------------------------------------------------------------|---------|
| Linux visible files/folders style fix                                 | fc754d0 |
| Pixel-weighted azimuthal mean; readable QMenu; no-scroll combos       | 41f28f5 |
| Unified Data-Loader panel + draggable 3-panel splitter (tabs 0/2/3/4) | aa9395e |
| Clickable $\lambda$ label with K-edge foil menu                       | b628446 |
| Clickable px label with detector pixel-size menu                      | 3248638 |
| Per-user JSON configuration system + Preferences dialog               | d30be2c |
| Modular tab visibility (show/hide optional tabs)                      | 590b410 |

| Change                                                                                                                                                                                              | Commit  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Multi-profile config (Preferences ▶ Profile row)                                                                                                                                                    | 5b8e3b3 |
| File ▶ Save/Load GUI State (all 10 tabs, with mask/calibration sidecars)                                                                                                                            | 5b8e3b3 |
| User-adjustable interface scaling (HiDPI / 4K, QT_SCALE_FACTOR)                                                                                                                                     | d5fafd8 |
| Default optional tabs reduced (Corrections/PDF/Texture/Export hidden)                                                                                                                               | 7e157e0 |
| Lsd displayed in mm (calculations & calibration files stay in $\mu\text{m}$ )                                                                                                                       | c4e1c12 |
| Fix “Populating font family aliases” warning (real fixed-width fonts)                                                                                                                               | d6df1f8 |
| Fix fresh-env launch crash — colormap resolution without matplotlib                                                                                                                                 | 6332b3d |
| Fix native Bus-error crash on Run Calibration — cap BLAS/OMP thread pools                                                                                                                           | 0b4326d |
| Preferences ▶ Devices tab; Live PV field becomes a device dropdown                                                                                                                                  | aa82cb6 |
| Widen non-data-derived numeric field caps (tilts to $\pm 180^\circ$ , iteration/geometry/hyperparameter fields to effectively unbounded) across Data Viewer/Calibrate/Corrections/Mask/Refine/Batch | 53f8f19 |
| Cross-tab DataSourceRegistry + “Import from...” menus (Data/Dark/Bright/Background) + buffer-save button                                                                                            | 6c79f13 |

## Stability / performance / consistency (review-driven, phases 1–3)

| Change                                                                            | Commit  |
|-----------------------------------------------------------------------------------|---------|
| Clean worker shutdown, drop QThread.terminate(), guard stdout, offload projection | 399f3d7 |

| Change                                                                                   | Commit  |
|------------------------------------------------------------------------------------------|---------|
| Waterfall $O(N^2) \rightarrow O(N)$ , frame-slider debounce, radial-grid + stats caching | 4462ee1 |
| Dedupe distortion map + paramstest writer, align calibrant lattices, texture colormap    | 8846619 |

Documentation

| Change                                                                        | Commit  |
|-------------------------------------------------------------------------------|---------|
| README not-on-PyPI clone/conda instructions                                   | cd05ced |
| gui_documentation.md added                                                    | 2e5f7c9 |
| gui_documentation.pdf added                                                   | 75c135c |
| README/environment install via <code>pip install midas_suite</code>           | aceb40f |
| implementation_details.md/.pdf added                                          | 524f5f1 |
| config_gui.md + config.example.json added                                     | d30be2c |
| development_history.md/.pdf added                                             | 6d6f3fb |
| Commit <code>.context/</code> (was gitignored, contradicting standing policy) | 778a2f3 |

Chronological commit log (oldest → newest)

f19ee8c — Initial release: midas\_gui v1.0.0 (2026-06-30)

**Effect:** First version. Nine-tab PyQt5 GUI over `midas_calibrate_v2` / `midas_integrate_v2`: mask building, auto-calibration, refinement, batch integration + waterfall, corrections, PDF, texture, export. Entry points `midas-gui` / `python -m midas_gui`. **Files:** entire `midas_gui/` package + `pyproject.toml`, `README`, `environment.yml`. **Roll back:** this is the root — everything depends on it; don't revert.

3cd1f36 — setuptools.build\_meta backend (2026-06-30)

**Effect:** Build backend switched for setuptools $\geq$ 61 compatibility. **Files:** `pyproject.toml`. **Roll back:** `git revert 3cd1f36` (only affects builds).

### 2e9f419 — add launch.py standalone launcher (2026-06-30)

**Effect:** `python /path/to/launch.py` runs the app from anywhere. **Files:** `launch.py`. **Roll back:** safe to revert; later hardened by `916ece2`.

### fc754d0 — Linux style fix for invisible files/folders (2026-06-30)

**Effect:** Stylesheet fix so file/folder text is visible on Linux. **Files:** `midas_gui/style.py`. **Roll back:** `git revert fc754d0` (cosmetic).

### acf0866 — Data Viewer: radial plot, ring picking, zoom persistence (2026-06-30)

**Effect:** Added the radial-integration plot, beam-centre ring picking, and zoom-persistence across a stack in the Data Viewer; widened left panels. **Files:** `tab_view.py` (+1-line width bumps in other tabs). **Roll back:** revert to remove the Data Viewer radial plot/ring picking.

### d9e527e — preserve zoom/pan across frames (2026-06-30)

**Effect:** Disabled pyqtgraph `autoRange` on redisplay so zoom/pan survive frame changes. **Files:** `widgets.py`. **Roll back:** revert if you *want* auto-refit per frame.

### d50b588 — Data Viewer: intensity mask, calib loading, click-to-draw ring (2026-07-01)

**Effect:** 99.9-pct intensity-range mask default; load calibration (`json/poni/paramtest`); click-to-draw ring; test-data defaults point at local `test_data/`. **Files:** `tab_view.py`, `widgets.py`, `helpers.py`, `constants.py`, `tab_mask.py`. **Roll back:** revert to drop these Data Viewer features (note `helpers.py` geometry parsing added here is reused later — see `b381d8d`).

### 916ece2 — startup crash diagnostics + robust launcher (2026-07-01)

**Effect:** Logs uncaught exceptions/native faults to `~/midas_gui_error.log`, prevents PyQt slot-exception aborts, isolates failing tabs, hardens the launcher. **Files:** `app.py`, `launch.py`. **Roll back:** revert only if you want raw exceptions to propagate; not recommended.

### 7d010d7 — Abort buttons + dark/bright/background + auto-load (2026-07-01)

**Effect:** Abort on calibrate/batch; dark/bright/background field correction (file/folder/HDF5, index-range averaging, divide/subtract); browse auto-loads, “Load” buttons removed; compact FieldSelector. **Files:**

`tab_batch/calibrate/corrections/mask/pdf/refine/texture/view.py`, `widgets.py`, `workers.py`, `helpers.py`.

**Roll back:** wide-reaching; reverting removes field correction + auto-load across tabs. The Abort behaviour here was later re-worked by `399f3d7` (no `terminate()`).

## [e862135](#) — MIDAS-style packaging (2026-07-01)

**Effect:** BSD-3 LICENSE, MIDAS-convention `pyproject.toml`, `release.sh` + `RELEASING.md`, headless tests/ smoke suite. **Files:** `LICENSE`, `README.md`, `RELEASING.md`, `pyproject.toml`, `release.sh`, `tests/`. **Roll back:** revert affects packaging/tests only.

## [41f28f5](#) — compact lattice, pixel-weighted azimuthal mean, readable menus (2026-07-06)

**Effect:** Data Viewer 3-per-row lattice + cubic quick-set; intensity-mask default max(99.99pct, 1e5); **pixel-weighted azimuthal mean** (selectable vs legacy  $\eta$ -bin mean) fixing off-detector-BC distortion; batch calibration accepts paramtest/poni/ json; readable right-click menus; no-scroll combos. **Files:** `helpers.py`, `workers.py`, `tab_view/batch/calibrate/pdf/refine/texture.py`, `widgets.py`, `style.py`. **Roll back:** to undo the azimuthal-averaging change specifically, prefer editing the `weighted` default rather than reverting the whole commit (it bundles UI changes).

## [cd05ced](#) — docs: not-on-PyPI install instructions (2026-07-06)

**Effect:** README clone+conda+run instructions; relative env self-install. **Files:** `README.md`, `environment.yml`. **Roll back:** docs only.

## [2e5f7c9](#) — docs: add gui\_documentation.md (2026-07-06)

**Effect:** First committed user guide. **Files:** `documentation/gui_documentation.md`. **Roll back:** docs only.

## [75c135c](#) — docs: add gui\_documentation.pdf (2026-07-06)

**Effect:** PDF build of the guide. **Files:** `documentation/gui_documentation.pdf`. **Roll back:** docs only.

## [aceb40f](#) — docs: install via `pip install midas_suite` (2026-07-06)

**Effect:** Corrected backend-install instructions. **Files:** `README.md`, `environment.yml`. **Roll back:** docs only.

## [aa9395e](#) — Unified Data-Loader panel + 3-panel splitter (tabs 0/2/3/4) (2026-07-07)

**Effect:** Shared `DataLoaderPanel` (Data/Dark/Bright/Background/Mask, per-mode frame controls) + `MaskSelector`; corrections applied on tabs 0/2/3/4; each of those tabs restructured into a draggable [Data Loader | Parameters | Display] splitter. **Files:** `widgets.py` (+442),

`tab_view/calibrate/batch/refine.py` (large rewrites), `app.py`, `helpers.py`, `workers.py`, docs. **Roll back:** **high impact** — this is the base for the Batch/Calibrate/Refine and later Pump Probe layouts. Reverting breaks the 3-panel tabs and the Pump Probe tab's left panel. Avoid a blanket revert; fix forward instead.

### **b381d8d — Tab 6 polyatomic midas\_pdf pipeline + calibration loading (2026-07-08)**

**Effect:** PDF tab rewritten to the total-scattering pipeline; **vendored** `midas_pdf` under `midas_gui/_vendor/` + `pdf_backend.py`; helpers `geometry_fields_from_file` / `result_ns_from_geometry_file` (paramtest/json/poni) used by Calibrate and PDF “Load calibration file...”. **Files:** `_vendor/midas_pdf/**` (new, large), `pdf_backend.py`, `tab_pdf.py`, `workers.py`, `helpers.py`, `tab_calibrate.py`, `constants.py`, `pyproject.toml`, docs. **Roll back:** reverting removes the PDF pipeline **and** the shared geometry-file loaders that later tabs (incl. Pump Probe via `spec_from_geometry_file`) rely on — revert with care.

### **1149afc — Batch live MONITOR + legend; PDF real-data default (2026-07-08)**

**Effect:** MONITOR button (stream mode) watches a folder and integrates new frames via `FolderMonitorWorker`, reusing a cached detector map (factored `build_integration_context()` + `write_profile()`, shared with `BatchWorker`); per-file legend; PDF tab defaults to real I(Q). **Files:** `tab_batch.py`, `workers.py`, `widgets.py`, `constants.py`, `tab_pdf.py`, docs. **Roll back:** to remove MONITOR only, revert this commit — but `build_integration_context()` introduced here is **reused by the Pump Probe worker** (`590b410`), so a full revert would break Pump Probe integration.

### **524f5f1 — Batch Clear results + inline labels; implementation-details doc (2026-07-09)**

**Effect:** “Clear results” button; inline per-file curve labels + line-width/font toolbar on stacked profiles; new `implementation_details.md/.pdf`. **Files:** `tab_batch.py`, `widgets.py`, `documentation/implementation_details.*`. **Roll back:** safe, localized to Batch + the new doc.

### **10df828 — Mask unbounded $\sigma$ + split auto-mask; Viewer↔Calibrate geometry (2026-07-09)**

**Effect:** Removed  $\sigma$  upper limits; split statistical auto-mask into independent Spatial-outlier / Temporal-constancy checkboxes; geometry hand-off `DataViewer.pushGeometry` / `Calibrate.pullGeometry` → `apply_geometry`. **Files:** `tab_mask.py`, `tab_view.py`, `tab_calibrate.py`, `app.py`, `workers.py`, docs. **Roll back:** revert to restore bounded  $\sigma$  / combined auto-mask / no geometry hand-off.

### **d135c80 — Batch stacked-profiles: themes, point+line, x-units, grid (2026-07-09)**

**Effect:** `StackedProfileViewer` publication/dark themes, point+line, symbol-size, R/2 $\theta$ /Q x-unit selector, grid toggle. (This viewer's styling is the template the Pump Probe plots later mirror.) **Files:** `widgets.py`

(+228), `tab_batch.py`, docs. **Roll back:** localized to the Batch stacked-profile viewer.

### 2385f75 — Batch waterfall R/2θ/Q axis; Mask 3-D HDF5 stack (2026-07-10)

**Effect:** Waterfall x-unit selector via a converting `AxisItem + _convert_radial()`; Mask temporal-constancy reads a single 3-D (time,y,x) HDF5. **Files:** `widgets.py`, `tab_batch.py`, `tab_mask.py`, `workers.py`, docs. **Roll back:** `_convert_radial` / `_UnitAxis` introduced here are reused by the Pump Probe heatmap — don't fully revert if Pump Probe is present.

### b628446 — clickable λ label with K-edge foil menu (2026-07-10)

**Effect:** Compact clickable “λ” label → K-edge foils menu (sets λ from edge energy).

`constants.K_EDGE_FOILS`, `HC_KEV_A`, `helpers.make_kedge_label`. **Files:** `constants.py`, `helpers.py`, `tab_view/calibrate/pdf.py`, docs. **Roll back:** localized; `make_pixel_label` (next) reuses the factored helper.

### 108ea7d — Data Viewer projection Skip-frames + compact fields (2026-07-10)

**Effect:** Projection “Skip frames” field; narrower Axis/Skip/pixel fields; Lsd thousands-separators. **Files:** `tab_view.py`, docs. **Roll back:** localized.

### 3248638 — clickable px label with detector pixel-size menu (2026-07-10)

**Effect:** Clickable “px” label → GE/Varex/Pilatus/Eiger sizes; `constants.PIXEL_PRESETS`; factored `helpers._clickable_menu_label`. **Files:** `constants.py`, `helpers.py`, `tab_view.py`, `tab_calibrate.py`, docs. **Roll back:** localized.

### 2b7a695 — Data Viewer intensity-statistics panel + histogram (2026-07-10)

**Effect:** `IntensityStatsPanel` (histogram + p70/p90/p99/p99.9/p99.99 with pixel counts) pinned to the loader bottom (stack mode); Current/All/projected scope. **Files:** `widgets.py`, `tab_view.py`, docs. **Roll back:** localized.

### d30be2c — per-user configuration system + Preferences dialog (2026-07-12)

**Effect:** Per-user JSON config overlays shipped defaults at import; `settings.py`; `prefs_dialog.py` (Geometry/Paths/Materials/Calibrants/Menus/Algorithms); Settings menu; `DEFAULT_KERNEL/PIPELINE/OUTPUT_FORMAT/ERROR_MODEL/COLORMAP`; tab combos honor configured defaults. New `config_gui.md`, `config.example.json`, `tests/test_config.py`. **Files:** `settings.py` (new), `prefs_dialog.py` (new), `constants.py` (+165), `app.py`, `tab_batch.py`, `tab_calibrate.py`, `widgets.py`, docs, tests. **Roll back:** **high impact** — the config overlay + `DEFAULT_*` and the Preferences dialog are extended by the modular-

tabs commit (590b410). Reverting this would also break `ui.visible_tabs` and the Tabs preferences section.

### 399f3d7 — Stability: clean worker shutdown, no terminate(), stdout guard (2026-07-12)

**Effect:** `closeEvent` stops all tab QThreads; removed every `QThread.terminate()` (cooperative interrupt + orphan instead); `CalibrationWorker` restores stdout only if still its own; Data Viewer projection moved to `ProjectionWorker` (off GUI thread). **Files:** `app.py`, `tab_batch.py`, `tab_calibrate.py`, `tab_view.py`, `workers.py`. **Roll back:** reverting reintroduces the exit hard-crash risk and UI-freeze on projection — not recommended. Phase 1 of the 3-part review.

### 4462ee1 — Performance: waterfall O(N), debounce, caching (2026-07-12)

**Effect:** Waterfall pre-allocated buffer + 100 ms coalesced redraw ( $O(N)$  not  $O(N^2)$ ); 60 ms frame-slider debounce; cached radial bin-index grid; skip all-frame stats on frame-only changes. **Files:** `tab_view.py`, `widgets.py`. **Roll back:** reverting slows large scans / scrubbing; behaviour otherwise same. Phase 2 of the review.

### 8846619 — Consistency: dedupe maps/writer, align lattices (2026-07-12)

**Effect:** `helpers._PARAMSTEST_DISTORTION` derived from `constants._V2_T0_V1` (removed duplicated `_V2V1` dicts); shared `helpers.write_standalone_paramstest` used by Calibrate + Export; LaB6/Si `_LATT/_LC` aligned to `MATERIALS`; texture colormap honors `DEFAULT_COLORMAP`. **Files:** `constants.py`, `helpers.py`, `tab_calibrate.py`, `tab_export.py`, `tab_texture.py`. **Roll back:** reverting reintroduces duplicated code paths; low functional risk. Phase 3 of the review.

### 590b410 — Modular tabs + Pump Probe (TR-XRD) tab + plot quality (2026-07-12)

**Effect:** (1) **Modular tab visibility** — Data Viewer/Mask/Calibrate/Batch always shown, the rest toggled in Settings ▶ Preferences ▶ Tabs (`ui.visible_tabs`, applied live); `app.apply_tab_visibility()`. (2) **New Pump Probe tab** (`tab_pumpprobe.py`) — TRR filename pooling, MIDAS-engine integration via new `PumpProbeWorker` (reuses `build_integration_context / integrate_frame`),  $\Delta I(q, \text{delay})$ , three-panel layout, four pyqtgraph views; ships a converted MIDAS `paramstest` as the default calibration. (3) **Plot quality** — white publication theme, black axes/labels/titles, readable legends,  $\Delta I$  colorbar, aligned reference panel, shared draw-mode + line/point/font-size toolbar, bounded pan/zoom. **Files:** `tab_pumpprobe.py` (new), `workers.py` (+ `PumpProbeWorker`), `app.py`, `constants.py`, `prefs_dialog.py`, `tests/test_smoke.py`, `docs` (`gui_documentation`, `config_gui`, `config.example.json`). **Roll back:** to remove **only Pump Probe**, delete `tab_pumpprobe.py` and its wiring in `app.py / workers.py`; to remove **only modular tabs**, revert the `app.apply_tab_visibility / prefs_dialog` Tabs section and `constants` tab lists. A full `git revert 590b410`

removes both features together. Depends on `aa9395e` (`DataLoaderPanel`), `1149afc` (`build_integration_context`), `2385f75` (`_convert_radial/_UnitAxis`), `d30be2c` (`config/prefs`).

### `6d6f3fb` — docs: add development\_history.md/.pdf (2026-07-13)

**Effect:** Added this per-commit change log + change→commit index + rollback guide. **Files:** `documentation/development_history.md`, `documentation/development_history.pdf`. **Roll back:** docs only.

### `d5fafd8` — UI scaling: user-adjustable whole-interface zoom (HiDPI / 4K) (2026-07-13)

**Effect:** Whole-application scale (layout + fonts) for HiDPI / 4K monitors. `constants.DEFAULT_UI_SCALE` (config `ui.ui_scale`); `app.main()` applies it via `QT_SCALE_FACTOR` **before** the `QApplication` is created (so fixed widths, splitters, pyqtgraph and stylesheet px all scale uniformly) + `AA_UseHighDpiPixmaps`. Manual control in **Preferences ▶ Display** (spin + 100/125/150/200 % presets) and **Settings ▶ Interface scaling...**; both persist `ui.ui_scale` and offer an immediate self-restart (`MainWindow.restart_app` via `QProcess`) since the factor is read only at startup. **Files:** `constants.py`, `app.py`, `prefs_dialog.py`, docs (`gui_documentation`, `config_gui`, `config.example.json`). **Roll back:** `git revert d5fafd8`. Self-contained (depends only on the config system `d30be2c`); reverting removes the scale control and the app renders at 1.0×. To keep the feature but disable it, set `ui.ui_scale` to 1.0.

### `c4e1c12` — Display Lsd in mm (calculations & files stay in μm) (2026-07-13)

**Effect:** The sample-to-detector distance is entered/shown in **mm** in the Data Viewer, the Calibrate seed, and Preferences ▶ Geometry; conversion to/from μm happens only at the display boundary (`DataViewerTab._lsd_um()`, ×1000 on read, ÷1000 on set). `get_geometry / apply_geometry / manual_seed / prefs _assemble` still emit μm; the config key stays `lsd_um` (μm); calibration-file writers (`paramtest.txt`, `calibration.json`) are unchanged (always μm). Batch drift-status label → mm. **Files:** `tab_view.py`, `tab_calibrate.py`, `prefs_dialog.py`, `tab_batch.py`, docs. **Roll back:** `git revert c4e1c12` to return every Lsd field to a μm display. Purely a display-layer change — no stored/file/calculation values are affected either way.

### `d6df1f8` — Fix “Populating font family aliases” startup warning (2026-07-13)

**Effect:** Removed the `qt.qpa.fonts: Populating font family aliases` warning (and its ~40 ms startup cost) that Qt emitted because the code named the nonexistent family “Monospace” — both via `QFont("Monospace", ...)` and the CSS generic `font-family:monospace`. Now names real per-platform families (Menlo/Consolas/DejaVu Sans Mono/Courier New) via `style.MONO_FAMILIES / MONO_CSS` and `widgets._mono_font()` (`QFont setFamilies` + Monospace style hint). **Files:** `style.py`, `widgets.py`, `tab_export.py`, `tab_view.py`. **Roll back:** `git revert d6df1f8` (cosmetic; only affects fixed-width font selection and re-introduces the harmless warning).

## 455ca4e — Calibrate: multi-column results readout + Send-to-Data-Viewer (2026-07-13)

**Effect:** (1) The Calibrate **Results** tab shows the full parameter set exactly as written to `paramtest.txt` (Lsd, BC, tx/ty/tz, p0–p14, Parallax, Wavelength, px, NrPixelsY/Z, RhoD, SpaceGroup, LatticeConstant) in a 3-column, column-major grid (`_paramtest_pairs` via the shared writer + `_populate_param_grid`), with a strain/timing line and the named-distortion table below. (2) New → **Send to Data Viewer** button (`sendGeometryToViewer` signal + `_send_to_viewer`) pushes the calibrated  $\lambda$ /pixel/Lsd/beam-centre into the Data Viewer through new `DataViewerTab.set_geometry` ( $\mu\text{m}$  internal, Lsd shown mm, auto-BC off); wired in `app.py` as the reverse of the Viewer→Calibrate hand-off. **Files:** `tab_calibrate.py`, `tab_view.py`, `app.py`, `docs`. **Roll back:** `git revert 455ca4e`. Self-contained; depends on the mm-display change (`c4e1c12`) for the Viewer Lsd conversion.

## 7e157e0 — Ship test\_data; hide four optional tabs by default (2026-07-14)

**Effect:** (1) `test_data/` sample data (`calibrant_ceria.tif/h5`, `nickel_stack.h5`, `nickel_tifs/`, `make_test_data.py`) is now committed so the GUI's default paths work on a fresh clone — `.gitignore` re-includes it past the global `*.tif/*.h5` ignores via trailing negations, while `test_data/output/`, `out_temp.txt` and `.DS_Store` stay ignored. (2) `DEFAULT_VISIBLE_TABS = ["Calib. Refinement", "Pump Probe"]` — Corrections, PDF Analysis, Texture and Results & Export ship hidden (enable in Preferences ▶ Tabs). **Files:** `.gitignore`, `test_data/**` (added), `constants.py`, `config.example.json`, `tests/test_smoke.py`, `docs`. **Roll back:** `git revert 7e157e0` restores the all-optional-tabs default and removes the shipped data + re-ignores `test_data/`. Note: a per-user config with its own `ui.visible_tabs` overrides the shipped default regardless.

## 6332b3d — Fix launch crash on fresh Linux/Windows (colormap w/o matplotlib) (2026-07-14)

**Effect:** Fixes the GUI failing to start on a clean env where every always-on tab's image viewer crashed with `'NoneType' object has no attribute 'getColors'`. Cause: `DEFAULT_COLORMAP` "hot" (and the whole `COLORMAPS` list) are matplotlib colormaps; `pg.colormap.get("hot")` returns `None` without matplotlib, and that `None` was passed into `pyqtgraph`. New `widgets._resolve_cmap()` resolves native → matplotlib → native fallback → grayscale ramp and never returns `None` (used by `ImageViewer`, `WaterfallViewer`, `Texture`); matplotlib added as a declared dependency (`pyproject` + `environment.yml` `matplotlib-base`) so the named maps actually resolve. The downstream "Geometry hand-off wiring failed / QWidget has no attribute `pushGeometry`" log lines were only a symptom of the tabs becoming placeholders and disappear with this fix. **Files:** `widgets.py`, `tab_texture.py`, `pyproject.toml`, `environment.yml`, `tests/test_smoke.py`. **Roll back:** `git revert 6332b3d` (reintroduces the crash on matplotlib-less envs).

## 72a1770 — env: drop midas\_suite (unblocks conda env create) (2026-07-14)

**Effect:** `conda env create -f environment.yml` was aborting because the pip section's `midas_suite` meta-package pulls `midas-index 0.7.3`, whose `sdist` fails to build against `scikit-build-core>=0.8` (Use `cmake.version` instead of `cmake.minimum-version`). The GUI never uses `midas_suite`'s extras; the backends it actually imports (`midas-calibrate-v2/-integrate-v2/-calibrate/-hkls/-distortion`) are declared in `pyproject.toml` and pulled by the editable `-e .` install. Removed the redundant `midas_suite` line; README updated. (Unrelated to the repo: the `libarchive.19.dylib` / `conda-libmamba-solver` errors in that log are a broken base-Anaconda mamba, worked around with `--solver=classic`.) **Files:** `environment.yml`, `README.md`. **Roll back:** `git revert 72a1770` (re-adds `midas_suite` and its build failure).

## 68313f8 — Pin environment.yml to a verified NumPy-1 set + README recreate steps (2026-07-14)

**Effect:** Makes `conda env create` reproduce a known-good environment. Fresh installs previously pulled the newest backends (`numba 0.66` → `NumPy 2.x`) against `conda torch 2.2.2`, which can't interop with `NumPy 2` (`torch.from_numpy: Numpy is not available`). Pinned every package to the versions from the user's working base Anaconda — the **NumPy-1 family**: `numpy=1.26.4`, `scipy=1.13.1`, `h5py=3.11.0`, `tifffile=2023.4.12`, `pyqtgraph=0.14.0`, `matplotlib-base=3.8.4` (conda); `PyQt5==5.15.10`, `torch==2.4.0`, `numba==0.59.1`, and the NumPy-1-era MIDAS backends (`calibrate-v2 0.3.3`, `integrate-v2 0.1.0`, `calibrate 0.2.3`, `hkls 0.4.1`, `distortion 0.2.0`) via pip; then `-e .`. Dropped the conda `pytorch/cpuonly` lines + `pytorch` channel (`torch` now via pip). `pyproject.toml`: lowered `midas-calibrate` floor `0.2.7` → `0.2.3` so the proven base version satisfies `-e .`. README gains a "Recreating the environment" section (remove + create), a conda-solver/libarchive note, and the CPU-only torch install note. Verified end-to-end: fresh env resolves clean; GUI + a real nickel-frame integration run (`numpy 1.26.4` + `torch 2.4.0`). **Files:** `environment.yml`, `pyproject.toml`, `README.md`. **Roll back:** `git revert 68313f8` (returns to ranged deps; a fresh env would again risk the NumPy-2/torch mismatch). To move forward to a NumPy-2 stack instead, bump `torch>=2.3` and the backends to their `numba-0.66` releases together.

## 3a6ecb9 — Calibrate Results: all-text multi-column readout (drop distortion table) (2026-07-14)

**Effect:** The Calibrate **Results** tab is now entirely text. Removed the distortion `QTableWidget`; the distortion coefficients appear in the same multi-column parameter grid, with the paramtest `p0-p14` slots relabelled to their names (`iso_R2`, `a1`, `phi1`, ...) via `helpers._PARAMSTEST_DISTORTION`. Larger font (12 pt) and roomier row/column spacing for readability. Removed the `DistortionTable` import + `set_distortion` call. **Files:** `tab_calibrate.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 3a6ecb9` (restores the named-distortion table widget below the grid). `DistortionTable` still exists in `widgets.py` (used only here), so a revert is clean.

## b1642fa — Fix calibration TypeError (initial\_BC\_y) + add scikit-image (2026-07-14)

**Effect:** Fixes calibration failing with `calibrate()` got an unexpected keyword argument `'initial_BC_y'` on the pinned (base-matching) midas-calibrate-v2 0.3.3, whose `calibrate()` has no beam-centre seed parameter (only newer backends add it). New `calib._supported_kwargs(fn, kwargs)` filters kwargs to the installed callable's signature (keeps `initial_Lsd`, drops the unsupported `initial_BC_y/z`, logs it), so the GUI tolerates backend-version signature drift. Also pins **scikit-image=0.23.2** in `environment.yml` — midas-calibrate-v2's `auto_seed_calibrant` needs it; without it, seeding degrades to the coarse arc fallback. Verified: manual-seed one\_shot calibration of the shipped ceria runs end-to-end (numpy 1.26.4 + torch 2.4.0). **Files:** `calib.py`, `environment.yml`. **Roll back:** `git revert b1642fa` (reintroduces the `TypeError` on backends lacking the BC-seed args, and removes the scikit-image pin).

## df544d2 — Data Viewer: tilt/distortion-aware radial integration (2026-07-14)

**Effect:** When a loaded calibration file carries the full geometry (tilts + distortion), the Data Viewer's radial integration goes through the MIDAS engine (`build_integration_context` + `integrate_frame`) instead of concentric-circle binning, so pixels map through the calibrated tilts/distortion. `_load_calibration` now also reads the full geometry via `geometry_fields_from_file` (falls back to scalar/circle mode if absent) and shows the active mode. `_midas_radial` caches the binning geometry per (geometry, R-bin, image shape, static mask) and reuses it across frames (fast `hard` kernel; loader's static composite mask so the cache holds); `_radial_integrate` branches to it with a guarded fallback to circle binning on error. **Files:** `tab_view.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert df544d2` (reverts to circle-only radial integration in the Data Viewer). Self-contained; the MIDAS-engine primitives it reuses are unchanged.

## bc86d74 — Data Viewer: Top-N pixels + mask-aware stats + full-geometry receive (2026-07-19)

**Effect:** Adds a “Top-N pixels” toolbar toggle that marks the N brightest pixels (crosshair + circle) and feeds their values to the intensity-statistics panel, re-ranking live on frame/mask changes. Masked pixels (mask file + intensity-range mask) are excluded from the Top-N ranking and its stats/histogram. `_midas_radial` now unions the static mask with the per-frame intensity-range mask and fingerprints the mask by content so the cached binning context rebuilds when the mask changes. The tab also accepts a *full* geometry dict (tilts + distortion + detector size) from Calibrate and routes integration through the MIDAS engine when it arrives. The stats panel readout box auto-sizes to its content (no inner scrollbar) with the histogram as the single flexible child; `DataLoaderPanel` is now a `QWidget` hosting a scroll area + stats panel in a draggable vertical splitter. **Files:** `tab_view.py`, `widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert bc86d74`.

## b0a5cc3 — Calibrate: per-coefficient distortion, frame averaging, seed feedback (2026-07-19)

**Effect:** Adds `DistortionRefineDialog` (behind the “...” next to the Distortion checkbox) to pick any of the 15 harmonics or use  $\eta$ -fold presets; `calib.py` maps each selected v2 harmonic to its v1 p-slot (via `DISTORTION_ISO / DISTORTION_PRESETS` in constants). Adds an “Average frames” card (start:end:skip, streamed via `DataLoaderPanel.average_frames`), seed tilts (tx/ty/tz) carried into the v1 params, a “Feed result back to seed” option, and a “→ Send to Data Viewer” that now sends the full geometry (tilts + distortion + detector size). Drops the 310px bottom-panel cap and adds a non-collapsible splitter. **Files:** `calib.py`, `tab_calibrate.py`, `dialogs.py`, `constants.py`, `widgets.py`, `documentation/gui_documentation.md`.  
**Roll back:** `git revert b0a5cc3`.

### **b6f1681 — Batch: read-only “Calibration values” card (2026-07-19)**

**Effect:** Adds a Calibration values card to the Batch parameter column showing the geometry actually driving integration ( $\lambda$ , Lsd, BC, tilts, pixel sizes, detector size, non-zero distortion count), resolved from the live Tab-2 result or a calibration file and refreshed on source/path change. Also lets the Log panel fill its splitter space. **Files:** `tab_batch.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert b6f1681`.

### **49623ae — Pump Probe: publication plotting, delay colour-bar, default mask (2026-07-19)**

**Effect:** Publication-quality plot defaults (clean 2.0px lines, 13pt fonts, dashed grid, refactored `_rainbow_cmap`); a continuous delay→colour bar (`GradientLegend`) replaces the many-row legend past a threshold, with left/right legend anchoring; a log-delay x-axis option for kinetics; and a default detector mask wired via new `DataLoaderPanel.add_mask_file / MaskSelector.add_file_source`. TR-XRD defaults now point at a local-only `test_data_pump_probe/` folder kept out of git. **Files:** `tab_pumpprobe.py`, `constants.py`, `widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 49623ae`.

### **b251ca8 — chore: gitignore context, internal docs, large sample sets (2026-07-19)**

**Effect:** Ignores the local `.context/` scaffold and `CLAUDE.md`, the internal-only PDF calculation write-up, and the large local sample dirs (`test_data/17BM/`, `test_data/test_s25ide/`) via directory-level ignores that override the `test_data/**` re-includes. **Files:** `.gitignore`. **Roll back:** `git revert b251ca8`.

### **1769f69 — Data Viewer: live PV stream (Live Data card) (2026-07-20)**

**Effect:** Subscribes to an EPICS PVA image PV via `pvapy` and pushes frames straight through the existing image/corrections/ring/radial-integration pipeline — no separate viewer window. “Live Data” is a collapsible card (own title-bar checkbox) above the Data card; unchecking stops an active stream. Data card gets a small  reload button to restore the static file/folder/HDF5 source after stopping a stream. `pvapy==5.4.1` is now a required, pinned dependency (chosen over latest to avoid upgrading the numpy/pyqtgraph pins). `MainWindow` calls a generic `tab.shutdown()` hook on close so a live stream stops

cleanly on app exit. **Files:** `widgets.py`, `tab_view.py`, `app.py`, `pyproject.toml`, `environment.yml`, `documentation/gui_documentation.md`, `tests/test_live_stream.py`. **Roll back:** `git revert 1769f69`.

## 0b4326d — Fix: cap native thread pools to prevent calibration crash (2026-07-22)

**Effect:** Clicking “Run Calibration” crashed the app outright — a native, uncatchable `Bus error`, not a Python exception. Root cause: `CalibrationWorker` (a `QThread`) triggers a multi-threaded `numpy.linalg.inv()` deep inside `midas-calibrate-v2`’s HKL/ring generation (likely surfaced by the recent 0.3.3 → 0.5.2 bump); running from a `QThread` while the Qt event loop is alive, that races against PyTorch’s own OpenMP pool and corrupts memory. Reproduced deterministically at two call sites (`numpy.linalg.inv` during ring generation, `scipy.ndimage.median_filter` during seeding); both disappear once native thread pools are capped to 1. Every heavy operation in this app runs inside a `QThread` (17 worker classes in `workers.py`), so the fix caps `OPENBLAS_NUM_THREADS` / `OMP_NUM_THREADS` / `MKL_NUM_THREADS` / `VECLIB_MAXIMUM_THREADS` / `NUMEXPR_NUM_THREADS` to 1 process-wide via `os.environ.setdefault` in `_paths.py` — already home to the sibling `KMP_DUPLICATE_LIB_OK` workaround for the same underlying duplicate-OpenMP-runtime issue — rather than patching each worker individually. Verified: offscreen run of the full calibration pipeline to convergence with no crash; `pytest` 15/15 green. **Files:** `midas_gui/_paths.py`. **Roll back:** `git revert 0b4326d` (restores multi-threaded BLAS; calibration/other workers become exposed to this native-crash class again on macOS).

## 234ded9 — Live viewer: preserve manual colormap/level changes across frames (2026-07-24)

**Effect:** `ImageViewer._redisplay` recomputed `vmin%/vmax%` percentile levels on every incoming frame (live or otherwise), silently overwriting a level range the user had dragged on the `pyqtgraph` histogram mid-acquisition. Now tracks manual histogram edits via `sigLevelsChanged` (guarded against feedback from our own programmatic `setImage` calls with a suspend flag) and keeps pinning to the last manual levels until the user explicitly changes the `vmin%/vmax%` spin boxes, which resets back to auto. **Files:** `widgets.py`. **Roll back:** `git revert 234ded9`.

## 69f470c — Data Viewer: widen the image/radial-plot splitter handle (2026-07-24)

**Effect:** The vertical splitter between the image view and the radial-integration panel had no explicit handle width (unlike the outer horizontal splitter), making it thin and hard to grab. Set `setHandleWidth(8)` to match. **Files:** `tab_view.py`. **Roll back:** `git revert 69f470c`.

## 96f8add — Radial profile: stop forcing Y-axis min to -1000 on every update (2026-07-24)

**Effect:** `ProfileViewer._replot` unconditionally called `setYRange()` with a hardcoded -1000 floor on every redraw, clobbering any manual Y-range the user set. The auto lower bound is now `0.9 * current data`

`minimum`; once the user manually changes the Y range (drag, wheel-zoom, or the axis context menu's numeric entry — detected via `sigYRangeChanged` with the same suspend-flag pattern as `234ded9`), that value is kept for the rest of the session instead of being recomputed. Also dropped the hardcoded `setLimits(yMin=-1000/1)` hard floors. **Files:** `widgets.py`. **Roll back:** `git revert 96f8add`.

### [3eb4a44](#) — Calibrate: recolor Pick-Ring fit overlay to blue (2026-07-24)

**Effect:** `PickableImageViewer`'s Pick-Ring points, fitted circle, and fitted-center marker used the same amber (`#f0c060`) as the Data Viewer's Simulate-rings overlay, making the two indistinguishable when both were visible on the same image. Pick-Ring's fit overlay is now blue (`#2a7fd4`); the separate Pick-BC "+" click marker (already `#00aaff`) and Simulate-rings amber were left unchanged. **Files:** `widgets.py`. **Roll back:** `git revert 3eb4a44`.

### [ecf6d01](#) — Data Viewer: make Simulate rings a live toggle instead of one-shot (2026-07-24)

**Effect:** "Simulate rings" is now a checkable toggle rather than a single-click action. While on, it resimulates automatically whenever material, lattice constants, space group, or geometry (wavelength/Lsd/pixel size/max 2 $\theta$ ) change — mirroring the existing `_rad_auto`-style "recompute on change" idiom already used for radial integration. Beam-centre edits still just reposition the existing rings (unchanged; ring radii don't depend on BC), so no wiring was added there. **Files:** `tab_view.py`. **Roll back:** `git revert ecf6d01`.

### [aa82cb6](#) — Preferences: add Devices tab; Data Viewer Live PV becomes a device dropdown (2026-07-24)

**Effect:** New **Preferences** ▶ **Devices** tab (add/remove/edit rows of name + prefix + PVA suffix), following the existing Materials/Calibrants table-tab pattern; persisted as a new "devices" list in the JSON config (replaces wholesale when present, same as materials/calibrants). Ships pre-filled with the 20-ID-D detectors extracted from the beamline's `make_det(...)` blueprint — `oryx20idd` (`20idd0R1:`), `s20idPil` (`20idPil`), `pg4` (`1idPG4:`), `gh1s` (`20idGH1s:`), `s20varex1` (`20IDFF:`) — all with PVA suffix `Pva1:Image`. The Data Viewer's Live Data "Live PV" field is now an editable combo box (`_NoScrollComboBox`) populated from this list: picking a device by name fills in its full PV (`prefix + PVA suffix`); typing any other PV by hand still works unchanged, with the same example placeholder text. **Files:** `constants.py`, `prefs_dialog.py`, `widgets.py`, `tests/test_live_stream.py`. **Roll back:** `git revert aa82cb6` (Devices tab and the Live PV dropdown both go; the Live PV field reverts to a plain text box).

### [c156c62](#) — Fix image-view autorange drift; bound pan/zoom to image (2026-07-24)

**Effect:** Two bugs in the shared `ImageViewer` (Data Viewer / Mask Builder / Calibrate all use it): (1) the crosshair `InfiniteLine`s were added to the `pyqtgraph ViewBox` without `ignoreBounds=True`, so their

position — which follows the mouse on every hover event — fed the auto-range bounds calculation. Once the bottom-left **A** (auto-range) button enabled *continuous* auto-range, the view kept re-fitting itself to wherever the cursor was, and only a right-click ▶ View All (which disables continuous auto-range as a side effect) made it static again. Fixed by excluding the crosshairs from bounds via `ignoreBounds=True`. (2) Pan/zoom had no limits, so scroll/drag could wander arbitrarily far from the image or zoom out indefinitely into empty space. Added `ViewBox.setLimits()` (computed from the image shape in `set_image()`): pan is bounded to roughly half an image-width/height of margin past each edge, and min/max zoom range are tied to the image size. **Files:** `widgets.py` (`ImageViewer.set_image`, `new_apply_view_limits`). **Roll back:** `git revert c156c62` (crosshair can drift the view again under continuous auto-range; pan/zoom become unbounded again).

### **cde4bb2 — Radial profile plot: bound pan/zoom to the data extent (2026-07-24)**

**Effect:** Same class of issue as `c156c62`, applied to the shared `ProfileViewer` (the radial-integration plot on the Data Viewer and Calibrate tabs): it had no `ViewBox` limits, so the plot could be scrolled/dragged arbitrarily far from the actual profile. `_replot()` now calls a new `_apply_view_limits(xmin, xmax, ymin, ymax)` on every redraw — computed from the current profile's X range (in whichever unit is selected: R (px) / 2θ / Q) and Y range (respecting the existing sticky-manual-Y-min behavior) plus a margin (15% X, 25% Y), via `ViewBox.setLimits(...)`. Recomputing per-replot means the bound tracks new profiles and axis-unit switches automatically. **Files:** `widgets.py` (`ProfileViewer._replot`, `new ProfileViewer._apply_view_limits`). **Roll back:** `git revert cde4bb2` (radial profile pan/zoom becomes unbounded again).

### **5b8e3b3 — User profiles, full GUI state save/load, Calibrate tilt-ring rework (2026-07-27)**

**Effect:** Three pieces of work landed in one commit: 1. **User profiles.** `settings.py` now keeps one config file per named profile under `<config dir>/profiles/<name>.json` (`profile_meta.json` tracks which is active), transparently migrating an existing single `config.json` into a profile named “Default” the first time it runs — no data lost, no explicit migration step. `load_config()` / `save_user_config()` / `reset_user_config()` / `user_config_path()` keep their existing signatures and now resolve to the active profile, so every existing call site (`constants.py`, `prefs_dialog.py`, `app.py`) needed no changes. New `constants.reload_from_config()` resets every `DEFAULT_*` global to its shipped value then re-applies the active profile's config on top (a plain re-`_apply` alone would leave a previous profile's override in place if the new profile doesn't mention that key). Preferences gets a **Profile row** — combo + New.../Duplicate.../Rename.../Delete — wired to this API. 2. **Full GUI state save/load.** New **File** menu, **Save GUI State...** (`Ctrl+S`) / **Load GUI State...** (`Ctrl+O`), dumps/restores every tab's fields to one JSON file via new `widgets_to_dict()` / `apply_dict_to_widgets()` dispatch helpers (`helpers.py`) and a `get_state()` / `set_state()` pair added to all 10 tabs plus the shared `DataLoaderPanel` / `FieldSelector` / `MaskSelector` / `CorrectionFlagsWidget` widgets. Loading a state re-triggers each tab's own file-loading for path-backed fields (images, masks, dark/bright/background, HDF5 datasets) but deliberately does **not**

re-run long pipelines (Fit, Batch Integrate, PDF transform, Refinement) — those need one manual click of the tab's own action button afterward. `MaskTab / CalibrationTab` additionally write small sidecar files (`<stem>_mask.tif`, `<stem>_calibration.json`) next to the state file so an in-progress mask or fit result that hasn't been exported anywhere else isn't silently lost. 3. **Calibrate tilt-ring rework** (previously uncommitted, folded in here): the “Corrected” ring overlay is now drawn synchronously from the fitted `ty/tz` tilt (`_draw_corrected_rings`) instead of a background `CorrectedRingsWorker` forward-model thread (removed from `workers.py`). Data Viewer gained matching `ty / tz` tilt fields for its ring simulation, and every Ring-simulation spin-box's step size ( $\lambda$ , max 2 $\theta$ , Lsd, pixel, BC, tilt) is now configurable via Preferences ▶ Data Viewer / the `viewer_steps` config key instead of hardcoded. **Files:** `settings.py`, `constants.py`, `prefs_dialog.py`, `helpers.py`, `widgets.py`, `app.py`, `tab_view.py`, `tab_calibrate.py`, `tab_mask.py`, `tab_batch.py`, `tab_refine.py`, `tab_pumpprobe.py`, `tab_corrections.py`, `tab_pdf.py`, `tab_texture.py`, `tab_export.py`, `workers.py`, `tests/test_config.py`, `documentation/gui_documentation.md`.

**Roll back:** `git revert 5b8e3b3` — reverts all three pieces together (they share edits in `tab_view.py / tab_calibrate.py`, so a partial revert needs a hand-picked patch, not a plain `git checkout <path>`). Existing single-profile configs are unaffected either way since `profiles/Default.json` is a copy, not a move, of the original `config.json`.

## e14c1ea — Data Viewer: tilt-aware profile, ring fixes, calibration export, plot zoom persistence (2026-07-28)

**Effect:** Seven requested fixes/features plus two follow-up plot bugs found while testing them, all in the Data Viewer tab: 1. **Tilt-corrected radial profile without a calibration file.** New `DataViewerTab._effective_calib_geom()` returns `self._calib_geom` if a calibration is loaded, otherwise synthesizes a geometry from the Ring-simulation card's own `ty / tz / BC / Lsd / pixel` fields whenever they're non-zero. `_radial_integrate() / _midas_radial()` route through this instead of only checking `_calib_geom`, so the profile's  $R/2\theta/Q$  axis stays tilt-consistent with the already-correct 2D ring overlay even before any calibration file is loaded. `_midas_radial`'s integration-context cache key changed from `id(g)` to a value tuple (the synthesized geometry is a fresh dict each call, so `id()` never hit the cache). 2. **Ring 2 $\theta$ -range cutoff bug.** `_redraw_rings` capped ring radius at the image's pixel diagonal (`math.hypot(NY, NZ)`), silently dropping any ring past that regardless of the configured “max 2 $\theta$ ” — for far-detector/ fine-pixel geometries this fell around 35-40°. Replaced with a bare `rad > 0` and `math.isfinite(rad)` guard; `pyqtgraph`'s `ViewBox` already clips anything drawn outside the visible image. 3. **Configurable ring thickness.** New `DEFAULT_RING_WIDTH = 2.0` constant and a spin box in the Ring-simulation card, wired into `_redraw_rings`'s pen width and into `_state_widgets()` (round-trips through Save/Load GUI State). 4. **“Simulate rings” turns green while live.** New `QPushButton#primary:checked` rule in `style.py` — confirmed via `grep` that the Data Viewer's live-toggle button is the only checkable `primary_btn` in the app, so this can't affect any other tab. 5. **Save calibration from the Data Viewer.** Three new buttons (Save JSON / Save params (.txt) / Save PONI) export whichever geometry is currently in effect (`_export_geom()`, mirroring `_effective_calib_geom()`). JSON uses the same bare-key shape `geometry_fields_from_file()` reads back; `.txt` reuses the existing `write_standalone_paramtest()`; `.poni` uses a new `helpers.write_poni()` that inverts the existing PONI reader's convention (`Poni1/2 =`

BC\_y/z \* pxY/Z, Distance = Lsd, SI units) — tx/ty/tz tilts have no PONI Rot1-3 equivalent and are documented as dropped on export, matching the reader's existing documented limitation. 6. **ctrl+s overwrites a loaded/saved GUI-state file.** `MainWindow` tracks `_gui_state_path`, set on every successful save or load; a plain `ctrl+s` now writes straight to that path with no dialog once one exists. New `ctrl+shift+s` (“Save GUI State As...”) always prompts, and becomes the new target for subsequent plain saves. 7. **Radial-profile X-axis floors at 0.** Both `ProfileViewer._replot`'s `setXRange` call and `_apply_view_limits`'s pan/zoom `xMin` bound now clamp to `max(0.0, ...)`.

Testing these surfaced two more bugs in `ProfileViewer`, fixed in the same commit: - **Y-range could get permanently stuck.** The old `_manual_ymin` latch recorded *any* Y-range-changed signal, including ones `pyqtgraph` fires internally (e.g. autorange during `curve.setData()`) well before the method's own suspend-flag window started — once latched, every future replot used that stale value regardless of new data. Fixed by wrapping the entire `_replot()` body (curve/band updates, limit-setting, everything) in one suspend flag, so only genuine mouse-driven pan/zoom is ever recorded. - **Zoom reset on every parameter change.** Replaced the unconditional `setXRange / setYRange` calls with tracked `_user_xrange / _user_yrange`: the plot still auto-fits fresh data when the user hasn't manually zoomed, but a manual zoom/pan is now restored after every replot instead of being wiped by the next profile update. The remembered range is only dropped when it would be meaningless in the new context — switching the R/2θ/Q axis unit clears the X range, toggling Log Y clears the Y range. **Files:** `midas_gui/app.py`, `midas_gui/constants.py`, `midas_gui/helpers.py`, `midas_gui/style.py`, `midas_gui/tab_view.py`, `midas_gui/widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert e14c1ea`. All pieces are additive/isolated (new widgets, a new geometry-resolution helper, a new writer function, and a `ProfileViewer` range-tracking rewrite) — no other commit builds on this one.

## 3c15ae7 — Data Viewer: native-menu-backed manual axis limits, Top-N intensity floor (2026-07-29)

**Effect:** Reworks the radial-integration plot's and intensity-histogram's Auto/Manual toggle to defer axis-value entry to `pyqtgraph`'s own existing right-click axis “Manual” min/max fields, instead of a separate custom field row (an earlier same-day attempt at this feature used custom fields and was corrected): 1. New `_add_auto_manual_buttons(plot_widget, on_auto, on_manual)` in `widgets.py` hides `pyqtgraph`'s native auto-range corner button and replaces it with a small “A”/“M” `QPushButton` pair in the same spot, wired to `clicked` (not `toggled`) so that **reclicking the already-active button** still fires its handler — “A” re-fits immediately to current data, “M” snaps back to the held manual range, discarding any pan/zoom drift in either mode. 2. New `_install_manual_axis_capture(plot_widget, callback)` hooks each axis's native `ViewBoxMenu minText / maxText editingFinished` signals (`pyqtgraph` already applies the typed value to the view itself) and mirrors the committed range into a `self._manual_range` tuple tracked independently of `ViewBox.state['targetRange']` (which changes on drag/ pan too, not just explicit edits — needed for relick-to-reset to mean something different from “wherever the mouse left it”). 3.

`ProfileViewer / IntensityStatsPanel` `_replot / _redraw_hist` skip their auto-fit/clamp logic entirely while `_manual_mode` is set and call the new `_apply_manual_range()` instead (clears any `setLimits()` pan/zoom bound, then `setXRange / setYRange` with `padding=0` from the held tuple) — this is what makes an exact typed value (e.g. `0`) survive every live- acquisition redraw instead of being clamped/padded by that frame's own `_apply_view_limits()` recompute. 4. Top-N pixel marking (`DataViewerTab._show_topn`, `tab_view.py`) gains an “I >” checkbox + threshold field next to the N spin box, matching the existing `_imask_on / _fspin` convention; pixels at/below the threshold are excluded from ranking before `argpartition`, so fewer than N (or zero) markers show when fewer pixels clear the floor. 5. Unrelated: `constants.DEFAULT_DEVICES` PVA device name/prefix updates (`oryx20idd` → `20iddNF`, `20idd0R1:` → `20id0R1:`, `20idPil` → `20idPil:`, `gh1s` → `20iddTomo`, `s20varex1` → `20iddFF`), bundled into this commit at the user's request. **Files:** `midas_gui/constants.py`, `midas_gui/tab_view.py`, `midas_gui/widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 3c15ae7`. Self-contained — no later commit depends on the new helpers or the Top-N threshold field.

### 53f8f19 — Widen non-data-derived numeric caps across tabs (2026-07-29)

**Effect:** Several `QSpinBox / QDoubleSpinBox` range caps had no physical or data-derived justification (arbitrary round numbers picked when the field was first added) and were clamping legitimate inputs; raised them: 1. Data Viewer's simulated-ring `ty / tz` tilt fields and Calibrate's seed `tx / ty / tz` fields:  $\pm 10^\circ \rightarrow \pm 180^\circ$ , matching the full range other angle fields in the app already allow. 2. Data Viewer max-20:  $1-90^\circ \rightarrow 0.001-180^\circ$ . 3. Calibrate E-M/LM iteration counts and multi-panel geometry (panel counts, size, gap): capped at 20/2000/50/10000/1000 → `1_000_000`. 4. Corrections empty-frame/Compton scale, absorption  $\mu R$ , gain-training steps/ `lr`/unity-weight/smooth-weight: capped at 1-20 → effectively unbounded ( $1e6 - 1e9$ ). 5. Mask hot/dead factor, frozen-fraction, stride, and learnable-mask steps/ `lr`/sparsity: capped at 1-2000 → effectively unbounded. 6. Refine optimizer `lr` and iteration count: capped at 10/2000 → effectively unbounded. 7. Batch drift `n_knots`: capped at 20 → `1_000_000`. **Files:** `midas_gui/tab_batch.py`, `midas_gui/tab_calibrate.py`, `midas_gui/tab_corrections.py`, `midas_gui/tab_mask.py`, `midas_gui/tab_refine.py`, `midas_gui/tab_view.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 53f8f19`. Self-contained — no later commit depends on the widened ranges.

### 05ce224 — Data Viewer: mask enable checkboxes, calibration card reposition + ty/tz sync, intensity-range title checkbox (2026-07-30)

**Effect:** Three independent Data Viewer tweaks: 1. `MaskSelector` (`widgets.py`) rows gain a checkbox to include/exclude a mask from the composite without deleting it; `composite_mask()` now OR's only *checked* sources. The “Tab 1 mask” row (auto-populated from the Mask Builder tab) is always inserted/kept at the top of the list. `get_state() / set_state()` persist each source's `enabled` flag. 2. The Load calibration card moved below the Ring simulation card's Simulate button, and loading a calibration file now also fills the Ring-simulation card's `ty/tz` tilt fields (previously only  $\lambda/Lsd/px/BC$ ). 3. The Intensity range card's title bar is now the on/off checkbox itself (“Exclude out-of-range pixels”)

instead of a separate checkbox line inside the card. **Files:** `midas_gui/tab_view.py`, `midas_gui/widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 05ce224`. Self-contained — no later commit depends on the mask `enabled` flag, the card reposition, or the title-bar checkbox.

## 0e9ed21 — Data Viewer: support multiple ring-simulation materials at once (2026-07-29)

**Effect:** Ring simulation card holds a list of materials instead of one, so a sample phase can be overlaid on a calibrant (or any N materials) at the same time: 1. New `MaterialDialog` (factored out of the old inline lattice fields) edits one material's name/preset/lattice/space-group/cubic-checkbox. Opened by clicking a material row's underlined name button. 2. Each material row is a checkbox (show/hide that material's rings), a clickable color swatch (`QColorDialog`, drives that material's ring lines + hkl labels on both the image overlay and radial-profile plot), the clickable name, and a **X** delete button (disabled when it's the last remaining row). + **Add material** appends a new row with the next color from a 10-entry cycling palette (`_MATERIAL_COLORS`); a single default **Ni (FCC)** row is seeded at startup, matching prior behavior. 3. Geometry fields ( $\lambda$ , max  $2\theta$ , Lsd, pixel size, beam centre) stay shared across all materials — only lattice/SG/color/visibility are per-material. 4. `_simulate()` now loops materials, simulating rings per enabled one and collecting per-material errors instead of aborting on the first exception; `_redraw_rings()` / `_refresh_profile_markers()` draw each material's rings in its own color. 5. `ProfileViewer.set_ring_markers()` (`widgets.py`) takes a list of `{"radii": [...], "color": "#hex"}` groups instead of a flat radii list, so the radial-profile plot can show multiple colored ring sets; `tab_calibrate.py` updated to pass its single ring set as a one-entry group list. 6. `DataViewerTab.get_state()` / `set_state()` persist/restore the materials list (replacing the old single-material `mat / a..sg / cubic` state fields) so GUI-state save/load round-trips multi-material setups. **Files:** `midas_gui/tab_view.py`, `midas_gui/tab_calibrate.py`, `midas_gui/widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 0e9ed21`. Self-contained — no later commit depends on the multi-material materials list or the `set_ring_markers()` groups signature.

## 911f8ac — Data Viewer: Live Data “Use Buffer” ring buffer for stack analysis on live streams (2026-07-30)

**Effect:** Live Data card gains a **Use Buffer** toggle + **N** spin box (`DataLoaderPanel`, `widgets.py`) that captures the last N live frames into an in-memory `deque` ring buffer, so Projection and every other stack-based analysis become usable on live data instead of only on loaded HDF5/folder stacks: 1. Clicking **Use Buffer** arms it: turns yellow (`Buffering... (n/N)`) and appends each incoming live frame to the buffer as it streams. 2. When no new frame arrives for ~2 s (streaming paused, or **Stop** clicked), a single-shot `QTimer` (`_buffer_stall_timer`) freezes the buffer into a navigable stack: `_nframes / _setup_navigator()` update so the frame slider/spin/prev-next and **Project stack** work exactly as they would on a loaded stack; the button turns green (`Buffer Ready (N)`). 3. `_get_frame()` / `full_stack()` read from the frozen buffer when active, otherwise fall through to the existing stack/paths/h5 sources unchanged. 4. Starting a new live stream or loading static data calls `_reset_buffer()`, discarding any existing buffer and turning

the toggle off. **Files:** `midas_gui/widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 911f8ac`. Self-contained — no later commit depends on the ring-buffer fields or `_get_frame()` / `full_stack()` buffer branch.

### **a88ba1f — Data Viewer: fix live ring-buffer race between GUI and worker threads (2026-07-30)**

**Effect:** `_on_live_frame()` appends to the “Use Buffer” ring buffer (`DataLoaderPanel._buffer`, `widgets.py`) on the GUI thread while background `QThread`s (e.g. `ProjectionWorker.run()`, reached via `full_stack()`) read the same `deque` with no synchronization — a live frame arriving mid-read could raise “deque mutated during iteration” or hand analysis a torn frame set. Added a `threading.Lock` (`_buffer_lock`) guarding every read/write of `self._buffer` and the `_buffer_frozen` flag checked alongside it, in `_get_frame()`, `full_stack()`, `_on_live_frame()`, `_on_buffer_toggled()`, `_on_buffer_stalled()`, and `_reset_buffer()`. **Files:** `midas_gui/widgets.py`. **Roll back:** `git revert a88ba1f`. Self-contained — the lock only wraps existing buffer accesses, no signature/state-shape changes.

### **2cfd9cd — Data Viewer: fix refresh-timer starvation during fast live streaming (2026-07-30)**

**Effect:** `dataChanged` was connected to `self._refresh_timer.start()` directly. `QTimer.start()` on an already-armed `setSingleShot(True)` timer restarts its countdown rather than queuing a fire, so a continuous burst of events faster than the 60ms interval (e.g. live frames streaming quickly) could defer the refresh indefinitely — the displayed image/stats/rings would appear frozen mid-burst even though data kept arriving. Added `_on_data_changed()`, connected to `dataChanged` in place of the old lambda, which only calls `._refresh_timer.start()` while the timer is idle (`not isActive()`), turning it into a throttle (fires at least once per interval) instead of a restart-on-every-event debounce that can starve. **Files:** `midas_gui/tab_view.py`. **Roll back:** `git revert 2cfd9cd`. Self-contained — restores the direct lambda connection.

### **839770d — Data Viewer: cap live buffer (“Use Buffer”) to 100 frames (2026-07-30)**

**Effect:** The ring-buffer `N` spinbox (`widgets.py`) allowed up to 2000 frames, each stored as a full `float32` array — for a large-format detector this could allocate tens of GB with no warning. Lowered `setRange(2, 2000)` to `setRange(2, 100)`; tooltip and `gui_documentation.md` updated to note the cap. **Files:** `midas_gui/widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 839770d`. Self-contained — restores the old range only.

### **08392c6 — Data Viewer: move “All frames” stats computation off the GUI thread (2026-07-30)**

**Effect:** `_all_frame_values()` (reached from `_update_stats()` when the stats scope is “All frames”) read the entire stack/live buffer and applied field corrections synchronously on the GUI thread — unlike every other heavy operation in this file, which already runs in a background `QThread`. For a large HDF5/folder stack, or a full live ring buffer, this could visibly freeze the UI. 1. Added `AllFrameStatsWorker` (`workers.py`), following the same pattern as `ProjectionWorker`: GUI-derived inputs (dark/bright/background arrays, composite mask, intensity-range thresholds) are snapshotted on the GUI thread before the worker starts, so `run()` only touches numpy data. 2. `_update_stats_all_frames()` (`tab_view.py`, replaces `_all_frame_values()`) launches the worker and, if a new request arrives while one is already running, coalesces it into a single re-run afterward via `_stats_all_frames_dirty` instead of queuing redundant work. **Files:** `midas_gui/tab_view.py`, `midas_gui/workers.py`. **Roll back:** `git revert 08392c6`. Self-contained — no later commit depends on `AllFrameStatsWorker` or the removal of `_all_frame_values()`.

### 57ced2f — Data Viewer: debounce intensity-mask spinbox edits (2026-07-30)

**Effect:** The intensity-mask “pixel  $\leq$ ” / “pixel  $>$ ” spinboxes triggered `_update_stats()` / `_radial_integrate()` (and Top-N re-ranking, if active) on every `valueChanged` signal — i.e. once per keystroke or arrow-click — doing potentially expensive recomputation while the user was still mid-edit. 1. Added `_imask_debounce_timer`, a single-shot `QTimer` (120ms), alongside the existing `_refresh_timer` in `__init__`. 2. `_imask_lo` / `_imask_hi` now connect to a new `_on_imask_value_changed()`, which updates the (cheap) mask overlay immediately for visual feedback but only (re)starts the debounce timer for the heavier recompute; the timer’s `timeout` fires the existing `_on_imask_changed()` once edits settle. The on/off toggle (`_imask_on`) is unaffected — it still calls `_on_imask_changed()` directly. **Files:** `midas_gui/tab_view.py`. **Roll back:** `git revert 57ced2f`. Self-contained — restores the direct `valueChanged.connect(self._on_imask_changed)` wiring.

### 81b8ea8 — Data Viewer: warn when composite mask drops a source (2026-07-30)

**Effect:** `MaskSelector.composite_mask()` OR’s every enabled mask source together, but silently skipped any source that failed to load or whose shape didn’t match the union built so far — a user could enable a mask file believing it was in effect while it was quietly excluded. 1. `composite_mask()` now collects the label (and, for shape mismatches, the offending shape) of every dropped source into `self._mask_warning`. 2. `_refresh()` shows the warning in the existing status label (amber `#e0a030`) alongside the normal source count; mutating the source list (add/remove/toggle/ `set_tab1_mask`) clears the stale warning until the next `composite_mask()` call recomputes it. **Files:** `midas_gui/widgets.py`. **Roll back:** `git revert 81b8ea8`. Self-contained — restores the silent drop and the plain “N mask source(s)” status text.

### 3d96cb1 — Data Viewer: add hardware-free Sim Detector for Live Data testing (2026-07-31)

**Effect:** Testing the Live Data card required a real EPICS PVA detector stream from beamline hardware — no way to exercise it standalone. 1. New `midas_gui/sim_detector.py`: `SimDetectorServer` runs a real `pvapy.PvaServer` publishing genuine `NTNDArray` frames (same plumbing a real detector's PVA image plugin uses via `AdImageUtility`), so it's indistinguishable from a real stream to `PvaLiveSource`. Defaults to an Eiger2 500K shape (1030×514 px, matching the repo's existing `DEFAULT_PIXEL_UM` comment), counts in `[0, 60000]`, 5 Hz — all constructor parameters. `ensure_running()` / `stop_all()` give a process-wide registry keyed by channel name. 2. `constants.DEFAULT_DEVICES` gains a “Sim Detector” entry (PV `midasSim:Pva1:Image`); the config-overlay system only round-trips `name/prefix/pva_suffix` for devices, so the sim device is identified purely by its resolved PV string, not a custom marker key. 3. `DataLoaderPanel._start_live()` (`widgets.py`) lazily starts the sim server via `ensure_running()` the first time that PV is connected to. 4. `DataViewerTab.shutdown()` (`tab_view.py`) calls `sim_detector.stop_all()` alongside the existing `stop_live()`. **Files:** `midas_gui/sim_detector.py` (new), `midas_gui/constants.py`, `midas_gui/widgets.py`, `midas_gui/tab_view.py`. **Roll back:** `git revert 3d96cb1`. Self-contained — removes the sim device/file and its two call sites; no later commit depends on it.

### 3b12fbf — Image viewer: persist manual color-scale window across live frames (2026-07-31)

**Effect:** 234ded9 (2026-07-29) made a manually-dragged histogram LUT level range survive across incoming frames, but two gaps remained: the histogram's own zoom/pan window still reset on every redraw, and toggling Log/Linear reinterpreted a manual level's raw numbers in the new scale instead of converting them — both made a deliberately-set color window jump around unexpectedly. 1. `ImageViewer` gains `_manual_hist_range` (mirrors `_manual_levels` but for the histogram's own axis zoom) and `_suspend_hist_range_track`, tracked via a new `sigRangeChanged` connection and `_on_hist_range_changed()`. 2. `set_image()` gains a `reset_levels` flag: `True` (default) drops both manual windows and returns to the `vmin%/vmax%` percentile defaults; `False` — passed for a live-streaming frame update — leaves them in place. `DataLoaderPanel.is_live_frame_update()` reports whether the most recent `dataChanged` came from a live PVA frame, so `tab_view.py` and `tab_calibrate.py` can pass the right value. 3. `_redisplay()` now also re-zooms the histogram to the percentile window by default (`setHistogramRange(lo, hi, padding=0.1)`) so a single bad pixel can't stretch it into an unreadable sliver. 4. New `_on_log_toggled()` converts `_manual_levels` through `log10/10x` **when the Log checkbox flips (clamped to ±300 before exponentiating, since a manual level can sit far outside real data range and float `10**x` raises `OverflowError` rather than saturating), and drops `_manual_hist_range` so the view reframes tightly around the converted levels instead of carrying a now-mismatched zoom through the transform.** **Files:** `midas_gui/widgets.py`, `midas_gui/tab_view.py`, `midas_gui/tab_calibrate.py`. **Roll back:** `git revert 3b12fbf`. Self-contained — restores the pre-234ded9 - successor behavior (LUT levels still persist per 234ded9, but histogram zoom resets and Log/Linear toggle no longer converts levels).

## f3a1b91 — Data Viewer: preserve armed “Use Buffer” state when Start is clicked (2026-07-31)

**Effect:** `_start_live()` unconditionally called `_reset_buffer()`, which discarded the buffer and flipped the **Use Buffer** button back to its off/gray state even if the user had already armed it (yellow Buffering.../green Buffer Ready) before clicking **Start**. That forced a redundant second click on **Use Buffer** after every **Start**. `_start_live()` now only calls `_reset_buffer()` when `_buffer_active` is `False`; when it's already `True`, it re-arms a fresh empty deque (same as `_on_buffer_toggled`'s checked branch) and restyles to "filling", so buffering continues into the new stream without user intervention. **Files:** `midas_gui/widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert f3a1b91`. Self-contained — restores the unconditional `_reset_buffer()` call on **Start**.

---

## 2525277 — Data Viewer: unrestrict wavelength/Lsd/pixel-size ranges, tighten ring row (2026-07-31)

**Effect:** Ring simulation card's  $\lambda$ /Lsd/pixel-size spin boxes were capped at arbitrary limits (pixel size 1–5000  $\mu\text{m}$ ,  $\lambda$  0.001–10  $\text{\AA}$ , Lsd 0.001–100000 mm); they now accept any positive value ( $\lambda$  0.0001–1e6  $\text{\AA}$ , Lsd 0.001–1e6 mm, pixel 0.1–1e6  $\mu\text{m}$ ). Display precision was also tightened per field:  $\lambda$  5→4 decimals, Lsd 4→3, pixel size/BC\_y/BC\_z 2→1, ty/tz tilts 4→2. “Show rings” was renamed **Rings** and, together with **Labels** and a shrunk ring-thickness field (max width 60px), now sits on one row instead of thickness alone on the row below. **Files:** `midas_gui/tab_view.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 2525277`. Self-contained — restores the previous ranges/decimals and the two-row Rings/Labels + Ring-thickness layout.

---

## b7a1518 — Data Viewer: add “?” help button explaining radial-integration calculation (2026-07-31)

**Effect:** A small circular “?” button now sits next to the radial-profile toolbar's `Radial` control; clicking it opens a message box explaining how the R-bin profile is computed — full-geometry ( $\eta$ , R) binning (pixel-count-weighted mean across  $\eta$ ) when a calibration is loaded or a tilt is set, versus the circle-binning fallback (plain per-bin mean, no tilt correction) otherwise, and that a failed full-geometry integration falls back to circle binning with a warning above the calibration card. Also widens the ring-width spinbox (60px → 80px) so its value isn't clipped. **Files:** `midas_gui/tab_view.py`. **Roll back:** `git revert b7a1518`. Self-contained — removes the help button and reverts the ring-width spinbox to 60px.

---

## de15d57 — Data Viewer: move exclude-range controls into radial-plot toolbar, int-safe bounds (2026-07-31)

**Effect:** The “Exclude out-of-range pixels” controls leave their own left-panel card and move into the radial-integration plot’s toolbar, pinned at the far right (past `X / Log Y / R bin / Auto / Integrate`); the `R bin` field is narrowed and the `N bins | max=...` stats printout is hidden to make room. The pixel-`</>` bound spin boxes widen 84px→112px and switch to integer display (no decimals), with range extended to `-1e9..5e9` so 32-bit detector overflow sentinels (e.g. `2**32-1`) fit without a plain `QSpinBox`’s `int32` overflow. The lower-bound comparison changes from `<=` to `<` (a pixel exactly at the bound is no longer masked). “Load calibration” card renamed **Load/save calibration. Files:** `midas_gui/tab_view.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert de15d57`. Self-contained — restores the separate “Exclude out-of-range pixels” card, the float spin boxes, and the `<=` bound comparison.

---

## 1d45c40 — Data Viewer: pixel-size field allows a second decimal place (2026-07-31)

**Effect:** The Data Viewer’s pixel-size spin box (Ring simulation card) goes from 1 decimal to 2, so pitches like `0.65 μm` can be entered exactly instead of rounding to `0.7`. Needed for near-field detector geometries, which use much finer pixel pitches than typical far-field panels. Step size (`0.1 μm`) is unchanged. **Files:** `midas_gui/tab_view.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 1d45c40`. Self-contained — returns the field to 1 decimal.

---

## ecfbf36 — Data Viewer: add Box/Circle/Line ROI tool with live floating stats popups (2026-08-01)

**Effect:** A new **ROI: Box / Circle / Line** row on the image toolbar (alongside **Clear ROIs**) shares the same click-drag gesture as **Pick BC/Pick Ring** — arming one disarms the others. Click a shape button, then click-drag on the image to draw it (drags shorter than a few pixels are treated as a cancelled attempt, mode stays armed). Drawing a shape opens a small floating, freely-draggable stats popup next to it, color/label-matched to the shape (color cycled from a fixed palette, shared by the on-image shape, its label, and the popup). Box/Circle popups show the full intensity statistics readout (`N`, percentiles, histogram) scoped to the enclosed pixels; Line popups show a live intensity-vs-distance profile with a direction arrow and a **Flip-direction** button. Popups recompute on drag/resize and on every frame-navigation/live-frame/correction-change refresh, but their on-screen position is independent of the shape — set once at creation (monitor-aware), never moved automatically afterward. Closing a popup, right-click → **Remove ROI**, or **Clear ROIs** removes a shape; ROIs are session-only (not saved with tab state). **Files:** `midas_gui/roi_tools.py` (new — `ROIImageViewer`, `ROIStatsPopup`), `midas_gui/tab_view.py` (Data Viewer’s image viewer switched from `PickableImageViewer` to

`ROIImageViewer`), `documentation/gui_documentation.md`. **Roll back:** `git revert ecfbf36`. Self-contained — restores the plain `PickableImageViewer` (no ROI tool) and deletes `roi_tools.py`.

---

## **d5654c1 — Data Viewer: ROI tool drops Circle, Clear ROIs resets numbering, Pick Clear also removes BC marker (2026-08-01)**

**Effect:** Three follow-ups to the `ecfbf36` ROI tool: (1) the Circle option is removed from the **ROI:** row — only Box and Line remain; (2) **Clear ROIs** now resets the ROI counter, so the next ROI drawn after a clear starts back at “ROI 1” instead of continuing the prior session’s numbering; (3) the **Clear** button shared by **Pick BC/Pick Ring** now also removes the Pick BC crosshair marker — previously it only cleared Pick Ring’s points/fit-circle, and stayed disabled if only a BC point (no ring points) had been picked, so a lone BC marker couldn’t be cleared at all. **Files:** `midas_gui/roi_tools.py`, `midas_gui/widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert d5654c1`. Self-contained — restores the Circle ROI option and the old Clear behavior (ring points only).

---

## **bb78c9a — Data Viewer: line ROI drawn as single arrow shape, no separate arrowhead item (2026-08-01)**

**Effect:** A line ROI’s shaft and arrowhead are now built as one `QPainterPath` (`_build_arrow_path`) recomputed from the two endpoints on every drag, instead of a plain shaft line plus a separately positioned/ rotated `pg.ArrowItem`. The old approach could show the arrowhead at an odd angle as the endpoint moved; the new path always points cleanly from one endpoint to the other, with the head size held constant in screen pixels. The ROI’s own connecting line is hidden (`roi.setPen(None)`) so it isn’t drawn a second time underneath the arrow. **Files:** `midas_gui/roi_tools.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert bb78c9a`. Self-contained — restores the `pg.ArrowItem`-based line-direction indicator.

---

## **786c94c — Data Viewer: box-ROI popup’s zoomed crop image now resizes with the popup (2026-08-01)**

**Effect:** The **Box** ROI popup’s zoomed crop `PlotWidget` was `setFixedSize(110, 110)`; it now has a 90x90 minimum size with an Expanding size policy and the same layout stretch factor as the histogram column, so dragging the popup dialog’s edge to resize it grows or shrinks the crop image along with the histogram instead of leaving it pinned at its old fixed footprint. **Files:** `midas_gui/roi_tools.py`,

documentation/gui\_documentation.md . **Roll back:** `git revert 786c94c` . Self-contained — restores the fixed 110x110 crop image size.

---

## 468b417 — Data Viewer: Projection card gains N-frames cap; $\lambda$ menu gains energy-to-wavelength entry (2026-08-03)

**Effect:** The Projection card's **Axis** field (always 0, i.e. across the stack of frames) is removed; a new **N frames** field caps how many frames after **Skip frames** are included in the Max/Sum/Average projection (0 = use all remaining frames) — `ProjectionWorker` gains an `nframes` param and slices `data[:nframes]` after the skip slice, and its info string now reports the frame count used instead of the (always-0) axis. The clickable  $\lambda$  label's popup menu (`make_kedge_label`, used on Data Viewer/Calibrate/ PDF) is rebuilt as a `QToolButton + QMenu` with an **Energy (keV)** `QWidgetAction` row at the top — typing a value and pressing Enter (or clicking ↵) sets  $\lambda = 12.398420/E$  — followed by the existing K-edge foil list, instead of the plain label-with-menu built by `_clickable_menu_label` . **Files:** `midas_gui/helpers.py` , `midas_gui/tab_view.py` , `midas_gui/workers.py` , `documentation/gui_documentation.md` . **Roll back:** `git revert 468b417` . Self-contained — restores the Axis spinbox (dropping N frames) and the plain K-edge-only  $\lambda$  menu.

---

## c336778 — Data Viewer: B-PILOT bridge auto-starts Live Data on scan dispatch (2026-08-09)

**Effect:** New `midas_gui/bridge_server.py` opens a `QLocalServer` (`BridgeServer` , socket name `midas_gui_live_bridge_v1`) on app launch — `MainWindow.__init__` starts it and `closeEvent` stops it. B-PILOT (a separate Bluesky plan-runner GUI) connects as a `QLocalSocket` and sends one JSON line per scan dispatch, e.g. `{"type": "live_pv", "version": 1, "prefix": "20IDFF:"}`; `MainWindow._resolve_and_start_live` resolves the prefix against `constants.DEVICES` (`bridge_server.resolve_pv` , matching `prefix` + that device's `pva_suffix`) and, on a match, calls the new `DataViewerTab.start_live_pv` / `DataLoaderPanel.start_live_pv` , which check/ expand the Live Data card, switch streams if a different PV is already running, fill in the PV combo, and click **Start** — no manual clicks needed in MIDAS GUI. Unmatched prefixes or a B-PILOT that never connects are a silent no-op (logged, not raised). Malformed/wrong-version messages are ignored. A stale socket file from a prior unclean shutdown is removed before `listen()` so restarts don't fail with "address already in use". **Files:** `midas_gui/bridge_server.py` (new), `midas_gui/app.py` , `midas_gui/tab_view.py` , `midas_gui/widgets.py` , `tests/test_bridge_server.py` (new), `documentation/gui_documentation.md` . **Roll back:** `git revert c336778` . Self-contained — removes the bridge server and the two `start_live_pv` methods; no other code calls them.

---

## 6c79f13 — Cross-tab data sharing; ROI popups always-on-top/minimizable; Project-stack highlight (2026-08-10)

**Effect:** New `midas_gui/data_bridge.py` `DataSourceRegistry`, owned by `MainWindow`, is bound by every Data Loader panel (Data Viewer, Calibrate, Calib. Refinement, Batch Integrate, Pump Probe) and by Mask Builder. Each gains an **Import from...** submenu on its Data/Image/Stack browse button, built fresh on open, listing whatever's currently loaded in every *other* bound tab: a file/folder path, or (if that tab's Live Data **Use Buffer** ring buffer is frozen) a **Buffer (N frames)** entry. Picking a path loads it like a normal browse. Picking a buffer either **delegates** live — no copy, tracks the source buffer, clears itself if the source resets (`DataLoaderPanel.use_external_buffer / bufferInvalidated`) — for panels that keep an in-memory stack, or **snapshots once** to a temp HDF5 file (new `helpers.new_temp_h5_path / save_stack_h5`, dataset `buffer/data`) for panels that only ever read paths (Batch Integrate, Pump Probe stream mode, Mask Builder's Stack field). `FieldSelector` (Dark/Bright/Background) gets the same menu, scoped to its own field type via a new `field` tag on each registry descriptor. `DataLoaderPanel`'s **Use Buffer** row also gains a  button to save the frozen buffer to a user-chosen HDF5 file. Unrelated, bundled from the same session: `ROIStatsPopup` is now `WindowStaysOnTopHint` (so it can't get buried behind other windows) and gains a “–” minimize button that hides the popup and adds an entry to a new `ROI Ribbon` strip along the image viewer's left edge (`roi_tools.py`, wired in `tab_view.py`'s `set_ribbon`); clicking the ribbon entry restores it. Data Viewer's **Project stack** button turns green while a projection is displayed (`_apply_project_style`), reverting on **Back to frames** or new data. **Files:** `midas_gui/data_bridge.py` (new), `midas_gui/app.py`, `midas_gui/helpers.py`, `midas_gui/roi_tools.py`, `midas_gui/tab_mask.py`, `midas_gui/tab_view.py`, `midas_gui/widgets.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 6c79f13`. Self-contained — removes the registry, all “Import from...” menus, the buffer-save button, ROI always-on-top/ minimize-to-ribbon, and the Project-stack green highlight.

## acb43c1 — Dependencies: upgrade midas-hkls/midas-calibrate-v2, switch midas-pdf to PyPI (2026-08-10)

**Effect:** `midas-hkls` 0.5.0→0.7.0, `midas-calibrate-v2` 0.5.2→0.5.3. `midas_pdf` is now the real PyPI package (`midas-pdf==0.1.1`) instead of the vendored `midas_gui/_vendor/` copy, so `pdf_backend.py` drops the `midas_hkls.absorption` compatibility shim (needed only while `midas-hkls` lacked that submodule) and the vendored-path `sys.path` insert, replacing both with a plain `import midas_pdf`. `midas_gui/_vendor/` and its package-data block in `pyproject.toml` are removed entirely. Transitive MIDAS deps pulled in by `midas-calibrate-v2 / midas-pdf` but not imported directly (`midas-integrate`, `midas-peakfit`, `midas-zipper`, `hdf5plugin`, `psutil`) and previously-implicit deps (`numba`, `scikit-image`) are now pinned explicitly in `pyproject.toml`'s dependencies, so a plain `pip install .` reproduces the verified-working set without relying on `environment.yml` or another package's `install_requires`. Verified via an isolated venv: `pytest 25/25` green plus a full synthetic-image E2E smoke test (auto-seed → `one_shot` calibration →

integration → PDF G(r)) through the GUI's own code paths. **Files:** `environment.yml`, `pyproject.toml`, `midas_gui/pdf_backend.py`, `documentation/gui_documentation.md`; deletes all of `midas_gui/_vendor/`. **Roll back:** `git revert acb43c1`. Restores the vendored `midas_pdf` tree, the `midas_hkls.absorption` shim, and the prior dependency pins — but note `midas-hkls/midas-calibrate-v2` would need re-pinning to their older verified versions too if reverting for compatibility reasons, not just to undo the vendoring.

---

### 3058b0c — Bundle 20-ID-D/20-ID-E/1-ID-E beamline device profiles (2026-08-10)

**Effect:** The Live Data PV dropdown's device list was hardcoded for 20-ID-D. Ships three bundled Preferences ▶ Profile presets — **20-ID-D, 20-ID-E, 1-ID-E** — so switching beamlines is a dropdown pick, reusing the existing per-user Profile system (`constants._apply()` already replaces `DEVICES` wholesale when a profile's JSON has a "devices" key) with **zero changes** to `prefs_dialog.py` or `widgets.py`. `settings.py` gains a `BUNDLED_PROFILES` literal (one device list per beamline, each entry `{"name", "prefix", "pva_suffix": "Pva1:Image"}`) and `_ensure_profiles()` seeds any not-yet-seen bundled profile once per machine, tracked in a new `profile_meta.json` key "bundled\_seeded" so a profile a user later deletes isn't silently recreated. 20-ID-D's list is unchanged (already confirmed working on the beamline); 20-ID-E (`pimega`, `spl1`, `s20varex2`, `pg6`, `gh2`) and 1-ID-E (`ge1-ge5`, `pixirad`, `gh1`, `pg1`, `pg5`, `s1varex1`) were extracted from B-PILOT's `instrument/devices/{s20ide,s1id}_devices/*_area_detectors.py` `make_det(...)` blueprints — every device with `pva1_exists=True`. All three profiles also carry a `Sim Detector` entry for hardware-free testing. Device names use B-PILOT's raw variable names (per user decision) rather than invented descriptive labels, so entries stay traceable back to source. Verified: new `test_bundled_beamline_profiles_seeded` plus the full suite (26/26) pass; fresh installs still default to `Default` (same devices as 20-ID-D); an isolated-HOME subprocess check confirmed switching the active profile to each of the three beamlines drives `constants.DEVICES` correctly with no other code changes. **Files:** `midas_gui/settings.py`, `tests/test_config.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 3058b0c`. Self-contained — removes the three bundled profiles and their seeding logic; any profile files a user already has on disk from this feature are untouched by the revert itself (delete them by hand from `<config dir>/profiles/` if desired).

---

### 97ae1ea — Dependencies: switch PyQt5 to conda-forge (fixes silent startup hang) (2026-08-10)

**Effect:** `environment.yml` pip-installed `PyQt5==5.15.10`. That wheel bundles its own Qt5 libs but `dlopen`s xcb-side system libraries (e.g. `libxcb-cursor.so.0`, required since PyQt5-Qt5 5.15.9+) at runtime instead of vendoring them. On a beamline workstation this produced a silent startup hang: `python launch.py` never returned to the shell prompt, no traceback, `~/midas_gui_error.log` stopped right after the "starting" / UI-scale lines (i.e. past `_install_diagnostics()` but before `app.exec_()`), and Ctrl+C did

nothing — the signature of a native deadlock inside Qt’s xcb platform plugin, not a catchable Python exception, so `launch.py`’s own crash-diagnostics wrapper couldn’t see it. Same failure class B-PILOT hit and fixed the same way (`bpilot_mpe_dev.yml`, 2026-08-10): moved Qt bindings to conda-forge’s `pyqt=5 / qt=5`, which vendor a self-consistent `libxcb / xcb-util-cursor / libxkbcommon-x11` stack inside the env instead of relying on the OS. Also drops the `-e .` editable install from `environment.yml`: it wasn’t needed (`launch.py` imports `midas_gui` straight off its own directory, no install required), and leaving it in would have reintroduced the bug — `pyproject.toml` still pip-pins `PyQt5==5.15.10`, so `pip install -e .` in this env would re-check that pin against the new conda-forge `pyqt` and could reinstall the pip wheel over it. **Files:** `environment.yml`. **Roll back:** `git revert 97ae1ea`. Restores the pip `PyQt5==5.15.10` pin and the `-e .` editable install — only do this if conda-forge’s `pyqt / qt` turn out to be unavailable or broken on a target machine, since the pip wheel is what caused the original hang.

---

### 23cd55e — PDF: rebuild tab for full Stage 2-3 workflow (2026-08-12)

**Effect:** The PDF tab moves from Stage-1-only (composition-weighted Faber-Ziman  $S(Q) \rightarrow G(r)$ ) to the full Stage 2-3 workflow: background/ Paalman-Pings empty-cell absorption subtraction, detector-efficiency correction, absolute normalization, differentiable multiple scattering, a fluorescence diagnostic, CIF-driven structure refinement, and  $\Delta$ -PDF significance testing, behind a new 4-tab left/right panel layout. Deliberately scoped to exclude Bayesian SVI/NUTS, RMC, SAXS/SANS joint refinement, multi-phase/core-shell, anisotropic ADP, and directional strain-PDF (kept out of `pdf_backend.py`’s re-exports on purpose). Ships a dedicated `test_data/test_pdf/` dataset (raw Varex frames, calibration, a rasterized mask, pre-integrated  $I(Q)$  for Ni/CeO<sub>2</sub>/IPA/Kapton/air-scatter, and an authored `Ni.cif`), gitignored like `test_data_pump_probe/` (~320 MB) so `constants.py`’s `DEFAULT_PDF_*` point to local-only data — a fresh checkout elsewhere just won’t have the tab preloaded. Every optional stage uses an explicit `QCheckBox` “Enable” toggle rather than a checkable `QGroupBox`, since `widgets_to_dict / apply_dict_to_widgets` (`helpers.py`) don’t persist `QGroupBox` checked state. Verified via 26/26 offscreen pytest plus a manual functional pass through the actual `PDFTab` widgets, including a structure fit recovering `a=3.5247 Å` vs. expected `3.524 Å`. **Files:** `midas_gui/constants.py`, `midas_gui/pdf_backend.py`, `midas_gui/tab_pdf.py`, `midas_gui/workers.py`, `.gitignore`, `documentation/gui_documentation.md`. **Roll back:** `git revert 23cd55e`. Self-contained — returns the PDF tab to the Stage-1-only pipeline from `b381d8d`; any `test_data/test_pdf/` already on disk is untouched by the revert itself.

---

### cc63d5a — Mask tab: allow multi-file selection for stack source (2026-08-12)

**Effect:** The Stack browse menu gains a “Files (multi-select)...” entry (`_browse_stack_files`) that opens a multi-select `QFileDialog`, letting users hand-pick exactly which frames feed the temporal-stack

methods (spatial-outlier temporal median, temporal constancy, cosmic-ray rejection) instead of only a whole folder or a single file/glob. The chosen list (sorted for a deterministic frame order) is stored in a new `self._stack_files` attribute that takes priority in `_collect_stack_paths()`; the stride spinner still applies to it. Picking Folder/File or typing a path clears `_stack_files` via the existing `_on_stack_path_changed` handler, so the two input modes can't conflict. Persisted across GUI-state save/load. Verified via a full offscreen pytest run (pre-existing `test_app_builds_offscreen` flakiness and a full-suite-only pyqtgraph teardown segfault in the unrelated PDF tab both reproduce identically on unmodified `main`, confirming neither is caused by this change). **Files:** `midas_gui/tab_mask.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert cc63d5a`. Self-contained — the “Files (multi-select)...” menu entry and `_stack_files` state disappear; stack input reverts to folder/file/glob only.

---

### 429d41a — Mask tab: add configurable bad-pixel dilation (2026-08-12)

**Effect:** A new “5 · Post-processing” card adds a **Dilation (px)** spin box (default 0, range 0-50). `_set_mask()` — the single point all mask-producing paths (threshold-only short-circuit, `MaskComputeWorker` result, mask loaded from disk) converge through before merging with hand-drawn shapes — now runs `scipy.ndimage.binary_dilation` with `iterations=N` on the *computed* mask when `N > 0`, before it's OR'd with `self._drawn_mask` in `_emit_final()`. The default 4-connected structuring element with `N` iterations gives exactly the requested semantics: dilation=1 marks every pixel directly touching a bad pixel, dilation=2 adds one further ring, etc.; hand-drawn shapes are never grown. `scipy` was already a pinned dependency and `scipy.ndimage` already used the same way in `workers.py`. Persisted via `_state_widgets()`. Verified with a targeted script instantiating `MaskTab` offscreen and asserting exact pixel counts at dilation 0/1/2 plus that a hand-drawn pixel is excluded from growth at dilation=5. **Files:** `midas_gui/tab_mask.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 429d41a`. Self-contained — removes the Post-processing card and the dilation step in `_set_mask()`.

---

### 188ea77 — Mask tab: switch dilation to 8-neighbor (full-block) growth (2026-08-12)

**Effect:** `_set_mask()`'s `binary_dilation` call now passes an explicit 3×3 full structuring element (`np.ones((3,3), dtype=bool)`) instead of relying on `scipy`'s default 4-connected (diamond) structure. With `iterations=N`, this changes the growth semantics from “`N` rings of 4-connected neighbors” to “the full  $(2N+1) \times (2N+1)$  square centered on each bad pixel” — dilation=1 now marks the entire 3×3 block around a bad pixel, dilation=2 the entire 5×5 block, matching the requested 8-neighbor behavior instead of the original commit's 4-connected one. Hand-drawn shapes are still never grown (same insertion point as 429d41a). Verified with a targeted offscreen script asserting exact pixel counts (9 at dilation=1, 25 at dilation=2 on an isolated bad pixel) and that a hand-drawn pixel outside the dilation

radius is unaffected. **Files:** `midas_gui/tab_mask.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 188ea77`. Self-contained — restores the 4-connected `binary_dilation` default from `429d41a`.

## b2616c6 — Data Viewer: ROI tool usability improvements (2026-08-13)

**Effect:** Five rough edges in `roi_tools.py`’s ROI drawing/popup tooling, all requested together as a Data Viewer ROI cleanup pass: 1. `ROIStatsPopup`’s custom “–” minimize `QToolButton` is removed; a new `changeEvent / _reject_native_minimize` pair intercepts the OS-level (title-bar) minimize via `QEvent.WindowStateChange + Qt.WindowMinimized`, deferred through `QTimer.singleShot(0, ...)` to avoid re-entering Qt’s window-state machinery, and routes it into the same “tuck into the `ROI.Ribbon`” behavior the old button had. 2. Box ROIs get three new `pg.TextItem`s (`coord_item / width_item / height_item`) showing the top-left (`x, y`) corner, `w =`, and `h =` in the ROI’s color, repositioned/retexted on every `sigRegionChanged` (move *and* resize) via a new `_update_roi_annotations()`. Line ROIs are unaffected. 3. New shared `_make_roi_text_item()` helper gives every on-image ROI text item (the existing “ROI N” label included) a translucent background via `pg.TextItem(fill=...)` and a font ~20% larger than the app default (`QFont.pointSize()`, confirmed reliable for `pg.TextItem`’s internal `QGraphicsTextItem` — unlike real `QWidget`s under this app’s QSS stylesheet, which report -1 there). 4. `ROIImageViewer.set_bad_mask()` (wired from `tab_view.py`’s existing `_update_intensity_overlay()` — the sole choke point already covering initial load, live frames, mask toggle, threshold edits, and autofill) feeds the active bad-pixel mask into `_refresh_roi_stats()`: box-ROI histogram/crop stats now exclude bad pixels (intersected at full resolution) and the popup’s crop image gains a `_bad_overlay pg.ImageItem` marking them translucent red, matching the main viewer’s `set_mask_overlay()` convention; line-ROI stats null out masked samples (`set_line_profile` shows “(all pixels masked)” if every sample is excluded, instead of raw NaNs). 5. Dragging a new line ROI previously rendered as a `QRubberBand.Line`, which can only paint an axis-aligned bounding box (the `.Line` shape only changes pen style, not the geometry it’s constrained to) — replaced with a real `QGraphicsLineItem` dropped into the `ViewBox` via `self._iv.addItem(..., ignoreBounds=True)`, the same pattern already used for the line-ROI’s persistent arrow overlay, so the live preview is a true diagonal. A shared `_map_drag_to_view()` helper replaces the old inline scene-mapping in `_finish_roi_draw`; a new `_abort_roi_drag()` cleans up whichever preview item is live if a draw mode is turned off mid-drag. Box-mode’s `QRubberBand` is unchanged. Verified with targeted offscreen scripts: box annotation text/position at known geometry, bad-mask-aware histogram/crop-overlay shape, an all-masked line producing the new stats string, and a simulated line drag producing a `QGraphicsLineItem` with non-degenerate dx/dy (a true diagonal) that’s cleaned up on release. Full `pytest` suite: 24/24 pass excluding the two known pre-existing, unrelated issues already logged in `.context/STATE.md` (`test_smoke.py::test_app_builds_offscreen` config flakiness and a full-suite-only `pyqtgraph` teardown segfault in `tab_pdf.py`), both of which reproduced identically and unchanged in this session. **Files:** `midas_gui/roi_tools.py`, `midas_gui/tab_view.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert b2616c6`. Self-contained — restores the custom minimize button, drops the corner/width/height

annotations and translucent/larger text styling, drops mask-awareness from ROI stats (`ROIImageViewer.set_bad_mask` / the `tab_view.py` wiring), and restores the `QRubberBand.Line` drag preview.

## a1a0b09 — Data Viewer: ROI usability follow-ups (2026-08-13)

**Effect:** Real-usage follow-up fixes on top of `b2616c6`, all in `roi_tools.py` plus one existing shared panel in `widgets.py`: 1. Fixed the OS-level minimize “pops back open” glitch: `_reject_native_minimize()` previously called `setWindowState` (clear `Qt.WindowMinimized`) *before* `hide()`, which asks the OS to reverse the minimize and starts a native un-minimize animation that `hide()` can lose a race against — once the animation completed the popup ended up visible again despite the ribbon entry already existing (fixed by the user clicking minimize a second time). Now `hide()` runs first (unconditionally takes the window off-screen) and the state bit is cleared afterward (invisible, since the window is already hidden); a `changeEvent isVisible()` guard and a defensive state-clear before `_on_roi_restore`’s `show()` round it out. Native minimize/animation behavior can’t be exercised under offscreen QPA — flagged for a real windowed manual check. 2. Box ROI  $(x, y) / w = / h =$  on-image annotations (`_update_roi_annotations`) now use `round(...)` instead of `f"{v:.1f}"` — whole pixels only, no fractional-pixel values. 3. Line ROIs get a new `length_item` `pg.TextItem` (created in `_register_roi`, alongside the existing arrow), positioned at the line’s midpoint and retexted (`f"{round(length)} px"`) on every `sigRegionChanged` inside `_update_line_arrow`. 4. Fixed the line-ROI “ROI N” label always appearing at the image’s top-left corner: `pg.LineSegmentROI.pos()` is always `(0, 0)` (its geometry lives in `listPoints()`, a local-frame handle list, not an item-level offset the way `RectROI` works) — `_on_roi_geom_changed`’s generic `entry["label_item"].setPos(entry["roi"].pos())` therefore parked every line label at the origin. Box ROIs keep that path unchanged; line ROIs now get their label positioned inside `_update_line_arrow` instead, reusing the already-computed, flip-aware `view_p0` (the line’s actual mapped-to-parent start point). 5. New shared `_apply_view_limits(plot_widget, xmin, xmax, ymin, ymax, clamp_xmin_zero=, clamp_ymin_zero=)` helper (same formula as `ProfileViewer._apply_view_limits` in `widgets.py`, the radial- integration plot) applied to the box-ROI histogram (`_redraw_hist`) and the line-ROI profile plot (`set_line_profile`), so neither can be zoomed/panned arbitrarily far from the current data. `widgets.py`’s `IntensityStatsPanel._redraw_hist` — which already had a partial, pan-only version (`xMin / yMin` only) — was brought to parity with `xMax / maxXRange / maxYRange`. 6. Gitignored `test_data_gitignore/` (large local-only functional-test dataset the user keeps on disk for manual GUI testing but never wants pushed). Verified with targeted offscreen scripts (line label anchored at the true start point and swapping correctly on flip, length text/position matching a known line geometry, box coord rounding) plus the full `pytest` suite — no new failures beyond the same two known pre-existing issues logged in `.context/STATE.md` (`test_app_builds_offscreen` config flakiness, and a full-suite-only `pyqtgraph` teardown segfault in `tab_pdf.py`), both reproduced identically and unchanged. **Files:** `midas_gui/roi_tools.py`, `midas_gui/widgets.py`, `.gitignore`, `documentation/gui_documentation.md`. **Roll back:** `git revert a1a0b09`. Self-contained — restores the old minimize-then-hide ordering (glitch returns), the one-decimal box annotations, drops the line-length text item, restores the old `roi.pos()`-based line-label positioning (top-left-corner bug returns), drops the popup-plot/Intensity-histogram zoom-out caps, and un-ignores `test_data_gitignore/`.

## 1181b58 — Data Viewer: bump ROI/histogram axis label font size (9pt -> 12pt) (2026-08-13)

**Effect:** Readability tweak — the axis labels (“distance (px)”/“intensity” on the ROI stats popup’s line-profile plot, “intensity”/“count” or “log(count+1)” on the ROI popup’s histogram, and “intensity”/“log(count+1)” on `IntensityStatsPanel`’s histogram) go from 9pt to 12pt. No layout, behavior, or data changes. **Files:** `midas_gui/roi_tools.py`, `midas_gui/widgets.py`. **Roll back:** `git revert 1181b58`. Self-contained — restores the 9pt axis label font size.

## cc6e90e — Calibrate tab: honor partial distortion-coefficient selection, live-update dark/bright/background preview (2026-08-16)

**Effect:** Two Calibrate-tab (Tab 2) fixes: 1. The **Distortion (n/15)** “...” per-coefficient dialog previously only affected the Four-stage/advanced pipelines — One-shot silently ignored a partial selection and refined all 15 coefficients regardless. `calib.py`’s `run_pipeline()` now detects a strict subset selection on the `one_shot` path and routes it through `midas_calibrate_v2.pipelines.single.autocalibrate` (the same lower-level, per-p# `Refine` -dict routine the other pipelines already use) instead of the high-level `calibrate()`, which only exposes an all-or-nothing `refine_distortion` bool. `normalize_result()` gained a matching branch (`raw.unpacked` present but no `raw.stage2`) to normalize the resulting `CalibrationResult` the same way `first_time`’s `pv.unpacked` case already does. Selecting “All (15)” or leaving Distortion unchecked still runs the normal One-shot path. 2. The Results tab’s parameter grid now lists only the distortion coefficients actually selected for the run that produced the displayed result (`_last_dist_coeffs`, captured when the run starts), instead of always showing all 15 `p0-p14` slots — so the display matches what was asked to refine. The saved `paramtest.txt/.json` exports are unaffected and still carry every slot’s real value (including any legitimately held-fixed nonzero value carried over from a prior calibration). 3. Unrelated same-commit fix: picking or changing a Dark, Bright, or Background field in the shared Data Loader panel now immediately refreshes the calibration image preview to the corrected frame (`DataLoaderPanel.fieldsChanged` wired to a new `_on_fields_changed`, mirroring the Data Viewer tab) — it previously kept showing the raw, uncorrected frame until the next full data load. The raw image (`self._image`) is untouched; only the on-screen render changes, since `CalibrationWorker` still needs the raw frame for the actual pipeline run (it and the backend apply bright/background/dark themselves). Verified via the full `pytest` suite — no new failures beyond the same two known pre-existing issues logged in `.context/STATE.md` (`test_app_builds_offscreen` config flakiness, and a full-suite-only `pyqtgraph` teardown segfault in `tab_pdf.py`), both reproduced identically and unchanged. No dedicated automated test covers the LM-fit coefficient routing or the live preview refresh (no offscreen harness drives an actual calibration run or a Data Loader field pick in this suite). **Files:** `midas_gui/calib.py`, `midas_gui/tab_calibrate.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert cc6e90e`. Self-contained — restores One-shot’s all-or-none distortion refinement, the always-show-all-15 Results grid, and the raw (uncorrected) calibration preview until the next full data load.

## 068bd0d — Add MIDAS ImTransOpt (image flip/transpose) support to Data Viewer + Mask tabs, persist in calibration files (2026-08-17)

**Effect:** MIDAS's `ImTransOpt` image-transform parameter (repeatable integer code in `.txt` parameter files — 1=flip-Y, 2=flip-Z, 3=transpose, applied in file order, interpreted *before* geometry/BC/Lsd) was previously only half-wired in: the Calibrate tab had three checkboxes (“Flip Y” / “Flip Z” / “Transpose”) that built an in-memory codes list applied to the calibration image/dark/bright/background via the shared `_apply_im_trans()`, but the codes were never written to or read back from any saved calibration file, and the Data Viewer and Mask Builder tabs had no transform controls at all. 1.

`midas_gui/helpers.py`: added `parse_im_trans(text)` (reads repeatable `ImTransOpt <code>` lines from a paramtest, dropping an explicit 0 no-op) and `im_trans_codes_from_checkboxes(flip_y, flip_z, transp)` (the fixed flips-then-transpose ordering, shared by all three tabs — replaces two previously-duplicated implementations in `tab_calibrate.py`). `read_geometry()` and `geometry_fields_from_file()` both now return an `im_trans` key ( [] if absent) for all three supported formats (paramtest, `.json`, `.poni` — the latter always [], no pyFAI equivalent). `write_standalone_paramtest()` now appends one `ImTransOpt <code>` line per code from `getattr(result, "im_trans", None)` after the main file write (same append-after-write pattern already used for `PanelShiftsFile`). 2. **Data Viewer** (`tab_view.py`): new “Transforms:” checkbox row in the Ring-simulation/geometry card. Applied at all three points the tab computes its current working frame (`_on_loader_data`, `_on_fields_changed`, `_on_projection_done` — the latter caches the untransformed projection output in a new `self._proj_raw` so toggling a checkbox mid-projection recomputes from the untransformed source instead of compounding transforms onto an already-transformed image). `get_geometry()/set_geometry()` (the Data Viewer <-> Calibrate push/pull) and `_export_geom()/_save_calibration()` (JSON/paramtest export) all carry `im_trans` now;

`_load_calibration()` restores the checkboxes from a loaded file's `ImTransOpt/im_trans`. 3. **Mask Builder** (`tab_mask.py`): same “Transforms:” row under the Image card, applied in the single-image `_load_image()` and passed into `MaskComputeWorker` (new `im_trans` constructor kwarg) for its multi-file and HDF5 stack-source loading (`midas_gui/workers.py`, applied per-frame in both branches). `set_calibration()` (the Calibrate -> Mask hand-off) pre-checks Mask's boxes to match the incoming `result.im_trans` (still user-overridable). 4. **Calibrate tab** (`tab_calibrate.py`): the two duplicated checkbox-to-codes blocks now call the shared helper; `result.im_trans` is set when a run completes (`_on_done`) so it flows into `_save_json()` (already dumps all non-underscore `vars(result)`, so no change needed there), `_save_paramtest()`'s standalone path (via the `write_standalone_paramtest()` change above) and its template path (`ff_paramtest_from_auto_result()` is external and untouched — `ImTransOpt` lines are appended manually afterward, the same way `PanelShiftsFile` already was), and the on-screen paramtest preview grid (`_paramtest_pairs()`, unchanged — it already renders whatever `write_standalone_paramtest()` produces). `_load_calib_file()` and `apply_geometry()` (Data Viewer -> Calibrate) restore the checkboxes from a loaded/pushed `im_trans`, logging a note if a file's `ImTransOpt` order doesn't match the fixed checkbox order (only matters when transpose is combined with a flip, since flips commute with each other but not with transpose — no real example file in the MIDAS repo does this). 5. All three tabs' `_state_widgets()` (Save/Load GUI State) gained `flip_y/flip_z/transp`

entries (Calibrate already had them). **Verified:** new `tests/test_im_trans.py` (19 cases — parsing, write/read round-trip, the checkbox-to-codes helper for all 8 combinations, `_apply_im_trans` composition order) plus targeted offscreen scripts confirming Data Viewer/Mask checkbox toggles actually flip/transpose the loaded array, and a full Calibrate-tab save-paramstest -> reload -> checkbox-state round trip. Full `pytest` suite: 43 passed, 2 deselected (the same pre-existing `test_app_builds_offscreen` config flakiness and full-suite-only `tab_pdf.py` `pyqtgraph-teardown segfault` logged in `.context/STATE.md`, both reconfirmed identical on unmodified `main` before this change). **Files:** `midas_gui/helpers.py`, `midas_gui/tab_calibrate.py`, `midas_gui/tab_view.py`, `midas_gui/tab_mask.py`, `midas_gui/workers.py`, `tests/test_im_trans.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 068bd0d`. Self-contained — restores the Calibrate-tab-only, in-memory-only `ImTransOpt` behavior and removes the Data Viewer/Mask transform controls.

---

## 73a7a2a — Calibrate tab: Transforms checkboxes now live-update preview and drive the actual calibration run (2026-08-17)

**Effect:** `068bd0d` made the Calibrate tab's Transforms checkboxes round-trip through saved/loaded calibration files, but toggling one still did nothing to the on-screen preview or the actual calibration run — the displayed/picked-on image and the array handed to the pipeline stayed untransformed regardless of the checkboxes. Two fixes: 1. **Live preview + picks.** The three checkboxes now call `_on_im_trans_changed()` on toggle, which re-renders `_show_calib_image()` through the same `_apply_im_trans()` helper Data Viewer/Mask use. Since Pick BC / Pick Ring read coordinates straight off the displayed `PickableImageViewer` array, picks now automatically land in the transformed coordinate space instead of the untransformed one — matching Data Viewer and Mask Builder's behavior. 2. **Actual calibration run.** `CalibrationWorker.run()` previously passed `cfg["im_trans"]` straight to `calib.run_pipeline()`, which only applies it internally on some code paths — Four-stage, Bayesian, Joint-cake, panel-layout, and partial-distortion-coefficient runs (`cc6e90e`) all silently ignored it, so the fitted beam centre/detector dimensions never matched a transformed image. The worker now applies `_apply_im_trans()` to the calibrant image and to Dark itself, once, right before the pipeline call, then clears `cfg["im_trans"]` so `run_pipeline`'s own internal transform (meant for callers handing it a raw image directly) doesn't double-apply it. 3. **Send to Data Viewer** now also carries `im_trans` in the geometry dict handed to Data Viewer, so its own Flip/Transpose checkboxes sync to match the calibration that produced the sent geometry (previously only  $\lambda$ /pixel size/Lsd/BC/tilts/distortion made the trip). 4. Unrelated same-commit cleanup: the Average frames card's **skip** (stride) spinbox was removed — it added a rarely-used degree of freedom that made the averaged-frame count harder to reason about; **start/ end (0=all)** remain. **Verified:** full `pytest` suite — 43 passed, 2 deselected (the same two pre-existing issues logged in `.context/STATE.md`: `test_app_builds_offscreen` config flakiness and the full-suite-only `tab_pdf.py` `pyqtgraph-teardown segfault`). No dedicated automated test covers the live preview refresh or the worker's transform-before-pipeline change (no offscreen harness drives an actual calibration run in this suite). **Files:** `midas_gui/tab_calibrate.py`, `midas_gui/workers.py`,

documentation/gui\_documentation.md . **Roll back:** `git revert 73a7a2a` . Self-contained — restores the untransformed live preview/picks, `run_pipeline` 's own (partial) internal transform handling, the Send-to-Data-Viewer payload without `im_trans` , and the Average frames skip/stride control.

---

## 683d150 — Add pip requirements.txt mirroring environment.yml + README pip install path (2026-08-21)

**Effect:** `midas-gui` previously only documented a conda install path (`environment.yml`); users without conda had no supported way to reproduce the pinned dependency set with plain pip. Added `requirements.txt` at the repo root, generated from `environment.yml` 's pinned versions (matches the same versions already declared in `pyproject.toml` 's `dependencies` ), and a new “Alternative: pip only (no conda)” section in the README with the `venv + pip install -r requirements.txt` commands. Carried over both of `environment.yml` 's load-bearing warnings as comments: the numpy 1.26.4 / numba 0.59.1 / torch 2.4.0 NumPy-1 compatibility pin, and the PyQt5 pip wheel's known xcb-library silent-startup-hang risk on Linux (with the `apt install libxcb-cursor0` workaround) versus conda-forge's self-contained Qt build. **Verified:** `pip install -r requirements.txt` was not run against a fresh environment in this session (no isolated network/venv sandbox available here); version pins were cross-checked line-by-line against `environment.yml` and `pyproject.toml` 's `dependencies` list instead, which already match. **Files:** `requirements.txt` (new), `README.md` . **Roll back:** `git revert 683d150` . Purely additive/documentation — safe to revert standalone; removes the pip install path and leaves conda as the only documented route.

---

## c8d98f1 — Test data: reorganize test\_data/ into per-dataset subfolders (2026-08-23)

**Effect:** `test_data/` mixed the shipped synthetic sample set with several local-only large datasets scattered across differently-named top-level dirs (`17BM/` , `test_s25ide/` , and the sibling `test_data_pump_probe/` outside `test_data/` entirely), making it unclear from the name alone which folders ship with the repo and which are git-ignored local assets. Renamed the shipped synthetic data (`calibrant_ceria.*` , `nickel_stack.h5` , `nickel_tifs/` , `make_test_data.py` ) into `test_data/gui_synthetic/` , and the large local-only sets into `test_data/s17bm/` , `test_data/trr_s25ide/` , and `test_data/trr_s7id/` (the latter absorbing what was `test_data_pump_probe/` at the repo root). `.gitignore` 's shipped-data re-includes now scope to `test_data/gui_synthetic/**` only, so every other `test_data/` subfolder stays git-ignored by default; the standalone `/test_data_pump_probe/` and `/test_data_gitignore/` ignore rules were removed since those paths no longer exist. `constants.py` 's Pump Probe tab default path (`DEFAULT_TRXRD_DIR` ) and `gui_documentation.md` 's reference to it were updated to `test_data/trr_s7id/pump_probe_BT0/detimages/` . **Verified:** offscreen 9-tab app build + full pytest suite still pass (same pre-existing `test_app_builds_offscreen` config flakiness as noted in `.context/STATE.md` , unrelated to this change); confirmed no other source file referenced the old `test_data_pump_probe/` , `test_data/17BM/` , or

`test_data/test_s25ide/` paths before renaming. **Files:** `.gitignore`, `midas_gui/constants.py`, `documentation/gui_documentation.md`, `test_data/**` (renames only, no content changes). **Roll back:** `git revert c8d98f1`. Self-contained rename/path change — restores the old top-level `test_data_pump_probe/`, `test_data/17BM/`, and `test_data/test_s25ide/` layout and the matching `.gitignore/` `constants.py` paths.

---

## 246dba7 — Viewers: flip detector-image origin to bottom-left (0,0), per MIDAS convention (2026-08-23)

**Effect:** Every `pg.ImageView`-based viewer (Data Viewer, Mask Builder, Calibrate) was drawing pixel `(0, 0)` at the top-left, because `pg.ImageView.__init__` calls `view.invertY()` internally. MIDAS's own convention places detector `(0, 0)` at the bottom-left, so the on-screen image now matches the physical world view of the detector looking downstream from the sample along the beam. Fixed with a single `vb.invertY(False)` override in `ImageViewer.__init__` (`widgets.py`), which propagates to `PickableImageViewer/ROIImageViewer` since both subclass it — covering all three viewers in one place. `roi_tools.py`'s ROI crop-preview popup (`ROIStatsPopup`) and the Data Viewer box-ROI corner-coordinate annotation/docstrings were updated in lockstep, since both were explicitly compensating for (or documenting) the old top-left-origin default. This is a pure display-orientation flip: it does not change click-to-pixel math (`mapSceneToView/` `mapFromScene` are invert-aware), Calibrate's ring/tilt geometry math, or the separate `ImTransOpt` data-level transform (the Transforms: Flip Y/Flip Z/Transpose checkboxes), which still operate on the underlying pixel data independent of which corner is rendered as the origin. **Verified:** confirmed via an offscreen render-and-inspect-pixmap script (not just coordinate round-trips, which can't prove the visual direction) across all three viewers plus the ROI crop popup, and a full pytest re-run (44 passed, 1 known pre-existing failure per `.context/STATE.md`). Not yet confirmed with a real windowed manual pass — recommended as a follow-up, especially Calibrate's ring overlay and the Data Viewer's ROI crop popup. **Files:** `midas_gui/widgets.py`, `midas_gui/roi_tools.py`, `documentation/gui_documentation.md`. **Roll back:** `git revert 246dba7`. Self-contained — restores the top-left-origin display convention and the matching ROI-popup/box-corner- annotation compensation.

---

## 3b785c9 — Fix stale DEFAULT\_\* test-data paths after gui\_synthetic/ reorg (2026-08-23)

**Effect:** The `246dba7/` `c8d98f1` reorg session moved `calibrant_ceria.tif`, `calibrant_ceria.h5`, `nickel_stack.h5`, `nickel_tifs/`, and `calibration_synthetic.json` into `test_data/gui_synthetic/`, but `constants.py`'s six `DEFAULT_*` constants (`DEFAULT_CALIBRANT_TIF`, `DEFAULT_CALIBRANT_H5`, `DEFAULT_NICKEL_H5`, `DEFAULT_NICKEL_DIR`, `DEFAULT_NICKEL_FRAME0`, `DEFAULT_CALIB_FILE`) still pointed at the old repo-root locations — silently breaking every tab's default-data preload on a fresh checkout (Data Viewer, Calibrate, Mask Builder, Batch Integrate, Corrections, PDF, Texture all reference one or more of these).

Added a `_GUI_SYNTH = _TEST_DATA / "gui_synthetic"` base and repointed the six constants at it. Found while verifying the new Hydra-mode `DetectorGeometryCard` extraction (see the following commit) — unrelated to that work, fixed as its own commit per project convention. **Note:** a locally-cached profile (e.g. `~/Library/Application Support/midas_gui/profiles/<name>.json`, seeded from the old shipped defaults before this fix) can still override these with the stale paths at runtime via `constants.reload_from_config()` 's config-overlay step — that's local machine state, not a repo file, and isn't touched by this commit. A user hitting this after upgrading should reset/re-seed that profile (or manually fix its `paths` section) to pick up the corrected defaults. **Verified:** confirmed all six paths resolve and exist under `test_data/gui_synthetic/` with the fix; full pytest re-run (same single pre-existing `test_app_builds_offscreen` flakiness, unrelated). **Files:** `midas_gui/constants.py`. **Roll back:** `git revert 3b785c9`. Self-contained — restores the stale repo-root paths (breaking default-data preload again).

---

### 3d2d99d — Data Viewer: add Hydra-mode ribbon scaffold; extract `DetectorGeometryCard` (2026-08-23)

**Effect:** First step of the Hydra (4-panel GE detector) viewer feature. Added a leftmost vertical mode ribbon (`HydraModeRibbon`, `hydra_widgets.py`) to the Data Viewer tab with two exclusive modes: **Single detector** (today's existing view — now “page 0” of a new `QStackedWidget`, behavior unchanged) and **Hydra** (a placeholder “coming soon” page). Also extracted the ring-simulation, calibration load/save, and radial-integration logic (~700 lines: materials list, `MaterialDialog`, tilted-ring drawing, beam-centre pick/ring-fit handling, the MIDAS-engine and circle-binning radial integration paths, calibration file read/write) out of `DataViewerTab` into a new reusable `DetectorGeometryCard` widget (`hydra_geometry_card.py`). The card is bindable rather than hard-wired — `set_viewer / set_profile_view / set_image_source / set_radial_controls` let it attach to whichever image viewer, radial plot, and frame source it should currently act on, and `set_viewer` cleanly clears its overlays off a previous viewer before attaching to a new one — so the same class can later be instantiated once per Hydra panel (ge1-4 + composite) without duplicating this logic five times. `DataViewerTab` keeps its external API (`get_geometry / set_geometry / pushGeometry`) as thin delegates to the card, so `app.py` 's Data-Viewer-to-Calibrate geometry hand-off wiring needed no changes. Saved-GUI-state JSON shape is unchanged (the card's fields are merged into the same flat `fields` dict `Save/Load GUI State` already used) for backward compatibility with existing saved sessions. **Verified:** the extraction (page 0) was checked against the pre-refactor code with an offscreen pixel-diff of the rendered tab (ring simulation + calibration load + radial integration all exercised) — only a 6px-wide cosmetic sliver at the very left edge differs (a margin artifact from the new ribbon itself, not a content regression); full pytest re-run (same single pre-existing, unrelated `test_smoke.py` `visible_tabs` flake). The Hydra page itself is not yet functional — no visual/behavioral change there beyond the placeholder label. **Files:** `midas_gui/tab_view.py`, `midas_gui/hydra_geometry_card.py` (new), `midas_gui/hydra_widgets.py` (new), `documentation/gui_documentation.md`. **Roll back:** `git revert 3d2d99d`. Self-contained — restores the single-page Data Viewer tab with the ring-sim/calibration/radial logic inline.

## dd44f38 — Hydra: geometry-compositing engine + sibling auto-discovery + tests (2026-08-23)

**Effect:** Adds `midas_gui/hydra.py`, the windmill-compositing math for the 1-ID-E Hydra detector (4x GE panels): `compute_inv_coords / remap_to_composite / composite / autopick_big_det_size / DetectorState / build_windmill_composite`, ported from a sibling project's own port of JSP's `multidet.py`. `DetectorState.load_from_geometry_dict` consumes this repo's own `helpers.geometry_fields_from_file` (already used by the Calibrate/Data-Viewer calibration-load UI) instead of a bespoke per-panel parser — the ported files' bundled param-file parser was intentionally not carried over. Bundled default geometry (`hydra_default_geometry/ps_ge{1..4}.txt`, a generic 1-ID-E-style example windmill layout) seeds a panel with no calibration loaded yet. Adds `helpers.hydra_panel_index / hydra_siblings` — given any one GE panel's file path, finds the other 3 by substituting the `geN` token (handles both a `geN/` folder segment and a `.geN` filename infix, this beamline's actual naming convention). Fixed a latent staleness bug in `build_windmill_composite`'s `BigDetSize` cache (found during testing): it was keyed only by which panel numbers were present, so it kept returning a stale canvas size after a panel's geometry changed (e.g. a new calibration file) for the same panel set — now keyed by each panel's actual BC/tx/px/size too. **Verified:** cross-checked against real local (uncommitted, gitignored) `test_data/slide CeO2 Hydra` data — the composite matches the reference project's own reported result (6656px canvas, 0% NaN, correct pinwheel arrangement), and rendering with the real fitted per-panel calibration shows Debye-Scherrer rings stitching into continuous arcs across all 4 panel boundaries — the physically-grounded confirmation that no chirality/mirroring error exists. This resolved an open question from the reference project (whose own custom viewer needed an X-mirror for its composite) — this codebase's `pg.ImageView`-based viewers need no such correction; full reasoning in `.context/DECISIONS.md`. Added a committed synthetic fixture (`test_data/gui_synthetic/hydra/`, 4 small 256x256 panels with a known idealized geometry, tx values deliberately not exact multiples of 90° so a sign error can't alias one panel's marker onto another's) and two new permanent test files: `tests/test_hydra_geometry.py` (12 tests: sibling discovery, `DetectorState`, bundled-default parsing, an independently-hand-derived-math marker-position check) and `tests/test_hydra_chirality.py` (the same marker check rendered through the real `R0IImageViewer` via `widget.grab()` — a permanent regression guard, not just a one-off manual check). Full pytest suite: same single pre-existing, unrelated `test_smoke.py` flake. **Files:** `midas_gui/hydra.py` (new), `midas_gui/hydra_default_geometry/*` (new), `midas_gui/helpers.py`, `test_data/gui_synthetic/hydra/*` (new), `tests/test_hydra_geometry.py` (new), `tests/test_hydra_chirality.py` (new). **Roll back:** `git revert dd44f38`. Self-contained — no other code references `hydra.py` yet (the Hydra page UI that will consume it lands in a follow-up commit).

## 778a2f3 — Commit `.context/` per global policy (2026-08-23)

**Effect:** `.context/` (STATE/DECISIONS/ARCHITECTURE/DOMAIN/ROADMAP + the `midas_pdf` reference stack) had been listed in `.gitignore` since this repo's early history, contradicting the standing global-CLAUDE.md rule that this folder always travels with the repo (so accumulated project knowledge/decisions survive across machines and clones). Removed the `.gitignore` rule and committed the folder as-is. Also formalized `/test_data/slide/` (real, local-only CeO2 Hydra calibration data, used read-only this session with explicit user approval for the Hydra compositing verification — see `dd44f38`) as gitignored, matching how it had already been treated all along (never committed, never a pytest dependency). **Files:** `.gitignore`, `.context/*` (new). **Roll back:** `git revert 778a2f3`. Self-contained, though reverting would re-orphan `.context/` from version control going forward.

---

## 1cc4dab — Hydra: wire loader/toolbar/per-panel calibration UI + composite into the tab (2026-08-23)

**Effect:** Replaces the Hydra page placeholder (from `3d2d99d`) with a working `HydraViewerPage`. New `HydraLoaderPanel` (one path field auto-discovers all 4 GE panels via `helpers.hydra_siblings`, plus a shared frame navigator) and `HydraDetectorToolbar` (ge1-4/composite buttons, enabling only buttons for panels actually found) in `hydra_widgets.py`. `HydraViewerPage` (`hydra_page.py`) owns one `hydra.DetectorState` and one `DetectorGeometryCard` per panel, plus a `DetectorGeometryCard` for the composite. Switching the toolbar rebinds the shared `R0IImageViewer / ProfileViewer` to the newly-active card (via `set_viewer / set_profile_view` — exactly what the `3d2d99d` extraction was built to support) and displays that panel's raw frame or the geometry-based composite. Loading a calibration file (or editing/picking BC) on a ge-card now syncs into its `DetectorState` and invalidates the composite so it rebuilds with the new geometry; the composite's own card auto-seeds its beam centre at the canvas centre (`BigDetSize/2`) the first time a given canvas size appears, so it has a working ring overlay for free. Added `DetectorGeometryCard.geometryChanged` signal + `get_full_geometry()` accessor for this syncing. `DataViewerTab.get_state() / set_state()` now folds in `HydraViewerPage`'s own state (loader path, active panel, every card's fields/materials). **Scope cuts for this version** (documented, not oversights): radial integration reuses the existing single-curve `ProfileViewer` (shows whichever panel/composite is active, one shared R-bin/Auto/Integrate control set across all 5 cards) rather than the eventual 4-curves + toggleable-composite plot; no dark/bright/mask corrections for Hydra frames yet (raw frames only). **Verified:** end-to-end with the synthetic fixture (`test_data/gui_synthetic/hydra/`) — loading matched per-panel calibration into all 4 cards rebuilds the composite at the expected canvas size with the composite card's BC correctly auto-seeded at centre; every ge1-4/ composite button displays the right frame with independent ring simulation and radial integration; an offscreen screenshot confirms the full page renders and functions together. New `tests/test_hydra_ui.py` (4 tests). Full pytest suite: same single pre-existing, unrelated `test_smoke.py` flake. **Files:** `midas_gui/hydra_page.py` (new), `midas_gui/hydra_widgets.py`, `midas_gui/hydra_geometry_card.py`, `midas_gui/tab_view.py`, `tests/test_hydra_ui.py` (new). **Roll back:** `git revert 1cc4dab`. Self-contained back to the `3d2d99d` placeholder state.

## 8707372 — Hydra: multi-curve radial profile plot with toggleable composite curve (2026-08-23)

**Effect:** Adds `HydraProfileViewer` (`hydra_widgets.py`): one fixed-color curve per Hydra panel (ge1-4) plus a toggleable “Composite” curve, sharing an R/2 $\theta$ /Q axis-unit selector and Log-Y toggle — replacing the single-curve `ProfileViewer` placeholder from `1cc4dab`. Each ge-card’s own

`DetectorGeometryCard.set_profile_view` is now bound once, permanently, via a small `_ProfileSinkAdapter` (`hydra_page.py`) into that panel’s named curve on the shared plot, since (unlike the image viewer) all 4 profiles need to stay live regardless of which panel is currently active in the toolbar. The **Composite** curve is deliberately *not* the composite card’s own `radial_integrate()` (which would integrate the already-composited image, double-counting any panel overlap and mixing registration error into the profile — exactly the approach the plan review flagged and the user asked to avoid). Instead

`HydraViewerPage._refresh_composite_curve` converts each available panel’s own profile to a shared 2 $\theta$  axis, resamples all onto one common grid, and takes a NaN-aware `nansum`, then round-trips through the normal `set_curve(r_px, ...)` API using one contributing panel’s geometry as a consistent reference axis (so X-axis unit switching still works). The composite card’s own profile/radial-control bindings are deliberately left unset so it can never write into that same curve slot. New

`_refresh_profile_curves()` / `_refresh_composite_curve()` orchestration: frame/sibling-list changes reload+reintegrate every available panel (not just the active one); “Integrate” force-refreshes all of them regardless of Auto; R-bin edits refresh the derived Composite curve after each card’s own pre-existing auto-radial wiring runs. **Also found and documented** (not silently worked around): adding these tests exposed a rare, pre-existing pyqtgraph interpreter-crash risk (`Segmentation fault / Bus error` in pyqtgraph’s own global `ViewBox / WidgetGroup` teardown internals) that surfaces more easily under a large test suite with many `ImageView / ViewBox` instances. An autouse `app.processEvents()` teardown fixture in `tests/test_hydra_ui.py` measurably reduced (did not guarantee-eliminate) it; `gc.collect()` there made it worse. Full detail — including what not to try next — in `.context/DECISIONS.md`. **Verified:** end-to-end with the synthetic fixture — all 4 curves populate independently, the Composite toggle correctly shows/hides and recomputes, the Integrate button refreshes everything with Auto off; an offscreen screenshot confirms the legend/colors/curves render correctly together. 2 new tests in `tests/test_hydra_ui.py` (6 total in that file). Full pytest suite: 3 consecutive clean runs post-mitigation, same single pre-existing `test_smoke.py` flake each time. **Files:** `midas_gui/hydra_widgets.py`, `midas_gui/hydra_page.py`, `tests/test_hydra_ui.py`, `.context/DECISIONS.md`. **Roll back:** `git revert 8707372`. Self-contained back to the `1cc4dab` single-curve-plot state.

## 0aa5feb — Hydra: fix 5 bugs found in the real windowed Phase 6 pass (2026-08-24)

**Effect:** The first real windowed (not offscreen) manual pass over Hydra mode surfaced 5 real bugs that headless tests/screenshots never exercised, all fixed: 1.  **$\lambda$ /max 2 $\theta$ /pixel size shared across ge1-4 + Composite.** `DetectorGeometryCard` gained `get_shared_fields()` / `apply_shared_fields()`;

`HydraViewerPage._sync_shared_fields()` mirrors an edit on any one of the 5 geometry cards onto the other 4 (same X-ray beam and GE detector model, so these three are always physically identical), guarded by a `_syncing_shared` re-entrancy flag. 2. **Dark/bright/background correction added for Hydra**, closing a documented scope cut. New `HydraFieldSelector` (`hydra_widgets.py`) reuses the single-detector tab's `helpers.apply_field_corrections / workers.FieldAverageWorker` as-is and auto-discovers the other 3 panels' field files via `helpers.hydra_siblings`. 3. **Composite windmill orientation**. Two rounds: (a) an earlier same-day attempt to "fix" the rotation to clockwise was itself wrong and reverted back to the original counterclockwise convention; (b) even after that revert, `ge2/ge4` were still on the wrong sides of the canvas, fixed by adding a vertical-axis mirror in `hydra.py::compute_inv_coords` (`Y_lab = (half - Yo) * px`) — scoped to the composite build only, independent of the rotation-direction math, and does not touch the per-panel `ge1-4` raw displays. Both fixes confirmed against real `park_may26_bc` calibration + real `park_may26/ge{1..4}` frames, not just offscreen tests. 4. **Stale radial-integration geometry fixed**. `_effective_calib_geom()` was returning a frozen snapshot from calibration-load time, so a post-load `BC/λ/Lsd/px/tilt` edit moved the ring overlay (reads live widgets) but not the radial profile. Fixed to always override `wavelength/Lsd/BC/pxY/pxZ/ty/tz` from the live widgets. 5. **ImageViewer vmin% auto-level now excludes exact-zero pixels** app-wide — fixes a washed-out Composite view whose mostly-empty `BigDet` canvas previously dominated the percentile calculation. **Verified:** full Hydra geometry/chirality test suite (14 tests) passes against the reverted rotation + new mirror; orientation and stale-geometry fixes additionally confirmed by rendering the composite from real `park_may26_bc / park_may26/ge{1..4}` data, not offscreen fixtures alone. Full reasoning for all 5 bugs, including the wrong-then-reverted clockwise attempt, in `.context/DECISIONS.md`. **Files:** `midas_gui/hydra.py`, `midas_gui/hydra_geometry_card.py`, `midas_gui/hydra_page.py`, `midas_gui/hydra_widgets.py`, `midas_gui/widgets.py`, `tests/test_hydra_chirality.py`, `tests/test_hydra_geometry.py`, `tests/test_hydra_ui.py`, `.context/DECISIONS.md`. **Roll back:** `git revert 0aa5feb`. Self-contained back to the `8707372` state (Phase 6 scope cuts — dark/bright/background, shared fields — would return; the still-wrong pre-revert orientation is not restored, since that never existed on `main`).

## Rollback recipes (common intents)

- **Undo the Pump Probe tab only:** `git revert 590b410` removes Pump Probe *and* modular tabs. To drop Pump Probe alone, hand-remove `midas_gui/tab_pumpprobe.py`, its import/construction/wiring in `app.py`, `PumpProbeWorker` in `workers.py`, and its entry in `constants.OPTIONAL_TABS / DEFAULT_VISIBLE_TABS`.
- **Undo modular tabs (show all 10 fixed again):** remove the `apply_tab_visibility` logic in `app.py` (add all tabs directly), the Tabs section in `prefs_dialog.py`, and the tab-list constants — see the `590b410` diff for the exact hunks.

- **Undo the config system:** `git revert d30be2c` — but first revert `590b410`'s config touches, since it extends the same `ui` overlay and Preferences dialog.
  - **Revert the azimuthal-averaging change:** don't blanket-revert `41f28f5` (bundled with UI); instead set the `weighted` default back to the legacy  $\eta$ -bin mean in the batch/pump workers.
  - **Go back to the pre-3-panel single-column tabs:** `aa9395e` is the pivot; a revert is large and cascades to later tabs — prefer fixing forward.
- 

*Generated from `git log`. To refresh after new commits: `git log --reverse --stat --date=short` and append entries above.*