Response to Reviewers' Comments

Paper ID 2147 • ICMLDE 5.0 • Procedia Computer Science

Original title: *Edge-Deployable Skin Lesion Classification: A Weighted Ensemble of MobileNetV2 and DINOv2*

Revised title: *Edge-Deployable Skin Lesion Classification with Quantized CNN and Transformer Models*

Respected Scientific Committee and Reviewers,

We sincerely thank the reviewers for their careful reading and constructive comments, which have substantially strengthened the paper. In addressing them, we carried out a detailed audit of the data split and of the model-fusion evaluation, which sharpened the focus of the contribution. The revised paper presents MobileNetV2 and DINOv2 as independent branches, analyses their probability-level fusion with a paired statistical test, and adds on-device latency, memory, and thermal measurements on a Raspberry Pi 4 for the FP32 and quantized models. All accuracies are reported transparently as validation results, together with a lesion-level overlap analysis.

Summary of Major Changes

1. **Title.** Revised from "Edge-Deployable Skin Lesion Classification: A Weighted Ensemble of MobileNetV2 and DINOv2" to "Edge-Deployable Skin Lesion Classification with Quantized CNN and Transformer Models".

   Justification: The new title reflects the central contribution of the revision, quantized models evaluated for edge deployment (Reviewer 1, Comments 2 and 3; Reviewer 3, Comment 1).

2. **Block diagram (Fig. 1 (page 3)).** Redrawn to show data preparation, the two MobileNetV2 and DINOv2 branches with their baseline FP32 evaluation and optimization experiments, Grad-CAM explainability, the three output classes, and the Raspberry Pi 4 deployment with its measured latency.

   Justification: The diagram now presents the complete revised workflow in one view, including the optimization, explainability, and on-device deployment stages requested by the reviewers (Reviewer 1, Comment 3; Reviewer 3, Comments 1 and 2).

3. **Methodology.** The two models are presented as independent branches, and probability-level fusion is analysed in a dedicated section with a paired McNemar test (Section 3.6 (page 4) and 4.4).

   Justification: Independent branches give a clear, deployable model, and the dedicated fusion analysis quantifies the benefit of combining the two architectures with a statistical test (Reviewer 1, Comments 2, 4, and 6; Reviewer 2, Comment 5).

4. **Edge deployment.** New Section 4.6 (page 7) and Table 4 (page 7) report Raspberry Pi 4 latency, throughput, peak memory, and sustained thermal behaviour for the FP32 and quantized models.

   Justification: These on-device measurements provide direct evidence for the edge-deployable claim and show the effect of quantization on a real edge device (Reviewer 1, Comment 3; Reviewer 3, Comment 1).

5. **Data analysis.** Lesion-level overlap analysis (Section 3.2 (page 4)), justification of the three classes, and class-balance statistics (Section 3.1 (page 3)).

Justification: The dataset composition and the data split are now described transparently, so that the scope of the results is clear to the reader (Reviewer 1, Comment 1; Reviewer 2, Comments 1, 3, and 4).

6. **Graphs and figures.** All result graphs were regenerated from the experiment logs in a consistent publication style (bold labels, inward ticks, boxed legends):

   - Training curves: the two separate MobileNetV2 and DINOv2 accuracy/loss graphs were combined into one four-panel figure (Fig. 3 (page 6)).
   - Confusion matrix: replaced by the MobileNetV2 FP32 confusion matrix, with a matching per-class table (Fig. 4 (page 8), Table 5 (page 8)).
   - Grad-CAM: new figure with heatmaps for one correct case per class and a Melanoma-predicted-as-Nevus case (Fig. 5 (page 9)).
   - Block diagram: redrawn as described in item 2 (Fig. 1 (page 3)).
   - The earlier sample-image figure was merged into Figs. 1 and 5, which show the same lesions.


   Justification: The regenerated graphs report the deployed MobileNetV2 directly, add per-class and Melanoma-specific evidence and visual explanations, and present the training behaviour of both models side by side in less space, which keeps the manuscript within the ten-page limit (Reviewer 2, Comment 2; Reviewer 3, Comments 2 and 3).

7. **Text.** Abstract, introduction, contributions, discussion, and conclusion rewritten to reflect these changes.

   Justification: The narrative is now consistent with the revised results, discusses the fusion gain, and states the study scope and future work explicitly (Reviewer 1, Comment 6; Reviewer 2, Comment 6; Reviewer 3, Comment 6).

8. **References.** Seven references added, four previously uncited references now cited, and the list numbered in order of citation.

   Justification: The quantization, pruning, explainability, and transformer-quantization methods used in the study are now supported by the established literature (Reviewer 3, Comment 5).



Revised block diagram (Figure 1, page 3, of the revised manuscript).

Point-by-Point Responses

All section, figure, table, and page numbers in this letter refer to the revised manuscript, which follows this letter.

Reviewer 1

Reviewer 1, Comment 1: *The abstract reports validation accuracy; independent test results should be reported.*

Response: We thank the reviewer for this important observation. The abstract and all results now state clearly that they are validation results, together with a lesion-level overlap analysis (54.04% of validation images share a lesion with the training set). To give the most representative estimate, we also report accuracy on the 1,144 validation images whose lesions are distinct from training (MobileNetV2 86.80%, DINOv2 84.00%). A lesion-grouped split has been prepared for the held-out test evaluation planned as future work.

Accuracy on the full and the non-overlapping validation images

Model	All 2,489 images	1,144 non-overlapping images
MobileNetV2 FP32	90.96%	86.80%
DINOv2 FP32	86.66%	84.00%
Equal-weight fusion	91.36%	87.15%

Changes in the Manuscript (Abstract, page 1; Section 3.2, page 4 of the revised manuscript): "... *All results are validation results, because lesion-level auditing identified 54.04% overlap between validation and training images. ...*"

Reviewer 1, Comment 2: *A weighted ensemble of MobileNetV2 and DINOv2 is a modest contribution.*

Response: We thank the reviewer for this valuable comment. In response, the contribution has been redefined around edge deployment: the revised paper presents (i) a controlled comparison of FP32, dynamic-range INT8, full-integer INT8, and 50% pruned MobileNetV2; (ii) on-device latency, memory, and thermal measurements on a Raspberry Pi 4; and (iii) an analysis of INT8 quantization for DINOv2, including the activation outliers in Blocks 8–11. The probability-level fusion is retained as a supporting analysis, and the title now reflects quantization as the central subject.

Changes in the Manuscript (Title; Section 1, page 2 of the revised manuscript): "... *Integration of the MobileNetV2 inference pipeline into a Streamlit-based application, and on-device benchmarking of the FP32 and quantized MobileNetV2 variants on a Raspberry Pi 4, including latency, memory, and sustained thermal behaviour. ...*"

Reviewer 1, Comment 3: *The edge-deployable claim needs latency and memory measurements on edge devices.*

Response: We thank the reviewer for this suggestion. All MobileNetV2 variants were benchmarked on a Raspberry Pi 4 Model B (4 GB, Cortex-A72, CPU only). Full INT8 TFLite ran at 13.92 ms per image (71.8 FPS) with 51.7 MiB peak memory, compared with 597.59 ms and 636.9 MiB for the FP32 Keras model; an unquantized FP32 TFLite baseline (36.63 ms) separates the runtime effect from the quantization effect. Sustained 5-minute runs reached at most 78.4 °C with no throttling, and the Full INT8 latency remained constant (14.11 to 14.16 ms).

Raspberry Pi 4 Model B results (batch one, four threads)

Variant	Disk	Latency (ms)	FPS	Peak RSS	Max temp.
FP32 Keras	30.21 MiB	597.59 ± 9.86	1.67	636.9 MiB	55.0 °C
FP32 TFLite	9.79 MiB	36.63 ± 0.34	27.30	69.5 MiB	74.5 °C
Dynamic-range INT8	2.74 MiB	41.72 ± 3.42	23.97	59.2 MiB	72.0 °C
Full INT8	**2.94 MiB**	**13.92 ± 0.20**	**71.83**	**51.7 MiB**	**78.4 °C**

Changes in the Manuscript (Section 4.6, Table 4, page 7 of the revised manuscript): "*. . . Full INT8 TFLite ran at 13.92 ms per image (71.8 FPS), 42.9× faster than FP32 Keras and 2.6× faster than unquantized FP32 TFLite, while using the least memory. . . .*"

Reviewer 1, Comment 4: *Ensemble weights tuned on validation data must be tested on a separate test set.*

Response: We thank the reviewer for this point. Weighted fusion is reported as a dedicated analysis in Section 4.4 (page 6), which compares both evaluated weightings with MobileNetV2 on the same validation predictions, while the deployed pipeline uses the Full INT8 MobileNetV2. Evaluation of the fusion weights on a separate lesion-disjoint test set is planned as future work.

Changes in the Manuscript (Section 4.4, Table 2, page 6 of the revised manuscript): "*. . . Table 2 sets MobileNetV2 against the two fusion weightings we tried. . . .*"

Reviewer 1, Comment 5: *Comparison with published ISIC 2019 results is needed.*

Response: We thank the reviewer for this suggestion. Published ISIC 2019 studies address the full eight-class task, mostly with balanced accuracy and with their own data splits, while this study focuses on a three-class subset. To keep every comparison like-for-like, the revised manuscript states the task scope explicitly and presents a controlled comparison of model and compression variants under one common protocol, in which every number is directly comparable.

Changes in the Manuscript (Abstract, page 1 of the revised manuscript): "*. . . The study focuses on a reproducible comparison of full-precision, quantized, and pruned models, together with a Grad-CAM explainability assessment. . . .*"

Reviewer 1, Comment 6: *The conclusion should discuss the small 1.24-point gain.*

Response: We thank the reviewer for this comment. Based on the verified predictions, the equal-weight fusion improves on MobileNetV2 by 0.40 points (10 additional correct images; McNemar $p = 0.174$), and the 0.4/0.6 configuration reaches 90.76%. The Discussion and Conclusion now discuss this gain and explain why the Full INT8 MobileNetV2, which combines high accuracy with a 2.94 MiB model and 13.92 ms on-device latency, is selected as the deployment model.

Fusion analysis on the 2,489 validation images

Configuration	Accuracy	Macro F1	Melanoma recall
MobileNetV2 FP32	90.96%	91.27%	87.06%
DINOv2 FP32	86.66%	86.82%	79.09%
Fusion ($w_M = 0.5$, $w_D = 0.5$)	91.36%	91.67%	87.39%
Fusion ($w_M = 0.4$, $w_D = 0.6$)	90.76%	91.01%	85.18%

Changes in the Manuscript (Section 5, page 8 of the revised manuscript): "... *On a Raspberry Pi 4 it ran at 71.8 FPS, which confirms Full INT8 MobileNetV2 as a practical edge model.* ..."

Reviewer 2


Reviewer 2, Comment 1: *Only three classes are used; the selection should be justified.*

Response: We thank the reviewer for this suggestion. The three classes were chosen because they cover a malignant melanocytic lesion (Melanoma), its most common benign look-alike (Nevus), and the most common non-melanocytic skin cancer (BCC). This isolates the clinically most consequential Melanoma–Nevus confusion and keeps the class distribution comparatively balanced. The limitations of this choice are stated in the Discussion.

Changes in the Manuscript (Section 3.1, page 3 of the revised manuscript): "... *They cover a malignant melanocytic lesion, its most common benign look-alike, and the most common non-melanocytic skin cancer, which isolates the clinically most consequential Melanoma–Nevus confusion.* ..."

Reviewer 2, Comment 2: *Per-class recall, especially for melanoma, should be reported.*

Response: We thank the reviewer for this suggestion. Table 5 (page 8) reports per-class precision, recall, and F1 for MobileNetV2 (Melanoma recall 87.06%), Table 3 (page 7) reports Melanoma recall for every model variant, and the confusion matrix in Fig. 4 (page 8) shows that the main error is Melanoma predicted as Nevus (78 images).



Confusion matrix of MobileNetV2 FP32 (Figure 4, page 8, of the revised manuscript).

Class-level performance of MobileNetV2 FP32

Class	Support	Precision	Recall	F1-score
BCC	665	93.04%	96.54%	94.76%
Melanoma	904	89.03%	87.06%	88.03%
Nevus	920	91.26%	90.76%	91.01%
Macro average	2,489	91.11%	91.45%	91.27%

Changes in the Manuscript (Section 4.7, Figure 4, Table 5, page 8 of the revised manuscript): "*. . . BCC achieved the highest recall, while Melanoma achieved the lowest. . . .*"

Reviewer 2, Comment 3: *Class balance should be described.*

Response: We thank the reviewer for this suggestion. The dataset contains 3,323 BCC, 4,522 Melanoma, and 4,600 Nevus images; the stratified split gives 2,658 / 3,618 / 3,680 training and 665 / 904 / 920 validation images. The classes are therefore close to balanced (largest-to-smallest ratio 1.38), and the stratified split preserves these proportions in both partitions.

Class distribution

Class	Total	Training (80%)	Validation (20%)
BCC	3,323	2,658	665
Melanoma	4,522	3,618	904
Nevus	4,600	3,680	920
Total	**12,445**	**9,956**	**2,489**

Changes in the Manuscript (Section 3.1, page 3 of the revised manuscript): "*. . . With 3,323 BCC, 4,522 Melanoma, and 4,600 Nevus images, the largest class is only 1.38 times the smallest, so the subset is close to balanced. . . .*"

Reviewer 2, Comment 4: *Lesion-level splitting should be confirmed.*

Response: We thank the reviewer for this important point. A lesion-ID audit was carried out and is now reported in Section 3.2 (page 4): the split is image-level, and 54.04% of validation images belong to lesions present in training (BCC 85.11%, Melanoma 79.31%, Nevus 6.74%). The manuscript reports this transparently, gives results on the non-overlapping subset, and a lesion-grouped split has been prepared for retraining in future work.

Share of validation images whose lesion also appears in training

Class	Validation images with lesion overlap
BCC	85.11%
Melanoma	79.31%
Nevus	6.74%
All classes	**54.04%**

Changes in the Manuscript (Section 3.2, page 4 of the revised manuscript): "... *Of the validation images, 1,345 (54.04%) belonged to lesions also represented in the training partition.* ..."

Reviewer 2, Comment 5: *Statistical significance should be tested.*

Response: We thank the reviewer for this suggestion. An exact two-sided McNemar test now compares MobileNetV2 with the equal-weight fusion on the same 2,489 images: the fusion corrected 27 MobileNetV2 errors and changed 17 correct predictions ($p = 0.174$), and it raised recall in every class. The manuscript reports this test together with the per-class gains, and confidence intervals on a lesion-disjoint test set are planned as future work.

Paired outcomes of MobileNetV2 and the equal-weight fusion (McNemar)

	Fusion correct	Fusion wrong
MobileNetV2 correct	2,247	17
MobileNetV2 wrong	27	198

Exact two-sided McNemar test on the discordant pairs (27 vs. 17): $p = 0.174$.

Changes in the Manuscript (Section 4.4, page 6 of the revised manuscript): "... *Equal-weight fusion corrected 27 MobileNetV2 errors and introduced 17 new ones, a net gain of 10 images, and raised recall in every class (BCC* +0.30*, Melanoma* +0.33*, Nevus* +0.54 *percentage points).* ..."

Reviewer 2, Comment 6: *Limitations of using a three-class subset of ISIC 2019 should be stated.*

Response: We thank the reviewer for this suggestion. The Discussion now describes the scope of the study clearly: three of the eight ISIC 2019 categories, 1,886 images without lesion IDs, and external multi-centre validation as a direction for future work. The results are accordingly presented as a comparative study of model and compression variants.

Changes in the Manuscript (Section 7, page 9 of the revised manuscript): "... *This work presented a comparative study of MobileNetV2 and DINOv2 for three-class skin lesion classification.* ..."

Reviewer 3

Reviewer 3, Comment 1: *DINOv2 deployment on edge devices should be discussed.*

Response: We thank the reviewer for this suggestion. DINOv2 FP32 requires 330.34 MiB and 235–373 ms per image on the development CPU. Native dynamic INT8 reduces it to 87.38 MiB and 173.54 ms, with accuracy of 61.59%. Layer-wise diagnostics trace this to activation outliers in Blocks 8–11, a known challenge for transformer quantization, and quantization-aware training or distillation to a smaller ViT is identified as the route to edge deployment.


DINOv2 deployment characteristics

Variant	Disk	Latency (dev. CPU)	Accuracy	Melanoma recall
DINOv2 FP32	330.34 MiB	235–373 ms	86.66%	79.09%
DINOv2 dynamic INT8	87.38 MiB	173.54 ms	61.59%	49.67%
MobileNetV2 Full INT8 (reference)	2.94 MiB	4.51 ms	90.72%	86.73%

Changes in the Manuscript (Section 4.5, page 7 of the revised manuscript): "... *Layer-wise diagnostics identified extreme activation outliers in transformer Blocks 8–11, a known obstacle to post-training transformer quantization, with magnitudes up to approximately 494.72 compared with upper-percentile values near 1.3–2.7 in the corresponding diagnostic summaries. ...*"

Reviewer 3, Comment 2: *Grad-CAM visualisations would help.*

Response: We thank the reviewer for this suggestion. A new Grad-CAM section and figure show MobileNetV2 heatmaps for one correctly classified image of each class and for a Melanoma image predicted as Nevus. In the correct cases the activation is concentrated on the lesion; in the misclassified case the model also attends to the lesion, indicating that the error arises from interpreting the lesion rather than from attention to irrelevant regions.




Grad-CAM heatmaps of MobileNetV2 (Figure 5, page 9, of the revised manuscript): (a)–(c) correct BCC, Melanoma, and Nevus; (d) Melanoma predicted as Nevus.

Changes in the Manuscript (Section 6, Figure 5, page 9 of the revised manuscript): "... *In the failure case, the model also attends to the lesion but still predicts Nevus, which indicates that the error arises from how the lesion is interpreted rather than from attention to irrelevant regions. ...*"

Reviewer 3, Comment 3: *Training settings should be reported.*

Response: We thank the reviewer for this suggestion. The training settings are reported in the methodology: input size (224×224), normalization for each model, the augmentations used (rotation, zoom, translation), ImageNet and self-supervised pretraining, the classification heads, and 50 training epochs for both models, with the epoch-wise curves in Fig. 3. Owing to the ten-page limit, they are given in the text rather than in a separate table.



Training and validation curves of MobileNetV2 (a, b) and DINOv2 (c, d) over 50 epochs (Figure 3, page 6, of the revised manuscript).

Changes in the Manuscript (Section 3.3, page 4 of the revised manuscript): "... *MobileNetV2 was trained with rotation, zoom, and translation augmentation. ...*"

Reviewer 3, Comment 4: *Fairness across skin tones should be discussed.*

Response: We thank the reviewer for raising this important point. ISIC 2019 does not include Fitzpatrick skin-type labels, and a reliable subgroup analysis requires a dataset with annotated skin types. The manuscript discusses this explicitly, and a skin-tone fairness evaluation on such a dataset is included in the planned future work.

Changes in the Manuscript (Section 7, page 9 of the revised manuscript): "... *Further work should include paired statistical tests, confidence intervals, power measurements and testing on additional edge devices, attention rollout for DINOv2, skin-tone fairness analysis, calibration, and comparison with external datasets. ...*"

Reviewer 3, Comment 5: *Recent edge-oriented skin lesion classifiers should be cited.*

Response: We thank the reviewer for this suggestion. The revised manuscript now cites the efficient-model and compression literature on which the edge results build: MobileNet and MobileNetV2, integer-only quantization, post-training quantization, magnitude pruning, and transformer quantization. Because the edge claim rests on direct on-device measurements, the work is positioned against these methods rather than against systems evaluated on different devices, datasets, and class sets.

Changes in the Manuscript (Section 4.5, page 7 of the revised manuscript): "... *Layer-wise diagnostics identified extreme activation outliers in transformer Blocks 8–11, a known obstacle to post-training transformer quantization, with magnitudes up to approximately 494.72 compared with upper-percentile values near 1.3–2.7 in the corresponding diagnostic summaries. ...*"

Reviewer 3, Comment 6: *Future work could include all ISIC classes.*

Response: We thank the reviewer for this suggestion. Future work now includes extending the study to all eight ISIC 2019 categories, together with lesion-disjoint retraining, quantization-aware training, and ViT-S distillation.

Changes in the Manuscript (Section 7, page 9 of the revised manuscript): "... *Extending the study to all eight ISIC 2019 categories, quantization-aware training, ViT-S distillation, out-of-distribution rejection, and imbalance-aware losses may improve the reliability of a future deployment-oriented system.* ..."

Editorial requirements

- **Figures:** all figures were produced by the authors for this manuscript from their own experiments.
- **References:** seven references were added (quantization, pruning, Grad-CAM, TensorFlow, transformer activation outliers), four previously uncited references are now cited, and the list is numbered in order of citation.

Sincerely,
Darapureddi Chetan Kumar and Jinka Venkata Aravind