

pds

Proportionally Dense Subgraphs - Overview

pds is a library written in *Python* for computing and showing proportionally dense subgraphs (PDSs) of maximum size in graphs. Alternatively, the library can be used to generate random cubic graphs and k -regular bipartite graphs. Specifically, cubic graphs, k -regular bipartite graphs, and trees can be drawn along with their PDSs. This library can be imported as a module in any *Python* project by using `import pds`.

Bazgan et al. defined "a proportionally dense subgraph (PDS) as an induced subgraph of a graph with the property that each vertex in the PDS is adjacent to proportionally as many vertices in the subgraph as in the graph" (source: <https://arxiv.org/abs/1903.06579>).

The project also contains a non-exhaustive list of *use cases* that show possible usage of the library. In addition, some use cases were used to test conjectures about PDSs in cubic graphs and k -regular bipartite graphs. The use cases are described in the section *Usage and Details* (see below).

Installation

On Debian-based Linux

In a **bash** terminal, type:

```
sudo apt update
sudo apt install python3-pip
git clone https://github.com/d-m-3/pds.git
pip install -r requirements.txt
```

On MacOS

1. Check that Python 3 is installed. In a terminal, type:

```
python3 --version
```

2. Download **pip**. In a terminal, type:

```
curl https://bootstrap.pypa.io/get-pip.py -o get-pip.py
```

3. Install **pip**. In a terminal, type:

```
python3 get-pip.py
```

4. Install the modules `networkx` and `matplotlib` with `pip`. In a terminal, type:

```
pip install networkx
pip install matplotlib
```

5. Get the files of the project. Two options:

- a) With `git clone`. In a terminal, type: `git clone https://github.com/d-m-3/pds.git`
- b) Or click on *Code - Download ZIP* on the project's GitHub page: <https://github.com/d-m-3/pds>

On Windows

1. To install `pip`, follow the `pip` documentation here: <https://pip.pypa.io/en/stable/installation/>
2. Install the modules `networkx` and `matplotlib` with `pip`. In a terminal, type:

```
pip install networkx
pip install matplotlib
```

3. Get the files of the project. Two options:

- a) With `git clone`. In a terminal, type: `git clone https://github.com/d-m-3/pds.git`
- b) Or click on *Code - Download ZIP* on the project's GitHub page: <https://github.com/d-m-3/pds>

Usage and Details

- `pds.py` is the main library for finding PDSs, drawing graphs along with their PDSs, and generating random cubic and k -regular bipartite graphs. It can be imported as a module in your project (see *External Usage* below).
- `pds_tests.py` contains the unit tests for all the functions in `pds.py`, except for the functions that draw and/or save graphs.
- `usecase_draw_1_pds.py`
Goal: Draw a cubic graph or a k -regular bipartite graph and show one PDS of maximum size.
Execution and details: It creates a random cubic graph or a k -regular bipartite graph on a given number of vertices. It finds a PDS of maximum size, draws the graph, and colors the vertices of the PDS in red. Alternatively, it can create and draw a random k -regular bipartite graph instead of a cubic graph. In that case, a specific layout for bipartite graphs can be used.
- `usecase_draw_all_pds.py`
Goal: Draw all the possible PDSs of maximum size for a given cubic graph or k -regular bipartite graph.
Execution and details: It creates a random cubic graph on a given number of vertices. It finds all its PDSs of maximum size and draws all the different PDSs on different figures (vertices belonging to a PDS are colored in red). Alternatively, it can create a random k -regular bipartite graph instead of a cubic graph. In that case, a specific layout for bipartite graphs can be used.
- `usecase_exceptions_cubic.py`
Goal: Search for cubic graphs on $|V|$ vertices with $|V| > 8$, that admit no PDS of maximum size.
Execution and details: It creates random cubic graphs and tests if they do not have a PDS of maximum size. If such a graph with no PDS of maximum size is found, it is drawn, saved as a .png

figure and as an edge list that can be imported later, and the program's execution is stopped. The number of vertices in a graph and the number of created and tested graphs can be defined. If the boolean "only_nh" is set to "True", only cubic graphs that do not have a Hamiltonian cycle are considered (please notice that it takes much longer).

- [usecase_exceptions_k_regular_bipartite.py](#)

Goal: Search for k -regular bipartite graphs on $|V|$ vertices with $|V| > 8$, that admit no PDS of maximum size.

Execution and details: It creates random k -regular bipartite graphs and tests if they do not have a PDS of maximum size. If such a graph with no PDS of maximum size is found, it is drawn and the program's execution is stopped. The number of vertices in a graph, the value of k , and the number of created and tested graphs can be defined.

- [usecase_every_v_in_pds.py](#)

Goal: Test the following conjecture computationally "For any cubic graph $G = (V, E)$ with $|V| > 8$, every vertex is part of at least one PDS of maximum size".

Execution and details: It creates random cubic graphs and tests if, for every graph, every vertex is part of at least one PDS of maximum size. If the program finds a graph in which some vertices are not part of any PDS, the graph is drawn, the vertices not belonging to any PDS are displayed, and the program's execution is stopped. The number of vertices in a graph and the number of created and tested graphs can be defined. If the boolean "only_nh" is set to "True", only cubic graphs that do not have a Hamiltonian cycle are considered (please notice that it takes much longer).

- [usecase_every_v_ds2.py](#)

Goal: Test the following conjecture computationally "Every cubic graph $G = (V, E)$ with $|V| > 8$, has at least one PDS $G[S]$ of maximum size, where $d_S(u) = 2$ for every vertex u in S ". This conjecture was proven to be wrong by the finding of counterexamples.

Execution and details: It creates random cubic graphs and tests if, for every graph, there exists a PDS of maximum size and $d_S(v) = 2$ for every vertex v . If there is no such PDS for a graph, the graph and all the PDSs of maximum size are drawn, and the program's execution is stopped. The number of vertices in a graph and the number of created and tested graphs can be defined. If the boolean "only_nh" is set to "True", only cubic graphs that do not have a Hamiltonian cycle are considered (please notice that it takes much longer).

- [usecase_every_v_ds2_ds3.py](#)

Goal: Test the following conjecture computationally "Every cubic graph $G = (V, E)$ with $|V| > 8$, has at least one PDS $G[S]$ of maximum size, where $d_S(u) = d_S(v) = 3$ for at most two vertices u, v in S ".

Execution and details: It creates random cubic graphs and tests if, for every graph, there exists a PDS of maximum size and $d_S(v) = 2$ for every vertex v , except for at most [ds3_nb](#) vertices, where $d_S(v) = 3$. If there is no such PDS for a graph, the graph and all the PDSs of maximum size are drawn, and the program's execution is stopped. The number of vertices in a graph and the number of created and tested graphs can be defined. If the boolean "only_nh" is set to "True", only cubic graphs that do not have a Hamiltonian cycle are considered (please notice that it takes much longer).

- [usecase_create_nham_graph.py](#)

Goal: Generate, display and save random non-Hamiltonian cubic graphs on a given number of vertices.

Execution and details: It creates a random non-Hamiltonian cubic graph on a given number of vertices, saves it in the given folder, with the number of vertices at the end of the filename. It also saves the figure in .png format in the same directory.

- `usecase_tree.py`
Goal: Create a random tree of maximum degree 3, find and draw a PDS of maximum size.
- `usecase_caterpillar.py`
Goal: Create a random caterpillar of maximum degree 3, find and draw a PDS of maximum size.
- `usecase_tree_without_max_pds.py`
Goal: Return a tree that does not admit a PDS of maximum size.
- `usecase_binomial.py`
Goal: Create an Erdős-Rényi graph, also known as a binomial graph, of maximum degree 3 and tries to find and draw a PDS of maximum size.
- `gex.py`
Contains specific graphs used for unit tests and exceptions of cubic graphs on eight vertices, i.e., cubic graphs that do not have a PDS of maximum size.

External Usage

You can import the `pds` library into any *Python* project:

```
import pds
```