



University of Innsbruck

Institute of Computer Science
Intelligent and Interactive Systems

Robot Simulation and Motion Planning

Martin Griesser

B.Sc. Thesis

Supervisor: Emre Ugur, PhD
Univ.-Prof. Dr. Justus Piater, PhD
27th August 2014

Abstract

This document explains how to write IIS theses using the \LaTeX 2 $_{\epsilon}$ ‘iisthesis’ class¹, which is itself based on the \LaTeX 2 $_{\epsilon}$ ‘book’ class and is intended for compiling with `pdflatex`. This document does not tell you how to structure your thesis.

¹version 00.06 , released on 2013/06/13.

Acknowledgements

Thank you to the friendly members of the IIS Team.

Contents

Abstract	i
Acknowledgements	iii
Contents	v
List of Figures	vii
List of Tables	ix
Declaration	xi
1 Introduction	1
1.1 IIS-Lab Robot Setup	1
1.2 The Robot Operating System(ROS)	2
1.3 Project Targets	3
2 Robot simulation	5
2.1 Choosing a suitable simulation platform	5
2.2 The Virtual Robot Experimentation Platform(V-Rep)	6
2.3 Dynamic simulations in V-REP	7
2.4 Designing the simulation scene	8
2.4.1 Modelling the Schunk SDH gripper	8
2.4.2 Putting the pieces together	9
2.4.3 Configuring the collision detection module	10
2.4.4 Configuring the IK calculation module	11
2.5 Implementation of the ROS control interface	11
2.5.1 Overview	11
2.5.2 Plugin Architecture	12
2.5.3 Identifying simulation components in the scene	14
2.5.4 Creating startup launch file	14
2.5.5 Documentation and usage examples	15
3 Pick and place	17
3.1 Overview	17
3.2 Pick and place tasks in MoveIt	19
3.3 Implementation of the benchmark task	20
3.3.1 Creating the environment	21
3.3.2 Generating possible grasps	21
3.3.3 Planning and executing the pickup	22

3.3.4	Planning and executing the placement	22
3.4	Executing the benchmark task	23
3.5	Observations	24
Bibliography		25

List of Figures

1.1	Current setup in the IIS-Lab TODO: provide more recent image	2
3.1	Stages of the pickup phase in the simulator	18
3.2	Stages of the placement phase in the simulator	19
3.3	Planning scene after inserting the collision objects	21
3.4	Grasp poses, gripper approach and retreat	22
3.5	Place locations, pre-place approach and post-place retreat	23

List of Tables

Declaration

By my own signature I declare that I produced this work as the sole author, working independently, and that I did not use any sources and aids other than those referenced in the text. All passages borrowed from external sources, verbatim or by content, are explicitly identified as such.

Signed: Date:

Chapter 1

Introduction

Operating a robot and developing high level control code for it is a cumbersome task. Very often various groups of developers are working simultaneously on different parts of the software. But in most cases there is only one device that can be used for testing and so only one can run his/her code at a time. The others have to wait until they get access to the robot. Moreover, tests on real robots always come with a high level of risk. Incorrect algorithms can lead very fast to damages on robot components or their environment and entail costly repairs. In the worst case even people can get hurt by uncontrolled robot motions.

The solution to those problems is the usage of a simulator that mimics the robot components and their behavior as accurate as possible. It has to provide the same control interface so that each part of the software can get tested on the simulator before it gets utilized on the real robot. Those considerations motivated the first part of this thesis – the realistic replication of the IIS-Lab robot setup on a suitable simulation platform. This involves the creation of an exact model of the robot setup, containing the various robot components and their environment. The necessary steps are explained in Chapter 2.

The second part of the thesis is about motion planning. Moving the robot hand cannot follow any arbitrary trajectory towards a target pose. During that motion it might collide with itself or any other obstacle within its environment. That means those trajectories have to be planned carefully to avoid accidental collisions and to generate smooth and well controlled robot motions. This also involves to create and maintain an internal representation of the robot and its environment, a step that is common to the simulation part of the thesis. Chapter 3 shows the configuration and integration of the motion planning framework MoveIt into the IIS-Lab robot setup along with some usage examples.

Chapter 4 focuses on MoveIt’s grasping functionality. It shows, how a reference ‘Pick and Place’ task can be planned with the planning tools and executed on the simulator and the real robot as well.

In Chapter 5, some test results will be presented, analyzing the quality of the various planning algorithms and approaches.

1.1 IIS-Lab Robot Setup

The robot setting, that was considered in this thesis can be seen in Figure 1.1 The main part of the robot setup in the IIS-Lab consists of an aluminium torso with two mounted KUKA light weight robot arms. Those arms have 7 degrees of freedom (DOF) each one can carry up to 7kg of payload. Additionally a Schunk SDH gripper can be mounted on each arm.

- **KUKA LWR 4+ arm**




Figure 1.1: Current setup in the IIS-Lab TODO: provide more recent image

Description of the arm(7 DOF, max. 7kg payload, 16kg weight, very flexible,...

- **Schunk SDH gripper**

Description of the gripper(3-finger-gripper, different grasp types, as powerful as human hand, very sensitive)

- **Kinect camera**

Description of Kinect(RGB camera, Depth sensor, 3d data under any light conditions)

1.2 The Robot Operating System(ROS)

As the control of the robot components is based on ROS, a brief introduction shall be given here. As stated in Quigley et al. (2009), ROS is not an operating system in the classical sense. It can be seen as a communication layer, providing various mechanisms for inter process communication. A ROS system consists of a number of nodes. Each node is an independent computation unit and runs in it's own process, adding some clearly defined functionality to the overall system. For example one node can be responsible for planning, another one for perception or controlling the hardware. Nodes communicate with each other by passing messages, using the ROS communication infrastructure. Messages are strictly typed data structures that can be defined in a special message composition language. They can be composed of primitive types like Float, Integer or Strings and also of other message types. That makes it possible to define custom messages for each use case. Messages can be published to topics. A topic can be seen as some kind of address, consisting of a string. Topics can be organized in namespaces. If two instances provide the same interface, each one can be operated in it's own namespace. This is important, as for example the simulator should provide exactly the same interface as the real robot. Without namespaces it would not be possible to operate the simulator and the real robot in parallel. So Each node can publish and also subscribe to a number of topics. It is also possible

that more than one node publishes to the same topic. The organization of the nodes of a system can be visualized as a graph.

A node can also advertise a service. This is a special type of topic that allows a synchronized message exchange. In contrast to topics, a service with a given name can only be offered by one node. The service message is composed of a request and a response part. When a node sends a service request to another node it will block, until the advertising node has handled the request and delivers a response. The nodes that make up a ROS system can be located on different machines. One machine has to be the dedicated master that runs the roscore. Other machines can connect to the master via network. ROS also provides a centralized parameter server that can be used to store configuration data for the various nodes. A system usually consists of a large number of nodes that have to be configured and started. This can be done in launch files. Those are simple textfiles, holding startup information and configuration details for one or more nodes in an XML syntax. Using the roslaunch command, a set of nodes can be configured and launched at once. It is important to understand this terminology because especially the terms node, topic and message are heavily used throughout this thesis. A more detailed documentation can be found on the ROS website.

1.3 Project Targets

Both objectives

- **Simulation**

Realistic replication of the robot setup on a suitable simulation platform
Generation of realistic sensor data
Visualization of collisions
Implementation of a ROS interface, corresponding to that one of the real robot

- **Motion Planning**

Configuration and integration of a motion planning framework
Implementation of a benchmark pick and place task, executable on simulator and real robot
Provide an easy to use interface to the planner
Analyse the quality of the various planning algorithms

Chapter 2

Robot simulation

This chapter focuses on the simulation part of the thesis. The objective is the creation of a simulation model, particularly designed for the IIS lab robot setup. The model has to reflect the properties and behaviour of the contained robot components as good as possible. Certainly the simulated components have to provide the same control interface as their real counterparts, allowing to test and optimize control code on the simulator before utilizing it on the real robot. Preferably, the control code sees no difference about on which instance it is executed. The recommendations on such a solution can be summarized as follows:

- The simulator needs to be able to generate realistic sensor and feedback data that can be used by the control software. This includes forces and torques that are measured within force sensors, the current state of the various robot joints (position, velocity, effort), but also RGB and depth images, usually produced by Kinect cameras and vision sensors.
- The simulation solution has to provide exactly the same ROS control interface as the real robot. This interface essentially consists of a number of ROS topics, that can be used to send control commands to the various different robot components or to read actual joint states and sensor data.
- The utilized simulation platform has to provide a graphical user interface that allows to visualize the motions of the robot and it's interaction with the environment. Possibly accidental collisions of robot parts have to be registered and should also be visualized.
- In order to be used by as many people as possible, it is very important that the solution is really easy to use and does not require a long lead time. Therefore it has to be put particular focus on usability.

The following sections explain in detail, how this goal was reached. At the beginning stands the process of finding a suitable simulation platform that meets the requirements and the considered criteria. After that, the chosen simulation platform V-Rep is introduced and an overview about how to design dynamic simulations is given, explaining some of the necessary terminology. Subsequent sections focus on the necessary steps to achieve the final solution, namely finding and modelling required robot components, assembling and configuring the final simulation scene and the implementation of the ROS control interface.

2.1 Choosing a suitable simulation platform

The tasks executed on the robot are in most cases variations of so called 'pick and place' tasks. An object gets picked up, lifted and placed somewhere else within the robot's workspace.

Therefore joint target positions are sent to the control interfaces of the various robot components and they execute the commanded motions if possible. The question, if the execution is possible at all and in that case in which velocity, is influenced by a number of dynamic parameters. The maximum effort of the motors in the joints is limited. If the force that acts upon a joint is higher than the maximum effort of the motor it will not be able to maintain its current position or to reach the desired target position. This can happen if the picked object is too heavy or if the robot collides with an immovable object in its environment. The forces that act upon each single joint are influenced by a number of parameters like the position within the kinematic chain of the robot, the summed own weight of the robot components and also the weight of a possibly additional payload.

The required solution should be able to provide a realistic simulation of those dynamic interactions. Therefore the utilized simulation platform has to take use of a powerful physics engine. A physics engine is a software component, that is capable of computing parameters of physical processes and the dynamic properties of the involved objects. Examples for such engines are the Open Dynamics Engine¹ (ODE) and Bullet physics². Some of the evaluated simulation platforms even provide a number of different physics engines to choose.

The candidates that have been taken into account were Gazebo³, V-Rep⁴, MORSE⁵ and Openrave⁶. After some investigation only two of them (Gazebo and V-Rep) had been evaluated in greater detail. Criteria for the selection had been:

- Which physics engine is used respectively is it possible to choose among various engines?
- Usability and stability
- Expandability
- Availability of required model components (arm model, gripper,...)
- Quality of the documentation
- Licence issues

Taking into account those criteria it went clear that V-Rep will be the simulation platform of choice. In some initial tests V-Rep seemed to be much more stable than Gazebo and the user interface is very intuitive. Another important point is that V-Rep ships with a fully functional model of the KUKA LWR4+ robot arm.

2.2 The Virtual Robot Experimentation Platform(V-Rep)

V-Rep is a powerful robot simulation platform, developed by Coppelia Robotics. The current version (V3.1.2) provides the ability to choose from three configurable physics engines (ODE, Bullet, Vortex – only trial version) for simulating dynamic processes. It also contains a very comfortable editor for modelling robot components and simulation scenes. In the *shape edit mode* it is possible to edit and simplify meshes. This is very important because for simulating dynamic processes only simple shapes with a low amount of vertices, edges and faces should be

¹<http://www.ode.org>

²<http://bulletphysics.org>

³<http://gazebo.org/>

⁴<http://coppeliarobotics.com>

⁵<http://www.openrobots.org/wiki/morse/>

⁶<http://openrave.org>

used to reduce complexity. The contained model browser provides a rich set of different robot models, static objects and various sensors, ready to use. A powerful feature are V-Rep's so called *calculation modules*. They can be configured to provide additional calculation functionalities on groups of scene objects. The *collision detection module* is capable of detecting and visualizing all kinds of collisions within the simulation scene. The *inverse kinematics calculation module* allows to solve inverse kinematics problems for robot components. The behaviour of the simulator is highly customizable via a rich programming API for C++ as well as the scripting language LUA⁷. V-Rep is no open source software but it provides a free licence for educational units and can therefore be used for research purposes. A more detailed introduction to V-Rep can be found in Freese et al..

2.3 Dynamic simulations in V-REP

For a better understanding of the modelling process it is necessary to explain a few fundamental concepts about designing dynamic simulations in V-Rep. This section just covers those aspects that are important for the underlying project. A more detailed explanation can be found in the official V-Rep documentation⁸.

Each simulation scene in V-Rep is composed from a number of models that are arranged within the environment. A model consists of various scene object, combined in a tree like structure to mimic the kinematic chain of a robot component. Each model has a dedicated model base and constitutes a sub-tree of the scene hierarchy. The model base is the root element of the model tree. There are existing various types of scene objects within V-Rep, but only those, which are important for the implementation will be explained here.

- **Shape**

A shape is a 3 dimensional body. Shapes represent the visual parts as well as the dynamically enabled parts of the scene. It is necessary to distinguish between primitive shapes (Cylinder, Cuboid, Sphere, Plane and Disk) and complex shapes (triangle meshes). Primitive shapes are much easier to handle for the physics engine as there can happen a lot of optimization during dynamics calculations. Complex shapes usually look better and therefore they are used mainly as the visual part of the model but also by the collision detection module. Various shapes can be combined to groups and therefore treated as one single object. Shapes can be defined as *static* or *non-static* objects. The position of a static object is fixed relative to it's parent node within the scene hierarchy and will not change during simulation. Non-static objects underlie gravity and will fall down if they are not constrained by a dynamically enabled joint or a force sensor connection. It is also necessary to distinguish between *respondable* and *non-respondable* shapes. Respondable shapes have a clearly defined mass and moment of inertia and therefore they create collision reactions when colliding with other respondable objects during simulation. Only respondable shapes are considered during dynamics calculation. Usually a model in V-Rep is composed of a visual part, consisting of complex shapes and a hidden part, consisting of groups of primitive shapes that are configured to be used for the dynamics calculations. This issue will be covered again when explaining the creation of the hand model.

- **Joint**

A joint is a flexible connection between two rigid parts of a robot. It has to be distinguished

⁷<http://www.lua.org>

⁸<http://www.coppeliarobotics/helpFiles>

between revolute or prismatic joints with one degree of freedom and spherical joints with three degrees of freedom. In the arm and hand model only revolute joints are used. Joints can be passive or actuated by a motor. The motor settings include maximum force or torque and velocity limits. If the control loop is enabled then a desired target position for the joint can be set. The controller will then try to reach this position, based on its PID settings while respecting the motor limits. It would also be possible to program a custom control loop for each joint but for the current project this is not necessary. Joints can be operated in various different modes. A joint in *torque/force mode* is simulated, using the physics engine. This is the most realistic control mode. A joint in *inverse kinematics mode* is controlled by the inverse kinematics calculation module and if additionally the option *hybrid operation* is selected then the dynamic parameters of the joint are also taken into account. Operating a joint in *dependent mode* means that its position depends on the position of another joint within the scene. How this dependency looks like can be configured by setting a *dependency equation*.

- **Vision sensor**

States a simulated image capturing device. A vision sensor can capture images of the simulation scene, depending on its configuration. It can deliver RGB image sequences as well as depth images. Vision sensors are used in the Kinect camera model.

- **Force sensor**

A force sensor in V-Rep is a rigid connection between two dynamically simulated objects. The calculated forces and torques can be measured and visualized. It is also possible to define a maximum force the connection is able to bear. When this maximum value is exceeded, the connection will break.

- **Dummy**

Dummies are the simplest scene objects at all but they provide some important functionality, especially for the various calculation modules of V-Rep. They can be understood as the origin of a named reference frame with a configurable position and orientation within the simulation scene. Two dummies can be linked as *tip-target pairs* to be used by the IK calculation module. The importance becomes more clear when the construction of the simulation scene will be explained, particularly when configuring the inverse kinematics calculation module.

Groups of scene objects can be organized in collections and treated as one single entity. Collections play an important role in the collision detection module.

2.4 Designing the simulation scene

This section explains in detail the structure of the simulation scene and the contained model components. Three types of robot models are used - the KUKA LWR3+ model, the Schunk SDH gripper model and the Kinect camera model. The arm and camera model are part of the V-Rep model browser but the gripper model had to be constructed from scratch.

2.4.1 Modelling the Schunk SDH gripper

The gripper has three fingers. One of them is fixed around the z-axis and cannot be rotated. Two fingers can be rotated 90° around the z-axis, but they are connected contrariwise. That means if one finger rotates to the left, the other one is rotated to the right for the same distance. The modelling process started with the search for suitable meshes for the rigid parts of the

gripper. They have been found in the `schunk_description` ROS package from the `schunk_sdh` stack. Those meshes have been arranged according to the technical description. After placing the meshes the 8 joints have been added at the correct locations. It was important to determine the correct location and orientation for each single joint within the model to allow the correct movement of the fingers. This was achieved by using the shape edit mode and select the circle shaped area within the mesh, where the joint had to fit. From that selection a cylinder shape was extracted and the joint was then centered within this newly created cylinder. Those steps had to be repeated for all 8 joints. The placement process can be seen in Fig???. After placing all the joints and links within the scene, the model tree was adjusted to form the kinematic chain of the hand. The dynamic parameters of the joints were set according to the technical description. Those parameters include the joint limits, maximum velocity and maximum effort. As the root joints of the 2 fingers are connected, the setting of the second finger root is configured slightly different. The joint is operated in the 'dependent mode' and the dependency equation just mirrors the position of the connected joint.

The meshes only form the visual part of the model as they are too complex to be used for dynamics calculations. So the shape of each link had to be approximated by groups of pure shapes. This has been achieved by executing the following steps for each single part of the model:

- within the shape edit mode extract parts of the mesh that could be approximated by a primitive shape (cuboid, cylinder), by selecting suitable groups of vertices - extract the corresponding shape by using this V-Rep editor functionality - repeat those steps until the most important parts of the link are approximated that way - group those primitive shapes to treat them as one single object - adjust the dynamic parameters (mass, material settings, inertial matrix) - adjust the local responsible mask - give the group the same name as the corresponding mesh, but with the '_responsible' suffix - remove the extracted shapes from the current visibility layer because they are just used for the dynamics calculations

The extraction process is visualized in Fig???. Dynamic parameters like mass and inertial matrix have been provided by Alex Rietzler. The predefined 'highFrictionMaterial' setting was used for each single part of the finger because that showed better results when picking up objects later on.

The last steps of the modelling process were the adjustment of the model hierarchy. The root element is the responsible part of the wrist which is also defined as the model base. It is important to follow the V-Rep guidelines for designing dynamic simulations because if the hierarchy is wrong, the model will simply fall apart when starting the simulation (see corresponding chapter in the documentation for more information). Each non-static and responsible shape has to be connected to its parent by a joint or a force sensor. The visual part of the link is always a child object of the corresponding responsible. That way, the kinematic chain of the gripper is formed.(TODO: insert images!!!)

2.4.2 Putting the pieces together

After finishing the modelling process of the gripper each necessary component was available to build up the simulation scene. Alex Rietzler had already created a mesh for the robot torso which was ready to use. The two robot arms were taken from the model browser and inserted into the scene. A dummy was placed at the bottom of each arm which will be used as the origin of the arms private reference frame. The exact translation of each arm was also already available so it had just to be configured. The grippers were placed on the tip of each arm. The correct rotation and offset was measured on the real counterpart and then configured accordingly.

The plate and the legs of the table are modelled as group of primitive cuboids in the correct

size. The table was defined as *responsible*, which means it will produce a collision reaction if a robot component collides with it. But as it is a static object it will not show a reaction to such a collision because its position is fixed within the scene. The chosen material setting is also the *'highFrictionMaterial'* but that can easily be changed by modifying the dynamic properties of the table plate.

The kinect camera model was also taken from the model browser. As its position and orientation in the real world is not fixed and might change from time to time, its position within the simulation scene is only an approximation to reflect the real world setting as good as possible. In the vision sensor settings, the option *'Ignore RGB info'* was selected. A vision sensor usually produces two images, namely a color image and a depth image on each simulation pass. This generation process slows down the simulation and therefore skipping one of the two images brings a speedup.

The origin of the overall reference frame is located on the upper left side of the table, indicated by a slightly green shimmering sphere. The position and orientation of the torso, the table and the two arms were configured relative to this reference frame. A dummy object called *'ref_frame_origin'* was placed at that location. Each position calculation later on will happen relative to that dummy. If it is necessary to move the origin to another location within the workspace this can simply be achieved by just moving that dummy to the required location.

2.4.3 Configuring the collision detection module

The solution should be able to detect and visualize possible accidental collisions of one of the robot components with their environment. It would also be good to have some kind of warning if one of the robot components comes dangerously close to an obstacle during a movement. Therefore a so called *'collision shield'* is modelled around the two robot arms, to detect if the arm comes closer than approximately 5cm to an obstacle. To achieve that functionality, for each single link another shape had to be modelled that is slightly larger than the corresponding link and that only purpose is to be checked for collisions. The modelling process started at the second link of each robot arm and on each link the following steps had to be performed:

- Copy the visible part of the robot link - Morph the copied object into a group of convex shapes (V-Rep editor functionality) - Ungroup the resulting shape and merge it into one single shape - Grow the resulting shape in x and y direction of its own reference frame to receive a mesh that is approximately 10cm larger than the original mesh but has the same height. - Adjust the outside color to make it green and nearly transparent - Rename the shape to the same name as the original shape, with the *'_col'* suffix - Make the new shape a sibling to the original one within the model tree - Define the new shape to be static and non-responsible. - Disable the *'collidable'* flag on the shape. This behaviour will be overridden in the collection settings later on when configuring the collision detection module

The modelling process is visualized in Fig???

Basically there are two different types of possible collisions:

- Soft collision - the collision shield hits another collidable object (no direct collision - only a collision warning) - Hard collision - a robot component directly hits another collidable object. This would also be a collision in real world.

The solution should be able to distinguish clearly between those two types of collisions. Therefore a number of so called collision objects have to be configured within V-Rep's collision detection module. Each collision objects checks for collisions between a collider against a colldee. Collider and colldee are single shapes or collections of shapes with the collidable flag set. For each arm two collision objects have to be set up - one for each collision type. The configuration is explained for the left arm but the steps for the right arm are similar. The first collision object

is named 'left_arm'. The collider is the collection called 'leftArm'. This collection contains the whole sub tree of the left arm, including the gripper, but excluding the elements of the left collision shield. The collidEE are all other collidable entities within the scene. This collision object detects the hard collisions. This also makes clear, why the collidable flag is disabled on the parts of the collision shield because otherwise collisions with the shield would also be detected which would not be correct. The second collision object is called 'left_armShield'. The collider is the collection called 'leftArmShield'. This collection is composed of the parts of the left collision shield and the whole subtree of the left gripper. This collection is defined to override the value of the collidable flag of the contained elements - this is important because as previously mentioned, the elements of the collision shield are defined as not collidable. The collidEE of the current collision object is the collection called 'exLeftArmShield'. This collection simply contains all other scene objects except those contained in the left arm's subtree. As mentioned before, the same configuration steps happened for the right arm. All collision objects are defined not to be handled explicitly. This means that V-Rep does not check for collisions automatically in each simulation pass. It has to be done manually and will be explained later on in the section about the control interface implementation.

2.4.4 Configuring the IK calculation module

The IK calculation module can be used to define different IK groups to solve the inverse kinematics for the required robot components. This functionality is used for the Cartesian positioning functionality of the ROS control interface. To define an IK group it is necessary to exactly define the kinematic chain of the robot component, starting at the base link up to the dedicated tip. The base link is the root element of the arm's model tree. The tip element is a dummy that is placed on the top end of the arm. That dummy must be a child element of the last link in the arm tree and it defines the reference frame that is used for Cartesian positioning. All the joints between the base and the tip, that are operated in IK mode will be taken into account by the IK calculation module. An additional dummy is used to define the target pose for IK calculation. Initially the pose of the target dummy is exactly the same as that from the tip dummy. When moving the target dummy to a new location, the IK calculation module tries to bring the tip dummy exactly to the same pose by setting the joint values of the manipulator accordingly, respecting the joint limits and the configured constraints and tolerances. More than one IK group can be defined for each manipulator. To improve performance three IK groups have been configured for each arm. The first one focuses on performance but the settings provide less stability. The second one is more or less the same configuration but with a little higher tolerance values. The third one is designed to increase stability especially for positions close to singularities. But that configuration is less performant and therefore it is only used if the other configurations have failed to find a solution. How those IK groups are used is explained in the ROS control interface section.

2.5 Implementation of the ROS control interface

2.5.1 Overview

After finishing the modelling process it was necessary to find a proper way to control the robot components via a ROS control interface. The arm as well as the hand is controlled via a set of inbound and outbound ROS topics that allow to send commands to the underlying component or to receive state data from the component(joint states, sensor data,...). Each simulated component should provide exactly the same interface as it's real counterpart.

One problem is how each type of component can be clearly identified within the current simulation scene. A scene is a hierarchy of various scene objects, organized in a tree structure. As already explained, those objects can be shapes, joints, sensors or even only dummies. The scene content can be modified by the user. Maybe a gripper gets replaced by another component, an arm gets removed or an additional Kinect camera gets installed. The required solution should be able to react to changes in the current scene. Parts of the model hierarchy should be clearly identifiable as a specific simulation component. Each single part of a component should be identifiable (joints, sensors, dummies, IK groups, collision objects). Luckily V-Rep provides various extension points for programmers and is therefore highly customizable.

After some investigation about the possibilities the decision was made to create a simulator plugin, using the V-Rep regular API. This approach states the most flexible solution as this API provides more than 400 functions. A plugin is a compiled library file, written in C++ that has to follow some V-Rep specific naming conventions and must reside in the V-Rep working directory. The library file gets automatically loaded on V-Rep startup and runs in the main simulation thread. This means that it has to be programmed really carefully to avoid performance leaks during simulation. The plugin has to provide a clearly defined interface, consisting of 3 functions:

- `v_RepStart` - called on startup and can handle some initialization
- `v_RepEnd` - called before shutdown and can do some cleanup
- `v_RepMessage` - called very often during the whole V-Rep lifecycle and is therefore a very performance critical method. Via this function V-Rep notifies the plugins about events like start/end of simulation, simulation step, scene content change, scene switch, The plugin code can react to those events accordingly.

2.5.2 Plugin Architecture

The plugin code is organized as can be seen in Fig???.

- **SimulationComponent** A simulation component is a single, reusable part of the robot that can be used in different environments. Each component provides it's own clearly defined control interface. A simulation scene can contain various types of components. The `SimulationComponent` class is the abstract base class for all simulation components. Currently there are existing two concrete implementations – the `LWRArmComponent` and the `SchunkHandComponent`. If the scenario should be extended and new components are introduced it is necessary to create a subclass of `SimulationComponent` and provide implementations for the abstract methods. Each `SimulationComponent` consists of two parts. The first one is a class that provides access to a concrete simulation component instance. The `LWRArm` class for example stands for a KUKA LWR4+ arm model in the scene. This class provides full access to the functionality of the underlying arm model.

The second part is a controller class for the component instance. This controller encapsulates the whole ROS interface to the simulation component and has to be a subclass of the abstract `ComponentController` class. On each simulation pass the controller publishes all the necessary state data to it's various topics and sends incoming commands to the simulation component. The names of the various provided topics are composed from the overall namespace, the defined unique name of the component and the actual topic name. For example the joint control topic of the right robot arm evaluates to `'/simulation/right_arm/joint_control/move'`

On simulation start each `SimulationComponent` registers it's `ComponentController` at the `ROSServer` and unregisters it on simulation end.

- **ComponentContainer** This class represents the set of all identified simulation components in the current simulation scene. On V-Rep startup an instance of `ComponentContainer` is created. Each time, the content of the current simulation scene changes, the method `'ComponentContainer::actualizeForSceneContent'` is triggered. This method performs the following steps: - It

validates each currently registered `SimulationComponent` instance if it is still valid and present in the scene. - It traverses the whole scene hierarchy to identify newly created components - If a new component is identified, a corresponding concrete instance of `SimulationComponent` is created and added to the container. To identify a component it has to be marked by using V-Rep's custom developer data functionality. Details are explained further on.

The `ComponentContainer` gets notified about each simulation step. It then simply forwards that message to all registered components. Those can then perform all necessary steps like triggering collision checking or the IK calculation module.

- `ROSServer` The `ROSServer` is a static class that encapsulates all ROS related functionality. It tries to initialize ROS on startup. If the connection to the master can be established it creates a ROS `NodeHandle` for the 'simulation' namespace. Otherwise it forces the plugin to unload, because it is not able to work without a running roscore. Each `SimulationComponent` registers its `ComponentController` instance at the `ROSServer`. On simulation start it initializes the registered controllers with the maintained `NodeHandle`. The `ROSServer` gets also notified about each simulation step and forces the controllers to handle the received commands and publish all the necessary data. On simulation end it forces the registered controllers to shutdown their publishers and subscribers.

- `ComponentController` This is the abstract base class for all controllers. A `ComponentController` gets initialized by the `ROSServer` on simulation start. Concrete implementations can use the provided `NodeHandle` to create all the necessary publishers and subscribers. The update method is called by the `ROSServer` on each simulation step and forces the controller to publish all the required data. On simulation end the shutdown method is called by the `ROSServer`, forcing the controller to shutdown all publishers and subscribers.

- `LWRArm` This class provides access to a correctly configured LWR arm model within the simulation scene. To fulfill the requirements for the control interface, the arm has to be able to operate in joint control mode and in inverse kinematics mode. Initially the arm starts in joint control mode. All the joints are switched to torque/force mode and accept target positions to be set. The simulated PID controllers will try to move the joints to their designated target positions.

Switching to IK mode means to operate all the joints in IK mode and use the previously configured IK calculation module. Setting a target pose in Cartesian space means to bring the IK target dummy into the required pose. The IK calculation module tries then to bring the linked IK tip dummy into the same pose by commanding the robot arm's joints accordingly and satisfying the configured constraints and precision settings. At the moment, three IK groups are configured for each arm with different settings to achieve performant and stable solutions. Those groups are sequentially called until one of them is successful. The configuration of the first group focuses on performance but provides less stability. The last group uses a configuration that is slower but provides more stability in positions closed to singularities. If none of the groups was successful it will result in an error message on the console, otherwise the arm will start or continue to move towards its target pose. When initializing the `LWRArmComponent`, it will search for IK groups that are named the same as the arm and with consecutive numbering (`left_arm`, `left_arm1`, `left_arm2`,...). That allows to reconfigure the IK calculation module and introduce additional IK groups without touching the plugin code. It is expected that at least one IK group is configured, otherwise an error message is written to the console.

The collision status of the arm is determined by using the configured collision detection module. On each simulation step the collision group that is responsible for detecting direct collisions is handled first. If that one detects a collision, a direct hit is reported and it is not necessary to handle the second group at all, because a direct hit always implies a hit with the shield as well. Only if no direct hit was detected, the second group is handled. The outcome

can be queried as the current collision state of the arm. During initialization it is searched for a collision group that has the same name as the arm, responsible for direct hit detection and a group that is named with the naming pattern [arm_nameShield], responsible for shield hit detection. If one or both of the required groups cannot be detected, an error message on the console will be stated and the collision detection functionality will not work as expected. Collision state is evaluated on each simulation time step.

Additional items that have to be identified within the model tree are the 7 joints, the end effector tip dummy, the IK target dummy and the force sensor on the last link of the arm. The origin of the reference frame can be defined by creating a dummy object within the scene with the special name 'ref_frame_origin'. If such a scene object is found, all Cartesian poses are taken with respect to the reference frame of that object, otherwise the poses are interpreted absolute within the world reference frame. All the necessary data that is published by the controller can be accessed via this class.

- LWRArmController The LWRArmController provides the implementation of the Kuki interface. This interface is created by Simon Hangl especially for the KUKA arms in the IIS Lab.

2.5.3 Identifying simulation components in the scene

As each scene is a hierarchy of various types of scene objects there had to be found a way how to identify subtrees within this hierarchy that belong to known simulation components and should therefore be handled by the plugin. One way would be to give each part a clearly defined, unique name and then search for those names within the scene. But then it would be necessary to hardcode the name of each single joint name and this is not a preferable solution for this problem. If somebody accidentally changes a name in the model tree then the solution is broken because the plugin loses connection to the underlying object and cannot control it any more. Here V-Rep's custom developer data functionality comes into play. It is possible to put auxiliary data segments to each single object in the scene. (TODO: show image of data segments) This data gets serialized together with the object and can be read programmatically. Each data segment starts with a header number which is used to uniquely identify the data from a specific developer. The second element is an integer value that holds the length of the data segment and then comes the data itself. The format of the data can freely be chosen by the developer. It was decided to use string representations of key/value pairs, separated by a colon (:). The key uniquely identifies the type of component (arm joint, hand joint, IK target dummy,...). The value segment can be used to provide additional data like for example the name of a joint. The left arm's model base for example is tagged with '2497,1:left_arm'. This tag data item identifies that element as the model base of a LWRArmComponent with the name 'left_arm'. When actualizing for scene content change, the ComponentContainer traverses the scene hierarchy and looks for objects, that are tagged as known components. On success, it creates the specific instance with the object handle of the underlying scene object. During the initialization, the concrete SimulationComponent instance searches then the model subtree for all the necessary parts (joints, dummies, force sensors...). The implementations for the arm and the hand model provide feedback output on the console window about the success of this initialization process.

2.5.4 Creating startup launch file

Describe startup script, environmental variable (VREP_PACKAGE_PATH), launch file, how to use different simulation scenes.

2.5.5 Documentation and usage examples

Detailed documentation and implementation details should go into the Appendix

Chapter 3

Pick and place

The implementation of a benchmark pick and place task, executable on simulator and real robot as well, states one of the objective targets of this project. The implementation heavily uses major parts of MoveIt's planning functionality. The overview at the beginning of this chapter gives some general information about pick and place tasks, explaining the process step by step and describing the single stages that have to be performed. The second part focuses on the pick and place functionality of MoveIt and discusses the involved action servers, topics and messages. The third section explains the implementation of the benchmark pick and place task in greater detail and demonstrates how that functionality of MoveIt was used. The last section describes some observations that have been made during the implementation process.

3.1 Overview

A pick and place task is the process of grasping an object, lifting it and dropping it somewhere else. Humans do that permanently, without even think about it. But when teaching a robot to perform a pick and place action, it shows how difficult and complex this task is and how much planning is involved to achieve the desired result. The planner requires exact knowledge about the robot and its environment, including the objects to grasp and possible obstacles. Accidental collisions have to be avoided but other collisions are mandatory when the robot has to get in contact with the world. The gripper definitely collides with the object to pick, but only during grasping and holding. Therefore there has to be a mechanism to explicitly tell the planner that specific collisions are allowed during particular stages of the operation. Moreover, after grasping an object it has to be considered as an additional part of the robot during subsequent planning requests. That means that it must be attached to the manipulator temporarily and removed, after releasing the object. As long as the object is part of the robot, it possibly increases the size of the end effector.

Stationary objects usually stand or lie on a surface, called the *support surface*. During the interaction with an object, possible collisions with the support surface have to be taken into account. It is also possible that the whole process underlies additional constraints, so called *path constraints*. This type of constraint has to be enforced along the whole path, the grasped object takes during the operation. For example when carrying a glass, filled with liquid it has to stay in an upright position, otherwise the liquid is lost. That means, the glass has to be held in a specific orientation during the whole task. This can be described as *orientation constraint* which is a special type of path constraint. The planning solution has to provide mechanisms to define and enforce such types of *path constraints*.

Pick and place tasks can be split into two independent phases, each one composed from a number of trajectory stages:

- **Pickup phase**

This phase starts at an arbitrary robot configuration. In the first stage, the manipulator has to be brought into a position closed to the object to grasp, but in a distance that allows the gripper to open safely without touching the object. This position is called the *pre-grasp pose*. The next stage is to set the gripper into *pre-grasp posture*. That means, bring it's fingers into an open configuration that allows to completely enclose the object (or at least that part that is used to clutch it) after approaching towards the final *pose*. How this configuration looks like depends on the shape of the object to grasp and the structure of the gripper. Further on, the gripper has to be moved towards the *grasp pose* using the correct approach direction. This is the place where the robot gets in contact with the object. The gripper moves it's fingers into the *grasp posture* - a configuration that encloses the object and applies as much force as necessary to be able to take and hold it. The resulting collisions between the gripper links and the object have to be ignored. At that point the object has to be attached to the gripper and further on treated like an additional link of the robot although still being in collision with the support surface. The pickup phase completes after lifting the object along the retreat direction. The object is now part of the robot and no collisions should be tolerated any more. Figure 3.1 shows the stages of the pickup phase.




Figure 3.1: Stages of the pickup phase in the simulator

- **Placement phase**

The placement phase starts after a successful pickup. The grasped object is enclosed by the gripper and considered to be part of the robot. Now the manipulator moves towards the *pre-place location* - the place where the final approach towards the goal starts. The easy way is to just drop the object at that point. In that case, the placement phase completes after bringing the gripper fingers into the *post-place posture* (opening it) and detaching the object from the robot.

If the object should to be placed carefully, the gripper has to approach from the *pre-place location* towards the final *place location* along the specified approach direction. Here has to be considered that the object will get into contact with the support surface again when it's final position is reached. At that stage the gripper can open and the object has to be detached from the robot. From that point, the object needs to be treated as obstacle again which means the planner is forced to avoid collisions with it. The placement phase completes after the manipulator has moved away from the object along the specified retreat direction. The stages of the placement phase can be seen in Figure 3.2.




Figure 3.2: Stages of the placement phase in the simulator

Both phases of the task are only considered to be complete if each single stage has successfully been executed. The necessary planning parameters like pre-grasp and grasp pose, gripper postures and approach and retreat directions are usually provided by a *grasp planner*. This is an additional node within the planning pipeline that identifies objects in the environment of the robot, usually based on 3D sensor data and calculates the necessary grasp parameters. Explaining the functionality of grasp planners is far beyond the scope of this project though the section about implementing the reference task discusses the used parameters in greater detail and shows what would be usually delivered by the grasp planner.

3.2 Pick and place tasks in MoveIt

During the various stages of the pickup and placement phases a lot of motion planning is required. Each single stage requires to plan a trajectory that is free of accidental collisions while respecting the limits of the robot and enforcing possible additional constraints. Each phase can only be considered executable if a valid motion plan for each single stage exists. Planning all the subsequent stages one after the other would be a cumbersome task. Therefore MoveIt provides a set of messages and action servers that greatly simplify those planning tasks.

The *PickupAction* server handles the planning and optionally execution of all required stages during the pickup phase at once. Pickup requests are done, using a *PickupAction* client to send *PickupGoal* messages to the server. The request message is composed of all the parameters that are necessary to completely describe the planning problem. Picking up an object can always be done in several ways. Depending on the shape of the object there hardly always exist a lot

of possible poses where the gripper can safely approach and grasp. Therefore MoveIt allows to provide a set of possible grasp definitions for a pickup request. There is also a quality parameter that can be used to tell the planner, how ‘good’ a specific grasp is compared to other ones. MoveIt can then favour grasps with higher quality if several valid solutions are found by the planner. Providing a number of different grasps increases the probability for the request to be successful. The grasp definition is composed of the pre- and post grasp postures for the gripper, the final grasp pose and the approach and retreat vectors. As MoveIt needs to know which object should be picked within the planning scene, it is also necessary to include the ID of the object to grasp.

The *PlaceAction* server is responsible for planning the whole placement phase. Therefore same concept is used as above - a set of possible place locations can be provided to increase the probability of a successful planning attempt. The parameters that are used to describe a place location include the post-place posture of the gripper along with its target pose, and vectors, describing the pre-place approach and the post-place retreat.

Pickup and placement requests as well require a number of additional parameters that are explained in greater detail within the section about benchmark task implementation.

Objects contained in the task environment have to be brought to MoveIt’s attention. This can be done either by manually adding them to the planning scene, using the corresponding topics or by configuring MoveIt to be aware of sensor data. As the integration of depth information from the Kinect camera did not work stable during the evaluation phase, that possibility is not covered within this thesis and all involved objects were added manually.

Pickup- and place action servers provide the ability to choose whether to execute motion plans immediately or to do just the planning and return the outcome. In that case the execution has to be handled manually later on. The first method is much more comfortable as MoveIt executes the trajectories and also handles additional requirements like attaching and detaching the grasped object in time. The drawback is that also possibly weird trajectories get executed immediately as they might be valid solutions for the given planning problem though they are obviously unsuitable. So an additional safety mechanism needs to be introduced that allows to interrupt the execution when facing any problems. The second method allows to visualize the resulting trajectories and then decide whether to execute them or not. But then each single trajectory stage has to be executed manually which also includes attaching or detaching objects to the manipulator. The advantage of this method is the clean separation between planning and execution, allowing maximum control over the execution flow. Therefore this method was favoured during benchmark task implementation.

3.3 Implementation of the benchmark task

This section describes the implementation of the benchmark pick and place task in greater detail. The source code can be found within the ‘uibk_moveit_tests’ package. The workspace is the table in front of the robot covered with a 9cm thick foam mat. This mat will be declared as the support surface later on. The object to grasp is a cylinder with 4cm radius and a height of 25cm. This corresponds to the size of a usual SIGG bottle which can be used to run the benchmark task in the real world. The cylinder is located on a fixed, known position. There is also a box shaped object located within the workspace that acts as an additional obstacle. The goal of the task is to pick the cylinder up, using the right arm of the robot and place it at the goal location without colliding with the obstacle or other parts within the robot’s environment. The implementation makes use of MoveIt’s pick and place functionality. The necessary steps

are explained in the following subsections.

3.3.1 Creating the environment

As MoveIt is currently not configured to use sensor data, it has to be notified about the task environment. The table and the surface mat are already part of the URDF description but the cylinder and the obstacle have to be added to the task environment. This is done utilizing the `planning_interface::PlanningSceneInterface` class that provides functionality to manipulate the current planning scene. The same effects can be achieved by manually publishing to the `'/collision_object'` topic but using the convenience class saves a lot of boilerplate code. The *CollisionObject* type is used to describe those objects. Both of them are primitive shapes. Necessary parameters are the shape type, dimensions and the target pose. Additionally each *CollisionObject* needs a unique ID which is used to identify the shape within the planning scene. After adding the *CollisionObjects* to the collision world, they are visualized in RViz. The image in Figure 3.3 shows the task environment after adding the *CollisionObjects*.




Figure 3.3: Planning scene after inserting the collision objects

3.3.2 Generating possible grasps

Before calling the pickup action server it is necessary to generate a set of possible grasps for the object to pick. This information is usually provided by a grasp planner. The sample task encapsulates the grasp planner functionality within the *generateGrasps* method. This method takes the current pose of the cylinder as input parameter and calculates 10 possible grasp poses along a semi circle around the cylinder location. Pre-grasp and grasp postures are joint trajectories for the gripper, containing just one trajectory point stating the target configuration for the gripper in the opened respectively the closed state. The pre-grasp approach and the post-grasp retreat are defined as *GripperTranslations*. This is a special message type that describes the direct gripper movement from one position towards a target. The direction is defined as a three dimensional vector. The length of the translation can be set in a flexible way by specifying a desired distance and a minimum distance. Experiments showed that the success rate is much better if the grasp parameters allow some flexibility to the planners. The approach vector depends on the grasp pose and points along the z-axis of the end effector frame towards the object. The desired distance between pre-grasp and grasp pose is set to 20cm while the minimum

distance is 10cm. The gripper retreat vector points up, along the z-axis of the world. Desired and maximum distances are also set to 20cm respectively 10cm. As no one of the generated grasps should be favoured among the others, the `grasp_quality` parameter of each grasp is set to 1. This means that they are equal in quality. The last necessary parameter is a unique identifier for each grasp. As usually a lot of different grasps are provided for each pickup request, this ID can be used to identify, which one was finally used to solve the planning problem.




Figure 3.4: Grasp poses, gripper approach and retreat

3.3.3 Planning and executing the pickup

After generating the set of grasps, the planning request can be sent to the pickup action server. As there is a lot of boilerplate code necessary, a reusable helper class was created that can be used to simplify all kinds of planning requests. The utility class is called *PlanningHelper* and can be found within the 'uibk_planning_node' package. A call to the pickup action server is done by using the 'plan_pick' method of the helper class. This method takes a set of possible grasps and the ID of the object to pick as parameters. The outcome is a pointer to an instance of *PlanningResult*, a structure that contains all the necessary information about a planning attempt. Success or failure is indicated by the 'status' parameter. On success, the parameter 'trajectory_stages' holds a vector, containing the resulting trajectory stages. The actual call to the pickup action server is done by defining the *PickupGoal*, using the predefined grasps. Additional parameters are the ID of the object to pick, the name of the chosen planning group and the name of the link within the robot model that acts as the support surface. Optional parameters are among others the ID of the planner to use and the maximum allowed planning time. The parameter 'plan_only' within the planning options is set to true to avoid the immediate execution of the planned trajectories. This allows a visual verification of the planning outcome before execution. The resulting robot path is shown in RViz. If the solution is satisfying it can be executed, passing the *PlanningResult* to the corresponding method of the *PlanningHelper* class. This method uses the '/execute_kinematic_path' service provided by the 'move_group' node. The service sends a given trajectory to the responsible controller and provides feedback information about the execution status. The 'PlanningHelper' also takes care to attach the picked object to the gripper after the grasp stage. The pickup phase completes after successful execution of all trajectory stages.

3.3.4 Planning and executing the placement

The placement phase is planned and executed in a somehow similar manor. The cylinder has to be placed on a specific location within the workspace in an upright position - the rotation around the z-axis doesn't matter. Therefore a set of possible place poses is generated in 20 different orientations around the z-axis. This again gives some freedom to the planner as it can choose which one to use (TODO: provide image that shows the principle). The final approach towards the goal location is specified as *GripperTranslation*. The direction vector points down

along the z-axis of the world. Desired and minimum distances are set to 20cm respectively 10cm, allowing some flexibility during that stage. As post-place posture for the gripper, the same configuration is used as for the pre-grasp posture. The last required parameter for a place location is the *GripperTranslation* that describes the retreat after releasing the object at the goal location. The direction depends on the chosen orientation and points towards the negative z-axis of the gripper reference frame.




Figure 3.5: Place locations, pre-place approach and post-place retreat

The call to the place action server is again handled by the formerly mentioned planning helper class. The ‘plan_place’ method takes a vector of the predefined place locations and the ID of the object to place as input parameters. The actual call to the place action server is done, defining a *PlaceGoal* message. The most important parameters are the ID of the object to place, the name of the planning group and the set of possible place locations. Optionally can be specified which planner to choose and also the maximum allowed planning time. The method returns the result of the planning request. On success, the resulting trajectories are again visualized in RViz and can then be executed the same way as during pickup phase. After the execution, the task is considered to be complete and the picked object is detached from the gripper and again part of the collision world.

3.4 Executing the benchmark task

The benchmark task is designed to run on the simulator and the real robot as well. The sample program only depends on a running ‘move_group’ instance. The easiest way to run the sample is to start MoveIt in demo mode (demo.launch) and then execute the sample code, using.

```
roslaunch uibk_moveit_tests sample_pick_place
```

This demonstrates the functionality but only executes the trajectories on the fake controllers provided by MoveIt. If the sample should be executed on the simulator or the real robot, the corresponding namespace has to be specified before running the code. This can be done by setting the ‘ROS_NAMESPACE’ environment variable to either ‘simulation’ or ‘real’, within the terminal. For example

```
export ROS_NAMESPACE=simulation
roslaunch uibk_moveit_tests sample_pick_place
```

runs the benchmark task on the simulator. Of course it is necessary to start the simulator and launch the corresponding MoveIt instance before doing that. After creating the environment and adding the objects to the planning scene the pickup phase gets planned. The outcome can be seen in RViz and the program will ask if the resulting trajectory is ok and should be executed. A negative answer will force the program to replan the pickup and ask again, otherwise the trajectory gets executed. After successful execution, the place phase gets planned. The resulting plan also is the visualized as well and execution needs confirmation again. The program exits after successful completing the placement phase.

3.5 Observations

This section gives an overview about the most important observations that have been made during the implementation of the sample task:

- It is very important to provide some degree of freedom to the planner at various points. Major points are the amount of different grasps or place locations and the allowed range within the defined gripper translations. Very strictly defined planning requests are very likely to fail whereas requests with a higher degree of flexibility drastically raise the overall success rate.
- Working with path constraints drastically drops the success rate because the high complexity of the planning problem. Enforcing path constraints requires much more allowed planning time and a very fast IK solver because of the large number of necessary IK requests. Maybe a faster IK solution than the one available could help to solve the problem but that is not guaranteed. Therefore there are no path constraints used within the sample task.
- Planning requests often fail due some MoveIt-internal issues and not because planning is not possible at all. Therefore it is necessary to repeat failed requests because it is very likely that planning succeeds on subsequent attempts. In the sample task implementation, the planning requests are done within a loop. If a request fails, it gets repeated. A successful request breaks the loop and continues the execution flow.
- Resulting trajectories should always be visualized in RViz before confirming the execution. The calculated motion plans might be valid but sometimes they are a bit confused and therefore unsuitable. Moreover, the planner can only take into account what it knows about the robot's environment. Especially in the robot lab there is equipment mounted in the area above the robot, that is not taken into account during planning. Therefore the visual validation is necessary to avoid damages on the robot and it's environment.

Bibliography

Marc Freese, Surya Singh, Fumio Ozaki, and Nobuto Matsuhira. Virtual robot experimentation platform v-rep: A versatile 3d robot simulator.

Morgan Quigley, Ken Conley, Brian Gerkey, Josh Faust, Tully Foote, Jeremy Leibs, Rob Wheeler, and Andrew Y Ng. Ros: an open-source robot operating system. In *ICRA workshop on open source software*, volume 3, 2009.