

Demo: Loading Macros via include-in-header

This page demonstrates the `include-in-header` strategy for loading macros. The YAML front matter of this file includes:

```
format:
  html:
    include-in-header:
      - macros.qmd
  pdf:
    include-in-header:
      - macros.qmd
  docx: default
```

Note: `revealjs` is omitted from this demo page because a Quarto website page cannot simultaneously be a RevealJS presentation. To use `include-in-header` with RevealJS, add a `revealjs:` entry in a standalone `.qmd` file or in `_quarto.yml` (see the project-wide config below).

Note: This demo uses `macros.qmd` because `macros.qmd` is at the root of this repository. When using this repository as a Git submodule (cloned into a `macros/` subdirectory), replace `macros.qmd` with `macros/macros.qmd`.

The same configuration can be placed in a shared `_quarto.yml` to apply project-wide:

```
format:
  html:
    include-in-header:
      - macros/macros.qmd
  pdf:
    include-in-header:
      - macros/macros.qmd
  revealjs:
    include-in-header:
      - macros/macros.qmd
```

This inserts `macros.qmd` verbatim into the document header for each output format:

- **PDF**: definitions go into the LaTeX preamble — all macros work, including `\providecommand`.
- **HTML/RevealJS**: MathJax processes the header — MathJax-supported commands (`\def`, `\newcommand`, `\renewcommand`, `\let`, environments) are recognized; `\providecommand` is silently ignored. The example table below uses only `\def`-based macros.
- **docx**: Word documents do not use a LaTeX preamble or MathJax header, so `\includeinheader` has no effect on math rendering for docx. The `docx: default` entry above produces docx output without macro support.

Example math

The table below uses macros defined with `\def` in `macros.qmd`, which work in all output formats that support MathJax or LaTeX:

Description	Code	Output
Greek: alpha	<code>\$(a)\$</code>	α
Greek: beta	<code>\$(b)\$</code>	β
Greek: gamma	<code>\$(g)\$</code>	γ
Greek: lambda	<code>\$(l)\$</code>	λ
Greek: sigma	<code>\$(s)\$</code>	σ
Log-likelihood	<code>\$(llik)\$</code>	ℓ
Independent	<code>\$X \ind Y\$</code>	$X \perp\!\!\!\perp Y$
IID distributed	<code>\$X_i \siid \Normal(m, ss)\$</code>	$X_i \sim_{\text{iid}} N(\mu, \sigma^2)$
Vector: mu	<code>\$(vm)\$</code>	$\vec{\mu}$
Hat beta	<code>\$(hb)\$</code>	$\hat{\beta}$