Source Code of texyc.tex

\catcode‘@=11'
\pdfliteral{1 1 1 rg 1 1 1 RG}'
\headline={\pdfliteral{1 1 1 rg 1 1 1 RG}\hfil}' \font\codefont=cmtt9'
\font\headerfont=cmbx12 at 14pt'
\parindent=0pt'
\headerfont Source Code of \jobname.tex \par' \vskip 10pt'
\pdfliteral{1 1 1 rg 1 1 1 RG}'
\hrule'
\vskip 5pt'
\begingroup'
Ψ\codefont'
Ψ\newread\mysource'
Ψ\openin\mysource=\jobname.tex'
Ψ\def\printSourceLoop{'
ΨΨ\readline\mysource to \sourceline' ΨΨ\unless\ifeof\mysource'
ΨΨΨ\hbox{\sourceline}\endgraf'
ΨΨΨ\expandafter\printSourceLoop'
ΨΨ\fi'
Ψ}'
Ψ\ifeof\mysource \else \printSourceLoop \closein\mysource \fi' \endgroup'
\vfill\eject'
\headerfont Output: **** and Encode! \par'
\vskip 10pt'
\pdfliteral{1 1 1 rg 1 1 1 RG}'
\hrule'
\vskip 20pt'
\font\mainfont=cmtt12 at 12pt \mainfont'
\newcount\ASIS@H \newcount\ASIS@L'
\newcount\tmp@cnt'
\newcount\CTF@A \newcount\CTF@B \newcount\CTF@res \newcount\CTF@mul \newcount\CTF@bit' \def\poly@H{60856} \def\poly@L{33568} \def\high@bit{32768}' \def\calc@CTF#1#2{\CTF@A=#1 \CTF@B=#2 \CTF@res=0 \CTF@mul=1 \CTF@recurse}' \def\CTF@recurse{'
Ψ\ifnum\CTF@A=0 \ifnum\CTF@B=0 \let\next\relax \else \let\next\CTF@step \fi'
Ψ\else \let\next\CTF@step \fi'
Ψ\next'
}'
\def\CTF@step{'
Ψ\ifodd\CTF@A \CTF@bit=1 \else \CTF@bit=0 \fi \divide\CTF@A by 2' Ψ\ifodd\CTF@B \advance\CTF@bit by 1 \fi \divide\CTF@B by 2' Ψ\ifodd\CTF@bit \advance\CTF@res by \CTF@mul \fi'
Ψ\multiply\CTF@mul by 2 \CTF@recurse'
}'
\def\r@true{T} \def\r@false{F}'
\def\ASIS@bitstep{'
Ψ\ifodd\ASIS@L \let\do@poly\r@true \else \let\do@poly\r@false \fi' Ψ\ifodd\ASIS@H \let\carry@bit\r@true \else \let\carry@bit\r@false \fi'

1

Ψ\divide\ASIS@H by 2 \divide\ASIS@L by 2' Ψ\ifx\carry@bit\r@true \advance\ASIS@L by \high@bit \fi' Ψ\ifx\do@poly\r@true'
ΨΨ\calc@CTF{\ASIS@H}{\poly@H}\ASIS@H=\CTF@res' ΨΨ\calc@CTF{\ASIS@L}{\poly@L}\ASIS@L=\CTF@res'
Ψ\fi'
}'
\def\ASIS@process@byte#1{'
Ψ\calc@CTF{\ASIS@L}{#1}\ASIS@L=\CTF@res'
Ψ\tmp@cnt=8'
Ψ\loop \ASIS@bitstep \advance\tmp@cnt by -1 \ifnum\tmp@cnt>0 \repeat' }'
\def\ASIS@loop#1{'
Ψ\ifx#1\end@marker \let\next\relax'
Ψ\else \ASIS@process@byte{‘#1}\let\next\ASIS@loop \fi'
Ψ\next'
}'
\def\MOP#1{\ifcase#1 1\or 2\or 3\or 4\or 5\or 6\or 7\or 8\or 9\or A\or B\or C\or D\or E\or F\or 0\fi}' \def\MEP#1{\ifcase#1 2\or 3\or 4\or 5\or 6\or 7\or 8\or 9\or A\or B\or C\or D\or E\or F\or 0\or 1\fi}' \def\computeAndExportHash{'
Ψ\tmp@cnt=\ASIS@H \divide\tmp@cnt by 4096'
Ψ\edef\dOne{\MOP{\the\tmp@cnt}}'
Ψ\tmp@cnt=\ASIS@H \divide\tmp@cnt by 256 \CTF@B=\tmp@cnt \divide\CTF@B by 16 \multiply\CTF@B by 16 \advance\tmp@ Ψ\edef\dTwo{\MEP{\the\tmp@cnt}}'
Ψ'

Ψ\tmp@cnt=\ASIS@H \divide\tmp@cnt by 16 \CTF@B=\tmp@cnt \divide\CTF@B by 16 \multiply\CTF@B by 16 \advance\tmp@c Ψ\edef\dThree{\MOP{\the\tmp@cnt}}'
Ψ\tmp@cnt=\ASIS@H \CTF@B=\tmp@cnt \divide\CTF@B by 16 \multiply\CTF@B by 16 \advance\tmp@cnt by -\CTF@B' Ψ\edef\dFour{\MEP{\the\tmp@cnt}}'
'

Ψ\tmp@cnt=\ASIS@L \divide\tmp@cnt by 4096'
Ψ\edef\dFive{\MOP{\the\tmp@cnt}}'
Ψ'

Ψ\tmp@cnt=\ASIS@L \divide\tmp@cnt by 256 \CTF@B=\tmp@cnt \divide\CTF@B by 16 \multiply\CTF@B by 16 \advance\tmp@ Ψ\edef\dSix{\MEP{\the\tmp@cnt}}'
Ψ'

Ψ\tmp@cnt=\ASIS@L \divide\tmp@cnt by 16 \CTF@B=\tmp@cnt \divide\CTF@B by 16 \multiply\CTF@B by 16 \advance\tmp@c Ψ\edef\dSeven{\MOP{\the\tmp@cnt}}'
'

Ψ\tmp@cnt=\ASIS@L \CTF@B=\tmp@cnt \divide\CTF@B by 16 \multiply\CTF@B by 16 \advance\tmp@cnt by -\CTF@B' Ψ\edef\dEight{\MEP{\the\tmp@cnt}}'
Ψ\xdef\ENCODE{\dOne\dTwo\dThree\dFour\dFive\dSix\dSeven\dEight}'
}'
\def\end@marker{\end@marker}'
\def\calculateHash#1{\begingroup'
Ψ\ASIS@H=65535 \ASIS@L=65535'
Ψ\ASIS@loop #1\end@marker'
Ψ\calc@CTF{\ASIS@H}{65535}\ASIS@H=\CTF@res' Ψ\calc@CTF{\ASIS@L}{65535}\ASIS@L=\CTF@res' Ψ\computeAndExportHash'
\endgroup}'
\newcount\char@counter'
\def\chunk@buffer{}'

2

\def\endStream{\endStream}'
\def\processStream#1{'
Ψ\ifx#1\endStream'
ΨΨ\ifnum\char@counter>0 \expandafter\printRow\expandafter{\chunk@buffer} \fi' ΨΨ\let\next\relax'
Ψ\else'
ΨΨ\edef\chunk@buffer{\chunk@buffer#1}'
ΨΨ\advance\char@counter by 1'
ΨΨ\ifnum\char@counter=4'
ΨΨΨ\expandafter\printRow\expandafter{\chunk@buffer}' ΨΨΨ\def\chunk@buffer{}'
ΨΨΨ\char@counter=0'
ΨΨ\fi'
ΨΨ\let\next\processStream'
Ψ\fi'
Ψ\next'
}'
\def\printRow#1{'
Ψ\calculateHash{#1}'
Ψ\line{\tt \hbox to 40mm{****\hfil} \ENCODE\hfil}' }'
\catcode‘@=12'
\newread\infile'
\openin\infile=flag.tex'
\ifeof\infile'
Ψ\message{Error: flag.tex not found!}' \else'
Ψ\endlinechar=-1'
Ψ\readline\infile to \flagData'
Ψ\closein\infile'
\fi'
\expandafter\processStream\flagData\endStream' \bye'

3

Output: **** and Encode!

**** C1D196B1
**** 9D074ADB
**** B544E197
**** 62A95FFA
**** 50BEDB0E
**** 7D4BC107
**** 1B4CD08A
**** AFD9830C

4