



Search Meta OpenAPI documentation and let me know that with WhatsApp Business API, we need POST request to both send and receive message right?

No, you don't need a POST request to receive messages. Here's the correct setup for WhatsApp Business API:

Sending Messages

- **POST request** ✓ to `/PHONE_NUMBER_ID/messages` endpoint
- This is used for all message types (text, media, templates, interactive) ^[1] ^[2] ^[3]

Receiving Messages

- You need to serve an **webhook endpoint** that supports **both GET and POST**:
 - **GET**: Used for endpoint verification (Meta verifies your webhook URL) ^[1]
 - **POST**: Used to receive incoming messages/changes from the API (Webhook callbacks) ^[1]

Key Difference

Action	HTTP Method	Purpose
Send message	POST	To <code>/PHONE_NUMBER_ID/messages</code> endpoint
Verify webhook	GET	Meta's webhook verification callback
Receive message	POST	Webhook callback with incoming message data

So to clarify: **Sending** uses POST to Meta's API, while **receiving** uses a webhook where Meta sends POST callbacks to your endpoint (after initial GET verification). You don't make a POST request to receive—Meta POSTs to your webhook when messages arrive. ^[1]

✱

Give me their payload structure for sending and receiving message.

Here's the complete payload structure for sending and receiving messages with WhatsApp Business API:

✉ Sending Message Payload (POST Request)

Endpoint: POST https://graph.facebook.com/v21.0/PHONE_NUMBER_ID/messages

```
{
  "messaging_product": "whatsapp",
  "to": "16505551234",
  "type": "text",
  "text": {
    "body": "Hello! This is my first WhatsApp Business message.",
    "preview_url": false
  }
}
```

For other message types:

Template Message:

```
{
  "messaging_product": "whatsapp",
  "to": "16505551234",
  "type": "template",
  "template": {
    "name": "hello_world",
    "language": {
      "code": "en_US"
    }
  }
}
```

Media Message (Image):

```
{
  "messaging_product": "whatsapp",
  "to": "16505551234",
  "type": "image",
  "image": {
    "link": "https://example.com/image.jpg",
    "caption": "This is an image caption"
  }
}
```

Response:

```
{
  "messaging_product": "whatsapp",
  "contacts": [
    {
      "input": "16505551234",
      "wa_id": "16505551234"
    }
  ],
  "messages": [
    {
      "id": "wamid.ID_HERE"
    }
  ]
}
```

☒ Receiving Message Payload (Webhook POST)

When a user sends you a message, Meta sends this to your webhook endpoint:

```
{
  "object": "whatsapp_business_account",
  "entry": [
    {
      "id": "WHATSAPP_BUSINESS_ACCOUNT_ID",
      "changes": [
        {
          "value": {
            "messaging_product": "whatsapp",
            "metadata": {
              "display_phone_number": "16505551234",
              "phone_number_id": "PHONE_NUMBER_ID"
            },
            "contacts": [
              {
                "profile": {
                  "name": "USER_NAME"
                },
                "wa_id": "16505551234"
              }
            ],
            "messages": [
              {
                "from": "16505551234",
                "id": "wamid.ID_HERE",
                "timestamp": "1678901234",
                "text": {
                  "body": "MESSAGE_BODY"
                },
                "type": "text"
              }
            ]
          }
        }
      ]
    }
  ],
  "field": "messages"
}
```

```

    }
  ]
}
]
}

```

Accessing message content:

```

// JavaScript example
const message = webhook.entry[^2_0].changes[^2_0].value.messages[^2_0];
const sender = webhook.entry[^2_0].changes[^2_0].value.contacts[^2_0].wa_id;
const body = message.text.body;

```

📄 Delivery Status Webhook Payload

When your sent message is delivered/read/failed:

```

{
  "object": "whatsapp_business_account",
  "entry": [
    {
      "id": "WHATSAPP_BUSINESS_ACCOUNT_ID",
      "changes": [
        {
          "value": {
            "messaging_product": "whatsapp",
            "metadata": {
              "display_phone_number": "PHONE_NUMBER",
              "phone_number_id": "PHONE_NUMBER_ID"
            },
            "statuses": [
              {
                "id": "wamid.ID_HERE",
                "recipient_id": "16505551234",
                "status": "delivered",
                "timestamp": "1678901234",
                "conversation": {
                  "id": "CONVERSATION_ID",
                  "expiration_timestamp": "1678901234",
                  "origin": {
                    "type": "user_initiated"
                  }
                },
                "pricing": {
                  "pricing_model": "CBP",
                  "billable": true,
                  "category": "service"
                }
              }
            ]
          },
          "field": "messages"
        }
      ]
    }
  ]
}

```

```
}
]
}
]
}
```

Key differences:

Action	Method	Where	
Send	POST	To Meta's /messages endpoint	
Receive	POST (webhook)	Meta sends to your webhook URL	
Status	POST (webhook)	Meta sends delivery status to your webhook URL	[11] [12]

✱

Search Meta OpenAPI documentation and let me know that with Messenger Business API, we need POST request to both send and receive message right?

No, for Messenger Business API (Facebook Messenger), you don't need POST for both sending and receiving. Here's the correct setup:

✱ Sending Messages (Messenger)

- POST request ✓ to /PAGE_ID/messages endpoint
- Same pattern as WhatsApp for sending

✱ Receiving Messages (Messenger)

- You need a webhook endpoint with:
 - GET: For webhook verification (similar to WhatsApp) [\[21\]](#)
 - POST: For receiving incoming messages from Meta [\[22\]](#) [\[21\]](#)

Key Difference from Your Question

No, you don't make a POST request to receive messages on Messenger API. The pattern is the same as WhatsApp:

Action	HTTP Method	Who sends it?
Send	POST	You → Meta's /messages endpoint
Receive	POST (webhook)	Meta → Your webhook URL

For receiving, Meta sends a POST request to your webhook endpoint when users message you. You set up a webhook URL in your Facebook App settings, and Meta POSTs incoming messages

there. ^[22] ^[21]

This is identical to WhatsApp Business API's webhook pattern - you only POST to send, and Meta POSTs to your webhook when receiving.



Give me their payload structure for sending and receiving message.

Here's the complete payload structure for **Messenger Business API** (Facebook Messenger):

❏ Sending Message Payload (POST Request)

Endpoint: POST `https://graph.facebook.com/v21.0/PAGE_ID/messages`

Text Message:

```
{
  "recipient": {
    "id": "USER_ID"
  },
  "message": {
    "text": "Hello! This is my first Facebook Messenger message."
  }
}
```

With Quick Replies:

```
{
  "recipient": {
    "id": "USER_ID"
  },
  "message": {
    "text": "What color do you prefer?",
    "quick_replies": [
      {
        "content_type": "text",
        "title": "Red",
        "payload": "DEVELOPER_DEFINED_PAYLOAD_RED"
      },
      {
        "content_type": "text",
        "title": "Blue",
        "payload": "DEVELOPER_DEFINED_PAYLOAD_BLUE"
      }
    ]
  }
}
```

Image Message:

```
{
  "recipient": {
    "id": "USER_ID"
  },
  "message": {
    "attachment": {
      "type": "image",
      "payload": {
        "url": "https://example.com/image.jpg"
      }
    }
  }
}
```

Generic Template (Button Template):

```
{
  "recipient": {
    "id": "USER_ID"
  },
  "message": {
    "attachment": {
      "type": "template",
      "payload": {
        "template_type": "generic",
        "elements": [
          {
            "title": "Product Title",
            "subtitle": "Product subtitle",
            "image_url": "https://example.com/product.jpg",
            "buttons": [
              {
                "type": "postback",
                "title": "Buy Now",
                "payload": "BUY_PRODUCT_PAYLOAD"
              },
              {
                "type": "url",
                "title": "View Details",
                "url": "https://example.com/product"
              }
            ]
          }
        ]
      }
    }
  }
}
```

Response:

```
{
  "recipient_id": "123456789",
  "message_id": "mid.1464990849238:b9a22a2bcb1de31773"
}
```

☒ Receiving Message Payload (Webhook POST)

When a user sends you a message, Meta sends this to your webhook endpoint:

```
{
  "object": "page",
  "entry": [
    {
      "id": "PAGE_ID",
      "time": 1458692752478,
      "messaging": [
        {
          "sender": {
            "id": "USER_ID"
          },
          "recipient": {
            "id": "PAGE_ID"
          },
          "timestamp": 1458692752478,
          "message": {
            "mid": "mid.1464990849238:b9a22a2bcb1de31773",
            "seq": 69,
            "text": "book me a cab",
            "metadata": "DEVELOPER_METADATA"
          }
        }
      ]
    }
  ]
}
```

With Quick Reply (payload sent back):

```
{
  "object": "page",
  "entry": [
    {
      "id": "PAGE_ID",
      "time": 1464990849275,
      "messaging": [
        {
          "sender": {
            "id": "USER_ID"
          },
          "recipient": {
            "id": "PAGE_ID"
          }
        }
      ]
    }
  ]
}
```

```

    },
    "timestamp": 1464990849275,
    "message": {
      "mid": "mid.1464990849238:b9a22a2bcb1de31773",
      "seq": 69,
      "text": "Red",
      "quick_reply": {
        "payload": "DEVELOPER_DEFINED_PAYLOAD_FOR_PICKING_RED"
      }
    }
  }
]
}

```

With Postback (button click):

```

{
  "object": "page",
  "entry": [
    {
      "id": "PAGE_ID",
      "time": 1464990849275,
      "messaging": [
        {
          "sender": {
            "id": "USER_ID"
          },
          "recipient": {
            "id": "PAGE_ID"
          },
          "timestamp": 1464990849275,
          "postback": {
            "title": "Buy Now",
            "payload": "BUY_PRODUCT_PAYLOAD",
            "mid": "mid.postback_1464990849238"
          }
        }
      ]
    }
  ]
}

```

☒ Delivery Notification Payload

```

{
  "object": "page",
  "entry": [
    {
      "id": "PAGE_ID",
      "time": 1458692752478,

```

```

    "messaging": [
      {
        "sender": {
          "id": "USER_ID"
        },
        "recipient": {
          "id": "PAGE_ID"
        },
        "delivery": {
          "mid": "mid.1464990849238:b9a22a2bcb1de31773",
          "watermark": 1458692752478,
          "seq": 69
        }
      }
    ]
  }
}

```

Key Differences from WhatsApp^[31] ^[32] ^[33]

Aspect	Messenger API	WhatsApp API
Send endpoint	/PAGE_ID/messages	/PHONE_NUMBER_ID/messages
Recipient field	recipient: { id: "USER_ID" }	to: "PHONE_NUMBER"
Message field	message: { text: "..." }	text: { body: "..." }
Webhook object	object: "page"	object: "whatsapp_business_account"
Webhook entry	messaging[] array	changes[].value.messages[] array
Quick reply	quick_reply: { payload }	Similar structure
Postback	postback: { payload }	Uses interactive messages

Accessing message content:

```

// JavaScript example
const entry = webhook.entry[^4_0];
const messaging = entry.messaging[^4_0];
const user_id = messaging.sender.id;
const message_text = messaging.message.text;
const postback_payload = messaging.postback?.payload;

```

✱

1. <https://github.com/emingure/whatsapp-business-api-ts>
2. <https://github.com/mittalVaghela/whtasappbusinessapi>
3. <https://medium.com/vectoscalar/different-types-of-messages-that-can-be-sent-using-whatsapp-api-by-meta-f7cfcf12a4de>

4. <https://www.postman.com/meta/whatsapp-business-platform/documentation/wlk6lh4/whatsapp-cloud-api>
5. <https://docs.360dialog.com/docs/waba-basics/waba-integration>
6. <https://developers.messagebird.com/api/whatsapp>
7. <https://stackoverflow.com/questions/72628983/whatsapp-business-api-not-sending-message-endpoint-or-test-messages-to-phone>
8. <https://developers.facebook.com/documentation/business-messaging/whatsapp/messages/send-messages>
9. https://www.youtube.com/watch?v=ul_9qe_fiT_Y
10. <https://whatsappbusiness.com/developers/developer-hub/>
11. <https://developer.linkmobility.eu/whatsapp-api/receive-whatsapp-messages>
12. <https://stackoverflow.com/questions/74314632/in-which-case-metas-whatsapp-payload-examples-will-receive-with-multiple-elements>
13. <https://docs.kapso.ai/docs/whatsapp/receive-messages>
14. <https://zernio.com/blog/whatsapp-api-tutorial-how-to-send-messages-and-templates>
15. <https://developers.facebook.com/documentation/business-messaging/whatsapp/webhooks/reference/messages>
16. <https://stackoverflow.com/questions/74790660/send-metadata-in-whatsapp-cloud-api>
17. https://www.reddit.com/r/WhatsappBusinessAPI/comments/1n0veml/whatsapp_cloud_api_meta_returns_200_ok_but_i_dont/
18. <https://developers.facebook.com/documentation/business-messaging/whatsapp/messages/send-messages>
19. https://www.youtube.com/watch?v=ul_9qe_fiT_Y
20. <https://notify.africa/blogs/whatsapp-api-message-templates>
21. <https://github.com/ccleung/fb-messenger>
22. <https://stackoverflow.com/questions/51058699/messenger-send-api>
23. <https://developers.facebook.com/documentation/business-messaging/whatsapp/messages/send-messages>
24. <https://whatsappbusiness.com/products/business-platform/>
25. https://help.chat-api.com/official_messenger_business_api/sending_messages_in_the_messenger_business_api_the_contacts_method/
26. https://www.greenwoodspellet.com/?_=%2Fdocs%2Fmessenger-platform%2Fsend-messages%2Fmessage-tags%23ugy7DKvAZSLDaOo7sutJgaAL4Rq5mS9vyGL3cL3rVA%3D%3D
27. <https://ultramsgr.com>
28. <https://developers.sinch.com/docs/conversation/channel-support/facebook-messenger/send-a-message-with-facebook-messenger>
29. <https://stackoverflow.com/questions/79412817/whatsapp-business-api-requires-that-the-user-sends-the-first-message-before-the>
30. https://www.youtube.com/watch?v=ul_9qe_fiT_Y
31. <https://stackoverflow.com/questions/40006641/facebook-messenger-api-whats-does-a-quick-reply-payload-do>
32. <https://github.com/ccleung/fb-messenger>
33. <https://stackoverflow.com/questions/51058699/messenger-send-api>
34. <https://api.messengerpeople.dev/docs/messages>
35. <https://github.com/RoySegall/facebook-messenger-send-api>

36. <https://www.messengerpeople.dev>
37. <https://developers.facebook.com/documentation/business-messaging/messenger-platform/send-messages>
38. <https://developers.facebook.com/documentation/business-messaging/whatsapp/messages/send-messages>
39. <https://developers.webexconnect.io/reference/facebook-messenger-api>
40. <https://developers.sinch.com/docs/conversation/channel-support/facebook-messenger/message-support>