

KOTLIN

FROM A JAVA DEVELOPER'S PERSPECTIVE

WHAT IS KOTLIN?

- object-oriented & functional
- statically typed with type inference
- concise
- compiles to JVM byte code

LESS VERBOSE

" Kotlin's modern language features allow you to focus on expressing your ideas and write less boilerplate code. Less code written also means less code to test and maintain. "

developer.android.com

LESS VERBOSE

Java

```
public class HelloWorld {  
    public static void main(String[] args) {  
        System.out.println("Hello World!");  
    }  
}
```

Kotlin

```
fun main() {  
    println("Hello World")  
}
```

SEMICOLONS ARE OPTIONAL

```
println("Hello World");
```

is equivalent to

```
println("Hello World")
```

RETURN TYPES

`Unit` return type can be omitted

```
fun main(): Unit {  
    println("Hello World")  
}
```

is equivalent to

```
fun main() {  
    println("Hello World")  
}
```

TYPE INFERENCE

```
val a: Int = 3  
val b: Int  
b = 5
```

is equivalent to

```
val a = 3 // type Int gets inferred  
val b: Int  
b = 5
```

VISIBILITY MODIFIERS

- `private`
- `protected`
- `internal`
- `public` (default)

```
private val a = 3  
val b = 5 // public by default
```


var AND val

```
var a = "mutable String"  
val b = "immutable String"  
  
a = "new value"  
b = "new value" // compilation error
```

ACCESSING PROPERTIES

Java

```
String name = somePerson.getName();
```

Kotlin

```
val name = somePerson.name
```

ASSIGNING PROPERTIES

Java

```
somePerson.setName("Dennis");
```

Kotlin

```
somePerson.name = "Dennis"
```

CREATING NEW INSTANCES

Java

```
Person somePerson = new Person("Dennis");
```

Kotlin (no `new` keyword)

```
val somePerson = Person("Dennis")
```

NAMED ARGUMENTS

```
class User(val username: String, val password: String)  
  
val admin = User(username = "admin", password = "12345")
```

order doesn't matter

```
val user = User(password = "54321", username = "user")
```

DEFAULT ARGUMENTS

```
class User(  
    val username: String,  
    val password: String = "not-so-secure-password"  
)  
  
val admin = User(username = "admin")
```

SINGLE-EXPRESSION FUNCTIONS

```
fun theAnswer(): Int {  
    return 42  
}
```

is equivalent to

```
fun theAnswer() = 42
```

NULL SAFETY

" I call it my billion-dollar mistake. It was the invention of the null reference in 1965. "

Tony Hoare

NULL SAFETY

```
var a: String = "abc"  
a = null // compilation error  
  
var b: String? = "abc"  
b = null // ok
```

SAFE CALL OPERATOR - ?.

```
val a: String = "abc"  
  
a.length  
  
val b: String? = "abc"  
  
b.length // compilation error  
  
b?.length
```

ELVIS OPERATOR - ? :

If the expression to the left of ? : is not null, the elvis operator returns it, otherwise it returns the expression to the right.

```
val b: String? = "abc"  
val l = b?.length ?: -1
```

TEMPLATE STRINGS

```
val name = "Dennis"  
println("My name is $name")
```

```
$ My name is Dennis
```

DATA CLASSES

- `equals()`
- `hashCode()`
- `toString()`
- `copy()`
- **Deconstructing Declarations**

DATA CLASSES

```
data class User(  
    val username: String,  
    val password: String  
)  
  
val admin = User("admin", "12345")
```

DESTRUCTURING DECLARATIONS

```
data class User(  
    val username: String,  
    val password: String  
)  
  
val (username, password) = User("admin", "12345")
```

DESTRUCTURING DECLARATIONS

very handy in maps

```
for ((key, value) in map) {  
    println("Key: $key, value: $value")  
}
```


SMART CASTS

`is` check

```
if (x is String) {  
    println(x.length) // x is automatically cast to String  
}
```

negative `is` check

```
if (x !is String) return  
println(x.length) // x is automatically cast to String
```

SMART CASTS

when-expressions

```
when (x) {  
    is Int -> println(x + 1) // x is Int  
    is String -> println(x.length + 1) // x is String  
    is IntArray -> println(x.sum()) // x is IntArray  
}
```

COLLECTIONS

Immutable

```
val x = listOf(a, b, c)
val y = setOf(a, b, c)
val z = mapOf(
    Pair("a", a),
    Pair("b", b),
    Pair("c", c)
)
```

COLLECTIONS

Mutable

```
val x = mutableListOf(a, b, c)
val y = mutableSetOf(a, b, c)
val z = mutableMapOf(
    Pair("a", a),
    Pair("b", b),
    Pair("c", c)
)
```

RANGES

ascending

```
for (i in 1..4) {  
    println("Current Value is $i")  
}
```

descending

```
for (i in 4 downTo 1) {  
    println("Current Value is $i")  
}
```

RANGES WITH STEP

ascending

```
for(i in 1..4 step 2) {  
    println("Current Value is $i")  
}
```

descending

```
for(i in 4 downTo 1 step 2) {  
    println("Current Value is $i")  
}
```

EXTENSION FUNCTIONS

" Provide the ability to extend a class with new functionality without having to inherit from the class or use any type of design pattern such as Decorator."

kotlinlang.org

UTIL CLASSES IN JAVA

```
public class CollectionUtil {  
    public static <T> void swap(  
        List<T> list,  
        int index1,  
        int index2  
    ) {  
        T tmp = list.get(index1);  
        list.set(index1, list.get(index2));  
        list.set(index2, tmp);  
    }  
}
```

```
List<Integer> list = Arrays.asList(1,2,3);  
CollectionUtil.swap(list, 0, 2);
```


EXTENSION FUNCTIONS

Replacement of Java Util function

```
fun <T> MutableList<T>.swap(index1: Int, index2: Int) {  
    val tmp = this[index1]  
    this[index1] = this[index2]  
    this[index2] = tmp  
}
```

```
val list = mutableListOf(1, 2, 3)  
list.swap(0, 2)
```

JAVA INTEROPERABILITY

" Kotlin is designed with Java Interoperability in mind. Existing Java code can be called from Kotlin in a natural way, and Kotlin code can be used from Java rather smoothly as well. "

kotlinlang.org

JAVA INTEROPERABILITY

Calling Java from Kotlin

```
import java.time.LocalDate

fun getDate7DaysAgo(): LocalDate {
    return LocalDate.now().minusDays(7)
}
```

JAVA INTEROPERABILITY

Calling Kotlin from Java

```
data class Person(var name: String)
```

```
import util.Person;
```

```
public class JavaInterop {  
    public static void main(String[] args) {  
        Person dennis = new Person("Dennis");  
        String name = dennis.getName();  
    }  
}
```

JAVA INTEROPERABILITY

Control JVM byte code generation via annotations

- `@JvmName`
- `@JvmMultifileClass`
- `@JvmField`
- `@JvmStatic`
- `@JvmDefault`
- ...

MORE AWESOME FEATURES

- Coroutines
- Kotlin Native
- Scope functions
- Infix notation
- Ability to create DSLs
- Contracts
- ...

FURTHER INFORMATION

- <https://play.kotlinlang.org/byExample/overview>
- <https://play.kotlinlang.org/koans/overview>
- <https://kotlinlang.org/docs/reference/>
- <https://kotlinlang.org/docs/books.html>
- Medium - Roman Elizarov
- YouTube - KotlinConf 2018

THANK YOU!

Questions?