Timeline: Adding the time dimension to spreadsheets

ANONYMOUS AUTHOR(S)



Fig. 1. A flappy bird game clone in Timeline. ❶ The selected formula computes the Y velocity in the current step. ❷ The system uses discrete time. ❸ Visualizations are built using a composable grammar of graphics and ❹ can be displayed inline or in a separate panel. The formula for the velocity Ⓐ specifies an initial value, Ⓑ reacts to user-interface events, and Ⓒ accesses a previous value to compute the current one.

Spreadsheets make it easy to express computations over two-dimensional data, but two dimensions are not enough to express rich computations with time such as simulations, complex systems models, analyses of historical data, or interactive systems. We present Timeline, a system that adds discrete time to spreadsheets.

The remarkable insight from our work is that a large number of advanced programming language concepts can be directly applied in the context of spreadsheets with time. Timeline draws from *dataflow languages* to express computations over time, *coeffect systems* to store only the necessary previous values, *functional reactive programming* to support interactivity, *grammars of graphics* to support composable visualizations, and *typed holes* for inserting cell references in the formula editor.

In this paper, we provide an overview of the Timeline design and discuss how it adapts the aforementioned programming language innovations for the context of spreadsheets. We then formalize the evaluation of spreadsheets with discrete time through a *core calculus*, describe a coeffect-based inference for computing the required number of past values and prove that the optimization is sound. More broadly, this paper shows that established programming language ideas can often be productively used outside of their original domain.

CCS Concepts: • **Software and its engineering → Very high level languages**.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.
© 2026 Copyright held by the owner/author(s). Publication rights licensed to ACM.
ACM 1557-735X/2026/8-ART111
https://doi.org/XXXXXXX.XXXXXXX

1 Introduction

Spreadsheets are sometimes referred to as "the most widely used programming systems in the world" [2]. Their uses range from personal productivity tools and decision making support systems to scientific analytical instruments and financial reporting systems [13]. However, spreadsheets are first-order, limited to tabular data structures, and lack abstraction mechanisms.

Many extensions to the core spreadsheet model have been proposed, generalising the tabular structure to more general forms [4, 8], adding support for objects [22], or incorporating support for streaming data to use spreadsheets as the back-end for web development [9, 10]. Abstraction mechanism developed for spreadsheets include sheet-defined functions [18, 27] and gridlets [17], while programming by example [14] simplifies data wrangling within spreadsheets.

As the above extensions show, extending spreadsheets is a difficult balancing act. How can we make spreadsheets more expressive, while preserving their liveness, directness and usability [16]? The aim of the Timeline project is to extend spreadsheets with a built-in notion of discrete time, making it possible to use spreadsheets in a range of domains that are difficult to tackle with only two dimensions [19] such as physics simulations, agent-based modelling [1], financial data analysis, or simple interactive applications. As illustrated in Figure 1, Timeline adds an implicit discrete time to the spreadsheet programming model and extends the formula language to allow references to previous values and user interface events, but otherwise preserves the standard spreadsheet model.

Adapting programming langauge research. Although Timeline is interesting as an exploration of the expressive power of spreadsheets with discrete time, this paper considers it primarily from the technical perspective of programming language design and implementation. We show that a large number of concepts and techniques developed in the context of programming language research are directly applicable to spreadsheets.

The key addition to Timeline is a built-in notion of discrete time. Formulas in cells can refer to other cells (e.g. `G19`), but also values computed in earlier steps (e.g. `F19[-1]`). The language design and runtime implementation of Timeline draws inspiration from research on *synchronous dataflow languages* [5, 15]. To ensure that simulations and interactive applications execute using bounded memory whenever possible, we augment the runtime with a program analysis based on *coeffects* [25, 26]. The support for discrete times also makes it possible to use the spreadsheet paradigm for building interactive applications. Here, we draw on the *functional reactive programming* paradigm [12, 28]. Although not strictly related to time, Timeline also adopts a *composable data visualization* model [20, 24, 29]. Finally, the Timeline also uses a notion of *typed holes* [23] to determine when the user may want to insert a cell reference during formula editing.

Contributions. This paper presents the design and implementation of a spreadsheet system with discrete time and captures its essence through a core calculus.

- We provide an overview of the Timeline system design through a simple physics simulation example (§2) and then examine the expressive power of the programming model through a number of case studies covering agent-based modelling, simulations and finance (§5).
- We discuss how how the design and implementation of Timeline adapts a range of advanced programming language concepts and techniques for the context of spreadsheet systems (§3), including dataflow languages, coeffects, functional reactive programming, visualization grammars and typed holes.
- We present a core calculus of the Timeline execution model, which captures the way previous values are stored during the spreadsheet evaluation (§4). We formalize a space optimization based on coeffects implemented in Timeline and prove its soundness (§4.6).



Fig. 2. Cannon ball.

2 Overview

We overview Timeline using a simple cannonball firing simulation (Figure 2). In each step, the simulation computes the cannonball position using the position in the previous step and the current time step. We ignore air resistance, but this could be easily added to a stepwise simulation model. The simulation stops when the cannonballs hit the ground.

Cannonball movement. bar

```
E5 = 0 => IF(AND(F5 == 0, STEP() != 1), E5[-1], E5[-1] + B5 * COS(RADIANS(C5)))
F5 = 0 => MAX(0, F5[-1] + B5 * SIN(RADIANS(C5)) - 1/2 * D5 * POWER(STEP(), 2))
```

3 Language features

3.1 Synchronous languages

3.2 Coeffects

3.3 Functional reactive programming

3.4 Composable data vis

3.5 Typed holes

Column name	N	$=$	A | B | C | ...	**Value**	V	$=$	$c \mid \{V_{i,j}\}$
Row index	m	$\in$	$\mathbb{N}_1$	**Formula**	F	$=$	$V \mid R \mid f(F_1, \ldots, F_n)$
Address	a	$=$	Nm	**Sheet**	σ	$\in$	$Address \longrightarrow Formula$
Range	R	$=$	$a_1 : a_2$	**Grid**	γ	$\in$	$Address \longrightarrow Value$

Fig. 3. Syntax of the core Timeline calculus.

Formula evaluation: $\sigma \vdash F \Downarrow V$

$$\mathsf{size}(N_1 m_1 : N_2 m_2) = (N_2 - N_1 + 1, m_2 - m_1 + 1)$$
$$N_1 m_1 + (i, j) = (N_1 + i - 1)(m_1 + j - 1)$$

$$\frac{}{\sigma \vdash V \Downarrow V} \qquad \frac{\sigma \vdash F_i \Downarrow V_i \quad [\![f]\!](V_1, \ldots, V_n) = V}{\sigma \vdash f(F_1, \ldots, F_n) \Downarrow V} \qquad \frac{\sigma \vdash a \,!\, V}{\sigma \vdash a : a \Downarrow V}$$

$$\frac{a_1 \neq a_2 \quad \mathsf{size}(a_1 : a_2) = (n, m) \quad \forall i \in 1..n, j \in 1..m \,.\, \sigma \vdash (a_1 + (i, j)) \,!\, V_{i,j}}{\sigma \vdash a_1 : a_2 \Downarrow \{V_{i,j}\}}$$

Address dereferencing: $\sigma \vdash a \,!\, V$

$$\frac{\sigma(a) = F \quad \sigma \vdash F \Downarrow V}{\sigma \vdash a \,!\, V}$$

Sheet evaluation: $\sigma \Downarrow \gamma$

$$\frac{\forall a \in \mathsf{dom}(\sigma) \,.\, \gamma(a) = V \wedge \sigma \vdash \sigma(a) \Downarrow V}{\sigma \Downarrow \gamma}$$

Fig. 4. Reduction rules that define formula evaluation of the core Timeline calculus.

4 Calculus

In this section, we present a core calculus of Timeline. We take the *core calculus for spreadsheets* [30] as our starting point (§4.1, §4.2), extend it with the notion of time (§4.3, §4.4) and then discuss our coeffect-based optimization (§4.5) and show its soundness (§4.6).

4.1 Syntax

Figure 3 defines the syntax of the calculus. Addresses Nm consist of a column name (such as A, AB) and a row index (starting from 1) and ranges are pairs of addresses. Values can be constants c or a two-dimensional arrays $\{V_{i,j}\}$ with indices $i \in 1..n$, $j \in 1..m$.

We treat error values as constants and omit explicit empty values [30] and explicit error propagation [7] for simplicity (functions called with error value as an argument return an error). Although we do not support spilling [30], we include arrays of values and later extend those to support ranges over time. Note also that a singleton array $\{V\}$ is distinct from a primitive value V. Formulas can be primitive values V, range references R or built-in function calls. For simplicity, cells can only be referenced through ranges so a reference B5 are modelled as a singleton range reference B5:B5.

Time	t	$\in$	$\mathbb{N}_1$	**Expression**	E	$=$	$V \mid R \mid f(E_1, \ldots, E_n)$
Interval	T	$=$	$-t_1 : -t_2$	**Formula**	F	$=$	$E \mid E \Rightarrow F$
Range	R	$=$	$a_1 : a_2 \mid a_1 : a_2[\tau]$	**Timeline**	ι	$\in$	$\{1 \ldots t\} \rightarrow \mathit{Value}$
Value	V	$=$	$\ldots \mid \{V_{t,i,j}\}$	**History**	ω	$\in$	$\mathit{Address} \rightarrow \mathit{Timeline}$

Fig. 5. Syntax of the Timeline calculus with time.

Following the terminology of Williams et al. [30], we use the term *sheet* to refer to the source code and *grid* for the result of evaluating a sheet. A sheet σ is a partial function from addresses to formulas, while a grid γ is a partial function from addresses to values.

4.2 Semantics

The evaluation rules are defined in Figure 4. We follow the style of Williams et al. [30] and define evaluation with respect to a an unevaluated sheet σ. This means that dereferencing an address, defined as an auxiliary relation $\sigma \vdash a\,!\,V$ obtains the formula of the target cell and evaluates it recursively. Consequently, evaluation of cyclic references is not defined. An alternative approach [7] defines evaluation with respect to (other) evaluated values as $\gamma \vdash F \Downarrow V$ and imposes consistency requirements on the recalculation process. This rules out cyclic references for which there is no consistent value assignment, such as A1 = A1 + 1, but permits self-references such as A1 = A1.

Formula evaluation $\sigma \vdash F \Downarrow V$ is then a relation that evaluates a formula F to a value V given the sheet definition σ. A value V evaluates to itself. A function call $f(F_1, \ldots, F_n)$ evaluates its arguments and then obtains the result by applying $[\![f]\!]$, which defines the semantics of the built-in function, to the arguments. Evaluating a singleton range $a : a$ obtains a single value at the given address using dereferencing. Evaluating a range $a_1 : a_n$ iterates over all addresses in the range. The helper size returns the size of the range and $a + (i, j)$ returns an address moved by 1-based offsets i and j.

Sheet evaluation $\sigma \Downarrow \gamma$ evaluates the value at each address $a \in \mathrm{dom}(\sigma)$ defined in the sheet σ. We do not specify evaluation order, but the evaluation is still deterministic (§4.6). Our Timeline implementation builds a dependency graph between cells and evaluates them in a topological order. As discussed earlier, sheet evaluation is not defined for sheets containing a cyclic reference.

4.3 Adding the time dimension

To model Timeline, we extend the core calculus with a notion of discrete time. The extended syntax is shown in Figure 5. Time t is modelled using positive integers and, following the Timeline implementation, we refer to history using negative values $-t$. An interval is defined by a pair of time values. A range R can now refer to a three-dimensional range over a sheet area and a time interval. A reference to a single past value such as `F19[-1]` is modelled as a singleton range `F19:F19[-1:-1]`. Evaluating a reference to a three-dimensional range produces a three-dimensional array of values, represented as a new kind of value written as $\{V_{t,i,j}\}$.

Note that intervals can only range over historical values and so we cannot write, for example, `SUM(F19[0:-1])` to add the current and the previous value of `F19`. This simplifies the model as previous and current values are stored differently. Corresponding computations can be expressed explicitly using, for example, `F19+F19[-1]`.

To model the *followed by* operator $\Rightarrow$, we separate formulas F and expressions E. A formula can be an expression, or a formula prefixed with an initial value (i.e., a formula has zero or more prefixed values). In addition to the previously defined grid γ, we maintain the history of previously evaluated values. A history ω is a partial function mapping addresses to timelines. A timeline stores a continuous range of t previous values of a cell, indexed by a time interval from 1 to t.

$\boxed{\text{Formula evaluation: } \sigma, \omega \vdash F \Downarrow V}$

$$N_1 m_1[-t_1] + (t, i, j) = (N_1 + i - 1)(m_1 + j - 1)[-(t_1 + t - 1)]$$

$$\frac{\sigma, \omega \vdash F \Downarrow V}{\sigma, \omega \vdash E \Rightarrow F \Downarrow V} \qquad \frac{\omega \vdash a[-t] \mathbin{¡} V}{\sigma, \omega \vdash a{:}a[-t{:}-t] \Downarrow V}$$

$$\frac{\begin{array}{c} a_1 \neq a_2 \vee t_1 \neq t_2 \qquad \mathsf{size}(a_1{:}a_2) = (n, m) \qquad l = t_2 - t_1 + 1 \\ \forall i \in 1..n, j \in 1..m, t \in 1..l \,.\, \omega \vdash a_1[-t_1] + (t, i, j) \mathbin{¡} V_{t,i,j} \end{array}}{\sigma, \omega \vdash a_1{:}a_2[-t_1{:}-t_2] \Downarrow \{V_{t,i,j}\}}$$

$\boxed{\text{History access: } \omega \vdash a[-t] \mathbin{¡} V}$ $\boxed{\text{Sheet evaluation: } \sigma, \omega \Downarrow \gamma}$

$$\frac{\omega(a)(t) = F}{\omega \vdash a[-t] \mathbin{¡} V} \qquad \frac{\forall a \in \mathsf{dom}(\sigma) \,.\, \gamma(a) = V \wedge \sigma, \omega \vdash \sigma(a) \Downarrow V}{\sigma, \omega \Downarrow \gamma}$$

Fig. 6. Reduction rules that define formula evaluation of the Timeline calculus with time.

Figure 6 defines the extended semantics. Formula evaluation is now defined with respect to the sheet σ but also previously evaluated values represented using a history ω. The additional context can be easily added to the rules in Figure 6, but we define new rules for three-dimensional ranges and formulas prefixed with initial values. The value of $E \Rightarrow F$ is the value of F. The initial value will be used later, when initializing the history ω.

To access past values, we define an auxiliary relation $\omega \vdash a[-t] \mathbin{¡} V$ akin to address dereferencing. However, the relation is defined with respect to the previously evaluated values and it accesses the past value from the timeline, rather than evaluating it.

The evaluation again distinguishes the case when a range refers to a single value. If so, the value is obtained from the history and returned. For larger ranges, we iterate over all the values and build a three-dimensional array $\{V_{t,i,j}\}$. We extend our earlier auxiliary definition of + to also support computing an offset for an address at a specified time. The sheet evaluation remains unchanged, except that it now provides the history ω to the formula evaluation. It evaluates the current values of the formulas, with respect to a given history.

TODO: Also model the case where interval is defined by expressions. This leads to unbounded buffers.
TODO: Also model some special functions, at least STEP().

4.4 Running the computation

Evaluation in time

$$\begin{array}{ll} \omega_0(a) = \{1 \mapsto V_1, \ldots, k \mapsto V_k\} & \text{if } \sigma(a) = E_k \Rightarrow \ldots \Rightarrow E_1 \Rightarrow E \\ \text{where } \sigma, \emptyset \vdash E_i \Downarrow V_i & \end{array}$$

$$\begin{array}{ll} \omega_{n+1}(a)(1) = \gamma_n(a) & \\ \omega_{n+1}(a)(1+t) = \omega_n(t) & \text{where } \sigma, \omega_n \Downarrow \gamma_n \end{array}$$

4.5 Coeffect optimization

$\mathcal{B} : \mathit{Address} \to \mathbb{N}_0$

4.6 Properties and coeffect soundness

sheet evaluation is deterministic?

5 Case studies

5.1 Formative interviews

6 Related work

static analysis [11] type inference [3]

sheet defined functions [18] [27] and their semantics [7] elastic [21]

gridlets [17] and their semantics [30] [6]

References

[1] Sameera Abar, Georgios K. Theodoropoulos, Pierre Lemarinier, and Gregory M.P. O'Hare. 2017. Agent Based Modelling and Simulation tools: A review of the state-of-art software. *Computer Science Review* 24 (2017), 13–33. doi:10.1016/j.cosrev.2017.03.001

[2] Robin Abraham, Margaret Burnett, and Martin Erwig. 2009. *Spreadsheet Programming*. John Wiley & Sons, Ltd, 2804–2810. doi:10.1002/9780470050118.ecse415

[3] Robin Abraham and Martin Erwig. 2006. Type inference for spreadsheets. In *Proceedings of the 8th ACM SIGPLAN International Conference on Principles and Practice of Declarative Programming* (Venice, Italy) *(PPDP '06)*. Association for Computing Machinery, New York, NY, USA, 73–84. doi:10.1145/1140335.1140346

[4] Pavel Bažant and Michaela Maršálková. 2018. A Non-Tabular Spreadsheet with Broad Applicability. In *Companion Proceedings of the 2nd International Conference on the Art, Science, and Engineering of Programming (Programming '18)*. Association for Computing Machinery, New York, NY, USA, 161–165. doi:10.1145/3191697.3214343

[5] A. Benveniste, P. Caspi, S.A. Edwards, N. Halbwachs, P. Le Guernic, and R. de Simone. 2003. The synchronous languages 12 years later. *Proc. IEEE* 91, 1 (2003), 64–83. doi:10.1109/JPROC.2002.805826

[6] Alexander Asp Bock, Thomas Bøgholm, Peter Sestoft, Bent Thomsen, and Lone Leth Thomsen. 2022. On the cost semantics for spreadsheets with sheet-defined functions. *J. Comput. Lang.* 69 (2022), 101103. doi:10.1016/J.COLA.2022.101103

[7] Alexander Asp Bock, Thomas Bøgholm, Peter Sestoft, Bent Thomsen, and Lone Leth Thomsen. 2020. On the semantics for spreadsheets with sheet-defined functions. *Journal of Computer Languages* 57 (2020), 100960. doi:10.1016/j.cola.2020.100960

[8] MARGARET BURNETT, JOHN ATWOOD, REBECCA WALPOLE DJANG, JAMES REICHWEIN, HERKIMER GOTTFRIED, and SHERRY YANG. 2001. Forms/3: A first-order visual language to explore the boundaries of the spreadsheet paradigm. *Journal of Functional Programming* 11, 2 (2001), 155–206. doi:10.1017/S0956796800003828

[9] Kerry Shih-Ping Chang and Brad A. Myers. 2014. Creating Interactive Web Data Applications with Spreadsheets. In *Proceedings of the 27th Annual ACM Symposium on User Interface Software and Technology (UIST '14)*. Association for Computing Machinery, New York, NY, USA, 87–96. doi:10.1145/2642918.2647371

[10] Kerry Shih-Ping Chang and Brad A. Myers. 2015. A Spreadsheet Model for Handling Streaming Data. In *Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems (CHI '15)*. Association for Computing Machinery, New York, NY, USA, 3399–3402. doi:10.1145/2702123.2702587

[11] Tie Cheng and Xavier Rival. 2015. Static Analysis of Spreadsheet Applications for Type-Unsafe Operations Detection. In *Programming Languages and Systems*, Jan Vitek (Ed.). Springer Berlin Heidelberg, Berlin, Heidelberg, 26–52.

[12] Conal Elliott and Paul Hudak. 1997. Functional reactive animation. In *Proceedings of the Second ACM SIGPLAN International Conference on Functional Programming* (Amsterdam, The Netherlands) *(ICFP '97)*. Association for Computing Machinery, New York, NY, USA, 263–273. doi:10.1145/258948.258973

[13] Thomas A Grossman and Vijay Mehrotra. 2023. A Use Case-Engineering Resources Taxonomy for Analytical Spreadsheet Models. In *21st EuSpRIG Annual Conference "The Spreadsheet Crisis: Regaining Control"*.

[14] Sumit Gulwani, William R. Harris, and Rishabh Singh. 2012. Spreadsheet Data Manipulation Using Examples. *Commun. ACM* 55, 8 (Aug. 2012), 97–105. doi:10.1145/2240236.2240260

[15] N. Halbwachs, P. Caspi, P. Raymond, and D. Pilaud. 1991. The synchronous data flow programming language LUSTRE. *Proc. IEEE* 79, 9 (1991), 1305–1320. doi:10.1109/5.97300

[16] Felienne Hermans, Bas Jansen, Sohon Roy, Efthimia Aivaloglou, Alaaeddin Swidan, and David Hoepelman. 2016. Spreadsheets are Code: An Overview of Software Engineering Approaches Applied to Spreadsheets. In *2016 IEEE 23rd International Conference on Software Analysis, Evolution, and Reengineering (SANER)*, Vol. 5. 56–65. doi:10.1109/SANER.2016.86

[17] Nima Joharizadeh, Advait Sarkar, Andrew D. Gordon, and Jack Williams. 2020. Gridlets: Reusing Spreadsheet Grids. In *Extended Abstracts of the 2020 CHI Conference on Human Factors in Computing Systems* (Honolulu, HI, USA) *(CHI EA '20)*. Association for Computing Machinery, New York, NY, USA, 1–7. doi:10.1145/3334480.3382806

[18] Simon Peyton Jones, Alan Blackwell, and Margaret Burnett. 2003. A user-centred approach to functions in Excel. In *Proceedings of the Eighth ACM SIGPLAN International Conference on Functional Programming* (Uppsala, Sweden) *(ICFP '03)*. Association for Computing Machinery, New York, NY, USA, 165–176. doi:10.1145/944705.944721

[19] Steve Litt. 2017. Mitigating Spreadsheet Risk in Complex Multi-Dimensional Models in Excel. In *Proceedings of the EuSpRIG 2017 Conference "Spreadsheet Risk Management"*. European Spreadsheet Risks Interest Group (EuSpRIG), London, UK.

[20] Mariana Marasoiu, Detlef Nauck, and Alan F. Blackwell. 2019. Cuscus: An End User Programming Tool for Data Visualisation. In *End-User Development*, Alessio Malizia, Stefano Valtolina, Anders Morch, Alan Serrano, and Andrew Stratton (Eds.). Springer International Publishing, Cham, 115–131.

[21] Matt McCutchen, Judith Borghouts, Andrew D. Gordon, Simon Peyton Jones, and Advait Sarkar. 2020. Elastic sheet-defined functions: Generalising spreadsheet functions to variable-size input arrays. *Journal of Functional Programming* 30 (2020), e26. doi:10.1017/S0956796820000234

[22] Matt McCutchen, Shachar Itzhaky, and Daniel Jackson. 2016. Object Spreadsheets: A New Computational Model for End-User Development of Data-Centric Web Applications. In *Proceedings of the 2016 ACM International Symposium on New Ideas, New Paradigms, and Reflections on Programming and Software (Onward! 2016)*. Association for Computing Machinery, New York, NY, USA, 112–127. doi:10.1145/2986012.2986018

[23] Cyrus Omar, Ian Voysey, Ravi Chugh, and Matthew A. Hammer. 2019. Live functional programming with typed holes. *Proc. ACM Program. Lang.* 3, POPL, Article 14 (Jan. 2019), 32 pages. doi:10.1145/3290327

[24] TOMAS PETRICEK. 2021. Composable data visualizations. *Journal of Functional Programming* 31 (2021), e13. doi:10.1017/S0956796821000046

[25] Tomas Petricek, Dominic Orchard, and Alan Mycroft. 2013. Coeffects: Unified Static Analysis of Context-Dependence. In *Automata, Languages, and Programming*, Fedor V. Fomin, Rūsiņš Freivalds, Marta Kwiatkowska, and David Peleg (Eds.). Springer Berlin Heidelberg, 385–397.

[26] Tomas Petricek, Dominic Orchard, and Alan Mycroft. 2014. Coeffects: a calculus of context-dependent computation. In *Proceedings of the 19th ACM SIGPLAN International Conference on Functional Programming* (Gothenburg, Sweden) *(ICFP '14)*. Association for Computing Machinery, New York, NY, USA, 123–135. doi:10.1145/2628136.2628160

[27] Peter Sestoft and Jens Zeilund Sørensen. 2013. Sheet-Defined Functions: Implementation and Initial Evaluation. In *End-User Development*, Yvonne Dittrich, Margaret Burnett, Anders Mørch, and David Redmiles (Eds.). Springer Berlin Heidelberg, Berlin, Heidelberg, 88–103.

[28] Zhanyong Wan and Paul Hudak. 2000. Functional reactive programming from first principles. In *Proceedings of the ACM SIGPLAN 2000 Conference on Programming Language Design and Implementation* (Vancouver, British Columbia, Canada) *(PLDI '00)*. Association for Computing Machinery, New York, NY, USA, 242–252. doi:10.1145/349299.349331

[29] Leland Wilkinson. 2012. *The Grammar of Graphics*. Springer Berlin Heidelberg, 375–414. doi:10.1007/978-3-642-21551-3_13

[30] Jack Williams, Nima Joharizadeh, Andrew D. Gordon, and Advait Sarkar. 2020. Higher-Order Spreadsheets with Spilled Arrays. In *Programming Languages and Systems - 29th European Symposium on Programming, ESOP 2020 (Lecture Notes in Computer Science, Vol. 12075)*, Peter Müller (Ed.). Springer, 743–769. doi:10.1007/978-3-030-44914-8_27