

# CPSC 213, Winter 2010, Term 1 — Quiz 2

Date: Oct 20, 2010; Instructor: Tamara Munzner

NAME: \_\_\_\_\_ STUDENT NUMBER: \_\_\_\_\_

**1** Consider the following C code.

```
int a[10] = { 1, 1, 2, 3, 5, 8, 13, 21, 34, 55};  
int j = *(a+(&a[4]-&a[1]) + *(&a[5]-3));
```

Does the execution of this code generate a runtime error? If not, what is the value of j after the code executes? **Show your work/calculations to justify your answer.**

**2** Give the SM213 assembly code that a compiler might generate for the function foo in the following C code; include comments. Assume that the location in memory for the variable a is 0x1000. You do not need to write down any .address/.pos specifications, just the assembly language commands.

```
struct A {  
    int i;  
    int j;  
};  
  
struct A* a;  
void foo () {  
    a->i = a->j + 3;  
}
```

SM213 assembly code with comments.

**3** Compare the following two alternatives implementing a similar computation. Recall that "strncpy (s1, s2, n)" copies string s2 into strings s1.

```
char* foo () {  
    char* x = (char*) malloc (11);  
    strncpy (x, "Tra la la!", 11);  
    return x;  
}  
  
void bar () {  
    char* y = foo ();  
}
```

```
char* foo () {  
    char* x = (char*) malloc (11);  
    strncpy (x, "Tra la la!", 11);  
    free (x);  
    return x;  
}  
  
void bar () {  
    char* y = foo ();  
}
```

Both versions of this code have a different bug. Carefully describe each bug (give its name if you can) and then fix the code.

**3a** Describe the bug on left-hand side.

**3b** Describe the bug on right-hand side.

**3c** Re-write the code so that neither bug is present.

OpCode	Format	Semantics/RTL	Eg Machine	Eg Assembly
load immediate	0d-- vvvvvvvv	$r[d] \leftarrow v$	0100 00000100	ld \$0x1000, r1
load base+dis	1osd	$r[d] \leftarrow m[o \times 4 + r[s]]$	1123	ld 4(r2), r3
load indexed	2sid	$r[d] \leftarrow m[r[i] \times 4 + r[s]]$	2123	ld (r1, r2, 4), r3
store base+dis	3sod	$m[o \times 4 + r[d]] \leftarrow r[s]$	3123	st r1, 8(r3)
store indexed	4sdi	$m[r[i] \times 4 + r[d]] \leftarrow r[s]$	4123	st r1, (r2, r3, 4)
halt	f000		f000	halt
nop	ff00		ff00	do nothing (nop)
rr move	60sd	$r[d] \leftarrow r[s]$	6012	mov r1, r2
add	61sd	$r[d] \leftarrow r[d] + r[s]$	6112	add r1, r2
and	62sd	$r[d] \leftarrow r[d] \& r[s]$	6212	and r1, r2
inc	63-d	$r[d] \leftarrow r[d] + 1$	6301	inc r1
inc addr	64-d	$r[d] \leftarrow r[d] + 4$	6401	inca r1
dec	65-d	$r[d] \leftarrow r[d] - 1$	6501	dec r1
dec addr	66-d	$r[d] \leftarrow r[d] - 4$	6601	deca r1
not	67-d	$r[d] \leftarrow !r[d]$	6701	not r1
shift	7dss	$r[d] \leftarrow r[d] \ll s$	7102 71fe	shl \$2, r1 shr \$2, r1
branch	8-oo	$pc \leftarrow pc + 2 \times o$	1000: 8004	br 0x1008
branch if equal	9roo	if $r[r] == 0$ , $pc \leftarrow pc + 2 \times o$	1000: 9104	beq r1, 0x1008
branch if greater	aroo	if $r[r] > 0$ , $pc \leftarrow pc + 2 \times o$	1000: a104	bgt r1, 0x1008
jump	b--- aaaaaaaa	$pc \leftarrow a$	b000 00001000	jmp 0x1000
get program counter	6f-d	$r[d] \leftarrow pc$	6f01	gpc r1
jump indirect	croo	$pc \leftarrow r[r] + 2 \times o$	c102	jmp 8(r1)
jump double ind, b+disp	droo	$pc \leftarrow m[4 \times o + r[r]]$	d102	jmp *8(r1)
jump double ind, index	eri-	$pc \leftarrow m[4 \times r[i] + r[r]]$	e120	jmp *(r1, r2, 4)