
## CPSC 313, Winter 2006 - Term 2 Pipelining


Assigned: March 9, Due: Sunday, March 18, 11:59PM

All of these questions are to be handed in on paper.

1. Consider a five-stage pipeline with stage gate delays of 150 ps, 75 ps, 100 ps, 100 ps and 175 ps and a memory delay of 10 ps, as shown below. Signals flow from left to right.



- (a) What is the maximum clock frequency this circuit could tolerate, measured in cycles per second?
- (b) What is best throughput this circuit could produce, measured in instructions-completed per second?
- (c) What is the execution latency of a single instruction, measured in seconds per instruction?
- (d) Answer questions a-c for a similar circuit that is not pipelined (i.e., where each stage is connected back-to-back with no intervening memory, as shown below)?



- (e) Suppose that in order to improve the throughput of the pipeline you could split a single stage into two equal sized stages. Which stage would you split to maximize the throughput improvement?
- (f) What if you could split 2 stages in half, which 2 stages would you split?
- (g) Answer questions a-c for your resulting seven-stage pipeline.
- 2. For each of the following code fragments indicate whether a data or control dependency exists and explain by giving the type of the dependency (i.e., control, causal, anti, or output) and indicating the registers involved.

```
(a)
          addl %eax, %ebx
          addl %ebx, %ecx
(b)
          irmovl $10, %ebx
          addl %ebx, %ecx
          mrmovl 10(%eax), %ebx
(c)
          addl %ebx, %ecx
(d)
          rmmovl %ecx, 10(%eax)
          irmovl $10, %ecx
          rmmovl %ebx, (%eax)
(e)
          rmmovl %ecx, (%eax)
(f)
          jmp target
          jle less-equal
(g)
(h)
          ret
```

- 3. Can any of the dependencies listed in problem 2 be eliminated simply by re-writing the assembly code? List all that can, explaining why and giving the revised code. (NOTE: you may assume that the remainder of the code that isn't shown in the problem can be changed in a similar manner.)
- 4. For each of the code fragments in problem 2, indicate whether a hazard exists in the y86 pipeline. Briefly explain why or why not.