

CPSC 213

Answers to Part II of Midterm Practice Questions

Part II

Question 1

```
ld  $0x3000, r0      # r0 = address of b
ld  0x0(r0), r0      # r0 = address of array b
ld  0x8(r0), r1      # r1 = *(b+2)
ld  $0x1000, r2      # r2 = address of i
ld  0x0(r2), r2      # r2 = i
ld  $0x2000, r3      # r3 = address of a
st  r1, (4*r2, r3)   # a[i] = r1
```

Question 2

We assume:

- i is stored at location 1000
- r5 points to the location for j and k is in the next word after k
That is, we assume that foo stoted r6 on the stack before calls bar(), and removed it after bar returned.

```
ld  $0x0 r0          # r0 = 0
ld  $0x1000, r1      # r1 = address of i
st  r0, 0x0(r1)      # i = 0
st  r0, 0x0(r5)      # j = 0
st  r0, 0x4(r5)      # k = 0
```

Question 3


We assume:

- i is stored at location 1000
- foo does not need to store r6 on the stack, as it does not call any other function

```
ld  $0x0 r0          # r0 = 0
ld  $0x1000, r1       # r1 = address of i
st  r0, 0x0(r1)       # i = 0
st  r0, 0x8(r5)       # m = 0 , m is stored just below k
st  r0, 0x0(r5)       # j = 0
st  r0, 0x4(r5)       # k = 0
```

Question 4

The following diagram shows the final values:



Question 5

The C code that correspond to the given assembly code is:

```
int sum (int* a, int aLength) {
    int i;
    int s;
    s = 0;
    for (i=0; i<aLength; i++)
        s += a[i];
    return s;
}
```

Question 6

```
typedef struct {
    int  noSides;           //number of sides
    float *  side;         // a dynamic array with the length of each side
} Polygon;
```

```
Polygon* createPolygon( int n ) {
    Polygon* p = (Polygon *) malloc( sizeof(Polygon));
    p->noSides = n;
    p->side = (float *) malloc( n * sizeof(float));
    return p;
}
```

```
setSide(Polygon* pg, int s, float length) {
    if ( 0 <= s && s < pg->noSides )
        pg->side[s] = length;
}
```

. . .