# **R Reference Card for Data Mining**

Yanchang Zhao, RDataMining.com, July 9, 2014

- See the latest version at http://www.RDataMining.com
- The package names are in parentheses.
- Recommended packages and functions are shown in bold.
- Click a package in this PDF file to find it on CRAN.

# **Association Rules and Sequential Patterns**

#### **Functions**

apriori() mine associations with APRIORI algorithm – a level-wise, breadth-first algorithm which counts transactions to find frequent itemsets (arules)

eclat () mine frequent itemsets with the Eclat algorithm, which employs equivalence classes, depth-first search and set intersection instead of counting (arules)

cspade() mine frequent sequential patterns with the cSPADE algorithm (arulesSequences)

seqef sub () search for frequent subsequences (TraMineR)

### **Packages**

arules mine frequent itemsets, maximal frequent itemsets, closed frequent itemsets and association rules. It includes two algorithms, Apriori and Eclat.

arules Viz visualizing association rules

arulesSequences add-on for arules to handle and mine frequent sequences TraMineR mining, describing and visualizing sequences of states or events

# **Classification & Prediction**

#### **Decision Trees**

ctree () conditional inference trees, recursive partitioning for continuous, censored, ordered, nominal and multivariate response variables in a conditional inference framework (party)

rpart () recursive partitioning and regression trees (rpart)

mob () model-based recursive partitioning, yielding a tree with fitted models associated with each terminal node (party)

#### Random Forest

cforest () random forest and bagging ensemble (party)

randomForest() random forest(randomForest)

importance() variable importance (randomForest)

varimp() variable importance (party)

#### **Neural Networks**

nnet () fit single-hidden-layer neural network (nnet)

neuralnet training of neural networks (neuralnet)

## **Support Vector Machine (SVM)**

svm() train a support vector machine for regression, classification or densityestimation (e1071)

ksvm() support vector machines (kernlab)

### **Bayes Classifiers**

naiveBayes () naive Bayes classifier (e1071)

#### **Performance Evaluation**

**performance ()** provide various measures for evaluating performance of prediction and classification models (*ROCR*)

**PRcurve ()** precision-recall curves (*DMwR*)

**CRchart ()** cumulative recall charts (*DMwR*)

roc() build a ROC curve (pROC)

auc () compute the area under the ROC curve (pROC)

ROC () draw a ROC curve (DiagnosisMed)

### **Packages**

party recursive partitioning

rpart recursive partitioning and regression trees

randomForest classification and regression based on a forest of trees using random inputs

**ROCR** visualize the performance of scoring classifiers

caret classification and regression models

r1071 functions for latent class analysis, short time Fourier transform, fuzzy clustering, support vector machines, shortest path computation, bagged clustering, naive Bayes classifier, ...

rpartOrdinal ordinal classification trees, deriving a classification tree when the response to be predicted is ordinal

rpart.plot plots rpart models

pROC display and analyze ROC curves

nnet feed-forward neural networks and multinomial log-linear models

RSNNS neural networks in R using the Stuttgart Neural Network Simulator (SNNS)

*neuralnet* training of neural networks using backpropagation, resilient backpropagation with or without weight backtracking

# Regression

### **Functions**

1m() linear regression

glm() generalized linear regression

**qbm ()** generalized boosted regression models (gbm)

predict () predict with models

residuals () residuals, the difference between observed values and fitted values

nls() non-linear regression

gls () fit a linear model using generalized least squares (nlme)

gnls () fit a nonlinear model using generalized least squares (nlme)

#### **Packages**

*nlme* linear and nonlinear mixed effects models *gbm* generalized boosted regression models

# **Clustering**

## **Partitioning based Clustering**

partition the data into k groups first and then try to improve the quality of clustering by moving objects from one group to another

**kmeans ()** perform k-means clustering on a data matrix

**kmeansruns ()** call kmeans for the k-means clustering method and includes estimation of the number of clusters and finding an optimal solution from several starting points (*fpc*)

pam () the Partitioning Around Medoids (PAM) clustering method (cluster)

**pamk ()** the Partitioning Around Medoids (PAM) clustering method with estimation of number of clusters (fpc)

kmeansCBI() interface function for kmeans (fpc)

cluster.optimal() search for the optimal k-clustering of the dataset (bayesclust)

clara() Clustering Large Applications (cluster)

fanny (x, k, . . . ) compute a fuzzy clustering of the data into k clusters (cluster)

kcca() k-centroids clustering (flexclust)

ccfkms () clustering with Conjugate Convex Functions (cba)

apcluster() affinity propagation clustering for a given similarity matrix (apcluster)

apclusterK() affinity propagation clustering to get K clusters (apcluster)

cclust () Convex Clustering, incl. k-means and two other clustering algorithms (cclust)

KMeansSparseCluster() sparse k-means clustering (sparcl)

tclust(x,k,alpha,...) trimmed k-means with which a proportion alpha of observations may be trimmed (*tclust*)

### **Hierarchical Clustering**

a hierarchical decomposition of data in either bottom-up (agglomerative) or topdown (divisive) way

hclust () hierarchical cluster analysis on a set of dissimilarities

birch() the BIRCH algorithm that clusters very large data with a CF-tree (birch)
pvclust() hierarchical clustering with p-values via multi-scale bootstrap resampling (pvclust)

agnes () agglomerative hierarchical clustering (cluster)

diana() divisive hierarchical clustering (*cluster*)

mona () divisive hierarchical clustering of a dataset with binary variables only (cluster)

rockCluster() cluster a data matrix using the Rock algorithm (cba)

proximus () cluster the rows of a logical matrix using the Proximus algorithm (cha)

isopam() Isopam clustering algorithm (isopam)

flashClust() optimal hierarchical clustering (flashClust)

fastcluster() fast hierarchical clustering (fastcluster)

cutreeDynamic(), cutreeHybrid() detection of clusters in hierarchical clustering dendrograms (dynamicTreeCut)

HierarchicalSparseCluster() hierarchical sparse clustering (sparcl)

# **Model based Clustering**

Mclust() model-based clustering (mclust)

HDDC () a model-based method for high dimensional data clustering (HDclassif)

fixmahal () Mahalanobis Fixed Point Clustering (fpc)

fixreg() Regression Fixed Point Clustering (fpc)

mergenormals () clustering by merging Gaussian mixture components (fpc)

# **Density based Clustering**

generate clusters by connecting dense regions

**dbscan (data, eps, MinPts,...)** generate a density based clustering of arbitrary shapes, with neighborhood radius set as eps and density threshold as MinPts (fpc)

pdfCluster() clustering via kernel density estimation (pdfCluster)

# **Other Clustering Techniques**

mixer() random graph clustering (mixer)

nncluster() fast clustering with restarted minimum spanning tree (nnclust) orclus() ORCLUS subspace clustering (orclus)



### **Plotting Clustering Solutions**

plotcluster() visualisation of a clustering or grouping in data (fpc)

bannerplot () a horizontal barplot visualizing a hierarchical clustering (cluster)

#### **Cluster Validation**

 $\verb|silhouette|()|$  compute or extract silhouette information (cluster)

cluster.stats() compute several cluster validity statistics from a clustering and a dissimilarity matrix (fpc)

clValid() calculate validation measures for a given set of clustering algorithms and number of clusters (clValid)

clustIndex() calculate the values of several clustering indexes, which can be independently used to determine the number of clusters existing in a data set (cclust)

NbClust () provide 30 indices for cluster validation and determining the number of clusters (NbClust)

### **Packages**

cluster cluster analysis

fpc various methods for clustering and cluster validation

mclust model-based clustering and normal mixture modeling

birch clustering very large datasets using the BIRCH algorithm

*pvclust* hierarchical clustering with p-values

apcluster Affinity Propagation Clustering

cclust Convex Clustering methods, including k-means algorithm, On-line Update algorithm and Neural Gas algorithm and calculation of indexes for finding the number of clusters in a data set

cba Clustering for Business Analytics, including clustering techniques such as Proximus and Rock

bclust Bayesian clustering using spike-and-slab hierarchical model, suitable for clustering high-dimensional data

biclust algorithms to find bi-clusters in two-dimensional data

clue cluster ensembles

clues clustering method based on local shrinking

clValid validation of clustering results

clv cluster validation techniques, contains popular internal and external cluster validation methods for outputs produced by package cluster

bayesclust tests/searches for significant clusters in genetic data

clustsig significant cluster analysis, tests to see which (if any) clusters are statistically different

clusterSim search for optimal clustering procedure for a data set

clusterGeneration random cluster generation

gcExplorer graphical cluster explorer

hybridHclust hybrid hierarchical clustering via mutual clusters

Modalclust hierarchical modal Clustering

*iCluster* integrative clustering of multiple genomic data types

EMCC evolutionary Monte Carlo (EMC) methods for clustering

rEMM extensible Markov Model (EMM) for data stream clustering

# **Outlier Detection**

#### **Functions**

boxplot.stats()\$out list data points lying beyond the extremes of the
 whiskers

**lofactor()** calculate local outlier factors using the LOF algorithm (*DMwR* or *dprep*)

lof() a parallel implementation of the LOF algorithm (*Rlof*)

#### **Packages**

**Rlof** a parallel implementation of the LOF algorithm extremevalues detect extreme values in one-dimensional data mvoutlier multivariate outlier detection based on robust methods outliers some tests commonly used for identifying outliers

# **Time Series Analysis**

#### **Construction & Plot**

ts() create time-series objects

plot.ts() plot time-series objects

smoothts() time series smoothing (ast)

sfilter() remove seasonal fluctuation using moving average (ast)

#### **Decomposition**

**decomp ()** time series decomposition by square-root filter (timsac)

decompose () classical seasonal decomposition by moving averages

**st1()** seasonal decomposition of time series by loess tsr() time series decomposition (ast)

ardec() time series autoregressive decomposition (ArDec)

### **Forecasting**

arima () fit an ARIMA model to a univariate time series

predict.Arima() forecast from models fitted by arima

auto.arima() fit best ARIMA model to univariate time series (forecast)

forecast.stl(), forecast.ets(), forecast.Arima()
 forecast time series using stl, ets and arima models (forecast)

### **Correlation and Covariance**

acf () autocovariance or autocorrelation of a time series

ccf () cross-correlation or cross-covariance of two univariate series

#### **Packages**

forecast displaying and analysing univariate time series forecasts

TSclust time series clustering utilities

dtw Dynamic Time Warping (DTW)

timsac time series analysis and control program

ast time series analysis

ArDec time series autoregressive-based decomposition

dse tools for multivariate, linear, time-invariant, time series models

# **Text Mining**

# **Text Cleaning and Preparation**

**Corpus ()** build a corpus, which is a collection of text documents (tm)

tm.map() transform text documents, e.g., stemming, stopword removal (tm) tm.filter() filtering out documents (tm)

TermDocumentMatrix(), DocumentTermMatrix() construct term-document matrix or a document-term matrix (tm)

Dictionary () construct a dictionary from a character vector or a termdocument matrix (tm)

**stemDocument ()** stem words in a text document (tm)

stemCompletion() complete stemmed words (tm)

SnowballStemmer() Snowball word stemmers (Snowball)

**stopwords (language)** return stopwords in different languages (tm)

removeNumbers(), removePunctuation(), removeWords() remove numbers, punctuation marks, or a set of words from a text document (tm)

removeSparseTerms() remove sparse terms from a term-document matrix (tm)

### **Frequent Terms and Association**

**findAssocs()** find associations in a term-document matrix (tm)

**findFreqTerms()** find frequent terms in a term-document matrix (tm)

termFreq() generate a term frequency vector from a text document (tm)

## **Topic Modelling**

**LDA ()** fit a LDA (latent Dirichlet allocation) model (*topicmodels*)

CTM() fit a CTM (correlated topics model) model (topicmodels)

terms () extract the most likely terms for each topic (topicmodels)

topics () extract the most likely topics for each document (topicmodels)

### **Sentiment Analysis**

polarity () polarity score (sentiment analysis) (qdap)

### **Text Categorization**

textcat() n-gram based text categorization (textcat)

#### **Text Visualizatoin**

wordcloud() plot a word cloud (wordcloud)

comparison.cloud() plot a cloud comparing the frequencies of words
across documents (wordcloud)

commonality.cloud() plot a cloud of words shared across documents
 (wordcloud)

### **Packages**

tm a framework for text mining applications

topicmodels fit topic models with LDA and CTM

wordcloud various word clouds

lda fit topic models with LDA

wordnet an interface to the WordNet

RTextTools automatic text classification via supervised learning

qdap transcript analysis, text mining and natural language processing

sentiment140 sentiment text analysis using free sentiment140 service

*tm.plugin.dc* a plug-in for package *tm* to support distributed text mining *tm.plugin.mail* a plug-in for package *tm* to handle mail

textir a suite of tools for inference about text documents and associated sentiment tau utilities for text analysis

textcat n-gram based text categorization

Rwordseg Chinese word segmentation using Ansi

# **Social Network Analysis and Graph Mining**

#### Functions

graph(), graph.edgelist(), graph.adjacency(),

**graph.incidence()** create graph objects respectively from edges, an edge list, an adjacency matrix and an incidence matrix (*igraph*)

plot(), tkplot(), rglplot() static, interactive and 3D plotting of graphs (igraph)

gplot(), gplot3d() plot graphs (sna)

vcount(), ecount() number of vertices/edges (igraph)

**V()**, **E()** vertex/edge sequence of igraph (*igraph*)


is.directed() whether the graph is directed (igraph)

are.connected() check whether two nodes are connected (igraph)

degree(), betweenness(), closeness(), transitivity() various centrality scores (igraph, sna)

add.edges(), add.vertices(), delete.edges(), delete.vertices()
 add and delete edges and vertices (igraph)

neighborhood() neighborhood of graph vertices (igraph, sna)





nei(), adj(), from(), to() vertex/edge sequence indexing (igraph) cliques(), largest.cliques(), maximal.cliques(), clique.number() find cliques, ie. complete subgraphs (*igraph*)

clusters(), no.clusters() maximal connected components of a graph and the number of them (*igraph*)

fastgreedy.community(), spinglass.community() community detection (igraph)

cohesive.blocks() calculate cohesive blocks (igraph)

induced.subgraph() create a subgraph of a graph (igraph)

%->%, %<-%, %--% edge sequence indexing (*igraph*)

get.edgelist() return an edge list in a two-column matrix (igraph)

read.graph(), write.graph() read and writ graphs from and to files of various formats (*igraph*)

### **Packages**

igraph network analysis and visualization

sna social network analysis

statnet a set of tools for the representation, visualization, analysis and simulation of network data

egonet ego-centric measures in social network analysis

snort social network-analysis on relational tables

network tools to create and modify network objects

bipartite visualising bipartite networks and calculating some (ecological) indices blockmodelinggeneralized and classical blockmodeling of valued networks diagram visualising simple graphs (networks), plotting flow diagrams

*NetCluster* clustering for networks

NetData network data for McFarland's SNA R labs

NetIndices estimating network indices, including trophic structure of foodwebs

NetworkAnalysis statistical inference on populations of weighted or unweighted

tnet analysis of weighted, two-mode, and longitudinal networks

# **Spatial Data Analysis**

#### **Functions**

**geocode ()** geocodes a location using Google Maps (ggmap)

plotGoogleMaps () create a plot of spatial data on Google Maps (plot-GoogleMaps)

qmap () quick map plot (ggmap)

get\_map() queries the Google Maps, OpenStreetMap, or Stamen Maps server for a map at a certain location (ggmap)

qvisGeoChart(), qvisGeoMap(), qvisIntensityMap(), gvisMap () Google geo charts and maps (google Vis)

GetMap() download a static map from the Google server (*RgoogleMaps*)

ColorMap() plot levels of a variable in a colour-coded map (*RgoogleMaps*)

PlotOnStaticMap() overlay plot on background image of map tile (RgoogleMaps)

TextOnStaticMap() plot text on map (RgoogleMaps)

### **Packages**

plotGoogleMaps plot spatial data as HTML map mushup over Google Maps RgoogleMaps overlay on Google map tiles in R

ggmap Spatial visualization with Google Maps and OpenStreetMap plotKML visualization of spatial and spatio-temporal objects in Google Earth SGCS Spatial Graph based Clustering Summaries for spatial point patterns spdep spatial dependence: weighting schemes, statistics and models

## **Statistics**

#### Summarization

**summary()** summarize data

**describe ()** concise statistical description of data (*Hmisc*)

boxplot.stats() box plot statistics

## **Analysis of Variance**

aov () fit an analysis of variance model

anova () compute analysis of variance (or deviance) tables for one or more fitted model objects

#### **Statistical Tests**

chisq.test() chi-squared contingency table tests and goodness-of-fit tests

ks.test() Kolmogorov-Smirnov tests

t.test() student's t-test

prop.test() test of equal or given proportions

binom.test() exact binomial test

### **Mixed Effects Models**

lme () fit a linear mixed-effects model (nlme)

nlme() fit a nonlinear mixed-effects model (nlme)

### **Principal Components and Factor Analysis**

princomp () principal components analysis

prcomp() principal components analysis

#### **Other Functions**

var(), cov(), cor() variance, covariance, and correlation

density() compute kernel density estimates

cmdscale() Multidimensional Scaling (MDS)

## **Packages**

nlme linear and nonlinear mixed effects models

# **Graphics**

#### **Functions**

plot () generic function for plotting

barplot(), pie(), hist() bar chart, pie chart and histogram

boxplot () box-and-whisker plot

stripchart () one dimensional scatter plot

dotchart () Cleveland dot plot

qqnorm(), qqplot(), qqline() QQ (quantile-quantile) plot

coplot() conditioning plot

splom() conditional scatter plot matrices (lattice)

pairs () a matrix of scatterplots

cpairs () enhanced scatterplot matrix (gclus)

parcoord() parallel coordinate plot (MASS)

cparcoord() enhanced parallel coordinate plot (gclus)

parallelplot() parallel coordinates plot (lattice)

densityplot() kernel density plot (lattice)

contour(), filled.contour() contour plot

levelplot(), contourplot() level plots and contour plots (lattice)

**smoothScatter()** scatterplots with smoothed densities color representation; capable of visualizing large datasets

sunflowerplot () a sunflower scatter plot

assocplot() association plot

mosaicplot() mosaic plot

matplot () plot the columns of one matrix against the columns of another

```
fourfoldplot () a fourfold display of a 2 \times 2 \times k contingency table
persp() perspective plots of surfaces over the x?y plane
cloud(), wireframe() 3d scatter plots and surfaces (lattice)
interaction.plot() two-way interaction plot
iplot(), ihist(), ibar(), ipcp() interactive scatter plot, histogram, bar
      plot, and parallel coordinates plot (iplots)
pdf(), postscript(), win.metafile(), jpeg(), bmp(),
      png(), tiff() save graphs into files of various formats
qvisAnnotatedTimeLine(), qvisAreaChart(),
      gvisBarChart(), gvisBubbleChart(),
      qvisCandlestickChart(), qvisColumnChart(),
      qvisComboChart(), qvisGauge(), qvisGeoChart(),
      gvisGeoMap(), gvisIntensityMap(),
      gvisLineChart(), gvisMap(), gvisMerge(),
      gvisMotionChart(), gvisOrgChart(),
      gvisPieChart(), gvisScatterChart(),
      qvisSteppedAreaChart(), qvisTable(),
      gvisTreeMap() various interactive charts produced with the Google
      Visualisation API (googleVis)
qvisMerge () merge two googleVis charts into one (googleVis)
```

#### **Packages**

ggplot2 an implementation of the Grammar of Graphics

googleVis an interface between R and the Google Visualisation API to create interactive charts

rCharts interactive javascript visualizations from R

lattice a powerful high-level data visualization system, with an emphasis on multivariate data

vcd visualizing categorical data *iplots* interactive graphics

# **Data Manipulation**

#### Functions

transform() transform a data frame

scale () scaling and centering of matrix-like objects

t() matrix transpose

aperm() array transpose

sample() sampling

table(), tabulate(), xtabs() cross tabulation

stack(), unstack() stacking vectors

split(), unsplit() divide data into groups and reassemble

reshape () reshape a data frame between "wide" and "long" format

merge () merge two data frames; similar to database join operations

aggregate() compute summary statistics of data subsets

**by ()** apply a function to a data frame split by factors

melt(), cast() melt and then cast data into the reshaped or aggregated form you want (reshape)

complete.cases() find complete cases, i.e., cases without missing values

na.fail, na.omit, na.exclude, na.pass handle missing values

# **Packages**

reshape flexibly restructure and aggregate data

data.table extension of data.frame for fast indexing, ordered joins, assignment, and grouping and list columns

gdata various tools for data manipulation



## **Data Access**

### **Functions**

sqlQuery() submit an SQL query to an ODBC database (RODBC)
sqlFetch() read a table from an ODBC database (RODBC)
sqlSave(), sqlUpdate() write or update a table in an ODBC database

sqlColumns() enquire about the column structure of tables (RODBC) sqlTables() list tables on an ODBC connection (RODBC)

odbcConnect(), odbcClose(), odbcCloseAll() open/close connections to ODBC databases (RODBC)

dbSendQuery execute an SQL statement on a given database connection (DBI) dbConnect (), dbDisconnect () create/close a connection to a DBMS (DBI)

### **Packages**

RODBC ODBC database access

foreign read and write data in other formats, such as Minitab, S, SAS, SPSS, Stata, Systat, ...

sqldf perform SQL selects on R data frames

DBI a database interface (DBI) between R and relational DBMS

RMySQL interface to the MySQL database

RJDBC access to databases through the JDBC interface

RSOLite SQLite interface for R

ROracle Oracle database interface (DBI) driver

RpgSQL DBI/RJDBC interface to PostgreSQL database

RODM interface to Oracle Data Mining

xlsx read, write, format Excel 2007 and Excel 97/2000/XP/2003 files

xlsReadWrite read and write Excel files

Twitter user (twitteR)

WriteXLS create Excel 2003 (XLS) files from data frames

SPARQL Use SPARQL to pose SELECT or UPDATE queries to an end-point

# **Web Data Access**

#### **Functions**

download.file() download a file from the Internet
xmlParse(), htmlParse() parse an XML or HTML file (XML)
userTimeline(), homeTimeline(), mentions(),
 retweetsOfMe() retrieve various timelines within the Twitter universe (twitteR)
searchTwitter() a search of Twitter based on a supplied search string (twitteR)
getUser(), lookupUsers() get information of Twitter users (twitteR)
getFollowers(), getFollowerIDs(), getFriends(),
 qetFriendIDs() get a list of followers/friends or their IDs of a

**twListToDF()** convert *twitteR* lists to data frames (*twitteR*)

#### **Packages**

*twitteR* an interface to the Twitter web API

RCurl general network (HTTP/FTP/...) client interface for R

XML reading and creating XML and HTML documents

httr tools for working with URLs and HTTP; a simplified wrapper built on top of RCurl

# **MapReduce and Hadoop**

#### **Functions**

mapreduce() define and execute a MapReduce job (rmr2)

keyval() create a key-value object (rmr2)

from.dfs(), to.dfs() read/write R objects from/to file system (rmr2)

#### **Packages**

rmr2 perform data analysis with R via MapReduce on a Hadoop cluster rhdfs connect to the Hadoop Distributed File System (HDFS)

rhbase connect to the NoSQL HBase database

Rhipe R and Hadoop Integrated Processing Environment

RHive distributed computing via HIVE query

 $\label{eq:conditional} \textit{Segue} \ \text{Parallel} \ R \ \text{in the cloud using Amazon's Elastic Map Reduce} \ (\text{EMR}) \ \text{engine}$ 

HadoopStreaming Utilities for using R scripts in Hadoop streaming

hive distributed computing via the MapReduce paradigm

rHadoopClient Hadoop client interface for R

# **Large Data**

### **Functions**

as.ffdf() coerce a dataframe to an ffdf(ff)

write.table.ffdf(), write.csv.ffdf() write an ffdf object to a flat file
 (ff)

ffdfappend() append a dataframe or an ffdf to an existing ffdf (ff)

big.matrix() create a standard big.matrix, which is constrained to available RAM(bigmemory)

read.big.matrix() create a big.matrix by reading from an ASCII file (big-

write.big.matrix() write a big.matrix to a file (bigmemory)

filebacked.big.matrix() create a file-backed big.matrix, which may exceed available RAM by using hard drive space (bigmemory)

mwhich () expanded "which"-like functionality (bigmemory)

## **Packages**

ff memory-efficient storage of large data on disk and fast access functions fbase basic statistical functions for package ff

*filehash* a simple key-value database for handling large data

g.data create and maintain delayed-data packages

BufferedMatrix a matrix data storage object held in temporary files biglm regression for data too large to fit in memory

bigmemory manage massive matrices with shared memory and memory-mapped

biganalytics extend the bigmemory package with various analytics
bigtabulate table-, tapply-, and split-like functionality for matrix

 $\begin{tabular}{ll} \it bigtabulate & table-, & tapply-, & and & split-like & functionality & for & matrix & and \\ \it big.matrix & objects & \end{tabular}$ 

# **Parallel Computing**

#### **Functions**

sfLapply(), sfSapply(), sfApply() parallel versions of
 lapply(), sapply(), apply() (snowfall)
foreach(...) %dopar% looping in parallel (foreach)
registerDoSEQ(), registerDoSNOW(), registerDoMC() register respectively the sequential, SNOW and multicore parallel backend with the

sfInit(), sfStop() initialize and stop the cluster (snowfall)

### **Packages**

snowfall usability wrapper around snow for easier development of parallel R programs

snow simple parallel computing in R

 $\it multicore$  parallel processing of R code on machines with multiple cores or CPUs

*snowFT* extension of *snow* supporting fault tolerant and reproducible applications, and easy-to-use parallel programming

Rmpi interface (Wrapper) to MPI (Message-Passing Interface)

foreach package (foreach, doSNOW, doMC)

rpvm R interface to PVM (Parallel Virtual Machine)

nws provide coordination and parallel execution facilities

foreach foreach looping construct for R

doMC foreach parallel adaptor for the multicore package

doSNOW foreach parallel adaptor for the snow package

doMPI foreach parallel adaptor for the Rmpi package

doParallel foreach parallel adaptor for the multicore package

doRNG generic reproducible parallel backend for foreach Loops

 ${\it GridR}$  execute functions on remote hosts, clusters or grids

fork R functions for handling multiple processes

# **Interface to Weka**

Package *RWeka* is an R interface to Weka, and enables to use the following Weka functions in R.

Association rules:

Apriori(), Tertius()

Regression and classification:

LinearRegression(), Logistic(), SMO()

Lazy classifiers:

IBk(), LBR()

Meta classifiers:

AdaBoostM1(), Bagging(), LogitBoost(), MultiBoostAB(),
Stacking(),

CostSensitiveClassifier()

Rule classifiers:

JRip(), M5Rules(), OneR(), PART()

Regression and classification trees:

J48(), LMT(), M5P(), DecisionStump()

Clustering:

Cobweb(), FarthestFirst(), SimpleKMeans(), XMeans(),
DBScan()

Filters:

Normalize(), Discretize()

Word stemmers:

IteratedLovinsStemmer(), LovinsStemmer()

Tokenizers:

AlphabeticTokenizer(), NGramTokenizer(), WordTokenizer()



# **Interface to Other Programming Languages**

#### **Functions**

- . jcall () call a Java method (rJava)
- . jnew() create a new Java object (rJava)
- . jinit () initialize the Java Virtual Machine (JVM) (rJava)
- . jaddClassPath() adds directories or JAR files to the class path (rJava)

### **Packages**

rJava low-level R to Java interface

# **Generating Reports**

#### **Functions**

**Sweave ()** mixing text and R/S code for automatic report generation **Packages** 

*knitr* a general-purpose package for dynamic report generation in R *R2HTML* making HTML reports

R2PPT generating Microsoft PowerPoint presentations

# **Building GUIs and Web Applications**

*shiny* web application framework for R *svDialogs* dialog boxes

gWidgets a toolkit-independent API for building interactive GUIs

# R Editors/GUIs

RStudio a free integrated development environment (IDE) for R

Tinn-R a free GUI for R language and environment

rattle graphical user interface for data mining in R

Rpad workbook-style, web-based interface to R

RPMG graphical user interface (GUI) for interactive R analysis sessions

Red-R An open source visual programming GUI interface for R

R AnalyticFlow a software which enables data analysis by drawing analysis flowcharts

latticist a graphical user interface for exploratory visualisation

# **Other R Reference Cards**

R Reference Card, by Tom Short

http://cran.r-project.org/doc/contrib/Short-refcard.pdf

R Reference Card, by Jonathan Baron

http://cran.r-project.org/doc/contrib/refcard.pdf

R Functions for Regression Analysis, by Vito Ricci

http://cran.r-project.org/doc/contrib/Ricci-refcard-regression.
pdf

R Functions for Time Series Analysis, by Vito Ricci

http://cran.r-project.org/doc/contrib/Ricci-refcard-ts.pdf

# **RDataMining Books**

R and Data Mining: Examples and Case Studies

introduces into using R for data mining with examples and case studies.

http://www.rdatamining.com/books/rdm

Data Mining Applications with R

presents 15 real-world applications on data mining with R.

http://www.rdatamining.com/books/dmar

# RDataMining Website, Group, Twitter & Package

RDataMining Website

http://www.rdatamining.com

RDataMining Group on LinkedIn (6000+ members)

http://group.rdatamining.com

RDataMining on Twitter (1700+ followers)

http://twitter.com/rdatamining

RDataMining Project on R-Forge

http://www.rdatamining.com/package

http://package.rdatamining.com

## **Comments & Feedback**

If you have any comments, or would like to suggest any relevant R packages/functions, please feel free to email me <yanchang@rdatamining.com>. Thanks.

