

## ④ XML Process Definition Language

**안 현**


컴퓨터공학부  
hahn@kgu.ac.kr

# Outline of This Chapter

- Petri Net
- Information Control Nets

- Business Process Model and Notation (BPMN)


- XML Process Definition Language (XPDL)



## **4.1 XPDL 표준 개요**

# The Workflow Reference Model

- 워크플로우 참조모델: 워크플로우 관리 시스템의 주요 컴포넌트들과 이들 사이의 인터페이스를 정의



Source: Workflow Management Coalition

# The Workflow Reference Model - Interfaces


**표준 인터페이스:** 워크플로우 엔진을 중심으로 다른 컴포넌트와의 통신 규격을 정의

- **인터페이스 1: 프로세스 정의**(Process Definition Tools)
  - 프로세스 정의를 생성하는 모델링 시스템들과 워크플로우 엔진과의 인터페이스
- **인터페이스 2: 클라이언트 애플리케이션**(Client Applications)
  - 수행자가 사용하는 클라이언트 애플리케이션과 워크플로우 엔진과의 인터페이스
- **인터페이스 3: 호출 애플리케이션**(Invoked Applications)
  - 워크플로우 엔진이 애플리케이션들을 호출하기 위한 API들을 제공하는 인터페이스
- **인터페이스 4: 상호운용성**(Interoperability with Heterogenous Workflow Enactment Services)
  - 이기종 워크플로우 실행 서비스 사이의 상호운용성(interoperability)을 제공하기 위한 인터페이스
- **인터페이스 5: 시스템 관리 및 모니터링**(System Administration and Monitoring)
  - 프로세스의 관리 및 모니터링 기능을 제공하기 위한 인터페이스


# The **XPDL** Standard

- **XPDL**(XML Process Definition Language) **표준**
  - 프로세스 정의의 상호교환을 목적으로 **WfMC**(Workflow Management Coalition)에  
IBM, Hewlett-Packard, Fujitsu 등  
서 제정한 표준
- **표준화 이력**
  - 1998년: WPDL(Workflow Process Definition Language) 발표
    - 워크플로우 참조모델의 인터페이스 1을 구현하기 위한 표준으로서 제안됨
  - 2002년: XPDL 1.0 발표
    - WPDL 표준을 XML 기반으로 재수정 및 배포한 버전
  - 2012년: XPDL 2.2 발표
    - BPMN 2.0 버전과의 호환성 제공

# XPDL Goal: Process Definition Interchange



## ex) Process Definition Interchange





# Different Objectives, Slightly Different Terms

- **BPMN과 XPDL의 표준화 목적**
  - BPMN: 비즈니스 프로세스의 시각적 표기법을 제공
  - XPDL: 프로세스 정의의 상호교환

BPMN 개체 유형	XPDL 개체 유형
Activity, Gateway, Event	Activity
Sequence Flow	Transition
Pool, Lane	Pool, Lane

## **4.2 XPDL 메타모델**




그림. XPD 메타모델

# Primary Entity Types

## 주요 개체 유형들

- **패키지(Package):** XPDL의 최상위 개체 유형(루트 노드)
  - BPMN 프로세스 다이어그램과 대응되며, 다수의 프로세스들을 포함
- **타입선언(Type Declaration):** 데이터 유형을 정의
- **데이터 필드(Data Field):** 데이터 아이템을 정의
- **나머지 유형:** BPMN 표준에서 제공하는 개체 유형과 동일

# Type Declaration & Data Field


```

<TypeDeclarations>
  <TypeDeclaration Id="POType" Name="PurchaseOrder">
    <SchemaType>
      <schema xmlns="http://www.w3.org/2000/10/XMLSchema">
        <element name="PO">
          <complexType>
            <sequence>
              <element name="CustomerName" type="string"/>
              <element name="Address" type="string"/>
              <element name="OrderNumber" type="string"/>
            </sequence>
          </complexType>
        </element>
      </schema>
    </SchemaType>
  </TypeDeclaration>
</TypeDeclarations>

  <DataFields>
    <DataField Id="newPO">
      <DataType>
        <DeclaredType Id="POType"/>
      </DataType>
    </DataField>
    <DataField Id="checkedPO">
      <DataType>
        <DeclaredType Id="POType"/>
      </DataType>
    </DataField>
  </DataFields>


```

# XPDL Basic Structure



# BPMN Activity == XPDL Generic Activity

- BPMN의 액티비티는 XPDL의 제네릭 액티비티를 나타냄



# BPMN Event == XPDL Event Activity

Start

Intermediate

End

– BPMN의 이벤트는 XPDL의 이벤트  
액티비티를 나타냄

## Event Types

Message



Timer



Exception



Cancel



Compensation



Rule



Link



Terminate



Multiple





# BPMN Gateway == XPDL Route Activity

- BPMN의 게이트웨이는 XPDL의 루트 액티비티를 나타냄

## Exclusive Decision/Merge (XOR)

Data-Based



or



Event-Based



## Inclusive Decision/Merge (OR)



## Complex Decision/Merge




## Parallel Fork/Join (AND)



# BPMN Connection == XPDL Transition

## Sequence Flow


- BPMN의 연결객체는 XPDL의 트랜지션을 나타냄








## Message Flow





## Association



# Mappings From BPMN to XPDL

개체 유형	BPMN 표기	XPDL 표현
Process or Pool		<pre>&lt;WorkflowProcess&gt; ... &lt;/WorkflowProcess&gt;</pre>
Start Event		<pre>&lt;Activity&gt;   &lt;Event&gt;     &lt;StartEvent Trigger="..."/&gt;   &lt;/Event&gt; &lt;/Activity&gt;</pre>
Sequence Flow		<pre>&lt;Transition/&gt;</pre>
Task		<pre>&lt;Activity&gt;   &lt;Implementation&gt;     &lt;Task&gt;...&lt;/Task&gt;   &lt;/Implementation&gt;   &lt;Performers&gt;...&lt;/Performers&gt; &lt;/Activities&gt;</pre>
Sub-Process		<pre>&lt;Activity&gt;   &lt;Implementation&gt;     &lt;SubFlow&gt;...&lt;SubFlow/&gt;   &lt;/Implementation&gt; &lt;/Activity&gt;</pre>


# Mappings From BPMN to XPD

개체 유형	BPMN 표기	XPD
<b>Intermediate Event</b> (attached to activity boundary)		<pre> &lt;Activity Id="100" ...&gt;   &lt;Event&gt;     &lt;IntermediateEvent Trigger="Error" ... /&gt;   &lt;/Event&gt; &lt;/Activity&gt; ... &lt;Transition Id="..." From="100" To="..."&gt;   ... &lt;/Transition&gt;                     </pre>
<b>Gateway</b> (split)		<pre> &lt;Activity&gt;   &lt;Route GatewayType="..." ... /&gt;   &lt;TransitionRestrictions&gt;     &lt;TransitionRestriction&gt;       &lt;Split Type="..."&gt;         &lt;TransitionRefs&gt;           ...         &lt;/TransitionRefs&gt;       &lt;/Split&gt;     &lt;/TransitionRestriction&gt;   &lt;/TransitionRestrictions&gt; &lt;/Activity&gt; ... &lt;Transition&gt;   ... &lt;/Transition&gt;                     </pre>

## **4.3** XPDL 프로세스 예제

# ex) Simple Order Process


- 프로세스 예제: 간단한 주문 프로세스(ICN ⇔ XPDL)



```

<?xml version="1.0" encoding="UTF-8"?>
<Package xmlns="http://www.wfmc.org/2004/XPD2.0alpha"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.wfmc.org/2004/XPD2.0alpha file:/D:/workspace/XPD2_v2/TC-
1025_bpmnxd2_24.xsd" Id="samplePkg" Name="samplePkg">
  <WorkflowProcesses>
    <WorkflowProcess Id="Process-1191836303703" Name="sampleProcess">
      ...
      ...
      ...
    </WorkflowProcess>
  </WorkflowProcesses>
</Package>


```



```

<?xml version="1.0" encoding="UTF-8"?>
<Package xmlns="http://www.wfmc.org/2004/XPDL2.0alpha"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.wfmc.org/2004/XPDL2.0alpha file:/D:/workspace/XPDL_v2/TC-
1025_bpmnxdl_24.xsd" Id="samplePkg" Name="samplePkg">
  <WorkflowProcesses>
    <WorkflowProcess Id="Process-1191836303703" Name="sampleProcess">
      ...
      <Activities>
        <Activity Id="start" Name="Start">
          <Event>
            <StartEvent Trigger="None"/>
          </Event>
          <NodeGraphicsInfos>
            <NodeGraphicsInfo FillColor="light blue" LaneId="1" ToolId="Interstage"
              IsVisible="true" Page="1">
              <Coordinates XCoordinate="81.0" YCoordinate="80.0"/>
            </NodeGraphicsInfo>
          </NodeGraphicsInfos>
        </Activity>
      </Activities>
      ...
    </WorkflowProcess>
  </WorkflowProcesses>
</Package>

```




```

<?xml version="1.0" encoding="UTF-8"?>
<Package xmlns="http://www.wfmc.org/2004/XPDL2.0alpha"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.wfmc.org/2004/XPDL2.0alpha file:/D:/workspace/XPDL_v2/TC-
1025_bpmnxdl_24.xsd" Id="samplePkg" Name="samplePkg">
  <WorkflowProcesses>
    <WorkflowProcess Id="Process-1191836303703" Name="sampleProcess">
      ...
      <Transitions>
        <Transition Id="Transition1191836491265" From="Activity1191836318687"
          To="Activity1191836331343" Name="Start_To_Receive Order">
          <ConnectorGraphicsInfos>
            <ConnectorGraphicsInfo FillColor="light blue" ToolId="Interstage"
              IsVisible="true" Page="1">
              <Coordinates XCoordinate="258.0" YCoordinate="365.0"/>
              <Coordinates XCoordinate="426.0" YCoordinate="365.0"/>
            </ConnectorGraphicsInfo>
          </ConnectorGraphicsInfos>
        </Transition>
      </Transitions>
      ...
    </WorkflowProcess>
  </WorkflowProcesses>
</Package>

```






```

<?xml version="1.0" encoding="UTF-8"?>
<Package xmlns="http://www.wfmc.org/2004/XPDL2.0alpha"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.wfmc.org/2004/XPDL2.0alpha file:/D:/workspace/XPDL_v2/TC-
1025_bpmnxdl_24.xsd" Id="samplePkg" Name="samplePkg">
  <WorkflowProcesses>
    <WorkflowProcess Id="Process-1191836303703" Name="sampleProcess">
      ...
      <Activities>
        <Activity Id="Activity1191836331343" Name="Receive Order">
          <NodeGraphicsInfos>
            <NodeGraphicsInfo FillColor="light blue" LaneId="1" ToolId="Interstage"
              IsVisible="true" Page="1">
              <Coordinates XCoordinate="81.0" YCoordinate="80.0"/>
            </NodeGraphicsInfo>
          </NodeGraphicsInfos>
        </Activity>
      </Activities>
      ...
    </WorkflowProcess>
  </WorkflowProcesses>
</Package>


```



```

<?xml version="1.0" encoding="UTF-8"?>
<Package xmlns="http://www.wfmc.org/2004/XPDL2.0alpha"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.wfmc.org/2004/XPDL2.0alpha file:/D:/workspace/XPDL_v2/TC-
1025_bpmnxdpdl_24.xsd" Id="samplePkg" Name="samplePkg">
  <WorkflowProcesses>
    <WorkflowProcess Id="Process-1191836303703" Name="sampleProcess">
      <Activitys>
        <Activity Id="Activity1191836368000" Name="OR_SPLIT">
          <Route GatewayType="XOR"/>
          <TransitionRestrictions>
            <TransitionRestriction>
              <Split Type="XOR">
                <TransitionRefs>
                  <TransitionRef Id="Transition1191836496437" />
                  <TransitionRef Id="Transition1191836494593" />
                </TransitionRefs>
              </Split>
            </TransitionRestriction>
          </TransitionRestrictions>
          <NodeGraphicsInfos>
            <NodeGraphicsInfo FillColor="light blue" LaneId="1" ToolId="Interstage" IsVisible="true" Page="1">
              <Coordinates XCoordinate="81.0" YCoordinate="80.0"/>
            </NodeGraphicsInfo>
          </NodeGraphicsInfos>
        </Activity>
      </Activitys>
    </WorkflowProcess>
  </WorkflowProcesses>
</Package>


```



```

<?xml version="1.0" encoding="UTF-8"?>
<Package xmlns="http://www.wfmc.org/2004/XPDL2.0alpha"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.wfmc.org/2004/XPDL2.0alpha file:/D:/workspace/XPDL_v2/TC-
1025_bpmnxdl_24.xsd" Id="samplePkg" Name="samplePkg">
  <WorkflowProcesses>
    <WorkflowProcess Id="Process-1191836303703" Name="sampleProcess">
      ...
      <Transitions>
        <Transition Id="Transition1191836494593" From="Activity1191836368000"
          To="Activity1191836361640" Name="tc1">
          <Condition Type="CONDITION" condition == true </Condition>
          <ConnectorGraphicsInfos>
            <ConnectorGraphicsInfo FillColor="light blue" ToolId="Interstage"
              IsVisible="true" Page="1">
              <Coordinates XCoordinate="258.0" YCoordinate="365.0"/>
              <Coordinates XCoordinate="426.0" YCoordinate="365.0"/>
            </ConnectorGraphicsInfo>
          </ConnectorGraphicsInfos>
        </Transition>
      </Transitions>
      ...
    </WorkflowProcess>
  </WorkflowProcesses>
</Package>


```



```

<?xml version="1.0" encoding="UTF-8"?>
<Package xmlns="http://www.wfmc.org/2004/XPDL2.0alpha"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.wfmc.org/2004/XPDL2.0alpha file:/D:/workspace/XPDL_v2/TC-
1025_bpmnxdpdl_24.xsd" Id="samplePkg" Name="samplePkg">
  <WorkflowProcesses>
    <WorkflowProcess Id="Process-1191836303703" Name="sampleProcess">
      <Activitiys>
        <Activity Id="Activity1191836403562" Name="AND_SPLIT">
          <Route GatewayType="AND"/>
          <TransitionRestrictions>
            <TransitionRestriction>
              <Split Type="AND">
                <TransitionRefs>
                  <TransitionRef Id="Transition1191836496437" />
                  <TransitionRef Id="Transition1191836497375" />
                </TransitionRefs>
              </Split>
            </TransitionRestriction>
          </TransitionRestrictions>
          <NodeGraphicsInfos>
            <NodeGraphicsInfo FillColor="light blue" LaneId="1" ToolId="Interstage" IsVisible="true" Page="1">
              <Coordinates XCoordinate="81.0" YCoordinate="80.0"/>
            </NodeGraphicsInfo>
          </NodeGraphicsInfos>
        </Activity>
      </Activitiys>
    </WorkflowProcess>
  </WorkflowProcesses>
</Package>


```



```

<?xml version="1.0" encoding="UTF-8"?>
<Package xmlns="http://www.wfmc.org/2004/XPDL2.0alpha"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.wfmc.org/2004/XPDL2.0alpha file:/D:/workspace/XPDL_v2/TC-
1025_bpmnxdl_24.xsd" Id="samplePkg" Name="samplePkg">
  <WorkflowProcesses>
    <WorkflowProcess Id="Process-1191836303703" Name="sampleProcess">
      ...
      <Transitions>
        <Transition Id="Transition1191836496437" From="Activity1191836403562"
          To="Activity1191836407937" Name="AND_SPLIT_To_Bill Order">
          <ConnectorGraphicsInfos>
            <ConnectorGraphicsInfo FillColor="light blue" ToolId="Interstage"
              IsVisible="true" Page="1">
              <Coordinates XCoordinate="258.0" YCoordinate="365.0"/>
              <Coordinates XCoordinate="426.0" YCoordinate="365.0"/>
            </ConnectorGraphicsInfo>
          </ConnectorGraphicsInfos>
        </Transition>
      </Transitions>
      ...
    </WorkflowProcess>
  </WorkflowProcesses>
</Package>

```



```

<?xml version="1.0" encoding="UTF-8"?>
<Package xmlns="http://www.wfmc.org/2004/XPDL2.0alpha"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.wfmc.org/2004/XPDL2.0alpha file:/D:/workspace/XPDL_v2/TC-
1025_bpmnxdl_24.xsd" Id="samplePkg" Name="samplePkg">
  <WorkflowProcesses>
    <WorkflowProcess Id="Process-1191836303703" Name="sampleProcess">

```

...

<Activity>

<Activity Id="Activity1191836462765" Name="AND\_JOIN">

<Route GatewayType="AND" />

<TransitionRestrictions>

<TransitionRestriction>

<Join Type="AND"/>

</TransitionRestriction>

</TransitionRestrictions>

<NodeGraphicsInfos>

<NodeGraphicsInfo FillColor="light blue" LaneId="1" ToolId="Interstage" IsVisible="true" Page="1">

<Coordinates XCoordinate="81.0" YCoordinate="80.0"/>

</NodeGraphicsInfo>

</NodeGraphicsInfos>

</Activity>


<Activity>

...

</WorkflowProcess>

</WorkflowProcesses>

</Package>



```

<?xml version="1.0" encoding="UTF-8"?>
<Package xmlns="http://www.wfmc.org/2004/XPDL2.0alpha"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.wfmc.org/2004/XPDL2.0alpha file:/D:/workspace/XPDL_v2/TC-
1025_bpmnxdl_24.xsd" Id="samplePkg" Name="samplePkg">
  <WorkflowProcesses>
    <WorkflowProcess Id="Process-1191836303703" Name="sampleProcess">

```

```

    ...
    <Activity>
      <Activity Id="Activity1191836462765" Name="OR_JOIN">
        <Route GatewayType="XOR" />
        <TransitionRestrictions>
          <TransitionRestriction>
            <Join Type="XOR"/>
          </TransitionRestriction>
        </TransitionRestrictions>
        <NodeGraphicsInfos>
          <NodeGraphicsInfo FillColor="light blue" LaneId="1" ToolId="Interstage" IsVisible="true" Page="1">
            <Coordinates XCoordinate="81.0" YCoordinate="80.0"/>
          </NodeGraphicsInfo>
        </NodeGraphicsInfos>
      </Activity>
    </Activity>
  </WorkflowProcess>

```

```


    ...
  </WorkflowProcess>
</WorkflowProcesses>
</Package>

```


## ex) E-Mail Voting Process

- 프로세스 예제: **이메일 투표 프로세스**(BPMN ⇔ XPDL)
  - 출처: XPDL 표준문서(LMS에 업로드)
  - 메인 프로세스: **EMailVotingProcess**
  - 서브 프로세스: **Discussion Cycle, Collect Votes**
  - 외부 참여자(external participants): **Voting Members**






# E-Mail Voting Process—Discussion Cycle Subprocess



# E-Mail Voting Process—Collect Votes Subprocess









# References



- social-biz.org, **The BPMN-XPDL-BPEL value chain** ([link](#))
- Swenson, K., et al., **XPDL 2.0 and BPMN 1.0 Tutorial**, Docplayer ([link](#))
- WfMC, **Process Definition Interface—XML Process Definition Language**, Version 2.1a, WfMC-TC-1025, 2008
- White, S.A., **XPDL and BPMN**, OMG ([link](#))
- xpdl.org, **What is XML Process Definition Language (XPDL)** ([link](#))



Questions?

<b>Start Event</b>		<pre>&lt;Activity&gt;   &lt;Event&gt;     &lt;StartEvent Trigger="..." /&gt;   &lt;/Event&gt; &lt;/Activity&gt;</pre>
<b>Sequence Flow</b>		<pre>&lt;Transition/&gt;</pre>
<b>Task</b>		<pre>&lt;Activity&gt;   &lt;Implementation&gt;     &lt;Task&gt; ... &lt;/Task&gt;   &lt;/Implementation&gt;   &lt;Performers&gt; ... &lt;/Performers&gt; &lt;/Activities&gt;</pre>
<b>Sub-Process</b>		<pre>&lt;Activity&gt;   &lt;Implementation&gt;     &lt;SubFlow&gt; ... &lt;SubFlow/&gt;   &lt;/Implementation&gt; &lt;/Activity&gt;</pre>
<b>Intermediate Event</b> (attached to activity boundary)		<pre>&lt;Activity Id="100" ...&gt;   &lt;Event&gt;     &lt;IntermediateEvent       Trigger="Error" ... /&gt;   &lt;/Event&gt;   ...   &lt;Transition Id="..." From="100"     To="..."&gt;   &lt;/Transition&gt;</pre>
		<pre>&lt;Activity&gt;   &lt;Route GatewayType="..." ... /&gt;   &lt;TransitionRestrictions&gt;     &lt;TransitionRestriction&gt;       &lt;Split Type="..."&gt;       &lt;TransitionRefs&gt;</pre>

# Mappings From BPMN to XPD

개체 유형	BPMN 표기	XPD 표현
<b>Intermediate Event</b> (attached to activity boundary)		<pre> &lt;Activity Id="100" ...&gt;   &lt;Event&gt;     &lt;IntermediateEvent Trigger="Error" ... /&gt;   &lt;/Event&gt; &lt;/Activity&gt; ... &lt;Transition Id="..." From="100" To="..."&gt; &lt;/Transition&gt;                     </pre>
<b>Gateway</b> (split)		<pre> &lt;Activity&gt;   &lt;Route GatewayType="..." ... /&gt;   &lt;TransitionRestrictions&gt;     &lt;TransitionRestriction&gt;       &lt;Split Type="..."&gt;         &lt;TransitionRefs&gt;           ...         &lt;/TransitionRefs&gt;       &lt;/Split&gt;     &lt;/TransitionRestriction&gt;   &lt;/TransitionRestrictions&gt; &lt;/Activity&gt; ... &lt;Transition&gt; ... &lt;/Transition&gt;                     </pre>