



Textile Image Retrieval Using Composite Feature Vectors of Color and Wavelet Transformed Textural Property

J.C Chun, W.G Kim

Computer Graphics & Image Processing Lab.
Dept. of Computer Science, Kyonggi University,
South Korea



Agenda

- 📌 Motivation
- 📌 Research Goals
- 📌 Related Works
- 📌 Proposed Method
- 📌 Experimental Results
- 📌 Concluding Remarks



Motivation

- 📌 **Content Based Image Retrieval (CBIR)** is a process of retrieving desired image from a large collection of images based on the features such as color, shape and texture that can be extracted from the image themselves.
- 📌 **Color** is widely used for identifying images but color histogram has a limitation to carry local spatial information of pixels even though its efficiency. Meanwhile, in transform domain some high-level features can be extracted.
- 📌 **Texture** is one of the most important attributes used in image analysis because it contains structural arrangement of textile surfaces and their relationship to the surrounding environments.



Research Goal

- ✚ We present a **hybrid approach** for content-based **textile image** retrieval which uses composite feature vectors of color feature from spatial domain and second-order statistic features from wavelet-transformed sub-band coefficients.
- ✚ Extract texture features such as **contrast**, **homogeneity**, **ASM(angular-second momentum)** and **entropy** from decomposed sub-band images by wavelet transform.
- ✚ Develop an image retrieval system which uses those multiple feature vectors with color histogram.




Related Work

- 📌 Use Wavelet Transform for Image Retrieval.
 - In early stage of the applications of wavelet transform for CBIR Gabor wavelet is widely used for extracting texture features for image retrieval since the scale and orientation tunable property of Gabor filter makes it useful for texture analysis[1,2].
 - Coefficients derived from Daubechies wavelet is used for pattern recognition with neural network because of its fast computation and regularity[3].



The Proposed System Overview





Color Feature Representation(1)


- ✚ We use HSV color model rather than using RGB to extract color histogram.
- ✚ The histogram intersection H_{\cap} which provides the similarity measure between each image (i) in the database and query image(q) can be defined as

$$H_{\cap} = \sum_{j=1}^n \min \left(H_i^j, H_q^j \right)$$

- ✚ Here, j is histogram bin, n is the total number of bins for each histogram, H_i and H_q are histograms of database and query image, respectively. The closer value of is to **1** the better images match.



Color Feature Representation(2)





Wavelet Decomposition(1)

- Wavelet transform is a multi-resolution representation that presents image variations at different scale since each frequency component can be analyzed with different resolution and scale.
- The continuous wavelet transform (CWT) decomposes a signal f into a set of scaling functions by using a wavelet function basis:


$$(W_a f)(b) = \int f(x) \psi_{a,b}(x) dx$$

$$\psi_{a,b}(x) = \frac{1}{\sqrt{a}} \psi\left(\frac{x-b}{a}\right)$$



Wavelet Decomposition(2)

1st level wavelet transform a textile image.



- The decomposed sub-band images are labeled as S_2 (LL), W_2^V (LH), W_2^H (HL) and W_2^D (HH), where L and H represent low and high frequency, respectively.
- From these decomposed sub-bands, we can obtain detail local information about the original image.



Texture Feature Representation(1)

- In order to extract better local information we use co-occurrence matrix $\mathbf{C}(\mathbf{i}, \mathbf{j})$ from the wavelet decomposed sub-band images.

$$C(i, j) = \sum_{x=1}^N \sum_{y=1}^N \begin{cases} 1, & \text{if } I(x, y) = i \text{ and } I(x + \delta_x, y + \delta_y) = j \\ 0, & \text{otherwise} \end{cases}$$

- The offset (δ_x, δ_y) is specifying the distance between a specific pixel and its neighbor pixels.
- It is known that the offset (δ_x, δ_y) parameterization makes the co-occurrence matrix sensitive to rotation.
- Thus choosing an offset vector, such that the rotation of the image is not equal to 180 degrees, will result in a different co-occurrence matrix for the same (rotated) image.



Texture Feature Representation(2)

- ✚ From the gray-level co-occurrence matrix (GLCM) contrast, homogeneity, ASM(Angular Second Momentum) and entropy are evaluated.
- ✚ **Contrast** and **homogeneity** presents the difference or similarity in light between parts of the image meanwhile **ASM** and **entropy** are the statistical measures of the randomness of the input image.



Texture Feature Representation(3)

- ✚ If $P(i, j)$ is the entry of GLCM and N_g is gray-level then the contrast, homogeneity, ASM, and entropy can be defined respectively as:

Contrast

$$\sum_{n=0}^{N_g-1} n^2 \sum_{i=1}^{N_g} \sum_{j=1}^{N_g} p(i, j), |i - j| = n$$

Homogeneity

$$\sum_{i=1}^{N_g} \sum_{j=1}^{N_g} \frac{p(i, j)}{1 + n^2}, |i - j| = n$$

ASM

$$\sum_{i=1}^{N_g} \sum_{j=1}^{N_g} p^2(i, j)$$


Entropy

$$- \sum_{i=1}^{N_g} \sum_{j=1}^{N_g} p(i, j) \ln(p(i, j))$$



Experimental Results(1)

- ✚ We use 1343 cases of textile image.
- ✚ Texture information evaluated from the wavelet transformed domain consists of 16 vector-valued features since 4 textural directions of $0^\circ, 45^\circ, 90^\circ, 135^\circ$ are considered from the GLCM.





Experimental Results(2)

- Thus the total texture similarity **(TS)** from wavelet transformed domain becomes


$$TS = N_Con_{k,l} + N_Hom_{k,l} + N_Asm_{k,l} + N_Ent_{k,l} \quad \text{for } \forall \quad k, l = 0^\circ, 45^\circ, 90^\circ, 135^\circ$$

- The similarity measure S_{iq} between a query **(q)** and a database image **(i)** is evaluated as follow when color similarity CS_{iq} , texture similarity TS_{iq} , and a control ratio α are provided.


$$S_{iq} = \left(CS_{iq} \times \frac{\alpha}{100} \right) + \left(TS_{iq} \times \frac{(100 - \alpha)}{100} \right)$$




Experimental Results(3)



$$\alpha = 100$$




$$\alpha = 0$$



$$\alpha = 50$$



Experimental Results(4)



$\alpha = 100$



$\alpha = 0$



$\alpha = 50$



Experimental Results(5)

Color 20 %, Texture 80%



File :
image\WW4E4CA03B5F1644D1BE198ECC6C863.j

유사도 : 99.9928



유사도 : 77.2714

유사도 : 73.6719

유사도 : 73.1611

유사도 : 69.8360

유사도 : 69.7685



2022-05-12

유사도 : 67.6095

유사도 : 67.4141

유사도 : 66.8762

유사도 : 66.0158

유사도 : 65.8310

Color 20 %, Texture 80%



File :
image\WW82AD54FEB24E4C24869F8FDE608B3.j

유사도 : 99.9518



유사도 : 64.1679

유사도 : 47.6715

유사도 : 43.5663

유사도 : 43.0199

유사도 : 42.5526



유사도 : 41.4326

유사도 : 40.0398

유사도 : 38.3610

유사도 : 37.0857

유사도 : 36.7612



Concluding Remarks

- ✚ We propose a hybrid content-based textile image retrieval approach which uses composite features of color from spatial domain and texture from wavelet-transformed domain.
- ✚ While applying texture features such as contrast, homogeneity, ASM and entropy from wavelet decomposed sub-band images, we can guarantee the rotational-invariant of images.
- ✚ From the experiments we can prove the efficiency based on these multiple textural feature vectors with HS color histogram to retrieve the desired images from a large set of textile image database.



References

- [1] A. Dimai: *Rotation Invariant Texture Description using General Moment Invariants and Gabor Filters*, in Proc. 11th Scandinavian Conf. on Image Analysis Vol. I (1999), pp. 391-398.
- [2] D. Zhang, A. Wong, M. Indrawan and G. Lu: *Content-based Image Retrieval Using Gabor Texture Features*, in Proc. IEEE Pacific-Rim Conference on Multimedia (PCM), (2000), pp. 392-395.
- [3] A.C. Gonzalez-Garcia, J.H. Sossa-Azuela, E.M. Felipe-Riverson and O. Pogrebnyak: *Image Retrieval Based on Wavelet Transform and Neural Network Classification*, in ComputaciÓn y Sistemas Vol. 11, No. 2 (2007) pp. 143-156.
- [4] S. Ardizzoni, I. Bartolini, and M. Patella: *Windsurf: Region-based Image Retrieval Using Wavelets*, in Proc 10th International Workshop on Database and Expert System Application (1999) pp. 167-173.
- [5] P.W. Huang, S.K. Dai and P.L. Lin: *Texture image retrieval and image segmentation using composite sub-band gradient vectors*, in Journal of Visual Communication & Image Representation, Elsevier Inc. Vol. 17, No. 5 (2006) pp. 947-957.
- [6] R. Rahmani, S.A. Goldman, H. Zhang, S.R. Cholleti, and J. E. Fritts: *Localized Content Based Image Retrieval*, in IEEE Transactions on Pattern Analysis and Machine Intelligence, Vol. 30, No. 11 (2008) pp. 1902-1912.
- [7] E. Loupias and N. Sebe: *Wavelet-based Salient Points: Applications to Image Retrieval Using Color and Texture Features*, in Lecture Note in Computer Science(LNCS) Vol. 1929 (2000) pp. 223-232.