



InClass Assignment 8

HTTP Services & Modern Control Flow rendering

Networking Infrastructure (HttpClient / @for Control Loops)

Objective: Master basic REST service calls by fetching JSON records over HTTP and unpacking them directly inside templates using modern block syntax.

Part 1: Configure App Configuration for Global HTTP Protocols

Open `src/app/app.config.ts` (or your bootstrapping initialization block) and pass the standard Angular HTTP client engine into your providers configuration array:

```
import { ApplicationConfig } from '@angular/core';
import { provideHttpClient } from '@angular/common/http';

export const appConfig: ApplicationConfig = {
  providers: [
    provideHttpClient() // Essential helper providing backend connection
    features
  ]
};
```

Part 2: Fetch Remote Server State

Open `src/app/data-list/data-list.ts`. Import `HttpClient`, `OnInit`, and the `inject` utility from their respective packages. Make an HTTP request to populate a local rendering array:

```

import { Component, OnInit, inject } from '@angular/core';
import { HttpClient } from '@angular/common/http';

@Component({
  selector: 'app-data-list',
  standalone: true,
  imports: [],
  templateUrl: './data-list.component.html',
  styleUrls: ['./data-list.component.css']
})
export class DataListComponent implements OnInit {
  private http = inject(HttpClient);

  // Data storage tracking incoming server records
  posts: any[] = [];

  ngOnInit() {
    this.loadRemoteData();
  }

  loadRemoteData() {
    this.http.get<any[]>('https://jsonplaceholder.typicode.com/posts?_limit=4')
      .subscribe({
        next: (response) => {
          this.posts = response;
        },
        error: (error) => {
          console.error('Network retrieval failed:', error);
        }
      });
  }
}

```

Part 3: Write Loop Controls for Display Rendering

Open `src/app/data-list/data-list.html`. Implement modern `@if/@else` and `@for` engine blocks to structure data visually on screen:

```
<section style="border: 1px solid #ddd; padding: 20px; border-radius: 8px; margin-top: 20px; background-color: #fcfcfc;">
```

```
  <h2 style="margin-top: 0; font-size: 1.25rem; color: #28a745;">Live Database Feed</h2>
```

```
  @if (posts.length === 0) {
    <p style="color: #666; font-style: italic;">Contacting server environment...</p>
  } @else {
    <div style="display: flex; flex-direction: column; gap: 12px;">
      @for (post of posts; track post.id) {
        <article style="background: #fff; padding: 15px; border-radius: 6px; border-left: 4px solid #28a745; box-shadow: 0 1px 3px rgba(0,0,0,0.05);">
          <h3 style="margin: 0 0 8px 0; font-size: 1rem; color: #333; text-transform: capitalize;">{{ post.title }}</h3>
          <p style="margin: 0; color: #666; font-size: 0.9rem; line-height: 1.4;">{{ post.body }}</p>
        </article>
      }
    </div>
  }
</section>
```

Part 4: Submission

Confirm that mock data panels load directly onto the page without compilation crashes. Submit your completed configuration and list files.

0 % 0 of 1 topics complete