

sh run

```
Current configuration : 2007 bytes
version 15.1
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
hostname BORDER_5
boot-start-marker
boot-end-marker
no logging buffered
no logging console
no logging monitor
no aaa new-model
dot11 syslog
ip source-route
no ip domain lookup
no ipv6 cef
multilink bundle-name authenticated
voice-card 0
crypto pki token default removal timeout 0
license udi pid CISCO2801 sn FCZ091413Z5
username cisco privilege 15 secret 5 $1$psld$7wrGYja3RiXfRND4MJyCm0
redundancy
interface FastEthernet0/0
no ip address
shutdown
duplex auto
speed auto
interface FastEthernet0/1
description TO_CARRIER_3
ip address 10.0.0.5 255.255.255.252
duplex auto
speed auto
mpls ip
interface Serial0/2/0
no ip address
shutdown
no fair-queue
clock rate 2000000
interface Serial0/2/1
no ip address
shutdown
clock rate 2000000
interface FastEthernet0/1/0
switchport access vlan 56
interface FastEthernet0/1/1
switchport access vlan 48
interface FastEthernet0/1/2
interface FastEthernet0/1/3
interface Vlan1
no ip address
```



```
interface Vlan48
description TO_B_POP_CIX
ip address 10.0.0.49 255.255.255.252
interface Vlan56
description TO_A_POP_CIX ip address 10.0.0.57 255.255.255
passive-interface Vlan48
passive-interface Vlan56
network 10.0.0.4 0.0.0.3 area 1
network 10.0.0.48 0.0.0.3 area 1
network 10.0.0.56 0.0.0.3 area 1
ip forward-protocol nd
no ip http server
no ip http secure-server
logging esm config
control-plane
mgcp profile default
banner motd ^CCarrier, Access prohibited^C
line con 0
logging synchronous
login local
line aux 0
line vty 0 4
logging synchronous login local
transport input all
line vty 5 807
logging synchronous
login local
transport input all
scheduler allocate 20000 1000
end
```