

## show running-config

Current configuration : 1232 bytes

```
version 12.2
no service pad
service timestamps debug uptime
service timestamps log uptime
no service password-encryption

hostname Switch

no logging buffered
no logging console
no logging monitor

no aaa new-model
ip subnet-zero

no file verify auto
spanning-tree mode pvst
spanning-tree extend system-id

vlan internal allocation policy ascending

interface FastEthernet0/1
interface FastEthernet0/2
interface FastEthernet0/3
interface FastEthernet0/4
interface FastEthernet0/5
interface FastEthernet0/6
interface FastEthernet0/7
interface FastEthernet0/8
interface FastEthernet0/9
interface FastEthernet0/10
interface FastEthernet0/11
interface FastEthernet0/12
interface FastEthernet0/13
interface FastEthernet0/14
interface FastEthernet0/15
interface FastEthernet0/16
interface FastEthernet0/17
interface FastEthernet0/18
interface FastEthernet0/19
interface FastEthernet0/20
interface FastEthernet0/21
interface FastEthernet0/22
interface FastEthernet0/23
interface FastEthernet0/24
interface GigabitEthernet0/1
interface GigabitEthernet0/2
```

```
interface Vlan1
no ip address
no ip route-cache

ip http server

control-plane

line con 0
line vty 5 15

end
```

## show ip route

```
^  
% Invalid input detected at '^' marker.
```

## show ipv6 route

```
^  
% Invalid input detected at '^' marker.
```

## show ip int brief

```
Interface IP-Address OK? Method Status Protocol
Vlan1 unassigned YES unset up down
FastEthernet0/1 unassigned YES unset down down
FastEthernet0/2 unassigned YES unset down down
FastEthernet0/3 unassigned YES unset down down
FastEthernet0/4 unassigned YES unset down down
FastEthernet0/5 unassigned YES unset down down
FastEthernet0/6 unassigned YES unset down down
FastEthernet0/7 unassigned YES unset down down
FastEthernet0/8 unassigned YES unset down down
FastEthernet0/9 unassigned YES unset down down
FastEthernet0/10 unassigned YES unset down down
FastEthernet0/11 unassigned YES unset down down
FastEthernet0/12 unassigned YES unset down down
FastEthernet0/13 unassigned YES unset down down
FastEthernet0/14 unassigned YES unset down down
FastEthernet0/15 unassigned YES unset down down
FastEthernet0/16 unassigned YES unset down down
FastEthernet0/17 unassigned YES unset down down
FastEthernet0/18 unassigned YES unset down down
FastEthernet0/19 unassigned YES unset down down
FastEthernet0/20 unassigned YES unset down down
FastEthernet0/21 unassigned YES unset down down
FastEthernet0/22 unassigned YES unset down down
FastEthernet0/23 unassigned YES unset down down
FastEthernet0/24 unassigned YES unset down down
GigabitEthernet0/1 unassigned YES unset down down
GigabitEthernet0/2 unassigned YES unset down down
```

## show ipv6 int brief

```
^  
% Invalid input detected at '^' marker.
```

## show cdp neighbors

Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge  
S - Switch, H - Host, I - IGMP, r - Repeater, P - Phone

Device ID Local Intrfce Holdtme Capability Platform Port ID

## show ipv6 ospf 10

```
^  
% Invalid input detected at '^' marker.
```



## show ipv6 ospf 10 neighbor

```
^  
% Invalid input detected at '^' marker.
```

## show ip bgp summary

^

% Invalid input detected at '^' marker.

## **show access-lists**

## show version

```
Cisco IOS Software, C2960 Software (C2960-LANBASE-M), Version 12.2(25)SEE3, RELEASE
SOFTWARE (fc2)
Copyright (c) 1986-2007 by Cisco Systems, Inc.
Compiled Thu 22-Feb-07 13:57 by myl
Image text-base: 0x00003000, data-base: 0x00AA3380

ROM: Bootstrap program is C2960 boot loader
BOOTLDR: C2960 Boot Loader (C2960-HBOOT-M) Version 12.2(25r)SEE1, RELEASE SOFTWARE (fc1)

Switch uptime is 4 days, 6 hours, 0 minutes
System returned to ROM by power-on
System image file is "flash:c2960-lanbase-mz.122-25.SEE3/c2960-lanbase-mz.122-25.SEE3.bin"

cisco WS-C2960-24TT-L (PowerPC405) processor (revision C0) with 61440K/4088K bytes of
memory.
Processor board ID FOC1123Z47J
Last reset from power-on
1 Virtual Ethernet interface
24 FastEthernet interfaces
2 Gigabit Ethernet interfaces
The password-recovery mechanism is enabled.

64K bytes of flash-simulated non-volatile configuration memory.
Base ethernet MAC Address : 00:1B:0D:84:69:00
Motherboard assembly number : 73-10390-03
Power supply part number : 341-0097-02
Motherboard serial number : FOC112203Q2
Power supply serial number : DCA1115824H
Model revision number : C0
Motherboard revision number : C0
Model number : WS-C2960-24TT-L
System serial number : FOC1123Z47J
Top Assembly Part Number : 800-27221-02
Top Assembly Revision Number : D0
Version ID : V02
CLEI Code Number : COM3L00BRA
Hardware Board Revision Number : 0x01

Switch Ports Model SW Version SW Image
-----
* 1 26 WS-C2960-24TT-L 12.2(25)SEE3 C2960-LANBASE-M

Configuration register is 0xF
```