

## show running-config

```
Current configuration : 1464 bytes

version 12.4
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption

hostname FRAD_CIX

boot-start-marker
boot-end-marker

logging message-counter syslog
no logging buffered
no logging console
no logging monitor

no aaa new-model

dot11 syslog
ip source-route

ip cef

no ipv6 cef

multilink bundle-name authenticated

voice-card 0
no dspfarm

username cisco privilege 15 secret 5 $1$EJga$0HI8Ah/9bb/V3BWKUXkN81
archive
log config
hidekeys

interface FastEthernet0/0
no ip address
shutdown
duplex auto
speed auto

interface FastEthernet0/1
description to_FW
ip address 3.3.3.5 255.255.255.252
duplex auto
speed auto
mpls ip

interface Serial0/2/0
description to_FR
ip address 128.0.0.3 255.255.255.0
encapsulation frame-relay
ip ospf network point-to-multipoint non-broadcast
no fair-queue
clock rate 2000000

interface Serial0/2/1
no ip address
shutdown
clock rate 2000000

router ospf 1
router-id 3.3.3.3
log-adjacency-changes
passive-interface FastEthernet0/1
network 3.3.3.5 0.0.0.0 area 1

ip forward-protocol nd
no ip http server
no ip http secure-server

control-plane
```

```
line con 0
logging synchronous
login local
line aux 0
line vty 0 4
logging synchronous
login local
line vty 5 15
logging synchronous
login local

scheduler allocate 20000 1000
end
```