

show run

```
Current configuration : 749 bytes

version 12.2
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption

hostname VIX_5553

no logging buffered
no logging console
no logging monitor

ip subnet-zero

voice call carrier capacity active

mta receive maximum-recipients 0

interface FastEthernet0/0
no ip address
shutdown
duplex auto
speed auto

interface Serial0/0
no ip address
shutdown
no fair-queue

interface FastEthernet0/1
ip address 10.10.10.1 255.255.255.0
duplex auto
speed auto

interface Serial0/1
no ip address
shutdown

ip classless
ip http server

call rsvp-sync

mgcp profile default

dial-peer cor custom

line con 0
line aux 0
line vty 0 4

end
```

show version

```
Cisco Internetwork Operating System Software
IOS (tm) C2600 Software (C2600-IS-M), Version 12.2(11)T9, RELEASE SOFTWARE (fc1)
TAC Support: http://www.cisco.com/tac
Copyright (c) 1986-2003 by cisco Systems, Inc.
Compiled Mon 23-Jun-03 15:43 by cmong
Image text-base: 0x8000809C, data-base: 0x81673E2C

ROM: System Bootstrap, Version 12.2(7r) [cmong 7r], RELEASE SOFTWARE (fc1)

VIX_5553 uptime is 1 day, 8 minutes
System returned to ROM by reload
System image file is "flash:c2600-is-mz.122-11.T9.bin"

cisco 2621XM (MPC860P) processor (revision 0x100) with 125952K/5120K bytes of memory.
Processor board ID JAD06350767 (894222584)
M860 processor: part number 5, mask 2
Bridging software.
X.25 software, Version 3.0.0.
2 FastEthernet/IEEE 802.3 interface(s)
2 Serial(sync/async) network interface(s)
32K bytes of non-volatile configuration memory.
16384K bytes of processor board System flash (Read/Write)

Configuration register is 0x2102
```