

show running-config

Current configuration : 1564 bytes

```
version 15.1
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
no service password-recovery

hostname Router

boot-start-marker
boot-end-marker

no logging buffered
no logging console
no logging monitor

no aaa new-model

dot11 syslog
ip source-route

ip cef

no ipv6 cef
multilink bundle-name authenticated

voice-card 0

crypto pki token default removal timeout 0

license udi pid CISCO2811 sn FHK1048U065

interface FastEthernet0/0
no ip address
shutdown
duplex auto
speed auto

interface FastEthernet0/1
no ip address
shutdown
duplex auto
speed auto

interface Serial0/0/0
no ip address
shutdown
no fair-queue

interface Serial0/0/1
no ip address
shutdown

interface Serial0/2/0
no ip address
shutdown

interface Serial0/2/1
no ip address
shutdown

interface FastEthernet0/3/0

interface FastEthernet0/3/1

interface FastEthernet0/3/2

interface FastEthernet0/3/3

interface Analysis-Module1/0
no ip address
shutdown
```

```
hold-queue 60 out

interface Vlan1
no ip address

ip forward-protocol nd

no ip http server
no ip http secure-server

control-plane

mgcp profile default

line con 0
line aux 0
line 66
no activation-character
no exec
transport preferred none
transport input all
transport output pad telnet rlogin lapb-ta mop udptn v120 ssh
line vty 0 4
login
transport input all

scheduler allocate 20000 1000
end
```

show ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
+ - replicated route, % - next hop override

Gateway of last resort is not set

show ipv6 route

% Specified IPv6 routing table does not exist

show ip int brief

```
Interface IP-Address OK? Method Status Protocol
FastEthernet0/0 unassigned YES unset administratively down down
FastEthernet0/1 unassigned YES unset administratively down down
Serial0/0/0 unassigned YES unset administratively down down
Serial0/0/1 unassigned YES unset administratively down down
Serial0/2/0 unassigned YES unset administratively down down
Serial0/2/1 unassigned YES unset administratively down down
FastEthernet0/3/0 unassigned YES unset up down
FastEthernet0/3/1 unassigned YES unset up down
FastEthernet0/3/2 unassigned YES unset up down
FastEthernet0/3/3 unassigned YES unset up down
Analysis-Module1/0 unassigned YES unset administratively down down
Vlan1 unassigned YES unset up down
```

show ipv6 int brief

```
FastEthernet0/0 [administratively down/down]
unassigned
FastEthernet0/1 [administratively down/down]
unassigned
Serial0/0/0 [administratively down/down]
unassigned
Serial0/0/1 [administratively down/down]
unassigned
Serial0/2/0 [administratively down/down]
unassigned
Serial0/2/1 [administratively down/down]
unassigned
FastEthernet0/3/0 [up/down]
unassigned
FastEthernet0/3/1 [up/down]
unassigned
FastEthernet0/3/2 [up/down]
unassigned
FastEthernet0/3/3 [up/down]
unassigned
Analysis-Module1/0 [administratively down/down]
unassigned
Vlan1 [up/down]
unassigned
```

show cdp neighbors

Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge
S - Switch, H - Host, I - IGMP, r - Repeater, P - Phone,
D - Remote, C - CVTA, M - Two-port Mac Relay

Device ID Local Intrfce Holdtme Capability Platform Port ID

show ipv6 ospf 10

```
^  
% Invalid input detected at '^' marker.
```


show ipv6 ospf 10 neighbor

```
^  
% Invalid input detected at '^' marker.
```

show ip bgp summary

% BGP not active

show access-lists

show version

Cisco IOS Software, 2800 Software (C2800NM-IPVOICEK9-M), Version 15.1(3)T1, RELEASE SOFTWARE (fc2)

Technical Support: <http://www.cisco.com/techsupport>

Copyright (c) 1986-2011 by Cisco Systems, Inc.

Compiled Sun 27-Mar-11 06:31 by prod_rel_team

ROM: System Bootstrap, Version 12.4(13r)T, RELEASE SOFTWARE (fc1)

Router uptime is 3 days, 21 hours, 24 minutes
System returned to ROM by reload at 19:57:46 UTC Fri Mar 3 2017
System image file is "flash:c2800nm-ipvoicek9-mz.151-3.T1.bin"
Last reload type: Normal Reload

This product contains cryptographic features and is subject to United States and local country laws governing import, export, transfer and use. Delivery of Cisco cryptographic products does not imply third-party authority to import, export, distribute or use encryption. Importers, exporters, distributors and users are responsible for compliance with U.S. and local country laws. By using this product you agree to comply with applicable laws and regulations. If you are unable to comply with U.S. and local laws, return this product immediately.

A summary of U.S. laws governing Cisco cryptographic products may be found at:
<http://www.cisco.com/wwl/export/crypto/tool/stqrg.html>

If you require further assistance please contact us by sending email to export@cisco.com.

Cisco 2811 (revision 53.51) with 249856K/12288K bytes of memory.
Processor board ID FHK1048U065
6 FastEthernet interfaces
4 Serial(sync/async) interfaces
1 terminal line
1 cisco nam sensor(s), nam monitoring on slot 1
DRAM configuration is 64 bits wide with parity enabled.
239K bytes of non-volatile configuration memory.
1964088K bytes of ATA CompactFlash (Read/Write)

License Info:

License UDI:

Device# PID SN

*0 CISCO2811 FHK1048U065

Configuration register is 0x2102