

## show running-config

Current configuration : 1519 bytes

```
version 12.2
no service pad
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption

hostname Switch

boot-start-marker
boot-end-marker

no logging buffered
no logging console
no logging monitor

no aaa new-model
switch 1 provision ws-c2960s-24ts-l

spanning-tree mode pvst
spanning-tree extend system-id

vlan internal allocation policy ascending

interface FastEthernet0
no ip address

interface GigabitEthernet1/0/1

interface GigabitEthernet1/0/2

interface GigabitEthernet1/0/3

interface GigabitEthernet1/0/4

interface GigabitEthernet1/0/5

interface GigabitEthernet1/0/6

interface GigabitEthernet1/0/7

interface GigabitEthernet1/0/8

interface GigabitEthernet1/0/9

interface GigabitEthernet1/0/10

interface GigabitEthernet1/0/11

interface GigabitEthernet1/0/12

interface GigabitEthernet1/0/13

interface GigabitEthernet1/0/14

interface GigabitEthernet1/0/15

interface GigabitEthernet1/0/16

interface GigabitEthernet1/0/17

interface GigabitEthernet1/0/18

interface GigabitEthernet1/0/19

interface GigabitEthernet1/0/20

interface GigabitEthernet1/0/21

interface GigabitEthernet1/0/22

interface GigabitEthernet1/0/23
```

```
interface GigabitEthernet1/0/24
interface GigabitEthernet1/0/25
interface GigabitEthernet1/0/26
interface GigabitEthernet1/0/27
interface GigabitEthernet1/0/28

interface Vlan1
no ip address

ip http server
ip http secure-server

line con 0
line vty 5 15

end
```