

## show running-config

Current configuration : 1797 bytes

```
version 12.2
no service pad
service timestamps debug uptime
service timestamps log uptime
service password-encryption

hostname SW1_7

no logging buffered
no logging console
no logging monitor
enable secret 5 $1$Pi40$4T.QY.w7niLt2lF2dk5d/.

username cisco privilege 15 password 7 02050D480809
no aaa new-model
system mtu routing 1500
ip subnet-zero

no ip domain-lookup

no file verify auto
spanning-tree mode pvst
spanning-tree extend system-id

vlan internal allocation policy ascending

interface FastEthernet0/1
switchport trunk allowed vlan 10,20
switchport mode trunk

interface FastEthernet0/2
switchport access vlan 10
switchport mode access

interface FastEthernet0/3
switchport access vlan 20
switchport mode access

interface FastEthernet0/4

interface FastEthernet0/5

interface FastEthernet0/6

interface FastEthernet0/7

interface FastEthernet0/8

interface FastEthernet0/9

interface FastEthernet0/10

interface FastEthernet0/11

interface FastEthernet0/12

interface FastEthernet0/13

interface FastEthernet0/14

interface FastEthernet0/15

interface FastEthernet0/16

interface FastEthernet0/17

interface FastEthernet0/18

interface FastEthernet0/19

interface FastEthernet0/20
```

---

```
interface FastEthernet0/21

interface FastEthernet0/22

interface FastEthernet0/23

interface FastEthernet0/24

interface GigabitEthernet0/1

interface GigabitEthernet0/2

interface Vlan1
no ip address
no ip route-cache
shutdown

interface Vlan10
no ip address
no ip route-cache

ip http server

control-plane

banner motd ^CWarning! This is a private system!!^C

line con 0
logging synchronous
login local
line vty 0 4
exec-timeout 0 0
logging synchronous
login local
line vty 5 15
exec-timeout 0 0
logging synchronous
login local

end
```

## show ip route

```
^  
% Invalid input detected at '^' marker.
```

## show ip bgp summary

```
^  
% Invalid input detected at '^' marker.
```

## show cdp neighb

Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge  
S - Switch, H - Host, I - IGMP, r - Repeater, P - Phone

Device ID Local Intrfce Holdtme Capability Platform Port ID

## show ip int brief

```
Interface IP-Address OK? Method Status Protocol
Vlan1 unassigned YES unset administratively down down
Vlan10 unassigned YES unset up down
FastEthernet0/1 unassigned YES unset down down
FastEthernet0/2 unassigned YES unset down down
FastEthernet0/3 unassigned YES unset down down
FastEthernet0/4 unassigned YES unset down down
FastEthernet0/5 unassigned YES unset down down
FastEthernet0/6 unassigned YES unset down down
FastEthernet0/7 unassigned YES unset down down
FastEthernet0/8 unassigned YES unset down down
FastEthernet0/9 unassigned YES unset down down
FastEthernet0/10 unassigned YES unset down down
FastEthernet0/11 unassigned YES unset down down
FastEthernet0/12 unassigned YES unset down down
FastEthernet0/13 unassigned YES unset down down
FastEthernet0/14 unassigned YES unset down down
FastEthernet0/15 unassigned YES unset down down
FastEthernet0/16 unassigned YES unset down down
FastEthernet0/17 unassigned YES unset down down
FastEthernet0/18 unassigned YES unset down down
FastEthernet0/19 unassigned YES unset down down
FastEthernet0/20 unassigned YES unset down down
FastEthernet0/21 unassigned YES unset down down
FastEthernet0/22 unassigned YES unset down down
FastEthernet0/23 unassigned YES unset down down
FastEthernet0/24 unassigned YES unset down down
GigabitEthernet0/1 unassigned YES unset down down
GigabitEthernet0/2 unassigned YES unset down down
```

## show track

```
^  
% Invalid input detected at '^' marker.
```

**show ip nat translations**



## **show access-lists**

## show route-map

```
^  
% Invalid input detected at '^' marker.
```

## show version

Cisco IOS Software, C2960 Software (C2960-LANBASE-M), Version 12.2(35)SE5, RELEASE SOFTWARE (fc1)

Copyright (c) 1986-2007 by Cisco Systems, Inc.

Compiled Thu 19-Jul-07 20:06 by nachen

Image text-base: 0x00003000, data-base: 0x00D40000

ROM: Bootstrap program is C2960 boot loader

BOOTLDR: C2960 Boot Loader (C2960-HBOOT-M) Version 12.2(25r)SEE6, RELEASE SOFTWARE (fc1)

SW1\_7 uptime is 6 days, 3 hours, 59 minutes

System returned to ROM by power-on

System image file is "flash:c2960-lanbase-mz.122-35.SE5/c2960-lanbase-mz.122-35.SE5.bin"

cisco WS-C2960-24TT-L (PowerPC405) processor (revision F0) with 61440K/4088K bytes of memory.

Processor board ID FOC1235W51L

Last reset from power-on

2 Virtual Ethernet interfaces

24 FastEthernet interfaces

2 Gigabit Ethernet interfaces

The password-recovery mechanism is disabled.

64K bytes of flash-simulated non-volatile configuration memory.

Base ethernet MAC Address : 00:23:34:5A:20:80

Motherboard assembly number : 73-11473-05

Power supply part number : 341-0097-02

Motherboard serial number : FOC123535HJ

Power supply serial number : DCA1234848U

Model revision number : F0

Motherboard revision number : A0

Model number : WS-C2960-24TT-L

System serial number : FOC1235W51L

Top Assembly Part Number : 800-29859-02

Top Assembly Revision Number : A0

Version ID : V05

CLEI Code Number : COM3L00BRD

Hardware Board Revision Number : 0x01

Switch Ports Model SW Version SW Image

```
-----
* 1 26 WS-C2960-24TT-L 12.2(35)SE5 C2960-LANBASE-M
```

Configuration register is 0xF