CUST⊛DIO

show running-config

```
Current configuration : 988 bytes

version 12.4
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption

hostname Router

boot-start-marker
boot-end-marker

logging message-counter syslog

no aaa new-model

dot11 syslog
ip source-route

ip cef

no ipv6 cef

multilink bundle-name authenticated

voice-card 0

archive
log config
hidekeys
!

interface FastEthernet0/0
ip address 192.168.1.10 255.255.255.0
duplex auto
speed auto

interface FastEthernet0/1
no ip address
shutdown
duplex auto
speed auto

interface Serial0/2/0
ip address 10.7.8.9 255.255.255.0
no fair-queue
clock rate 2000000

interface Serial0/2/1
ip address 10.5.100.78 255.255.255.252
clock rate 2000000

ip forward-protocol nd
no ip http server
no ip http secure-server

control-plane

line con 0
line aux 0
line vty 0 4
login

scheduler allocate 20000 1000
end
```

CUST⊛DIO

show ip int brief

```
Interface IP-Address OK? Method Status Protocol
FastEthernet0/0 192.168.1.10 YES manual up up
FastEthernet0/1 unassigned YES unset administratively down down
Serial0/2/0 10.7.8.9 YES manual down down
Serial0/2/1 10.5.100.78 YES manual down down
```

CUST◉DIO

show version

```
Cisco IOS Software, 2800 Software (C2800NM-ADVENTERPRISEK9-M), Version 12.4(24)T2, RELEASE
SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Mon 19-Oct-09 17:38 by prod_rel_team

ROM: System Bootstrap, Version 12.4(13r)T11, RELEASE SOFTWARE (fc1)

Router uptime is 1 week, 2 days, 23 hours, 43 minutes
System returned to ROM by reload at 12:59:28 UTC Fri Dec 23 2016
System image file is "flash:c2800nm-adventerprisek9-mz.124-24.T2.bin"


This product contains cryptographic features and is subject to United
States and local country laws governing import, export, transfer and
use. Delivery of Cisco cryptographic products does not imply
third-party authority to import, export, distribute or use encryption.
Importers, exporters, distributors and users are responsible for
compliance with U.S. and local country laws. By using this product you
agree to comply with applicable laws and regulations. If you are unable
to comply with U.S. and local laws, return this product immediately.

A summary of U.S. laws governing Cisco cryptographic products may be found at:
http://www.cisco.com/wwl/export/crypto/tool/stqrg.html

If you require further assistance please contact us by sending email to
export@cisco.com.

Cisco 2811 (revision 53.51) with 512000K/12288K bytes of memory.
Processor board ID FCZ142270AY
2 FastEthernet interfaces
2 Serial(sync/async) interfaces
1 Virtual Private Network (VPN) Module
DRAM configuration is 64 bits wide with parity enabled.
239K bytes of non-volatile configuration memory.
62720K bytes of ATA CompactFlash (Read/Write)

Configuration register is 0x2102
```