

show running-config

```
Current configuration : 2905 bytes

version 12.4
service timestamps debug datetime msec
service timestamps log datetime msec
service password-encryption

hostname R2-23_ISPC-B6

boot-start-marker
boot-end-marker

logging message-counter syslog
enable secret 5 $1$SIBi$S5wNrbIY3O9kmAfokZ/.P.

no aaa new-model

dot11 syslog
ip source-route

ip cef

no ip domain lookup
ipv6 unicast-routing
ipv6 cef

multilink bundle-name authenticated

voice-card 0

username cisco privilege 15 secret 5 $1$Vx/2$.FfFNwlTCOjPbG.7onaUW0
archive
log config
hidekeys
!

interface Loopback0
ip address 23.1.1.1 255.255.255.0
ipv6 address 2001:23::1/64
ipv6 enable
ipv6 ospf 10 area 1

interface FastEthernet0/0
ip address 200.6.0.1 255.255.255.0
duplex auto
speed auto

interface FastEthernet0/1
no ip address
shutdown
duplex auto
speed auto

interface Serial0/1/0
description ToR2-20_ISPC
no ip address
encapsulation frame-relay
no keepalive
no fair-queue
clock rate 2000000

interface Serial0/1/0.402 point-to-point
description ToR2-20_ISPC
ip address 10.30.0.14 255.255.255.252
ip access-group s010_IN in
ip access-group s010_OUT out
ipv6 address 2001:4::2/64
ipv6 enable
ipv6 ospf 10 area 1
frame-relay interface-dlci 402

interface Serial0/1/1
no ip address
```

```
shutdown
clock rate 2000000

interface Serial0/2/0
ip address 200.4.30.1 255.255.255.0
clock rate 2000000

interface Serial0/2/1
ip address 200.4.31.1 255.255.255.0
clock rate 2000000

router ospf 1
log-adjacency-changes
network 10.30.0.12 0.0.0.3 area 1
network 23.1.1.0 0.0.0.255 area 1

router bgp 300
bgp router-id 23.1.1.1
no bgp default ipv4-unicast
bgp log-neighbor-changes
neighbor 9.1.1.1 remote-as 300
neighbor 9.1.1.1 update-source Loopback0
neighbor 2001:9::1 remote-as 300
neighbor 2001:9::1 update-source Loopback0
!
address-family ipv4
neighbor 9.1.1.1 activate
neighbor 9.1.1.1 next-hop-self
no auto-summary
no synchronization
network 200.6.0.0
exit-address-family
!
address-family ipv6
neighbor 2001:9::1 activate
exit-address-family

ip forward-protocol nd
ip route 2.2.2.0 255.255.255.0 190.20.0.1
no ip http server
no ip http secure-server

ipv6 router ospf 10
router-id 23.1.1.1
log-adjacency-changes

ipv6 access-list s010_IN
permit tcp host 2001:9::1 host 2001:23::1 eq bgp
permit tcp host 2001:9::1 eq bgp host 2001:23::1
permit tcp 2001:4::/64 FF02::/64 eq 89

control-plane

banner motd ^CCNot Authorized!^C

line con 0
exec-timeout 0 0
password 7 030752180500
logging synchronous
login local
line aux 0
line vty 0 4
exec-timeout 0 0
password 7 05080F1C2243
logging synchronous
login local
transport input telnet
line vty 5 15
exec-timeout 0 0
password 7 05080F1C2243
logging synchronous
login local
transport input telnet

scheduler allocate 20000 1000
end
```

show ip route

Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

23.0.0.0/24 is subnetted, 1 subnets
C 23.1.1.0 is directly connected, Loopback0

show ip int brief

```
Interface IP-Address OK? Method Status Protocol
FastEthernet0/0 200.6.0.1 YES manual up down
FastEthernet0/1 unassigned YES manual administratively down down
Serial0/1/0 unassigned YES manual down down
Serial0/1/0.402 10.30.0.14 YES manual down down
Serial0/1/1 unassigned YES manual administratively down down
Serial0/2/0 200.4.30.1 YES manual down down
Serial0/2/1 200.4.31.1 YES manual down down
Loopback0 23.1.1.1 YES manual up up
```

show cdp neighbors

Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge
S - Switch, H - Host, I - IGMP, r - Repeater

Device ID Local Intrfce Holdtme Capability Platform Port ID

show ip bgp summary

BGP router identifier 23.1.1.1, local AS number 300
BGP table version is 1, main routing table version 1

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
9.1.1.1	4	300	0	0	0	0	0	never	Active

show version

Cisco IOS Software, 2800 Software (C2800NM-ADVENTERPRISEK9-M), Version 12.4(24)T2, RELEASE SOFTWARE (fc2)

Technical Support: <http://www.cisco.com/techsupport>

Copyright (c) 1986-2009 by Cisco Systems, Inc.

Compiled Mon 19-Oct-09 17:38 by prod_rel_team

ROM: System Bootstrap, Version 12.4(13r)T, RELEASE SOFTWARE (fc1)

R2-23_ISPC-B6 uptime is 5 days, 16 minutes

System returned to ROM by reload at 00:11:39 UTC Sat May 31 2014

System image file is "flash:c2800nm-adventerprisek9-mz.124-24.T2.bin"

This product contains cryptographic features and is subject to United States and local country laws governing import, export, transfer and use. Delivery of Cisco cryptographic products does not imply third-party authority to import, export, distribute or use encryption. Importers, exporters, distributors and users are responsible for compliance with U.S. and local country laws. By using this product you agree to comply with applicable laws and regulations. If you are unable to comply with U.S. and local laws, return this product immediately.

A summary of U.S. laws governing Cisco cryptographic products may be found at:
<http://www.cisco.com/wwl/export/crypto/tool/stqrg.html>

If you require further assistance please contact us by sending email to export@cisco.com.

Cisco 2811 (revision 53.51) with 249856K/12288K bytes of memory.

Processor board ID FCZ124671CY

2 FastEthernet interfaces

4 Serial(sync/async) interfaces

1 Virtual Private Network (VPN) Module

DRAM configuration is 64 bits wide with parity enabled.

239K bytes of non-volatile configuration memory.

62720K bytes of ATA CompactFlash (Read/Write)

Configuration register is 0x2102