

Lecture 12: Finite Elasticity

David Al-Attar

Michaelmas Term, 2025

Outline and motivation

In this lecture, we derive the equations of motion for an elastic body. These equations provide a good though not complete model for understanding seismic wave propagation and other related topics in geophysics. Most of you will have encountered elasticity within earlier courses, but here we will go back to first principles. In particular, we discuss **finite elasticity**, this meaning that there is no assumption that the deformation has to remain small in an appropriate sense. Within later applications it will actually be sufficient to consider linearised motions about an equilibrium state, but by starting with the exact theory it is easier to appreciate the underlying physics.

Basic definitions

We start by considering the kinematics of a solid body. At an instant in time, t , the body occupies a subset M_t of physical space, $\mathbb{R}^3$. A useful way to describe the motion is through the introduction of a reference body, M . Each point $\mathbf{x}$ in the reference body corresponds to a unique particle. At time t , the particle $\mathbf{x}$ sits at a point in physical space that we denote by $\varphi(\mathbf{x}, t)$. In this manner we see that the body's motion is completely described by this time-dependent mapping, $\varphi(\cdot, t)$, from the reference body into physical space. We will call φ the **motion** of the body, this being the field within this classical field theory. We will not consider motions for which the body is torn or fractured. As a result, we suppose that φ is continuously differentiable, and that at each fixed time, t , it establishes a one-to-one correspondence between M and M_t . These ideas are summarised graphically within Fig.1.




Fig. 1: A schematic illustration of the mapping from the reference body M into the body's instantaneous position in physical space.

In making these definitions we have not specified how the reference body is chosen. Indeed, it turns out that there are infinitely many ways of doing this. Nevertheless, a common approach is to let points in the reference body correspond to the position of the particles at some reference time, t_0 . Having done this, we then have

$$\varphi(\mathbf{x}, t_0) = \mathbf{x} \quad (1)$$

for all $\mathbf{x}$. It can, however, sometimes be useful to select a different reference body for both theoretical and computational reasons.

Velocity, deformation gradient, and Jacobian

If we fix attention to a particle $\mathbf{x}$, then the function $t \mapsto \varphi(\mathbf{x}, t)$ describes its trajectory through space. Differentiating with respect to time, we obtain the **referential velocity**

$$v_i(\mathbf{x}, t) = \frac{\partial \varphi_i}{\partial t}(\mathbf{x}, t) \quad (2)$$

Note that this is the velocity of a fixed particle, and not at a fixed spatial point. This differs from what is commonly done in fluid mechanics. In what follows, we will generally drop the term “referential” and just say “velocity” for this vector field.

A second quantity that will be important is the **deformation gradient**, $\mathbf{F}$, which is defined by

$$F_{ij} = \frac{\partial \varphi_i}{\partial x_j} \quad (3)$$

Physically, the deformation gradient quantifies how the motion differs between nearby points in the reference body. For example, if we consider particles $\mathbf{x}$ and $\mathbf{x} + \delta\mathbf{x}$ with $\delta\mathbf{x}$ small, then we can use a Taylor expansion to obtain

$$\varphi_i(\mathbf{x} + \delta\mathbf{x}, t) = \varphi_i(\mathbf{x}, t) + F_{ij}(\mathbf{x}, t)\delta x_j + \cdots, \quad (4)$$

which is accurate to first-order in $\delta\mathbf{x}$. The deformation gradient is related to, but not identical with, the concept of **strain**, with this correspondence discussed further in the next lecture.

Because we have assumed that the motion establishes a one-to-one correspondence between M and M_t at each time, it can be shown that $\mathbf{F}(\mathbf{x}, t)$ is an invertible matrix at each point.¹ The determinant of the deformation gradient is known as the **Jacobian** of the motion, and is written

$$J(\mathbf{x}, t) = \det \mathbf{F}(\mathbf{x}, t). \quad (5)$$

Invertibility of the deformation gradient implies that J is never equal to zero, while continuity of φ implies that it is always of one sign. We will assume that J is always positive. This implies in particular that a right-handed set of basis vectors in M is mapped to a right-handed set of basis vectors in M_t .

Consider a function f defined in the instantaneous body M_t , and its integral

$$I = \int_{M_t} f(\mathbf{y}) d^3\mathbf{y}. \quad (6)$$

¹ This follows from a result known as the **inverse function theorem**.

Using the motion at this instant in time, we can change variables to write the integral as one over the reference body

$$I = \int_M f[\varphi(\mathbf{x}, t)] J(\mathbf{x}, t) d^3\mathbf{x}. \quad (7)$$

This ability to easily transform integrals between the instantaneous and reference bodies will be very useful in what follows.

Conservation of mass

Let U be a subset of the reference body and U_t the region of physical space it occupies at time t . The mass of this sub-body can be written

$$\int_{U_t} \rho(\mathbf{y}, t) d^3\mathbf{y}, \quad (8)$$

where $\rho(\mathbf{y}, t)$ is the density at the point $\mathbf{y}$ in M_t and time t . During the deformation matter is not created nor destroyed. This means that the mass of this arbitrary sub-body is constant, and hence we must have

$$\frac{d}{dt} \int_{U_t} \rho(\mathbf{y}, t) d^3\mathbf{y} = 0. \quad (9)$$

To simplify this expression we use the motion to transform the integration in eq.(9) to the reference body

$$\frac{d}{dt} \int_U J(\mathbf{x}, t) \rho[\varphi(\mathbf{x}, t), t] d^3\mathbf{x} = 0. \quad (10)$$

This integral is over a fixed domain, and so we can interchange the order of differentiation and integration. Furthermore, as U is an arbitrary subset of M , the equality can hold if and only if

$$\frac{\partial}{\partial t} \{J(\mathbf{x}, t) \rho[\varphi(\mathbf{x}, t), t]\} = 0. \quad (11)$$

It follows we can introduce a time-independent **referential density** ρ_0 such that

$$\rho_0(\mathbf{x}) = J(\mathbf{x}, t) \rho[\varphi(\mathbf{x}, t), t] \quad (12)$$

This is a statement of mass conservation expressed within the reference body. Note that if the reference body is chosen such that eq.(1) holds at some time $t = t_0$ then at this time eq.(12) simplifies to

$$\rho_0(\mathbf{x}) = \rho(\mathbf{x}, t_0). \quad (13)$$

Thus, when using this common choice of reference body, the referential density is precisely the density at the reference time.

Kinetic energy

By analogy with particle mechanics, the kinetic energy density of the body per-unit volume within the reference body M is defined as

$$\frac{1}{2} \rho_0(\mathbf{x}) \|\mathbf{v}(\mathbf{x}, t)\|^2, \quad (14)$$

and summing up such contributions, we see that the total kinetic energy can be written

$$\mathcal{T}(t) = \frac{1}{2} \int_M \rho_0(\mathbf{x}) \|\mathbf{v}(\mathbf{x}, t)\|^2 d^3\mathbf{x}. \quad (15)$$

Potential energy

What should the potential energy of an elastic body look like? The basic idea is that the body has a preferred shape and/or volume, and that energy is required to deform the body away from this equilibrium state. As a starting point we assume that the potential energy can be expressed in the form

$$\mathcal{V}(t) = \int_M W[\mathbf{x}, t, \boldsymbol{\varphi}(\mathbf{x}, t), \mathbf{F}(\mathbf{x}, t)] d^3\mathbf{x}, \quad (16)$$

where W is a potential energy density measured per unit volume within the reference body. This is not the most general form that the potential energy could take, but defines what is known as a **simple hyperelastic body**. That a body is **hyperelastic** means that it has a well-defined potential energy. A consequence of this assumption – that you will establish in the first problem set – is that energy is conserved during the deformation of the body, and hence within this theory we are discounting dissipative processes². Energy dissipation is relevant to seismology, but it is a relatively minor effect that we will neglect in this course. The term **simple** in the above context means that the potential energy density at a point, $\mathbf{x}$, depends only on the motion and the deformation gradient at the same point.

Simplifying the potential energy using symmetries

Having accepted the form of the potential energy in eq.(16), we are now in a position to obtain the equations of motion using Hamilton's principle. Before doing this, the form of the potential energy density can be simplified by imposing certain physical constraints:

- (i) **Time-translation invariance** Consider a motion $\boldsymbol{\varphi}(\mathbf{x}, t)$ and its time-translation $\boldsymbol{\varphi}'(\mathbf{x}, t) = \boldsymbol{\varphi}(\mathbf{x}, t - \tau)$ for some τ . The second motion takes exactly the same form but is just shifted in time, and hence it is natural to require that their respective potential energies satisfy

$$\mathcal{V}'(t) = \mathcal{V}(t - \tau). \quad (17)$$

This condition is automatically met if the potential energy density has no explicit dependence on time, and hence we simplify its form to

$$\mathcal{V}(t) = \int_M W[\mathbf{x}, \boldsymbol{\varphi}(\mathbf{x}, t), \mathbf{F}(\mathbf{x}, t)] d^3\mathbf{x}. \quad (18)$$

The necessity of this condition can also be established.

² The situation is analogous to particle mechanics restricted to the case of conservative forces, i.e., those forces that are derived from a potential energy

- (ii) **Invariance under rigid body motions** As stated above, an elastic body has a preferred shape and/or volume, and the potential energy is associated with deformations of the body away from this. Motions that do not alter its shape nor volume should not, therefore, be associated with a change in potential energy. Within Euclidean space, motions that do not change the relative lengths between points arise through a combination of rotations and translations. If φ is a motion of the body, we can define a second motion φ' by setting

$$\varphi'(\mathbf{x}, t) = \mathbf{a}(t) + \mathbf{Q}(t)\varphi(\mathbf{x}, t) \quad (19)$$

where $\mathbf{Q}(t)$ is a rotation matrix. Because these motions differ only by a superimposed rigid body motion, they must be associated with the same potential energy. Noting that $\mathbf{F}'(\mathbf{x}, t) = \mathbf{Q}(t)\mathbf{F}(\mathbf{x}, t)$, it follows that this invariance condition will be met so long as the potential energy density satisfies

$$W[\mathbf{x}, \varphi(\mathbf{x}, t), \mathbf{F}(\mathbf{x}, t)] = W[\mathbf{x}, \mathbf{a}(t) + \mathbf{Q}(t)\varphi(\mathbf{x}, t), \mathbf{Q}(t)\mathbf{F}(\mathbf{x}, t)]. \quad (20)$$

Again, necessity of this condition can also be proven. Assuming that $\mathbf{Q}(t) = \mathbf{1}$ this identity reduces to

$$W[\mathbf{x}, \varphi(\mathbf{x}, t), \mathbf{F}(\mathbf{x}, t)] = W[\mathbf{x}, \mathbf{a}(t) + \varphi(\mathbf{x}, t), \mathbf{F}(\mathbf{x}, t)]. \quad (21)$$

For fixed $(\mathbf{x}, t)$, we can vary $\mathbf{a}(t)$ such that the second argument on the right hand side takes any possible value. It follows that the potential energy density must be independent of its second argument. Given this result, it is useful to again re-define the potential energy density to depend only on $\mathbf{x}$ and $\mathbf{F}(\mathbf{x}, t)$, and having done this the condition in eq.(20) reduces to

$$W[\mathbf{x}, \mathbf{F}(\mathbf{x}, t)] = W[\mathbf{x}, \mathbf{Q}(t)\mathbf{F}(\mathbf{x}, t)], \quad (22)$$

for all deformation gradients, and all rotation matrices $\mathbf{Q}(t)$. This condition limits the allowable form of the potential energy density, and we will explore its consequences further within the next lecture.

In summary, we find that the potential energy takes the simpler form

$$\mathcal{V}(t) = \int_M W[\mathbf{x}, \mathbf{F}(\mathbf{x}, t)] d^3\mathbf{x}. \quad (23)$$

where W is subject to eq.(22). Within continuum mechanics this potential energy density is called the **strain energy function**, and this what we will say from now on. The invariance of the potential energy under (i) time-translation, and (ii) superimposed rigid body motions, goes under the collective name of the principle of **material frame indifference**. This idea was introduced by Clifford Truesdell in the 1950s, and plays a central role within all branches of theoretical continuum mechanics. Here we have only formulated this principle for a simple hyperelastic body, but it can be generalised to other types of material, and to incorporate thermodynamics and electromagnetism.

Hamilton's principle

A Lagrangian density for a hyperelastic body is defined in the usual manner³ as the difference between the kinetic and potential energy densities

$$\mathcal{L}(\mathbf{x}, t, \boldsymbol{\varphi}, \mathbf{v}, \mathbf{F}) = \frac{1}{2} \rho_0(\mathbf{x}) \|\mathbf{v}\|^2 - W(\mathbf{x}, \mathbf{F}) \quad (24)$$

while the the associated action is

$$\mathcal{S}(\boldsymbol{\varphi}) = \int_0^T \int_M \mathcal{L}[\mathbf{x}, t, \boldsymbol{\varphi}(\mathbf{x}, t), \mathbf{v}(\mathbf{x}, t), \mathbf{F}(\mathbf{x}, t)] d^3\mathbf{x} dt, \quad (25)$$

where $[0, T]$ is the time-interval of interest, and it is understood that the referential velocity and deformation gradient on the right hand side are those associated with the given motion. Note that the Lagrangian density in eq.(24) shows no explicit dependence on t nor $\boldsymbol{\varphi}$, but we shall retain this more general expression in what follows. Hamilton's principle states that the true motion is a stationary point of the action with respect to all smooth variations $\delta\boldsymbol{\varphi}$ which satisfy the fixed end-point condition

$$\delta\boldsymbol{\varphi}(\mathbf{x}, 0) = \delta\boldsymbol{\varphi}(\mathbf{x}, T) = 0. \quad (26)$$

Mathematically, this means that we require the first-variation of the action

$$\delta\mathcal{S} = \lim_{h \rightarrow 0} \frac{1}{h} [\mathcal{S}(\boldsymbol{\varphi} + h \delta\boldsymbol{\varphi}) - \mathcal{S}(\boldsymbol{\varphi})] \quad (27)$$

be equal to zero for all smooth variations $\delta\boldsymbol{\varphi}$ satisfying eq.(26). We readily find that this first-variation can be written

$$\delta\mathcal{S} = \int_0^T \int_M \left\{ \frac{\partial \mathcal{L}}{\partial \varphi_i} \delta\varphi_i + \frac{\partial \mathcal{L}}{\partial v_i} \delta v_i + \frac{\partial \mathcal{L}}{\partial F_{ij}} \delta F_{ij} \right\} d^3\mathbf{x} dt, \quad (28)$$

where the variations in the referential velocity and deformation gradient are given by

$$\delta v_i = \frac{\partial \delta \varphi_i}{\partial t} \quad (29)$$

$$\delta F_{ij} = \frac{\partial \delta \varphi_i}{\partial x_j} \quad (30)$$

and we have suppressed all arguments for clarity. From the following identities

$$\frac{\partial \mathcal{L}}{\partial v_i} \delta v_i = \frac{\partial}{\partial t} \left(\frac{\partial \mathcal{L}}{\partial v_i} \delta \varphi_i \right) - \frac{\partial}{\partial t} \left(\frac{\partial \mathcal{L}}{\partial v_i} \right) \delta \varphi_i \quad (31)$$

$$\frac{\partial \mathcal{L}}{\partial F_{ij}} \delta F_{ij} = \frac{\partial}{\partial x_j} \left(\frac{\partial \mathcal{L}}{\partial F_{ij}} \delta \varphi_i \right) - \frac{\partial}{\partial x_j} \left(\frac{\partial \mathcal{L}}{\partial F_{ij}} \right) \delta \varphi_i, \quad (32)$$

³ For those with less experience with variational principles, the necessary ideas are developed here from first principles. But please ask either in the supervisions or otherwise if you would like any additional help with this material.

along with eq.(26) and the divergence theorem, we obtain

$$\delta S = \int_0^T \int_M \left\{ \frac{\partial \mathcal{L}}{\partial \varphi_i} - \frac{\partial}{\partial t} \left(\frac{\partial \mathcal{L}}{\partial v_i} \right) - \frac{\partial}{\partial x_j} \left(\frac{\partial \mathcal{L}}{\partial F_{ij}} \right) \right\} \delta \varphi_i d^3 \mathbf{x} dt + \int_0^T \int_{\partial M} \frac{\partial \mathcal{L}}{\partial F_{ij}} \hat{n}_j \delta \varphi_i dS dt, \quad (33)$$

where $\hat{\mathbf{n}}$ denotes the outward unit normal vector to ∂M , and dS is the surface element. As $\delta \varphi$ is arbitrary, this first variation can vanish only if both the volumetric term and boundary term are independently equal to zero⁴. Hamilton's principle, therefore, implies that the Euler-Lagrange equations

$$\frac{\partial \mathcal{L}}{\partial \varphi_i} - \frac{\partial}{\partial t} \left(\frac{\partial \mathcal{L}}{\partial v_i} \right) - \frac{\partial}{\partial x_j} \left(\frac{\partial \mathcal{L}}{\partial F_{ij}} \right) = 0, \quad (34)$$

hold within the body, while on ∂M we also have the natural boundary conditions

$$\frac{\partial \mathcal{L}}{\partial F_{ij}} \hat{n}_j = 0, \quad (35)$$

on ∂M . Note that these boundary conditions are called "natural" because they have arisen directly from the variational principle, and not because of some prior restriction on the class of admissible motions.

For the Lagrangian density in eq.(24) we readily find that

$$\frac{\partial \mathcal{L}}{\partial \varphi_i} = 0, \quad (36)$$

$$\frac{\partial \mathcal{L}}{\partial v_i} = \rho_0 v_i \quad (37)$$

$$\frac{\partial \mathcal{L}}{\partial F_{ij}} = - \frac{\partial W}{\partial F_{ij}}. \quad (38)$$

The **first Piola-Kirchhoff stress tensor** is defined by

$$T_{ij}(\mathbf{x}, t) = \frac{\partial W}{\partial F_{ij}}[\mathbf{x}, \mathbf{F}(\mathbf{x}, t)], \quad (39)$$

so that the Euler-Lagrange equations can be written

$$\rho_0 \frac{\partial v_i}{\partial t} - \frac{\partial T_{ij}}{\partial x_j} = 0, \quad (40)$$

while the boundary condition becomes

$$T_{ij} \hat{n}_j = 0. \quad (41)$$

The vector $\mathbf{t} = \mathbf{T} \hat{\mathbf{n}}$ occurring in the boundary conditions is known as the traction. Within the first problem set you will see that it represents a surface force measured per unit area within the reference body. Indeed, what the first Piola-Kirchhoff stress does

⁴ If this statement is not obvious, then you might wish to ask in a supervision. But for the purposes of this course it is sufficient to know how to apply this method.

is relate the orientation of a surface within the reference body to the force per unit area acting on the instantaneous image of that surface within physical space.

As a final comment, the equations of motion are defined on the *fixed* reference body, and hence we need not worry about applying boundary conditions on a moving boundary as is sometimes required in fluid mechanics problems that use a spatial formulation of continuum mechanics. This fact considerably simplifies the solution of free-boundary problems in elasticity, and is one of the reasons for working with a referential description of the motion.

What you need to know and be able to do

- (i) Understand the terminology needed to described the kinematics of an elastic body.
- (ii) Use the conservation of mass to derive the relation between the spatial and referential densities.
- (iii) State expressions for the kinetic and potential energies of a simple hyperelastic body, and to explain the underlying physical ideas and assumptions.
- (iv) Give a statement of Hamilton's principle in the context of finite elasticity, and use it to derive the equations of motion and associated boundary conditions.