Title: capture.ini

Product: OrCAD Capture with and without CIS Option and Allegro DE CIS

Summary: Description of the configuration file capture.ini.

Author/Date: Beate Wilke / 05.04.2011

Table of Contents

1 Introduction

Capture has a central configuration file for every user. When you start Capture first it reads nearly all settings out of the installation files and creates a default capture.ini. If the user changes any setting, Capture writes this into the user capture.ini. Only your personal database paths are missing and must be filled into capture.ini by the user or administrator.

It's useful to define a master capture.ini to start up the system and provide new users. This master capture.ini should contain all library paths and company specific settings.

Capture damages his capture.ini sometimes. Then delete the user capture.ini and restart the program with master capture.ini

We tried to explain the main commands in capture.ini to help you to define your local company and user settings. Capture will add additional information to report queries and opened database tables. You can delete this information every time.

2 Capture.ini - Location

For XP select Start -> Programs -> Cadence SPB 16.01 and right click on Design Entry CIS. Open the properties menu.



In the field Target you find these settings:

e.g.: C:\Cadence\SPB_1601\tools\capture\capture.exe -CIS -i "D:\Home\Capture"

C:\Cadence\SPB_1601\tools\capture\capture.exe is the path to the Capture.exe.
-CIS starts Capture with CIS Option
-i "D:\Home\Capture" is the path to the Capture.ini

Select OK to close the window.

By default this path is <CDSROOT>/tools/capture. We changed it to a folder where the user has full privileges.

Note: If the user do not has full system privileges to the install area of the Cadence tool it's important to change this path to a folder with full privileges. The Allegro HOME folder would be perfect.

3 Overview

	Command Name	Useful for master capture.ini	Automatically generated by Capture
1	Application	no	Yes
2	Footprint Viewer Type	yes	No
3	Allegro Footprints	Yes	No
4	Part Library Directories	Yes	No
5	Part Management	Yes	No
6	CIS Browse Directories	Yes	No
7	Part Selector Configured Libraries	No	Yes
8	Symbol Selector Configured Libraries	No	Yes

8	Visibility Frame	No	Default settings from installation
10	Schematic Part Frame	No	Default settings from installation
11	FootPrint Frame	No	Default settings from installation
12	Relational Table Frame	No	Default settings from installation
13	Explore Frame	No	Default settings from installation
14	Part Manager	Yes	Default settings from installation
15	Design Template	Yes	Default settings from installation
16	Preferences	Yes	Default settings from installation
17	Text Editor	Yes	Default settings from installation
18	ERC Matrix	Yes	Default settings from installation
19	Default Colors	Yes	Default settings from installation
20	BoM	Yes	Default settings from installation
21	Crystal Reports BOM	Only if you want to use Chrystal Report	Default settings from installation
22	Variant	Yes	Default settings from installation

23	Intersheet References	Yes	Default settings from installation
24	Variant.LST	Yes	Default settings from installation
25	Spreadsheet	Yes	Default settings from installation
26	Project Wizard	No	Default settings from installation
27	Place Part Search	No	Default settings from installation
28	__MRURegList	No	yes
29	Translators	No	Default settings from installation
30	Print Settings	Depends on your Installation	Default settings from installation
31	Recent File List	No	yes
32	CIS Database Tables	no	yes

4 Description

4.1 Application

4.1.1 Syntax

[Application]
Version=16.3.0 b003.b003

4.1.2 Description

It shows the installed software and Hotfix version.

4.2 Footprint Viewer Type

4.2.1 Syntax

[Footprint Viewer Type]
Type=Allegro

4.2.2 Description

This setting should always be Allegro. It describes the footprint viewer which CIS Explorer uses for 2D footprint preview.

4.3 Allegro Footprints

4.3.1 Syntax

[Allegro Footprints]
Dir0=E:\FlowCAD_Library\Allegro_Footprints_163\Footprints\all
Dir1=E:\FlowCAD_Library\Allegro_Footprints_163\Pads
Dir2=E:\FlowCAD_Library\Allegro_Footprints_163\Pads\padsym

4.3.2 Description

It contains the path definitions to all footprint and pad folders.

4.4 Part Library Directories

4.4.1 Syntax

[Part Library Directories]
Dir0=E:\FlowCAD_Library\CIS-Symbols_163
Dir1=E:\Sales\customer\DB

4.4.2 Description

It contains the path definitions to all Capture OLB files.

4.5 Part Management

4.5.1 Syntax

[Part Management]
Configuration File=E:\FLOWCAD_LIBRARY\FILES\FC_LIB_163.DBC
DemoConfiguration File=D:\CADENCE\SAMPLES\BENCHACC.DBC]Width=536BarID=219

4.5.2 Description

It contains the path to the current DBC file. The DBC file contains the configuration and link to the property database. Capture uses the DemoConfiguration if Capture is started in demo mode. In demo mode the database must be less than 9 components.

4.6 CIS Browser Directories

4.6.1 Syntax

[CIS Browse Directories]
Dir0=C:\OrCAD\OrCAD_16.3\tools\Capture\Library
Dir1= D:\Training\CIS\Starter_Lib \Files

4.6.2 Description

If you use browsable Properties in CIS to link to external documents, you can set the path to these documents here.

4.7 Part Selector Configured Libraries

4.7.1 Syntax

[Part Selector Configured Libraries]
Number of Configured Libraries=3
Library0=D:\CADENCE\SPB_16.3\TOOLS\CAPTURE\LIBRARY\FILTER.OLB
Library1=E:\HOTLINE\6815\6815.OLB
Library2=E:\FLOWCAD_LIBRARY\CIS-SYMBOLS_163\FC_VIRTEX5.OLB

4.7.2 Description

It reports all OLBs which the CIS Explorer used. This list is a report and can't be configured, only deleted.

4.8 Symbol Selector Configured Libraries

4.8.1 Syntax

[Symbol Selector Configured Libraries]
Number of Configured Libraries=4
Library0=D:\Cadence\SPB_16.3\tools\Capture\LIBRARY\CAPSYM.OLB
Library1=E:\FLOWCAD_LIBRARY\CIS-SYMBOLS_163\FC_STANDARD.OLB
Library2=D:\Cadence\SPB_16.3\tools\capture\library\pspice\source.olb

4.8.2 Description

It reports all OLBs which place part or place symbol (power, titleblock, offpage connector, and port) used. This list is a report. You can predefine some OLB which contains your power, titleblock, offpage connector and port symbols.

4.9 Visibility Frame

4.9.1 Syntax

[Visibility Frame]
Visible=1
Visible In ICA Mode=1

4.9.2 Description

It shows if the visibility frame is visible in CIS Explorer.



	Property	Database Contents	Visible
1	PACK_TYPE	THT	☑
2	HDL_SYM	CAPPOL	☑
3	CLASS	DISCRETE	☑
4	AvtivepartsID		☑
5	BQR_PartNum	BQR_CAP_ELEC	☑
6	Delta_y	0	☑
7	Delta_x	0	☑
8	Delta_Rotation	0	☑
9	Model_3D	capp_th_r_50_125_25	☑
10	Implementation		☑
11	EDA_Status	verified	☑
12	UL_Status	yes	☑
13	Availability	in Stock	☑
14	Price	0,23	☑
15	Manufacturer	Panasonic	☑

4.10 Schematic Part Frame



4.10.1 Syntax

[Schematic Part Frame]
Visible=1
Visible In ICA Mode=1

4.10.2 Description

It shows if the schematic part frame is visible in CIS Explorer.

4.11 FootPrint Frame



4.11.1 Syntax

[FootPrint Frame]
Visible=1
Visible In ICA Mode=1

4.11.2 Description

It shows if the footprint frame is visible in CIS Explorer.

4.12 Relational Table Frame

4.12.1 Syntax

[Relational Table Frame]
Visible=1
Visible In ICA Mode=1

4.12.2 Description

It shows if the relational table frame is visible in CIS Explorer.

4.13 Explore Frame



4.13.1 Syntax

[Explore Frame]
Wdw Pos=32 52 1802 823
Maximized=1

4.13.2 Description

It describes position and size of Explorer window.

4.14 Part Manager

4.14.1 Syntax

[Part Manager]
#=120
Schematic Page=120
Part Reference=120
Value=120
Part Number=120
Part Status=154
Source Library=120
Source Package=120
Database Table=120
Wdw Pos=-241 58 1051 342
Maximized=2
Variant Mark Column=120
Variants in PowSup=240

4.14.2 Description

It contains the settings for the part manager. Which properties are displayed and which size the columns have.



4.15 Design Template

4.15.1 Syntax

[Design Template]
Border Printed=True
Border Displayed=True
Organization Address3=
Organization Address2=
Organization Address1=
Organization Name=
Title=
Revision=
Pin Number.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
Part Reference....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
ANSI Grid Refs=True
Title Block Part Name=TitleBlock4
Title Block Library Name=E:\FlowCAD_Library\CIS-Symbols_163\FC_STANDARD.OLB
Property.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
Power Text.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
Part Value.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
OffPageConnector..=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
Title Block.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
Comment Text.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
Alias.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
A Width=9700
A Height=7200
Pin Name.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
Border Text.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
Page Size=Custom
Is Metric=False
Custom Width=16500
Custom Height=11700
E Width=42200
E Height=32200
D Width=32200
D Height=20200
C Width=20200
C Height=15200
B Width=15200
B Height=9700
Grid Ref Vertical Count=4
Document Number=
Grid Ref Vertical Ascending=1
Title Block Printed=True
Grid Ref Printed=True
Grid Ref Displayed=True
Grid Ref Vertical Alphabetic=0
Grid Ref Horizontal Alphabetic=1
Pin to Pin=100
Parts=Primitive
HierarchicalBlock=NonPrimitive
Title Block Displayed=True

Grid Ref Horizontal Ascending=1
Title Block Style=0
Organization Address4=
Cage Code=
Port.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
NetName.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
Hierarchical Block=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
Bookmark.....=[-9, 4, 0, 0, 400, 0, 0, 0, 0, 3, 2, 1, 34, Arial]
PartField8=PCB Footprint
PartField7=7TH PART FIELD
PartField6=6TH PART FIELD
PartField5=5TH PART FIELD
PartField4=4TH PART FIELD
PartField3=3RD PART FIELD
PartField2=2ND PART FIELD
PartField1=1ST PART FIELD
Grid Ref Vertical Width=100
Grid Ref Horizontal Width=100
Grid Ref Horizontal Count=5

4.15.2 Description

A design template is read when a new project or page is created. It contains all setting you find in Capture -> Options -> Design Template. It should be the same for the whole company to have the same style and looking of all schematic pages.

4.16 Preferences

4.16.1 Syntax

[Preferences]
DrawPinArrows....=True
UndoOnSave.....=True
AutoReference....=True
HPathNetName.....=False
StrokeFont.....=False
SessionLogFont...=[-14, 6, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, Arial]
ViewerShowPinInfo=True
Autosave.....=False
FillText.....=False
DockingPlacePart....=True
AutosaveMinutes..=15
FlushCommand.....=True
EnableITC.....=True
DragPreference....=True
PreserveReference....=False
Journaling.....=False
IREFGlobalVisibility...=True
RotateInstPropInContext...=False
PathLookupTimeout....=10
EnableLegacyITC.....=False
SearchToolBar...=True
JunctionDotSize....=Small
IncrementalSave..=False

IssueUndoWarning=FALSE
LastFilter=Cadence-Allegro
CheckReadOnlyOnViewActivate.....=True
BackAnnotatePinNumbersOnly......=False
LegacySaveAs.....=True

4.16.2 Description

The preferences contain nearly all user settings you find in Capture -> Options -> preferences. It can be useful to predefine a standard.

4.17 Text Editor

4.17.1 Syntax



[Text Editor]
SaveOnDeactivate=True
ShowLineNumbers=True
Font Color=RGB(0, 0, 0)
VHDL Strings Color=RGB(128, 0, 0)
SaveFilesBeforeTools=True
VHDL Keywords Color=RGB(0, 0, 192)
ShowPalette=True
AutoReloadFiles=True
Hilight=True
VHDL Identifiers=RGB(128, 0, 0)
VHDL Comments Color=RGB(0, 128, 128)
Font=[-13, 8, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, Courier New]
Tab Setting=4

4.17.2 Description

It contains all settings from this menu.

4.18 ERC Matrix

4.18.1 Syntax

[ERC Matrix]
Open Emitter.....=--EW--WE---W--E-
3 State Port.....=-------W----WW--
Input Port.....=-WEE-EE-----W-EW
Output Port.....=-W---------W--E-
Power.....=-WEE-EEEEE------
Open Emitter Port..=----------W---
Open Collector.....=--E---WE---E--E-
Open Collector Port=----------W----
Input.....=----------W---W
Unconnected.....=W------W--------
Bidirectional Port.=--E--------W--E-
Passive.....=----------
Output.....=-WEE-EEEE--E--E-
Bidirectional.....=--W----W-W-W--W-
3 State.....=--E----E---W--E-
Passive Port.....=WWEE-WW-WWWW----

4.18.2 Description

The ERC Matrix settings are use during design rule check. They should be configured for the local company requirements.



4.19 Default Colors

4.19.1 Syntax

[Default Colors]
Off-Page Connector Text=RGB(255, 0, 0), TRUE
Pin=RGB(0, 128, 0), TRUE
Part Body=RGB(0, 0, 255), TRUE
DRC Marker=RGB(0, 128, 0), FALSE
Part Reference=RGB(0, 0, 128), TRUE
Comment Text=RGB(0, 0, 0), TRUE
Hierarchical Port=RGB(0, 0, 0), TRUE
Part Value=RGB(0, 0, 128), TRUE
Pin Number=RGB(0, 0, 0), TRUE
DNI Part=RGB(128, 128, 128), TRUE
Variant Part=RGB(255, 0, 0), TRUE
Grid=RGB(221, 221, 221), FALSE
Hierarchical Block Port=RGB(0, 128, 64), TRUE
Wire=RGB(128, 0, 64), TRUE
Hierarchical Block=RGB(0, 128, 0), TRUE
Title Block=RGB(0, 0, 0), TRUE
Locked Object=RGB(54, 48, 139), TRUE
Power Text=RGB(0, 0, 0), TRUE
Display Property=RGB(0, 0, 0), TRUE
Part Body Rectangle=RGB(0, 255, 255), TRUE
Connection Square=RGB(128, 128, 128), FALSE
Off-Page Connector=RGB(0, 0, 0), TRUE
Alias=RGB(255, 0, 0), TRUE
Bookmark=RGB(0, 128, 0), FALSE
Bus=RGB(0, 0, 255), TRUE
Selection=RGB(255, 0, 255), FALSE
Background=RGB(255, 255, 255), FALSE
Hierarchical Port Text=RGB(255, 0, 0), TRUE
No Connect=RGB(128, 64, 0), TRUE
Title Text=RGB(0, 0, 0), TRUE
Junction=RGB(255, 0, 255), TRUE
Comment Graphics=RGB(0, 0, 0), TRUE
Hierarchical Block Name=RGB(0, 64, 64), TRUE
Pin Name=RGB(0, 64, 128), TRUE
Power=RGB(255, 0, 0), TRUE



4.19.2 Description

It contains all Color Setting from Preferences Menu.

4.20 BoM

4.20.1 Syntax

[BoM]
Current Report= Eng Bill Of Materials
Report Names=""Eng Bill Of Materials","Partlist","PickAndPlace""

4.20.2 Description

It contains the current BOM template name in the first row and all BOM template names in the second row. The BOM Templates are listed below.

4.20.3 Syntax

[BoM Eng Bill Of Materials]
Property Count=9
Property0=Item Number
Property1=Quantity
Property2=Part Reference
Property3=Value
Property4=*Part_Number
Property5=PCB Footprint
Property6=Manufacturer_Part_Number
Include Header=1
Exclude Part References=
Style=0
Export to Excel=1
Reference List Separator=0
Property7=Price
Property8=Datasheet
Property9=MPN3
Property10=Part Type
Property11=PCB Footprint
Property12=STATUS
Property13=Tolerance
Property14=Voltage
Property15=ADDINFO
Property16=^Variant Name
Property17=Pick_MirroPick_MirroPick_MirroPick_Mirror
Property18=Pick_Rotation
Property19=Pick_X
Property20=Pick_Y
Property21=^OrgAddr3
Property22=^OrgAddr4
Property23=^OrgName
Property24=^Page Count
Property25=Part Type
Property26=Power
Property27=Price
Property28=Rating
Property29=^RevCode

Property30=Schematic Part Path
Property31=Source Library
Property32=Source Package
Property33=^Title
Show Variant Not Stuffed=0
List Relational Fields=0
Output Relational Data=0
Horizontal Bom Output=1
Max Rows To Output=5
[BoM PickAndPlace]
Property Count=11
Property0=Part Reference
Property1=Value
Property2=Part Number
Property3=MOUNTING_TYPE
Property4=Part Type
Property5=PCB Footprint
Property6=^Variant Name
Property7=Pick_X
Property8=Pick_Y
Property9=Pick_Rotation
Property10=Pick_Mirror
Property11=Pick_Y
Property12=Pick_Mirro
Property13=Tolerance
Property14=Voltage
Property15=ADDINFO
Property16=^Variant Name
Property17=Pick_Rotation
Property18=Pick_X
Property19=Pick_Y
Property20=Pick_Mirro
Include Header=0
Exclude Part References=
Style=1
Export to Excel=1
Reference List Separator=0
[BoM Partlist]
Property Count=15
Property0=Part Number
Property1=Quantity
Property2=Part Reference
Property3=Value
Property4=MOUNTING_TYPE
Property5=Part Type
Property6=MPN1
Property7=MPN2
Property8=MPN3
Property9=PCB Footprint
Property10=Tolerance
Property11=Voltage
Property12=ADDINFO
Property13=STATUS
Property14=MATERIAL_DOCUMENTS

Property15=Quantity
Property16=^RevCode
Property17=Source Library
Property18=Source Package
Property19=STATUS
Property20=Tolerance
Property21=Voltage
Property22=Schematic Part Path
Property23=^Variant Name
Include Header=0
Exclude Part References=
Style=0
Export to Excel=1
Reference List Separator=0

4.21 Crystal Reports BOM

4.21.1 Syntax

[Crystal Reports BOM - D:\Cadence\SPB_16.3\tools\capture\samples\eng_bom.rpt]
Exclude Part References=
Style=0
[Crystal Reports BOM]
MRU0=D:\CADENCE\SPB_16.3\TOOLS\CAPTURE\SAMPLES\ENG_BOM.RPT

4.21.2 Description

It contains all user crystal report BOM templates

4.22 Variant

4.22.1 Syntax

[Variant]
Current Report=Report 1
Report Names=""Report 1""

4.22.2 Description

It contains the current report name in the first row and all report templates in the second row. The report template is listed below.

[Variant Report 1]
Property Count=4
Property0=Value
Property1=Description
Property2=Part Number
Property3=Part Reference

4.23 Variant.LST

4.23.1 Syntax

[Variant.LST]
CFGFILEPATH=D:\CADENCE\SPB_16.3\TOOLS\CAPTURE

4.23.2 Description

It describes the path to the configuration file for export of variant.lst. Variant.lst is used by PCB Editor to create variant assembly and BOM

4.24 Intersheet References

4.24.1 Syntax

[Intersheet References]
IRefStyle=Standard
IRefOnHier=1
IRefOnPage=1
X Offset=20
Y Offset=0
Offset From Name=1
Reset Positions=1
Prefix=P
Suffix=
View Output=0
Report FileName=E:\CIS-TRAINING\LABS\CHAPTER8\CHAPTER8_SOLUTION.csv
IRefMatch00=1
IRefMatch10=1
IRefMatch11=1
IRefMatch20=1
IRefMatch21=1
IRefMatch22=1
IRefMatch30=1
IRefMatch31=1
IRefMatch32=1
IRefMatch33=1
IRefMatch40=1
IRefMatch41=1
IRefMatch42=1
IRefMatch43=1
IRefMatch44=1
IRefMatch50=1
IRefMatch51=1
IRefMatch52=1
IRefMatch53=1
IRefMatch54=1
IRefMatch55=1
IRefMatch60=1
IRefMatch61=1
IRefMatch62=1



IRefMatch63=1
IRefMatch64=1
IRefMatch65=1
IRefMatch66=1
IRefMatch70=1
IRefMatch71=1
IRefMatch72=1
IRefMatch73=1
IRefMatch74=1
IRefMatch75=1
IRefMatch76=1
IRefMatch77=1

4.24.2 Description

It contains all Intersheet References settings.

4.25 Spreadsheet

4.25.1 Syntax

[Spreadsheet]
Pivot=1
PrefPropPath=D:\Cadence\SPB_16.3\tools\capture\prefprop.txt

4.25.2 Description

It contains the pivot status of Property Editor in the first row and path to prefprop.txt in the second row. Prefprop.txt contains all filter settings for Property Editor.

4.26 Project Wizard

4.26.1 Syntax

[Project Wizard]
Project Directory=E:\SCHULUNGSUNTERLAGEN162\ORCAD CAPTURE EMA BRANDED\DATABASES\CAPTURE\lesson10
Project Type=0

4.26.2 Description

It contains the folder of the last opened project.

4.27 Place Part Search

4.27.1 Syntax

[Place Part Search]
Search Path=D:\Cadence\SPB_16.3\tools\capture\library

4.27.2 Description

It contains the path to the libraries for Part Search in Place Part menu.

4.28 __MRURegList

4.28.1 Syntax

[__MRURegList]
Workspace0=Software\OrCAD\CaptureWorkSpace\16.3.0

4.28.2 Description

It contains the registry folder where the Workspace settings are stored. If Capture doesn't start, delete the entries under HKEY_CURRENT_USER/%Workspace0"

4.29 Translators

4.29.1 Syntax

[Translators]
Custom out destination=E:\HOTLINE\6817\AC_PROC_PERI.EDF
Custom out config=D:\Cadence\SPB_16.3\tools\capture\CAP2EDI.CFG

4.29.2 Description

It contains two path definitions for Config files when importing old DSN or SCM files which have no internal library.

4.30 Print Settings

4.30.1 Syntax

[Print Settings]
PrintXOffset=0.000000
PrintYOffset=0.000000
PrintBlackWhite=0
PrintOrientation=2
PrintScaleMethod=0
InstanceMode=1
CenterPrintInX=0
PrintPageSizeToScaleTo=0
CenterPrintInY=0
PrinterDevice=CutePDF Writer
IncludeExternalPages=1
PrintArea=0
IncludePagesOutsideHierarchy=1
PrintScaleFactor=1.000000

4.30.2 Description

It contains all settings for printing from menu File -> Print.



4.31 Recent File List

4.31.1 Syntax

[Recent File List]
File1=e:\schulungsunterlagen162\orcad capture ema branded\databases\capture\release\release.opj
File2=e:\schulungsunterlagen162\orcad capture ema branded\databases\capture\training\training_solution_142.opj
File3=e:\schulungsunterlagen162\orcad capture ema branded\databases\capture\intro\intro.opj
File4=e:\newdemo\grosses_demo board\cis_gross\cis_large.opj
File5=e:\schulungsunterlagen162\orcad capture ema branded\databases\capture\lesson10\lesson10.opj
File6=E:\HOTLINE\9999\Design1.opj
File7=e:\demos\cis-allegro\new_demo.opj
File8=E:\Schulungsunterlagen162\OrCAD Capture EMA BRANDED\Databases\Capture\trng.OLB
File9=C:\Dokumente und Einstellungen\Beate Wilke\Desktop\ToDo\Comprion\4690\LIBRARY1.OLB

4.31.2 Description

It contains the last opened files. These could be – projects, libraries, netlist files, BOM and all other report files.

4.32 CIS Database Tables

4.32.1 Syntax

[2-Resistor]
Row Height=44
Column Count=28
Title1=Table
Width1=70
Title2=Part_Number
Width2=70
Title3=Part_Type
Width3=70
Title4=Value
Width4=70
Title5=Tolerance
Width5=70
Title6=Rating
Width6=70
Title7=Description
Width7=70
Title8=Schematic Part
Width8=144
Title9=PCB Footprint
Width9=160
Title10=Height

Width10=70
Title11=ALT_SYMBOLS
Width11=174
Title12=Datasheet
Width12=70
Title13=Manufacturer_Part_Number
Width13=89
Title14=Manufacturer
Width14=70
Title15=Price
Width15=70
Title16=Availability
Width16=70
Title17=UL_Status
Width17=70
Title18=EDA_Status
Width18=70
Title19=Implementation
Width19=70
Title20=Model_3D
Width20=70
Title21=Delta_Rotation
Width21=70
Title22=Delta_x
Width22=70
Title23=Delta_y
Width23=70
Title24=BQR_PartNum
Width24=70
Title25=AvtivepartsID
Width25=70
Title26=CLASS
Width26=70
Title27=HDL_SYM
Width27=70
Title28=PACK_TYPE
Width28=70

4.32.2 Description

It contains the database table name in square brackets an all properties in this database table with the column width in CIS Explorer.