


# React Fundamentals

## Module – Http communication




Peter Kassenaar –  
[info@kassenaar.com](mailto:info@kassenaar.com)




# Communicating with external APIs

Fetching and handling external data over http

# Calling a backend from your React App







# Options for using external data

- Tons of external (open/public) API's available
  - <https://github.com/public-apis/public-apis>
- React can *not* do http-calls by itself.
- Options for calling them from your app
  - `fetch` – natively built in to the browser
  - JQuery `$.ajax()`
  - `axios` – popular open source http-library
  - ...lots of **other options**



# Our choice: axios

A screenshot of the npm website showing the package page for 'axios'. The page includes a search bar at the top, a navigation menu, and a banner for 'Need private packages and team management tools? Check out npm Orgs. »'. The main content area displays the package name 'axios', version '0.19.0', and publication status 'Public • Published 5 months ago'. Below this are tabs for 'Readme', '2 Dependencies', '25.871 Dependents', and '40 Versions'. The 'Readme' tab is active, showing a description: 'Promise based HTTP client for the browser and node.js'. It also lists features: 'Make XMLHttpRequests from the browser', 'Make http requests from node.js', and 'Supports the Promise API'. On the right side, there is an 'install' section with a code block showing '> npm i axios', a 'weekly downloads' graph showing 5,921,879 downloads, and a table with version '0.19.0', license 'MIT', 583 open issues, and 135 pull requests.

```
npm install axios [--save]
```


<https://www.npmjs.com/package/axios>

# API of choice: Restful Countries

A screenshot of the REST Countries API website. The browser address bar shows 'restcountries.eu'. The page has a light blue header with 'REST Countries', 'View on GitHub', and 'Issues' links. A left sidebar contains links for 'REST COUNTRIES' (Donate!, Users, Stay up-to-date), 'API ENDPOINTS' (All, Name, Full Name, Code, List of codes, Currency, Language, Capital city, Calling code, Region, Regional Bloc, Response Example), 'FILTER RESPONSE', 'SOURCES', 'SIMILAR PROJECTS', and 'LICENSE'. The main content area is divided into three sections: 'REST COUNTRIES' with a description and a 'build unknown' badge; 'DONATE!' with a paragraph about the project's acquisition; and 'USERS' with a list of users including 'TTÜ' and 'Spotify International Pricing Index'.


<https://restcountries.eu/>

# Goal – fetching country data from API



1. **Prepare State** for the data you're about to receive
2. Discover the **URL** that you want to talk to
3. Use `axios` to **call** the url
  - For instance in the `componentDidMount()` lifecycle hook
  - But it can be in a button `clickHandler` as well..
4. **Set the state** in the `.then()` handler of the promise
5. **Pass state** to the component as usual

# Set state and call URL



```
import axios from 'axios'
const url = 'https://restcountries.eu/rest/v2/all';
```

URL to talk to

```
state = {
  error: null,
  isLoading: false,
  countries: []
};
```


Prepare state

```
componentDidMount() {
  axios.get(url)
    .then(response => {
      this.setState({
        isLoading: true,
        countries: response.data
      })
    })
}
```

Set state with data



# Loading indicator, aka Spinner





Depends on `this.state.isLoaded`. For instance like:

```
{/*Show a Loading indicator as long as the countries are not Loaded*/}
{
  !this.state.isLoaded &&
    <LoadingIndicator/>
}
```

```
class LoadingIndicator extends Component {
  render() {
    return (
      <div>
        <img src={require('./spinner.gif')} alt="Please wait..."/>
      </div>
    );
  }
}
```


## Result w/ simulated delay




 React  
vacation picker



# Result after delay



`../examples/500-api-call`



# On `async` / `await`

- You *can* use the `async/await` notation if you like.
  - It's just syntactic sugar over Promises

```
async componentDidMount() {  
  const response = await axios.get(url)  
  this.setState({  
    isLoading: true,  
    countries: response.data  
  })  
}
```




`async / await`



# Fetching details

Doing subsequent API calls



## Same principle



- Pass click handler as prop to `<VacationPicker />`
- find URL, do an `axios` call, update state
- Pass the state to a (new) detail component


```
<VacationPicker  
  countries={this.state.countries}  
  select={(country) => this.getCountry(country)}  
>
```

Get specific country

```
// get details for a specific country  
getCountry(name) {  
  axios.get(`${detail_url}/${name}`)  
    .then(response => {  
      this.setState({  
        country: response.data[0]  
      })  
    })  
}
```


# Result






# Workshop

- Create a new project, or work from the example project
  - Install `axios` if necessary
- Use the **Typicode API** to fetch dummy random users:
  - <https://jsonplaceholder.typicode.com/users>
- Show usernames and e-mail addresses in a list
- Clicking a user fetches details for that specific user. Show them in a detail component
- Optional – Create a `<SearchCountry>` component for the example app
  - where the user can type in (a part of) the name.
  - Search for that country/countries, show them.
- Example `../500-api-call`






# More API's




```
VacationPicker.js x JavaScript APIs.txt x
1
2 // DEZE API's zijn open, zonder registratie beschikbaar, of al geregistreerd (reg
3 // THESE API's are open, free, mostly available without registration (or already
4
5 https://opendata.rdw.nl/resource/m9d7-ebf2.json?kenteken= + kenteken
6 http://swapi.co/ - The Star Wars API
7 http://api.openweathermap.org/data/2.5/weather?units=metric&appid=8566d604cd9402b
8 http://ergast.com/mrd/ - Ergast Motor (Formule 1) API
9 https://randomuser.me/api/?results=10 - random user data
10 http://www.omdbapi.com/?apikey=f1f56c8e& - Open Movie Database (gebruik liever je
11 https://api.github.com/users/ - GitHub user information.
12 http://dev.markitondemand.com/Api/v2/Quote/json?symbol=AAPL - Aandelen/stock quot
13 http://restcountries.eu/ - Information on all countries in the world.
14 https://restcountries.eu/rest/v1/all - Andere API met Country-informatie
15 http://api.postcodedata.nl/v1/postcode/?postcode=1211EP&streetnumber=60&ref=domein
16 http://opendata.cbs.nl/dataportaal/portal.html?_la=nl&_catalog=CBS - Honderden AP
17 https://data.pdok.nl/datasets - Allerlei informatie van het Kadaster
18 https://coinmarketcap.com/api/ - Blockchain/Bitcoin information
19 https://www.anwb.nl/feeds/gethf - realtime file-informatie Nederlandse snelwegen
20 https://api.spacexdata.com/v3/launches/ - SpaceX rocket launch information
```

File: JavaScript APIs.txt in the root of the repository


# Workshop #2




- Create a small application using one of the other API's in the file `JavaScript API's.txt`
- Store and fetch data in a store. Use for instance:
  - Pokemon API
  - Open Movie Database API
  - OpenWeatherMap API
  - ...



# More info



 **React**

Docs Tutorial Blog Community

🔍 Search

v16.11.0 🌐 Languages GitHub

# AJAX and APIs

## How can I make an AJAX call?

You can use any AJAX library you like with React. Some popular ones are [Axios](#), [jQuery AJAX](#), and the browser built-in [window.fetch](#).

## Where in the component lifecycle should I make an AJAX call?

You should populate data with AJAX calls in the `componentDidMount` lifecycle method. This is so you can use `setState` to update your component when the data is retrieved.

## Example: Using AJAX results to set local state

The component below demonstrates how to make an AJAX call in `componentDidMount` to populate local component state.

INSTALLATION ▾

MAIN CONCEPTS ▾

ADVANCED GUIDES ▾

API REFERENCE ▾

HOOKS ▾

TESTING ▾

CONCURRENT MODE (EXPERIMENTAL) ▾

CONTRIBUTING ▾

FAQ ^

**AJAX and APIs**

Babel, JSX, and Build Steps

Passing Functions to Components


Component State

Styling and CSS

File Structure

<https://reactjs.org/docs/faq-ajax.html>

# Checkpoint



- You know how to make Ajax/API calls from an application
- You are able to handle data coming from a Restful endpoint and show it in your app
- ALWAYS read the documentation of the corresponding API