

React Fundamentals

Module – functionbased components



Peter Kassenaar –
info@kassenaar.com



Components


Adding and using your own components

Types of components


Function Components

Class Components

First: import Bootstrap



- Import Bootstrap to make it look nice
- There *are* React-specific libraries
 - But we're not using them here (yet)
- <https://getbootstrap.com/>
- `npm install bootstrap jquery popper.js`




Update index.js

```
// bootstrap stuff
import 'bootstrap/dist/css/bootstrap.min.css'

ReactDOM.render(
  <HelloReact/>,
  document.getElementById('root')
);
```


Function-based components




- Components are just functions
- They are rendered to the screen by the `ReactDOM.render()` function
 - 1st parameter – the component to render
 - 2nd parameter – the element to render it to

```
function HelloReact() {  
  return <div>Hello React!</div>  
}  
  
ReactDOM.render(  
  <HelloReact />,  
  document.getElementById( 'root' )  
) ;
```

HelloReact Component




- The HelloReact Component is NOT valid JavaScript
- It is JSX, compiled to React API calls by Babel



<https://babeljs.io/>,


menu option *Try it out*

Convention: Component Names




- Start components with Uppercase first letter
 - `function Button() {...}` NOT
 - `function button() {...}`
- Preferred: use two words to distinguish from standard HTML elements
 - `function ReactButton() {...}`
- Opinion: React Style Guide(s)
 - AirBnB JSX Style Guide:
<https://github.com/airbnb/javascript/tree/master/react>
 - More options: <https://css-tricks.com/react-code-style-guide/>


Creating a simple Counter component



Simple result:




Component functionality - Hooks




- We need *state* to hold the value of counter
 - Using a built in method `React.useState()`
 - This returns two objects – you can call them any way you like
 - First object: *state object (getter)*
 - Second object: *updater function (setter)*
- We use ES6 *destructuring* to assign them to variables
- We initialize the first variable (in our case: `counter`) with a value

```
const [counter, useCounter] = React.useState(0)
return (
  <div>
    <h2>counter: {counter}</h2>
  </div>
)
```





On JSX Syntax



- You can use variables anywhere in JSX, using the **single curly brace** syntax
 - `<h2>{counter}</h2>` to display the current value of counter
 - Other frameworks often use double curly braces `{{ ... }}`
- To update the counter we use an *event handler*
 - This is the second argument that `useState()` returns
 - It looks like the DOM API, but it is case sensitive (`onClick`, `onBlur`, `onSubmit`, etc).
 - The event handler receives a function reference


```
function Counter() {  
  
  const [counter, setCounter] = React.useState(0);  
  
  function updateCounter() {  
    return setCounter(counter + 1);  
  }  
  
  return (  
    <div>  
      <button onClick={updateCounter}>+1</button>  
      <h2>counter: {counter}</h2>  
    </div>  
  )  
}
```




Or, use ES6-notation:

```
const updateCounter = () => setCounter(counter + 1);
```

Workshop



- Continue with your own project, or use the sample project.
- Implement the subtract function (-1) for the counter component.
- Create a new button, that doubles ($*2$) the current value of the counter.
- Create a Reset button, that sets the counter back to 0.
- Example `../110-counter-component`







Using Props

Passing data down to other components

Passing state – One-way-dataflow



- SoC: We want to create a new component for showing the value of the counter:
 - `<Counter />` **functional component** (it updates the state)
 - `<DisplayCounter />` **display component** (it just displays the counter)
- But: state is unique to each component
- We need to pass the counter state to new component
- Introducing the *props* object




Pass props down. In this case the value of counter

We can pass as many props as we need.

Every prop becomes an *attribute* on the receiving component

Props



- Every component receives a `props` object
 - Again, you can name it anything you want
 - But it is commonly named `props`
- It holds key/value-pairs for every property passed down
- In `Counter.js` we create a prop `counter` and pass it the current value of `counter`:
 - `<DisplayCounter counter={counter} />`

Receiving props



```
import React from 'react'

function DisplayCounter(props) {
  return(
    <div>
      {props.counter}
    </div>
  )
}
export default DisplayCounter
```

But what if the components are siblings?


```
<Counter />
```

```
<DisplayCounter />
```

We need an enclosing *parent* component that holds the state.

React: “*We are lifting state up*”


But what if the components are siblings?



Now `<App />` holds the state.

It is passing *functionality* down to `<Counter />`
and *data* down to `<DisplayCounter />`

Next – passing functionality down




- We can also pass *functions* as props
 - After all: functions are just JavaScript objects
- Lift state up from `<Counter />` to `<App />`

```
// Our parent component - it holds the state for the child components
function App() {
  const [counter, setCounter] = React.useState(0);

  const incrementCounter = () => setCounter(counter + 1);

  return (
    ...
  );
}
```


Send props down to child components



```
function App() {  
  const [counter, setCounter] = React.useState(0);  
  
  const incrementCounter = () => setCounter(counter + 1);  
  
  return (  
    <div className="container">  
      <h2>Hello React</h2>  
  
      <Counter increment={incrementCounter}/>  
      <DisplayCounter counter={counter}/>  
    </div>  
  );  
}
```



Update `<Counter />` to receive props





```
function Counter(props) {  
  return (  
    <div>  
      <button className="btn btn-primary"  
        onClick={props.increment}>+1</button>  
    </div>  
  )  
}
```

`props.increment` is just a function pointer here.


It points to the function in the parent component

Result




Result is the same visually,
but with a different, more flexible architecture

Workshop



- Lift state up in your own application, passing props and functions to child components
- OR: start with the sample application, and implement the decrement function
- New: pass the `className` for the button as a prop (for instance: `btn-primary`, `btn-success`, `btn-info`,...)
- Update the `<App />` component
- Example [../120-props](#)






Passing arguments for props

What if your functions (passed down as props) needs parameters?

Component Reusability



- Let's say we want to make the `<Counter />` more generic and reusable
- We want to pass in a `value` to add or subtract from the `counter`
- We need to pass parameters to the function!


Update the parent component

1. Update the `incrementCounter` function in the parent component (`<App />`)


```
const incrementCounter = (val) => setCounter(counter + val);
```

2. Update the `prop` that is passed. However, this is **invalid!**:

```
<Counter increment={incrementCounter(30)} />
```



This is also invalid

```
function Counter(props) {  
  return (  
    <div>  
      <button className="btn ..."   
        onClick={props.increment(30)}>+30</button>  
    </div>  
  )  
}
```

Error: Maximum update depth exceeded. This can happen when a component repeatedly calls `setState` inside `componentWillUpdate` or `componentDidUpdate`. React limits the number of nested updates to prevent infinite loops. ×


▶ 3 stack frames were collapsed.

incrementCounter [as increment]
C:/Users/Gebruiker/Desktop/react-fundamentals/training-app/src/components/App.js:12


```
9 | function App() {  
10 |   const [counter, setCounter] = React.useState(0);  
11 |  
> 12 |   const incrementCounter = (val) => setCounter(counter + val);  
13 |  
14 |   return (  
15 |     <div className="container">
```


[View compiled](#)

Solution: create a prop and inline function





```
<Counter increment={incrementCounter} val={30} />
```

```
function Counter(props) {  
  return (  
    <div>  
      <button className="btn ..."   
        onClick={() => props.increment(props.val)}>  
        {props.val}  
      </button>  
    </div>  
  )  
}
```


A red arrow pointing upwards from the bottom of the code block towards the `props.val` property access in the `onClick` handler.

Result



Example `../130-props-parameters`


Workshop




- Create a more generic `<Counter />` component, so you can add/subtract a random number from the counter.
- Start from `../130-props-parameters`
- You should be able to call it like this:

```
<Counter increment={incrementCounter} increment={1}/>  
<Counter increment={incrementCounter} increment={5}/>  
<Counter increment={incrementCounter} increment={10}/>  
<Counter increment={incrementCounter} increment={50}/>
```

(workshops: ../1-generic-counter)



Checkpoint



- There are two types of components. `function-based` and `class-based`
 - We're going to use class-based components next.
- You know how to load 3rd party libraries.
- You can add and use as many components as you like.
- You know about component state.
- You know how to pass state and functionality as `props` to child components.