Practica 2.0 Despliegue Apache

Revisar la configuración del sitio

```
david@Despliegue:~$ sudo cat /etc/apache2/sites-enabled/000-default.conf
<VirtualHost *:80>
        # The ServerName directive sets the request scheme, hostname and port that
        # the server uses to identify itself. This is used when creating
        # redirection URLs. In the context of virtual hosts, the ServerName
        # specifies what hostname must appear in the request's Host: header to
        # match this virtual host. For the default virtual host (this file) this
        # value is not decisive as it is used as a last resort host regardless.
        # However, you must set it for any further virtual host explicitly.
        #ServerName www.example.com

        ServerAdmin webmaster@localhost
        DocumentRoot /var/www/html

        # Available loglevels: trace8, ..., trace1, debug, info, notice, warn,
        # error, crit, alert, emerg.
        # It is also possible to configure the loglevel for particular
        # modules, e.g.
        #LogLevel info ssl:warn

        ErrorLog ${APACHE_LOG_DIR}/error.log
        CustomLog ${APACHE_LOG_DIR}/access.log combined

        # For most configuration files from conf-available/, which are
        # enabled or disabled at a global level, it is possible to
        # include a line for only one particular virtual host. For example the
        # following line enables the CGI configuration for this host only
        # after it has been globally disabled with "a2disconf".
        #Include conf-available/serve-cgi-bin.conf
</VirtualHost>
david@Despliegue:~$
```

Habilitar módulos de apache

```
david@Despliegue:~$ sudo a2enmod proxy_fcgi setenvif
Considering dependency proxy for proxy_fcgi:
Enabling module proxy.
Enabling module proxy_fcgi.
Module setenvif already enabled
To activate the new configuration, you need to run:
  systemctl restart apache2
david@Despliegue:~$
```

```
david@Despliegue:~$ sudo a2enconf php8.5-fpm
Enabling conf php8.5-fpm.
To activate the new configuration, you need to run:
  systemctl reload apache2
david@Despliegue:~$
```

```
david@Despliegue:~$ sudo systemctl reload apache2
david@Despliegue:~$
```

Copiar la aplicación PHP al directorio de Apache.

```
david@Despliegue:~$ sudo mkdir -p /var/www/html/running-zones
david@Despliegue:~$
```

Copiar la aplicación PHP a Apache

```
david@Despliegue:~$ sudo rsync -av /var/www/running-zones/ /var/www/html/running-zones/
sending incremental file list
./
02calculadoraBootstrap.php
04ArrayBootstrap.php
Instalación y configuración del servidor web NGINX.odt
Instalación y configuración del servidor web NGINX.pdf
Práctica 2.1 Despliegue de NGINX  PHP FPM.odt
mi-app-php/
mi-app-php/.env
mi-app-php/config/
mi-app-php/config/database.php
mi-app-php/public/
mi-app-php/public/index.php
running_zone/

sent 974,222 bytes  received 191 bytes  1,948,826.00 bytes/sec
total size is 973,078  speedup is 1.00
david@Despliegue:~$
```

Comprobación

