Product Data Sheet

System name	Flowline
Intended use	Rainwater, sanitary and combined sewer systems sewer connections, sub-soil installations in buildings
Areas of application	Underground sewerage and drainage
Material	Unplasticised Polyvinyl Chloride UPVC / PP Polypropylene
Colour	Orange brown colour
Design of fittings	Solid homogeneous wall
Designation	SDR41
Diameter	DN/OD 110, DN/OD 160, DN/OD 200, DN/OD 250, DN/OD 315, DN/OD 400, DN/OD 500mm
System components	Bends, branches, reducers, sliding couplings, two-pipe couplings, couplings for cast iron and vitrified clay pipes, plugs, caps, clean-outs, brick slips, storm gates, non-return valves.
Circumferential stiffness classes	SN >= 8 kN/m² (EN ISO 13967:2019)
Chemical resistance	High chemical resistance to aggressive effluents and environments according to ISO/TR 10358 and ISO/TR 7620, pH 2-12
Maximum sewage temperature	DN110-500: 60°C (instantaneous effluent flow up to 5 min. up to 75°C)
Type of connections	Socket connections with elastomer seals
Can be connected to other systems	With DN/OD smooth-walled pipe systems, including the KG2000 PP-MD DN/OD system; with DN/OD socket sockets of SC manholes; with DN/ ID structural pipe systems–transition coupling DN OD/DN ID required
Can be used in areas of mining damage	Positive opinion of GIG up to and including mining damage class IV (DN110-DN315)
Standards, national technical specifications	EN 1401-1, EN 1329-1 National Institute of Hygiene hygienic certificate, Technical Opinion of GiG on the perimeter stiffness of uPVC fittings Flowline
Additional information	Replacement thermoplastic seals with stiffening ring (DIN-LOCK) possible

About Dadex

Dadex was established as a public limited company in 1959. We started with the manufacturing of FC roofing systems at our facility in Hyderabad, under the dynamic leadership of our Founder Chairman, Mr. Kassim Dada. Being a forward-looking organization, his son, Mr. Sikander Dada kept up to date with the market, and was instrumental in the diversification with plastic piping systems. Presently we produce various thermoplastic systems such as UPVC, PP-R, PP-RCT, PP, PE.

Headquartered in Karachi, our two manufacturing facilities based in Hyderabad and Sundar Industrial Estate (near Lahore) are equipped with state of the art machinery. Our joint efforts have led Dadex to the ISO 9001, ISO 14001, ISO 45001 and PSQCA certifications.

We aim to set standards in every field we enter. Customer focus, quality and innovation are reflected in every aspect of our business. Offering customized solutions to a cross section of markets for over 66 years, Dadex today is a hallmark of trust and reliability.

We believe that our strength lies in delighting our customers. That is why providing quality products backed by round the clock technical support services are the Dadex promise to all our valued customers.

DADEX Eternit Limited

Dadex House, 34-A/1, P.E.C.H.S. Block-6, Shahrah-e-Faisal, Karachi.

UAN: (92-21) 111 000 789, Email: marketing@dadex.com.pk

For more information, please visit www.dadex.com.
For Technical information and assistance, please contact Dadex Techno Commercial Department at sales@dadex.com.pk.

TÜV AUSTRIA ISO 9001 · SGS ISO 14001 · SGS ISO 45001 · Pakistan Standards

Feb. 2026

FlowLine

SEWERAGE AND DRAINAGE





UPVC

SPECIALLY DESIGNED FOR UNDERGROUND SEWERAGE AND DRAINAGE

magnaplast

DADEX

Introduction

Flowline piping system is a suitable solution for underground drain and sewer applications in homes, commercial plazas, community buildings and infrastructure projects. This easy push-fit rubber ring/solvent cement jointing system is durable, corrosion free and lightweight. Flowline is the first UPVC based underground sewer pipe system in Pakistan that conforms to international quality standards. It is **specially designed for Underground Sewerage and Drainage Applications.**

Material

Flowline pipe system is manufactured from Unplasticised Polyvinyl Chloride (UPVC) compound. Flowline pipes and fittings are terra cotta (orange brown) in color, which is recommended color for buried drainage system.

Standards and Specifications

Flowline pipes and fittings are manufactured in accordance with EN 1401-1.

Available Range

Flowline pipes and fittings are available from 110mm to 355mm in standard lengths of 3 & 4 meters. A range of imported injection molded fittings could be made available.

Features & Benefits

- **Efficient Disposal:** Exceptionally low friction and smooth inside surface of Flowline minimizes build up of deposits commonly seen in conventional sewer pipe systems.
- **Low Bacterial Growth:** All conventional sewer pipes collect a coating of algae or slime. Flowline offers lesser grips for slime.
- **Thermal Expansion/Contraction:** Flowline pipe system with rubber ring socket joint allows natural provisions against thermal expansion.
- **Non Corrosiveness and chemical Resistance:** Flowline is non-corrosiveness. It resists chemical reactions from acids, alkalis and salt solutions.
- **Lightweight and Easy to install:** Flowline pipes are light weight and easy to install. This leads to lower transportation and installation costs.
- **Leak Free:** Flowline has water tight connections. There is no chance of infiltration or pollution of ground water.
- **Easy to Maintain:** Flowline pipe system is easy to access after installation for inspection, cleaning, repairs, etc.

Nominal OD (mm)	Mean OD (mm) min-max	Min Wall Thickness (mm) SN 8, (SDR 34)	Min Wall Thickness (mm) SN 4, (SDR 41)
110	110.0 - 110.3	3.2	3.2
160	160.0 - 160.4	4.7	4.0
200	200.0 - 200.5	5.9	4.9
250	250.0 - 250.5	7.3	6.2
315	315.0 - 315.6	9.2	7.7
355	355.0 - 355.7	10.4	8.7

Jointing Method

Ring-Seal / Push-Fit Jointing

- Ensure any pipe cut on site is also chamfered.
- Check that the sealing ring is properly seated in its housing in the socket of the fitting.
- Ensure all components to be joined are dry, clean and free from grit or dust. Note any deep scratches on the pipe or fitting spigot as these may prevent the sealing ring from forming a water tight seal.
- Lubricate evenly around the pipe or fitting spigot end with Silicone Lubricant. Do **NOT** lubricate inside the socket and the ring seal. The spigot can then be inserted into the socket. Use of washing liquid is not recommended as lubricant. However, soap solution can be used as lubricant.
- Correctly align the components to be joined.
- Push the pipe or fitting spigot fully into the socket. Mark the pipe or fitting spigot at the socket face and then withdraw it by a minimum of 12mm to allow for thermal expansion.
- Make a subsequent check to ensure that the expansion gap is not lost during further installation work.

Solvent Cement Jointing

- Before using solvent based cleaners or cement:
  - Read instructions on the can
  - Ensure there is sufficient ventilation.
- Make sure pipe or fitting spigot and solvent weld socket are dry, clean and free from grit or dust.
- Clean surfaces of spigot and socket with Dadex Degreasing Cleaner. Apply liberally using a clean non synthetic rag or absorbent paper.
- Apply one coat of Dadex Solvent Cement. Apply an even coat to both surfaces using applicator provided or a paint brush. Stroke cement along and not around the surfaces.
- Immediately insert pipe or fitting spigot fully into the socket. Each solvent weld joint MUST be completed within 1½ minutes.
- Hold for 20-30 seconds. Remove any surplus cement from the mouth of the socket.
- The joint may be handled after 10 minutes and commissioned after 24 hours.

Safety

When making solvent weld joints it is essential to observe normal safety rules for handling solvent:

- Never smoke or bring naked flames near the area of work
- Work in a well ventilated area to avoid inhaling fumes
- Close the solvent container after use & store in a cool area
- Do not allow solvents or cleaners to come into contact with skin.

Refer to COSHH (Control of Substances Hazardous to Health) and local safety regulations where applicable.

Available Fittings

A wide range of compatible imported fittings is available

