Installation Guidelines

Concealed installations

Polydex does not cause any problem when embedded in the wall or floor, because naturally occurring frictional forces prevent the thermal expansion and contraction. Also the characteristic of deformability of the system can absorb expansions in walled installation.

Fastening technique for open installation

Suspended pipelines require compensation for thermal changes and this can be achieved by proper placement of fixed and sliding clamps in the installation network.

(a) Fixed Point

Fixed clamps help limit the uncontrollable movements of the pipelines and divide them into sections. Fixed point spacing must be performed on the basis of the pipe diameter. The material used to perform this operation must possess certain characteristics so that it does not damage the external surface of the pipe.

(b) Sliding Point

Sliding clamps allow the axial movement of the pipe without damaging it. On locating a sliding clamp it has to be ensured that movements of the pipeline are not hindered by fittings or armatures installed next to them.





TÜV AUSTRIA ISO 9001 SGS SGS Pakistan Standards

About Dadex

Dadex was established as a public limited company in 1959. We started with the manufacturing of FC roofing systems at our facility in Hyderabad, under the dynamic leadership of our Founder Chairman, Mr. Kassim Dada. Being a forward-looking organization, his son, Mr. Sikander Dada kept up to date with the market, and was instrumental in the diversification with plastic piping systems. Presently we produce various thermoplastic systems such as UPVC, PP-R, PP-RCT, PP, PE.

Headquartered in Karachi, our two manufacturing facilities based in Hyderabad and Sundar Industrial Estate (near Lahore) are equipped with state of the art machinery. Our joint efforts have led Dadex to the ISO 9001, ISO 14001, ISO 45001 and PSQCA certifications.

We aim to set standards in every field we enter. Customer focus, quality and innovation are reflected in every aspect of our business. Offering customized solutions to a cross section of markets for over 66 years, Dadex today is a hallmark of trust and reliability.

We believe that our strength lies in delighting our customers. That is why providing quality products backed by round the clock technical support services are the Dadex promise to all our valued customers.

DADEX Eternit Limited

Dadex House, 34-A/1, P.E.C.H.S. Block-6, Shahrah-e-Faisal, Karachi.
UAN: (92-21) 111 000 789, Email: marketing@dadex.com.pk

Dadex Authorised Distributor for Nikasi

Galaxy Pipe Store

Shop # 6E, Building No. 7E, 27th Com. Street, Tauheed Com. Area, Phase V, DHA. Karachi.
Tel: 0300-2929567 | E-mail: akhtarnawaz38@gmail.com

Feb. 2026

POLYDEX

HOT & COLD WATER SYSTEM





PP-R

DADEX

Introduction

Polydex is designed for transport of hot and cold water. It is also used for the distribution of compressed air. Polydex is the first complete PP-R piping system in Pakistan that conforms to international quality and standards. In order to take advantage of system properties, its chemical resistance and use of system for transport of other liquids, gaseous or solid - an individual assessment of any such case would be needed.

Polydex pipe systems are available with high quality PP-R pipes and PP-R fittings.

Material

Polydex pipes and fittings are manufactured from Polypropylene Random PP-R material. PP-R is 100% certified food-grade material. Its resistance to high temperatures has made PP-R a popular piping system recommended for domestic, commercial buildings and industrial usage. The physical and chemical properties of PP-R make it a superior and safe piping system for supply of potable water and other fluids. Polydex pipes and fittings are supplied in green colour.

Available Range

20mm - 250mm in 4m length.

Standards & Specifications

Polydex pipe system conforms to the following standards:

Pipes (PN-16 & PN-20)	DIN 8077-8078
Fittings (PN-25)	DIN 16962

Threaded Fittings are imported and are available in Lead Free Brass with Silver Nickle Coating.

Fields of Application



- Residence and apartments.
- Hospitals.
- Hotels and Offices.
- School buildings.
- Swimming pools.
- Commercial buildings and plazas.
- Various industries-transportation of aggressive fluids.
- Chilled water for central air conditioning.

Features & Benefits

- The High-end Hot & Cold water pipe system for use in buildings and chilled water applications.
- Highest quality PPR imported fittings.
- Unwavering commitment to quality & reliability.
- Providing customers with outstanding pre sales, during sale and after sales services.
- Low electrical and heat conductivity.
- Resistance to corrosion & abrasion.
- Welding capability.
- Easy to handle and transport.
- Reduce head loss.
- Noise free and Environment friendly.

Jointing Method

Jointing of Polydex pipes is carried out by 'heat fusion' (socket fusion or butt fusion). This is done by means of welding machine. The pipes from outside and fittings from inside are joined together by heat fusion method.

- Polydex pipe sizes from 20mm to 110mm are joined through 'socket fusion'.
- Polydex pipe sizes from 160mm to 250mm are joined through 'butt fusion'.

Welding - Guidelines

1. Cut the pipe at the right angle with a cutter.
2. Chamfers should be given to the outer ends of the pipe by a knife or chamfering tool.
3. Mark off welding depth at the pipe end.
4. Always clean the pipe & fitting, free of dust, grease, burs / chips.
5. Required operating temperature of the welding machine is approximately 260°C.
6. Simultaneously heating the male and female parts to be joint together as per recommended heating time.
7. Push the pipe end into the fitting and ensure its alignment of assembly within the specified time period.
8. After welding, the heater and matrixes of the machine should be cleaned for the next use.

Available Fittings

Complete range of PPR fittings is available. Special fittings could be made available on demand such as flange connections and short by-pass bends.

Elbow 90 °



Elbow 45°



Tee



Reducing Tee



Socket



Union



Reducer Internal / External



End Cap



Flange Adaptor



Reducing Sleeve with Metal Female Thread



Reducing Sleeve with Metal Male Thread



Elbow 90° with Metal Female Thread



Elbow 90° with Metal Male Thread



Tee with Metal Female Thread



Tee with Metal Male Thread



Straight - Way Valve



Ball Valve



Double Union Valve

