PRODUCT PORTFOLIO

THERMOPLASTICS

- Water Supply (Housing)
- Water Supply (Infrastructure)
- Above Ground Drainage (Soil, Waste & Vent)
- Below Ground Sewerage & Drainage
- Electrical and Communication
- Specialised Piping Applications

DADEX

Welcome

This product guide presents an integrated range of piping and drainage systems currently offered by Dadex, supported by internationally recognized product partners. It is intended to assist consultants, engineers, contractors, and project stakeholders in identifying suitable solutions based on application requirements.

The guide is structured by application, reflecting standard engineering and specification practices. This approach allows clear comparison between systems performing similar functions and ensures technical clarity across different materials and installation environments.

The product range is organized under the following application categories:

- Water Supply - Housing
- Water Supply - Infrastructure
- *Above Ground Drainage (Soil, Waste & Vent)*
- *Below Ground Drainage & Sewerage*
- *Electrical & Communication Infrastructure*
- *Specialised Systems*

Each product is presented in a consistent one-page format, providing a concise description, material information, applicable standards, available range, key features, and jointing method.

This guide is intended as a general reference document. Detailed technical data, approvals, and installation guidelines are available separately and should be consulted for project-specific requirements.

Products Partners

wavin An Orbia business. | magnaplast | EFFAST

Certifications

TÜV AUSTRIA ISO 9001 | SGS | SGS | Pakistan Standards

DADEX

About DADEX

Dadex was established as a public limited company in 1959. We started with the manufacturing of FC roofing systems at our facilities in Hyderabad, under the dynamic leadership of our Founder Chairman, Mr. Kassim Dada. Being a forward-looking organization, his son, Mr. Sikander Dada kept up to date with the market, and was instrumental in the diversification with plastic piping systems. Presently we produce various thermoplastic systems such as UPVC, PP-R, PP-RCT, PP, PE.

Headquarters in Karachi, our two manufacturing facilities based in Hyderabad and Sundar Industrial Estate (near Lahore) are equipped with state-of-the-art machinery. Our joint efforts have led Dadex to the ISO 9001, ISO 14001, ISO 45001 and PSQCA certifications.

We aim to set standards in every field we enter. Customer focus, quality and innovation are reflected in every aspect of our business. Offering customized solutions to a cross section of markets for over 66 years, Dadex today is a hallmark of trust and reliability.

We believe that our strength lies in delighting our customers. That is why providing quality products backed by the round-the-clock technical support services is the Dadex promise to all our valued customers.



DADEX



OUR VISION

FOUNDATION OF OUR SUCCESS AND THE PATH TO A SUSTAINABLE FUTURE

We are driven by an unwavering commitment to become the most valued company for all our stakeholders, including our customers, employees, and partners. We achieve this by focusing on customer needs, fostering a culture of innovation, and upholding the highest standards of quality and reliability. Our success is built on a foundation of ethical practices and a dedication to a better, more sustainable future.

DADEX

OUR VALUES

The guiding vision of Dadex encompasses all of the company's intrinsic values. Each value is a fundamental building block of the company's existence and subsistence. These values – referred to as the "Building Blocks of Dadex Values" – reflect the true spirit of the company and its employees and are now the foundation of all business practices.



Customer Focus

Superior Customer Support - Magnified Focus



Innovation

Boundless Thinking. Timeless innovation




Quality

Quality Assured is Quality Delivered.



Reliability

Reliability and Trust - A Secure Balance.



Ethical Practices

Solid Links to Strong Principles.

DADEX

POLYDEX PREMIUM





Polydex Premium

Polydex Premium is designed for hot and cold water distribution and compressed air applications. Manufactured from PP-RCT, a 4th-generation polypropylene material with a modified crystalline structure, it offers higher long-term strength at elevated temperatures. Reduced wall thickness allows improved flow capacity while maintaining system reliability.

Material :	PP-RCT - Polypropylene random copolymer with modified crystallinity and temperature resistance.
Appearance :	Green colour with red lines
Standards & Specifications :	Pipes: EN ISO 15874 / DIN 8077-8078 Fittings: EN ISO 15874
Available Range :	Polydex Premium PP-RCT piping system is manufactured in the metric sizes of 20, 25, 32, 40, 50, 63, 75, 90, 110, 125, 160, 200 and 250mm in standard lengths of 4m. Complete range of imported fittings is available.

Features & Benefits :

- Resistance to corrosion & abrasion
- Welding capability
- Material insert in fittings
- Easy to handle & transport
- Reduced head loss
- Environment friendly
- Low electrical & heat conductivity
- Noise free
- Simple to join and quick to install
- Maintenance free

Jointing Method : Heat fusion

DADEX

wavin
An Orbia business.

Water Supply - Housing

Polydex

Polydex is a corrosion-free PPR piping system for the safe transport of hot and cold water. It provides a hygienic alternative to metal piping, with leak-proof joints achieved through heat-fusion technology. Polydex is suitable for residential, commercial, community, and industrial water distribution systems.

Material :	Polypropylene Random (PP-R)
Appearance :	Green colour.
Standards & Specifications :	Pipes: DIN 8077-8078 Fittings: DIN 16962 PN 25
Available Range :	Diameters (OD) 20, 25, 32, 40, 50, 60, 75, 90, 110, 125, 160, 180, 200 and 250mm in standard lengths of 4m. Larger size diameters can be supplied upon request.

Features & Benefits :

- Resistance to corrosion & abrasion
- Welding capability
- Material insert in fittings
- Easy to handle & transport
- Reduced head loss
- Environment friendly
- Low electrical & heat conductivity
- Noise free
- Simple to join and quick to install
- Maintenance free

Jointing Method : Heat fusion






DADEX

Thermoline





Thermoline

Thermoline is a complete PPR piping system designed for hot and cold water distribution. It is suitable for domestic, commercial, and industrial installations where durability and thermal resistance are required. The system ensures long service life and reliable performance.

Material : Polypropylene Random (PPR)

Appearance : Grey colour.

Standards & Specifications : Pipes DIN 8077 - 8078
Fittings DIN 16962

Available Range : Diameters (OD) 20, 25, 32, 40, 50, 60, 75, 90, 110, 125, 160, 180, 200 and 250mm in standard lengths of 4m.
Larger size diameters can be supplied upon request.

Features & Benefits :

- Easy to handle & transport
- Suitable in seismic areas
- Resistance to corrosion & abrasion
- Simple to join and quick to install
- Nickel plated brass insert fittings
- Approved internationally for drinking water
- Environment friendly & food grade
- Welding capability
- Resistant to frost
- Reduce head loss & maintenance free
- Poor conductor of heat

Jointing Method : Heat fusion

DADEX

wavin
An Orbia business.

T-Flex

T-flex pipes systems are designed for many pressure and non pressure applications such as distribution of water, compressed air, industrial effluents, hazardous wastes, house & service connections, mining, agriculture, fibre optic cable ducting and various other applications.

Material : Polyethylene PE-100.

Appearance : Black or Black with blue stripes.

Standards & Specifications : T-flex pipes are manufactured according to international standard ISO 4427-2(E):2007, DIN 8074/8075 and PS 3580:1997

Available Range : Diameters 20, 25, 32, 40, 50, 63, 75, 90, 110, 125, 160, 180, 200, 315, 355, 400, 450, 500, 560, and 630mm.
Coils of 100m are available for sizes up to 90 mm.
For sizes from 110mm to 630mm, available in the lengths of 6m and 12m

Features & Benefits :

- Flexibility & toughness
- Sealed joints
- Non-contaminating (food grade material)
- Outstanding chemical resistance
- Light weight & easy to install
- Excellent hydraulics
- UV resistant

Jointing Method : Compression fitting, butt fusion & electro fusion.





DADEX

aquadex





Aquadex

Aquadex is a UPVC pressure piping system designed for potable water supply and industrial fluid conveyance. It offers high pressure resistance, corrosion protection, and long service life. The system is suitable for municipal, commercial, and industrial applications.

Material :	Unplasticised Polyvinyl Chloride (UPVC)	
Appearance :	Dark grey colour.	
Standards & Specifications :	Pipes	BS 3505 / BS EN 1452.
	Fittings	BS EN 1452-3 (Imported)
Available Range :	Diameters ¾", 1", 1¼", 1½", 2", 2½ ", 3", 4", 5", 6" and 8" in standard lengths of 4m and 6m in classes B (6 bar), C (9 bar), D (12 bar) and E (15 bar). Other sizes of 10", 12", 14" and 16" can be manufactured against confirmed orders.	

Features & Benefits :

- Total resistance to corrosion, abrasion and growth of algae and fungi.
- Light in weight, durable and economical.
- Simple to join & quick to install.
- Non-toxic and non-conductive.
- Smooth bore.
- Self-extinguishing.

Jointing Method : Solvent cement jointing and z-joint with rubber rings.

DADEX EFFAST

Above Ground Drainage (Soil, Waste & Vent)

Nikasi

Nikasi is a uPVC soil, waste, and vent piping system designed for above-ground drainage in residential and commercial buildings. It provides excellent resistance to corrosion and chemical attack, ensuring smooth and hygienic waste discharge. The system is lightweight and easy to install.

Material :	Unplasticised Polyvinyl Chloride (UPVC)
Appearance :	Light gray colour.
Standards & Specifications :	Nikasi pipes conform to ISO 3633 & EN 1329. Imported fittings with solvent cement socket jointing and with rubber ring socket joint, both conform to ISO 3633 & EN 1329.
Available Range :	Diameters 40, 50, 75, 110, 160 and 200mm in lengths of 3 & 4 m.
Features & Benefits :	• Low flow loss • Non-corrosiveness & chemical resistance • Light weight • Self-extinguishing • Non-conductivity of electricity
Jointing Method :	Solvent Cement Welding (using Dadex UPVC Solvent Cement) or Rubber Ring (Push-fit) joints for pressure applications.

Nikasi





DADEX

FlowLine



Flow Line

Flow Line is a UPVC sewer system designed for underground gravity sewer applications. With superior ring stiffness and chemical resistance, it handles domestic and industrial wastewater efficiently in buried conditions with minimal maintenance requirements. It provides excellent resistance to corrosion, chemicals, and soil conditions, ensuring long-term structural integrity.

Material :	Unplasticised Polyvinyl Chloride (UPVC)
Appearance :	Terracotta Color (Orange-Brown)
Standards & Specifications :	Flowline pipes and imported fittings are manufactured in accordance with EN 1401
Available Range :	110, 160, 200, 250, 315 and 355mm in SN-4 and SN-8. Complete range of compatible imported fitting is available

Features & Benefits :

- Corrosion and soil resistant.
- Smooth internal surface for efficient disposal .
- High structural strength.
- Long service life.
- Lightweight, easy to install and low maintenance.

Jointing Method :	Rubber Ring (Push-fit) joints for specific applications. Solvent Cement Welding (using Dadex UPVC Solvent Cement for a permanent bond)

DADEX magnaplast

FlowLine

Non-Return Valves

Non-Return Valves are designed to prevent backflow in drainage and sewerage systems. They protect buildings from flooding caused by reverse flow during surcharge conditions. The valves offer reliable operation and easy integration into piping networks.





Material :	Unplasticised Polyvinyl Chloride (UPVC)
Appearance :	Terracotta Color (Orange-Brown)
Standards & Specifications :	EN 1401 - 1
Available Range :	110mm, 160mm and 200mm

Features & Benefits :

- Prevents backflow and flooding
- Reliable automatic operation
- Easy inspection and maintenance
- Possibility and ease of combining with other materials.
- Total resistance to general and pitting corrosion.
- Resistance to harmful effects of chemical compounds

Jointing Method :	Push-fit / socket connection

magnaplast

DADEX



Electrical Conduits

Dadex Electrical Conduits are manufactured to ensure the safe and efficient routing of electrical wiring. They offer superior protection and long-lasting performance for all types of electrical systems. Designed to meet industry standards, these conduits provide reliable performance and easy installation across a wide range of electrical applications.

Material :	Unplasticized Polyvinyl Chloride (UPVC)
Appearance :	Grey colour.
Available Range :	½", ¾", 1", 1 ¼", 1 ½" and 2" in lengths of 3m.

Features & Benefits :

- Flexible and uniform in shape
- Resistant to chemical reactions
- Yield best results while concealed in concrete or used underground
- Heat resistant, rust-proof and free from decomposition
- Smooth internal & external surface
- Easy to cut and install on site

DADEX

Electrical & Communication Infrastructure

Cable Duct

Dadex cable duct systems can be used for guiding and protecting cables used for various telecommunications, data and energy networks such as long haul networks, city rings and inter-city network.

Material :	Polyethylene (PE)
Appearance :	Black
Standards & Specifications :	Black colour with a ribbed interior surface.
Available Range :	Diameters 25, 32, 50, and 90mm in coils of 100m.

Features & Benefits :

- Durability
- Superior resistance to corrosion, chemicals, weather & abrasion
- Leak proof joints, preventing ingress of ground water
- Easy to handle and install

Jointing Method : Compression fittings.


Cable Duct Systems for Fibre Optics



DADEX

POLYDUCT
LOW NOISE SWV SYSTEM





PolyDuct

Polyduct is a premium, low-noise polypropylene drainage system designed for multi-story buildings. Its material and construction significantly reduce water flow noise, making it ideal for hotels, hospitals, and high-end residential projects where acoustic comfort is essential.

Material : Unique recipe of polypropylene (PP-MD) + mineral additives.

Appearance : **Internal layer** (white) ensures resistance to high temperatures up to +90°C, +95°C for a short-term flow, high chemical resistance, and reduction of noise level.
External layer (blue, smooth surface) ensures resistance to external stress, impacts and atmospheric conditions.

Standards & Specifications : The system complies with EN 1451-1:2018

Available Range : The system is available in the diameters of 50, 75, 110, 125, 160mm.
A wide range of compatible imported fittings is available.

Features & Benefits :

- **Noise Reduction:** As low as 16 dB at a flow rate of 4 l/s.
- **Temperature Resistance:** Handles temperatures from -20°C to +95°C.
- **Chemical Resistance:** Suitable for pH levels between 2 and 12.
- **Stiffness Class:** ≥ SN8 kN/m² for diameters DN 110 to DN 200.
- **Socket Tightness:** Withstands pressure of up to 4.5 bar.
- **Triple Lip Seal:** Enhanced improved acoustic absorption.

Jointing Method : Lip seals made of a rubber-based compound are used to connect the system components with one another.

DADEX magnoplast

T-Flex for Gas Application

Gas lines require piping systems that deliver high quality, high performance and are maintenance free. This makes Dadex's T-flex pipes for gas the ideal solution. Our specially produced T-flex gas pipes have been successfully installed throughout Pakistan for the supply and distribution of gas.

Material : Polyethylene (PE) PE-80 and PE-100.

Appearance : Bright yellow (PE-80) and bright orange (PE-100).

Standards & Specifications : T-flex pipes conform to ISO 4437, DIN 8074, DIN 8075, ASTM D-2513.

Available Range :

Diameters 20, 25, 32, 40, 50 63 and 90mm in coil of 100m lengths.
Diameters 110, 125, 140, 160, 180, 200, 225 and 250mm in 6m or 12m lengths.
Also available in imperial sizes of ¾", 1", 1 ¼", 1 ½", 2", 2 ½", 3", 3 ½", 4" and 6".

Features & Benefits :

- Corrosion resistant
- Relatively light in weight
- Flexible & low frictional resistance
- Good absorption of impact loads vibration & ground movement
- Suitable for narrow trenching resulting in cost saving

Jointing Method : Butt fusion and electro fusion.

T-flex
PE Gas Pipes





DADEX

DADEX Eternit Limited

Dadex House : 34-A/1, P.E.C.H.S. Block-6, Shahrah-e-Faisal, Karachi, Pakistan.
Tel. # (92-21) 111 000 789, E-mail : marketing@dadex.com.pk
Web : www.dadex.com www.facebook.com/dadexpk/

Feb. 2026