



# HomeTeam API System Integration Document

HomeTeamNS CRM Backend API

Version 2.6





# Copyright & Confidential

© 2020 TechStudio Solutions Pte Ltd.

18 Boon Lay Way, TradeHub 21, #08-133, Singapore 609966.

All rights reserved. This document or any part thereof may not, without the written consent of TechStudio Solutions Pte Ltd., be copied, reprinted or reproduced in any material form including but not limited to photocopying, transcribing, transmitting or storing it in any medium or translating it into any language, in any form or by any means, be it electronic, mechanical, xerographic, optical, magnetic or otherwise.

Unless otherwise indicated, the information contained in this document is proprietary and confidential and all copyright, trademarks, trade names, patents and other intellectual property rights in the documentation are the exclusive property of TechStudio Solutions Pte Ltd. unless otherwise specified. The information including but not limited to data, drawings, specification, documentation, software listings, source or object code shall not at any time be disclosed directly or indirectly to any third party without TechStudio Solutions Pte Ltd.'s prior written consent.

The information contained herein is believed to be accurate and reliable. TechStudio Solutions Pte Ltd. accepts no responsibility for its use by any means or in any way whatsoever. TechStudio Solutions Pte Ltd. shall not be liable for any expenses, costs or damage that may result from the use of the information contained within this document. The information contained herein is subject to change without notice.



## Document Control

Title:	HomeTeamNS API System Integration document		
Filename:	HomeTeamNS_API_System_Integration_Document_v2.6		
Owner:	Steve Wang		
Reviewer(s):	Sylvester Lee		
Approved by:	Sylvester Lee		
Version No.	Date	Author	Description
1.0	24th May 2021	Steve	Initial the SRS document and create API specs for Authorization, Authentication, Forgot Password, and Get Membership Detail.
1.1	13th Jul 2021	Leo, Yc	Adding in more API specs
1.2	30th Jul 2021	Leo, Yc	Adding in more API specs
1.3	4th Aug 2021	Steve	Remove the duplicated API
1.4	13th Aug 2021	Leo	Adding in more API specs
1.5	20th Aug 2021	Leo	Adding in more API specs
1.6	6th Sep 2021	Leo	Modify API specs
1.7	10th Sep 2021	Leo	Modify API Specs
1.8	24 Sep 2021	Leo	Modify API Specs
1.9	11 Oct 2021	Leo	Modify API Specs for 24, 41,42,43,44

2.0	18 Oct 2021	Leo	Add API Specs for 45,46 and Event 11
2.1	22 Oct 2021	Leo	Add API 47 and modify api 33
2.2	1 Nov 2021	Leo	Add API 48 and modify api get membership detail (4)
2.3	2 Nov 2021	Leo	Modify api 29.
2.4	9 Nov 2021	Leo	Add api 49,50
2.5	12 Nov 2021	Leo	Add api 51, modify addmember, signup member to input username, modify getmemberdetail to get username, Put error message to all return
2.6	15 Nov 2021	Leo	Add api 52, Modify api 14 and api 23



# Table of Contents

<b>Copyright &amp; Confidential</b>	<b>2</b>
<b>Document Control</b>	<b>3</b>
<b>Table of Contents</b>	<b>5</b>
<b>Introduction</b>	<b>11</b>
Document Purpose	11
<b>Getting started</b>	<b>11</b>
<b>API Reference</b>	<b>11</b>
1. Authorization API	11
1.1 Overview	11
1.2 Specification	12
2. Authentication API	13
2.1 Overview	13
2.2 Specification	13
3. Forgot Password API	15
3.1 Overview	15
3.2 Specification	15
4. Get Membership Details API	17
4.1 Overview	17
4.2 Specification	17
5. Get Membership Card Details API	21
5.1 Overview	21
5.2 Specification	21
6. Sign Up API	23
7. Send OTP API	23
7.1 Overview	23
7.2 Specification	23
8. Verify OTP API	25
8.1 Overview	25
8.2 Specification	25
9. Get Pricing Information API	27
9.1 Overview	27
9.2 Specification	27
10. Activate Email API	30
10.1 Overview	30

10.2 Specification	30
11. Set Password API	32
11.1 Overview	32
11.2 Specification	32
12. Change Password API	34
12.1 Overview	34
12.2 Specification	34
13. View Profile API	36
13.1 Overview	36
13.2 Specification	36
14. Edit Profile API	39
14.1 Overview	39
14.2 Specification	39
15. Check Nric Unique API	46
15.1 Overview	46
15.2 Specification	46
16. Check Mobile Unique API	48
16.1 Overview	48
16.2 Specification	48
17. Check Email Unique API	50
17.1 Overview	50
17.2 Specification	50
18. Get MemberList By Filter	52
18.1 Overview	52
18.2 Specification	52
19. Get Transaction Detail By transaction ID	55
19.1 Overview	55
19.2 Specification	55
20. Get Invoice Detail By Invoice Number	57
20.1 Overview	57
20.2 Specification	57
21. Get NRIC List API	59
21.1 Overview	59
21.2 Specification	59
22. Upload Supporting Document API	61
22.1 Overview	61
22.2 Specification	61
23. Edit Family / Social API	63
23.1 Overview	63
23.2 Specification	63
24. Create Member Account	68

24.1 Overview	68
24.2 Specification	68
25. View Guest Account	70
25.1 Overview	70
25.2 Specification	70
26. Edit Guest Account	72
26.1 Overview	72
26.2 Specification	72
27. List Guest Account	74
27.1 Overview	74
27.2 Specification	74
28. Guest Login	76
28.1 Overview	76
28.2 Specification	76
29. Remove Family / Social from Main member API	79
29.1 Overview	79
29.2 Specification	79
30. Replacement Card Status API	81
30.1 Overview	81
30.2 Specification	81
31. Sign Up Form API	83
31.1 Overview	83
31.2 Specification	83
32. Sign Up Member API	97
32.1 Overview	97
32.2 Specification	97
33. Add member API	102
33.1 Overview	102
33.2 Specification	102
34. Get Transaction History API	107
34.1 Overview	107
34.2 Specification	107
35. Pay Membership Sign Up API	110
35.1 Overview	110
35.2 Specification	110
36. Replacement Card API	112
36.1 Overview	112
36.2 Specification	112
37. Check NRIC Eligible for Renew API	114
37.1 Overview	114
37.2 Specification	114

38. Check Promotion for Renew API	116
38.1 Overview	116
38.2 Specification	116
39. Renew Membership API	118
39.1 Overview	118
39.2 Specification	118
40. Add Transaction API (CRM)	120
40.1 Overview	120
40.2 Specification	120
41. Check Username Unique API (CRM)	123
41.1 Overview	123
41.2 Specification	123
42. Membership Validation API (CRM)	125
42.1 Overview	125
42.2 Specification	125
43. Update Username Password API (CRM)	127
43.1 Overview	127
43.2 Specification	127
44. Retrieve Username API (CRM)	129
44.1 Overview	129
44.2 Specification	129
45. Get Member By Type API (CRM)	131
45.1 Overview	131
45.2 Specification	131
46. Get Member By Expiry Duration API (CRM)	133
46.1 Overview	133
46.2 Specification	133
47. Add Member Pay (CRM)	135
47.1 Overview	135
47.2 Specification	135
48. Add member check price API	137
48.1 Overview	137
48.2 Specification	137
49. Get Member ID By Username And DOB API	142
49.1 Overview	142
49.2 Specification	142
50. Mark Email Verified API	144
50.1 Overview	144
50.2 Specification	144
51. Sign Up Member Check Price API	146
51.1 Overview	146



51.2 Specification	146
52. Get Member ID By Mobile And DOB API	151
52.1 Overview	151
52.2 Specification	151
<b>API Reference - Event</b>	<b>153</b>
1. Get Event List API	153
1.1 Overview	153
1.2 Specification	153
2. Get Event Detail API	156
2.1 Overview	156
2.2 Specification	156
3. Event Booking List API	159
3.1 Overview	159
3.2 Specification	159
4. Get Booking Form API	161
4.1 Overview	161
4.2 Specification	161
5. Check PromoCode API	166
5.1 Overview	166
5.2 Specification	166
6. Check Available Capacity API	169
6.1 Overview	169
6.2 Specification	169
7. Get Booking Status API	171
7.1 Overview	171
7.2 Specification	171
8. Cancel Booking API	173
8.1 Overview	173
8.2 Specification	173
9. Create Booking API	175
9.1 Overview	175
9.2 Specification	175
10. Add Transaction API	178
10.1 Overview	178
10.2 Specification	178
11. Get Booking By MemberID And Date Range API	181
11.1 Overview	181
11.2 Specification	181





# Introduction

## Document Purpose

---

This documentation is a developer guide to integrate with HomeTeamNS API System.



## Getting started

1. You need to contact HomeTeamNS IT Team to approve your account creation request.
2. You need to inform the HomeTeamNS IT Team about which APIs that your application wants to access.
3. Upon request approval, you will receive the client key and secret.
4. Refer to the API reference and start to use the APIs.



## API Reference

### 1. Authorization API

#### 1.1 Overview

This API is the Authorization API, and is necessary to access any of the HomeTeamNS APIs. This API will provide an authorised user an access token which can be used to access the other secured APIs.

## 1.2 Specification

<b>HTTP Request</b>	https://{domain_name}/oauth2/access_token	
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>
	Authorization	Basic base64_encode({client_key}:{client_secret})  Notes: * Developer is to send a base64 encoded string of client_key and client secret joined by a colon.
	Content-Type	application/x-www-form-urlencoded  Notes: * To specify the type of the body.
<b>Request Body</b>	grant_type	client_credentials  Notes: *Value must be "client_credentials"
<b>Response Type</b>	<b>Status</b>	<b>Sample Response</b>
	200 (Successful response)	{ "expires_in": "300", "issued_at": "15/01/2021T22:11:20+0800", "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXZWQ" }  Notes: * The unit of expires_in is seconds * The format of issued_at is dd/MM/yyyy'T'HH:mm:ssZZZZ
	401 (Unauthorized request)	{ "error_code": "001", "error": "Access Denied" }

## 2. Authentication API

### 2.1 Overview

This API is the Authentication API. It will validate whether an account's credentials exist and are valid in the CRM system.

### 2.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/member_authentication		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	<b>user_info</b>	<b>username</b> (string) <b>password</b> (string)	<pre>{   "user_info":{     "username":"12345678",     "password":"12345",     "mobile":""   } }</pre> <p>Notes: Username refer to username input from signup member  Mobile refer to mobile input from signup member  Mobile and username cannot put at the same time</p>
<b>Response Type</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result":{     "member_id":"uks9a-ssd9d-a2scp"   } }</pre>	

	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (server error)	{ "result": { "msg": "wrong username/password" }, "result_code": "0000" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code" : "003", "msg" : "Bad Request - Parameter Missing" }

## 3. Forgot Password API

### 3.1 Overview

This API is the Forgot Password API. It will create a new password and send it to the user's email box.

### 3.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/forgot_password		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	<b>user_info</b>	<b>NRIC</b> (string) <b>DOB</b> (string) <b>postal_code</b> (string)	<pre>{   "user_info":{     "NRIC":"123A",     "DOB":"15/05/1982",     "postal_code":"329979"   } }</pre> <p>Notes: * NRIC is last 4 character of the full NRIC * DOB format is dd/MM/yyyy</p>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result":{     "status":"success",     "email":"test@htns.com"   } }</pre>	

		Notes: * email will be the recipient's email address
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code" : "003", "msg" : "Bad Request - Parameter Missing" }



## 4. Get Membership Details API

### 4.1 Overview

This API is the Get Membership Details API. It will return all the detailed information about this member which includes family/social member details under this member.

### 4.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/get_member_detail		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	<b>user_info</b>	<b>member_id</b> (string)	<pre>{   "user_info":{     "member_id":"59482358-0EFD-46C0-A0F0-F229C36F4B66"   } }</pre>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": {     "personal_details": {       "member_id": "59482358-0EFD-46C0-A0F0-F229C36F4B66",       "status": "Active",       "approvalStatus": "Approved",       "nric": "G3825469W",       "marital_status": "Others",       "salutation": "Dr",       "email": "leo.nam@techstudio.com.sg",       "office_phone": "",       "full_name": "LEO",       "hand_phone": "86840926",       "PA_CAN_Number": "",       "dob": "",       "nationality": "Singapore PR",       "golf_handicap": "",</pre>	

		<pre> "gender": "male", "race": "Chinese", "residential_address": {   "blk": "",   "street": "JURONG EAST STREET 32",   "unit": "02-241",   "postal_code": "600315" }, "economic_status": "", "highest_education": "", "car_plate": "", "car_IU": "", "occupation": "", "annual_income": "", "emergency_contact": {   "name": "ASD",   "relationship": "Spouse",   "contact_no": "86840926" }, "communication_preference": {   "handphone": "TRUE",   "postal_mail": "TRUE",   "comm_email": "TRUE",   "frontline_magazine": "TRUE" }, "membershipInfo": {   "type": "Associate Membership",   "expired_date": "29-02-2024 ",   "registration_type": "",   "card_type": "",   "membership_group": "" } }, "family_members": [], "social_members": [], "event": [   {     "eventName": "Go Green Part 2",     "eventStartDate": "Oct 1, 2021 12:00:00 AM",     "eventEndDate": "Oct 6, 2021 12:00:00 AM",     "registrationStartDate": "Sep 24, 2021 12:00:00 AM",     "registrationEndDate": "Sep 30, 2021 12:00:00 AM",     "registrationDate": "Sep 24, 2021 11:46:24 AM",     "name": "JANICE",     "membershipTypeName": "Non-Member",     "category": "-",     "dob": "Mar 30, 1990 12:00:00 AM",     "email": "janice.yeo@techstudio.com.sg", </pre>
--	--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre> "mobile": "93837131", "totalPax": 1, "totalSession": 0 }, { "eventName": "Furniture Event", "eventStartDate": "Oct 1, 2021 12:00:00 AM", "eventEndDate": "Oct 9, 2021 12:00:00 AM", "registrationStartDate": "Sep 24, 2021 12:00:00 AM", "registrationEndDate": "Sep 30, 2021 12:00:00 AM", "registrationDate": "Sep 24, 2021 3:50:55 PM", "name": "QWE", "membershipTypeName": "SAFRA Membership", "category": "Adult Category", "dob": "Nov 12, 1991 12:00:00 AM", "email": "leo.nam@techstudio.com.sg", "mobile": "93214654", "totalPax": 1, "totalSession": 0 } ] }, "result_code": "0000" } </pre>
	200 (server error)	<pre> { "result_code": "1003", "msg": "Server Error" } </pre>
	200 (Database Error)	<pre> { "result_code": "1004", "msg": "Database Error" } </pre>
	200 (Parameter empty)	<pre> { "result_code": "1005", "msg": "Missing required parameter data" } </pre>
	200 (wrong Member ID)	<pre> { "result_code": "1007", "msg": "invalid member ID" } </pre>
	401	<pre> { </pre>

	(Unauthorized request)	<pre>"error_code":"000", "msg":"Access Denied" }</pre>
	400 (Bad Request)	<pre>{ "error_code":"001", "msg":"Access Denied" }</pre>

## 5. Get Membership Card Details API

### 5.1 Overview

This API is the Get Membership Card Details API. It will return all the detailed information about the membership cards of this member.

### 5.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/get_membership_card_detail		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	<b>user_info</b>	<b>member_id</b> (string)	<pre>{   "user_info":{     "member_id":"59482358-0EFD-46C0-A0F0-F229C36F4B66"   } }</pre>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": {     "personal_details":{       "type":"HomeTeamNS-PAssion-POSB/HomeTeamNS-PAssion/HomeTeamNS",       "NRIC":"S1234567A",       "full_name":"Mike Tan",       "mobile":"81238123",       "email":"test@htns.com",       "residential_address":{         "blk":"31",         "street":"Ah Hood Rd",         "unit":"01-21",         "postal_code":"329979"       },       "can_number":"1009710029638742",       "estimated_value":"10.0000",     }   } }</pre>	

		<pre> "recovery_option":"none/bank account/ez-link card", "bank_account":{ "account_name":"Mike Tan", "bank":"POSB/DBS", "account_number":"205203622" }, "ezlink_number":"1000199002104111", "invoice_number":"HTNS00012345", "co_brand_card_printed":"TRUE/FALSE", "pa_email_sent":"TRUE/FALSE", "status":"Draft/Pending Processing/Faulty Card Received/Completed/Rejected/Failed", "membership_expiry_date":"2023-11-30 23:59:59.000" } }, "result_code": "0000" } </pre>
	200 (server error)	<pre> { "result_code" : "1003", "msg" : "Server Error" } </pre>
	200 (Database Error)	<pre> { "result_code" : "1004", "msg" : "Database Error" } </pre>
	200 (Parameter empty)	<pre> { "result_code": "1005", "msg": "Missing required parameter data" } </pre>
	200 (wrong Member ID)	<pre> { "result_code": "1007", "msg": "invalid member ID" } </pre>
	401 (Unauthorized request)	<pre> { "error_code":"000", "msg":"Access Denied" } </pre>
	400 (Bad Request)	<pre> { "error_code":"001", "msg":"Access Denied" } </pre>

## 6. Sign Up API

Refer - 32. Sign Up Member API

## 7. Send OTP API

### 7.1 Overview

This API is the Send OTP API. It will send an OTP to the user's mobile number when it is called.

### 7.2 Specification

HTTP Request	https://{domain_name}/v1/send_otp		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (text/plain)	
Request Body	Key	Value	Example
	mobile	(string)	mobile = "91113333"
Response	Status	Sample Response	
	200 (Successful response)	{ "result":{ "status":"success" } }	
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }	
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }	
	401	{	

	(Unauthorized request)	"error_code":"000", "msg":"Access Denied" }
	400 (Bad Request)	{ "error_code":"001", "msg":"Access Denied" }
	400 (Parameter type not match)	{ "error_code":"002", "error":"Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code" : "003", "msg" : "Bad Request - Parameter Missing" }



## 8. Verify OTP API

### 8.1 Overview

This API is the Verify OTP API. It will verify whether the OTP submitted by the user is valid.

### 8.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/verify_otp		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (text/plain)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	<b>mobile</b>	(string)	mobile = "91113333"
	<b>otp</b>	(string)	otp = "039678"
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	{ "result":{ "verification":"verified/invalid/expired" "status":"success" } }	
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }	
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }	
	401 (Unauthorized request)	{ "error_code":"000", "msg":"Access Denied" }	

	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code": "003", "msg": "Bad Request - Parameter Missing" }

## 9. Get Pricing Information API

### 9.1 Overview

This API is to Get pricing information about different registration types and duration

### 9.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/registrationtype		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	type	(String)	type="s"  Notes: Expected value "s"-newsignup "r"-renewal "u" - upgrade  All are small caps
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": [     {       "RegistrationTypeName": "Associate Membership - 10 Year Renewal",       "Price": 150,       "productNumber": "HTMRT000006"     },     {       "RegistrationTypeName": "Associate Membership - 2 Year Renewal",       "Price": 50,       "productNumber": "HTMRT000008"     },     {       "RegistrationTypeName": "Associate Membership - 5 Year Renewal",       "Price": 100,       "productNumber": "HTMRT000010"     },     {       "RegistrationTypeName": "Ordinary Membership - 10 Year Renewal",       "Price": 150,       "productNumber": "HTMRT000033"     }   ] }</pre>	

		<pre> "RegistrationTypeName": "Ordinary Membership - 2 Year Renewal", "Price": 50, "productNumber": "HTMRT000035" }, { "RegistrationTypeName": "Ordinary Membership - 5 Year Renewal", "Price": 100, "productNumber": "HTMRT000037" }, { "RegistrationTypeName": "Family Membership - 2 Year Renewal", "Price": 20, "productNumber": "HTMRT000025" }, { "RegistrationTypeName": "Family Membership - 5 Year Renewal", "Price": 35, "productNumber": "HTMRT000027" }, { "RegistrationTypeName": "Family Membership - 10 Year Renewal", "Price": 50, "productNumber": "HTMRT000023" } ], "result_code": "0000" } </pre>
	200 (server error)	<pre> {   "result_code": "1003",   "msg": "Server Error" } </pre>
	200 (Database Error)	<pre> {   "result_code": "1004",   "msg": "Database Error" } </pre>
	200 (Parameter empty)	<pre> {   "result_code": "1005",   "msg": "Missing required parameter data" } </pre>
	200 (wrong Parameter value)	<pre> {   "result_code": "1006",   "msg": "Enter only s, r, u is allow" } </pre>
	401 (Unauthorized request)	<pre> {   "error_code": "000",   "msg": "Access Denied" } </pre>
	400 (Bad Request)	<pre> {   "error_code": "001", </pre>

		<pre>"msg": "Access Denied" }</pre>
	400 (Parameter type not match)	<pre>{   "error_code": "002",   "error": "Bad Request - Parameter type not match" }</pre>

## 10. Activate Email API

### 10.1 Overview

This API is to check if the email is activated

### 10.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/activateEmail		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	id	(String)	id="xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx"
	email	(String)	email="xxxxxxx@gmail.com"
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": [     {       "emailVerified": "Activaed"     }   ],   "result_code" : "0000", }</pre> <p>Notes:</p> <ul style="list-style-type: none"><li>- If user email was not validate previously</li></ul>	
	200 (Successful response)	<pre>{   "result": [     {       "emailVerified": "Your email has already been Activated"     }   ],   "result_code": "0000" }</pre> <p>Notes:</p> <ul style="list-style-type: none"><li>- If user email was already validated</li></ul>	

	200 (wrong member ID or email)	{ "result": [ { "emailVerified": "Wrong Email / Member ID" } ], "result_code": "0000" }
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	200 (wrong Member ID)	{ "result_code": "1007", "msg": "invalid member ID" }
	200 (wrong Member ID or Email)	{ "result_code": "1008", "msg": "Wrong Email / Member ID" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 11. Set Password API

### 11.1 Overview

This API will overwrite the current member password

### 11.2 Specification

HTTP Request	https://{domain_name}/v1/setpassword		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	(string)	<pre>{   "id": "73908130-48B4-4F9C-92CE-51A73ACF47AA",   "password": "abc", }</pre> <p>Note:</p> <p>Minimum password length is <b>6</b> and any <u>2 criteria</u> from below</p> <ol style="list-style-type: none"><li>1. Password length &gt; 7</li><li>2. Password contains both lowercase and uppercase characters</li><li>3. Password contains number and character</li><li>4. Password has one special character</li><li>5. Password has two special characters</li></ol>
Response	Status	Sample Response	
	200 (Successful response)	<pre>{   "result": [     {       "name": "TESTER ONE",       "id": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx",       "message": "Password is valid"     }   ],   "result_code": "0000", }</pre>	



	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	200 (wrong Member ID)	{ "result_code": "1007", "msg": "invalid member ID" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 12. Change Password API

### 12.1 Overview

This API is to change the member password

### 12.2 Specification

HTTP Request	https://{domain_name}/v1/changepassword		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	(string)	<pre>{   "id": "73908130-48B4-4F9C-92CE-51A73ACF47AA",   "oldPassword": "abc",   "newPassword": "Password@1!" }</pre> <p>Note:</p> <p>Minimum password length is <b>6</b> and any <u>2 criteria</u> from below</p> <ul style="list-style-type: none"><li>6. Password length &gt; 7</li><li>7. Password contains both lowercase and uppercase characters</li><li>8. Password contains number and character</li><li>9. Password has one special character</li><li>10. Password has two special characters</li></ul>
Response	Status	Sample Response	
	200 (Successful response)	<pre>{   "result": [     {       "id": "9A4089EB-3BC8-4EAD-9C4A-3620317D944C",       "message": "You have successfully changed your password."     }   ],   "result_code": "0000", }</pre>	

		<pre>} Notes: - If user enter the correct old password</pre>
	200 (Successful response)	<pre>{   "result": [     {       "id": "9A4089EB-3BC8-4EAD-9C4A-3620317D944C",       "message": "Your old password is incorrect."     }   ],   "result_code": "0000" }</pre> <p>Notes:</p> <ul style="list-style-type: none"> <li>- If user enter wrong old password</li> </ul>
	200 (server error)	<pre>{   "result_code" : "1003",   "msg" : "Server Error" }</pre>
	200 (Database Error)	<pre>{   "result_code" : "1004",   "msg" : "Database Error" }</pre>
	200 (Parameter empty)	<pre>{   "result_code": "1005",   "msg": "Missing required parameter data" }</pre>
	200 (wrong Member ID)	<pre>{   "result_code": "1007",   "msg": "invalid member ID" }</pre>
	401 (Unauthorized request)	<pre>{   "error_code": "000",   "msg": "Access Denied" }</pre>
	400 (Bad Request)	<pre>{   "error_code": "001",   "msg": "Access Denied" }</pre>

## 13. View Profile API

### 13.1 Overview

This API is to get the member profile

### 13.2 Specification

HTTP Request	https://{domain_name}/v1/getprofile		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	id	(String)	id="xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxxx"
Response	Status	Sample Response	
	200 (Successful response)	<pre>{   "result": [     {       "personal_details":{         "member_id":"uks9a-ssd9d-a2scp",         "status":"active/inactive",         "approval_status":"approved/pending approval/rejected",         "NRIC":"S1234567A",         "marital_status":"single/married/others",         "home_phone":"",         "salutation":"Dr/Mdm/Mr/Mrs/Ms/Prof/Miss",         "email":"test@htns.com",         "office_phone":"",         "full_name":"Mike Tan",         "hand_phone":"81238123",         "PA_CAN_Number":"",         "dob":"15/05/1982",         "nationality":"Singapore Citizen/Singapore PR/Others",         "golf_handicap":"",         "gender":"male/female",         "race":"Chinese/Malay/Indian/Others",         "residential_address":{           "blk":"31",           "street":"Ah Hood Rd",           "unit":"01-21",</pre>	

		<pre> "postal_code":"329979" }, "economic_status":"working/not working", "highest_education": "", "car_plate": "", "car_IU": "", "occupation": "", "annual_income": "", "emergency_contact": { "name": "Sara",  "relationship": "spouse/parents/child/siblings/relatives/friends", "contact_no": "91111111" }, "communication_preference": { "handphone": "false", "postal_mail": "true", "email": "true", "frontline_magazine": "true" }, "membership_info": { "type": "ordinary/associate/corporate/social/honorary/family", "expired_date": "30/11/2023", "registration_type": "Ordinary Membership - 2 Year Renewal",  "card_type": "HomeTeamNS-PAssion-POSB/HomeTeamNS-PAssio n/HomeTeamNS", "membership_group": "" } } ], "result_code" : "0000", } </pre>
	200 (server error)	<pre> { "result_code" : "1003", "msg" : "Server Error" } </pre>
	200 (Database Error)	<pre> { "result_code" : "1004", "msg" : "Database Error" } </pre>
	200 (Parameter empty)	<pre> { "result_code": "1005", </pre>

		"msg": "Missing required parameter data" }
	200 (wrong Member ID)	{ "result_code": "1007", "msg": "invalid member ID" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 14. Edit Profile API

### 14.1 Overview

This API is to edit main member profile

### 14.2 Specification

HTTP Request	https://{domain_name}/v1/editprofile		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	userDetails	<div>member_id(string) status (string) approval_status(string) nric(string) marital_status(string) home_phone(string) salutation(string) email(string) office_phone(string) full_name(string) hand_phone(string)  PA_CAN_Number(string) dob(string) nationality(string) golf_handicap(string) gender(string) race(string) residential_address(Map&lt;String,String&gt;) blk(string) street(string) unit(string) postal_code(string) economic_status(string) highest_education(string) car_plate(string) car_IU(string) occupation(string) annual_income(string)  emergency_contact(Map</div>	<div>{   "userDetails":{      "Member_id":"xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxxx",     "partial_update": 0,     "status":"active/inactive",     "approval_status":"approved/pending approval/rejected",     "nric":"S1234567A",     "marital_status":"single/married/others",     "home_phone":"",      "salutation":"Dr/Mdm/Mr/Mrs/Ms/Prof/Miss",     "email":"test@htns.com",     "office_phone":"",     "full_name":"Mike Tan",     "hand_phone":"12345678",     "PA_CAN_Number":"",     "dob":"dd/mm/yyyy",     "nationality":"Singapore Citizen/Singapore PR/Others",     "golf_handicap":"",     "gender":"male/female",     "race":"Chinese/Malay/Indian/Others",     "residential_address":{       "blk":"31",       "street":"Ah Hood Rd",       "unit":"01-21",</div>





		<pre> "personal_details":{   "member_id": "",   "status": "",   "approval_status": "",   "NRIC": "",   "marital_status": "",   "home_phone": "",   "salutation": "",   "email": "",   "office_phone": "",   "full_name": "",   "hand_phone": "",   "PA_CAN_Number": "",   "dob": "",   "nationality": "",   "golf_handicap": "",   "gender": "",   "race": "",   "residential_address": {     "blk": "",     "street": "",     "unit": "",     "postal_code": ""   },   "economic_status": "",   "highest_education": "",   "car_plate": "",   "car_IU": "",   "occupation": "",   "annual_income": "",   "emergency_contact": {     "name": "Sara",     "relationship": "",     "contact_no": ""   },   "communication_preference": {     "isVoicecall": "",     "isHandphone": "",     "isPostal_mail": "",     "isEmail": "",     "isFrontline_magazine": "",     "isFrontline_magazine_digital": ""   },   "membership_info": {     "type": "",     "expired_date": "",     "registration_type": "",     "card_type": "",     "membership_group": ""   } </pre>
--	--	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre>     }   },   "result_code" : "0000", } </pre> <p>Note: information will be filled accordingly</p> <p><b>//For partial</b></p> <pre> {   "result": "Update success",   "result_code": "0000" } </pre>
	200 (server error)	<pre> {   "result_code" : "1003",   "msg" : "Server Error" } </pre>
	200 (Database Error)	<pre> {   "result_code" : "1004",   "msg" : "Database Error" } </pre>
	200 (Parameter empty)	<pre> {   "result_code": "1005",   "msg": "Missing required parameter data" } </pre>
	200 (wrong Member ID)	<pre> {   "result_code": "1007",   "msg": "invalid member ID" } </pre>
	200 (wrong Status)	<pre> {   "result_code": "1008",   "msg": "Only accept active or inactive" } </pre>
	200 (wrong Approval Status)	<pre> {   "result_code": "1008",   "msg": "Only accept approved/pending approval/rejected" } </pre>
	200 (wrong nric format)	<pre> {   "result_code": "1008",   "msg": "Invalid nric" } </pre>
	200 (wrong marital status format)	<pre> {   "result_code": "1008",   "msg": "Only accept single/married/others" } </pre>

		}
	200 (wrong salutation format)	{ "result_code": "1008", "msg": "Only accept Dr/Mdm/Mr/Mrs/Ms/Prof/Miss" }
	200 (wrong email format)	{ "result_code": "1008", "msg": "Invalid email format" }
	200 (wrong name format)	{ "result_code": "1008", "msg": "Invalid name format" }
	200 (wrong mobile phone format)	{ "result_code": "1008", "msg": "Only accept numbers and numbers must start with 8 or 9" }
	200 (wrong date of birth format)	{ "result_code": "1008", "msg": "Invalid Date of Birth format - dd/mm/yyyy" }
	200 (wrong nationality Format)	{ "result_code": "1008", "msg": "Only accept Singapore Citizen/Singapore PR/Others" }
	200 (wrong gender)	{ "result_code": "1008", "msg": "Only accept male/female" }
	200 (wrong race)	{ "result_code": "1008", "msg": "Only accept Chinese/Malay/Indian/Others" }
	200 (wrong economic status)	{ "result_code": "1008", "msg": "Only accept working/not working" }
	200 (wrong Emergency Contact name)	{ "result_code": "1008", "msg": "invalid Emergency Contact Name" }

	200 (wrong Emergency Contact Relationship)	{ "result_code": "1008", "msg": "invalid Emergency Contact Relationship, only accept spouse/parents/child/siblings/relatives/friends" }
	200 (wrong Emergency Contact number)	{ "result_code": "1008", "msg": "invalid Emergency Contact number, only accept numbers" }
	200 (wrong Communication Preferences)	{ "result_code": "1008", "msg": "invalid Communication Preference, only accept true/false" }
	200 (wrong Membership InfoType)	{ "result_code": "1008", "msg": "invalid Membership Info Type, only accept ordinary/associate/corporate/social/honorary/family" }
	200 (wrong Membership Info Expiry Date)	{ "result_code": "1008", "msg": "invalid Membership Info expired date format - dd/mm/yyyy" }
	200 (wrong Membership Info card type)	{ "result_code": "1008", "msg": "Only accept HomeTeamNS-PAssion-POSB/HomeTeamNS-PAssion/HomeTeamNS" }
	200 (member do not exist)	{ "result_code": "1000", "result": "Member do not exist in database" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }



## 15. Check Nric Unique API

### 15.1 Overview

This API is to check the unique of nric

### 15.2 Specification

HTTP Request	https://{domain_name}/v1/checknricunique		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	nric	String	G111111G
Response	Status	Sample Response	
	200 (Successful response)	{ "result": "true", (true = nric exists/ false = nric not exists) "result_code": "0000" }	
	200 (server error)	{ "result_code": "1003", "msg": "Server Error" }	
	200 (Database Error)	{ "result_code": "1004", "msg": "Database Error" }	
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }	
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }	

	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code": "003", "msg": "Bad Request - Parameter Missing" }

## 16. Check Mobile Unique API

### 16.1 Overview

This API is to check the unique of mobile

### 16.2 Specification

HTTP Request	https://{domain_name}/v1/checkmobileunique		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	mobile	String	88889999
Response	Status	Sample Response	
	200 (Successful response)	{ "result": "false", (false = mobile not exists) "result_code": "0000", "message": "" }	
	200 (Successful response, mobile used)	{ "result": "true", "result_code": "0000", "message": "This hand phone number is already registered to an existing member account. Please provide a different hand phone number. Using the same number will overwrite the existing member account." }	
	200 (Successful response, invalid mobile)	{ "result": "true", "result_code": "0000", "message": "Please enter a valid hand phone number" }	
	200 (server error)	{ "result_code": "1003", "msg": "Server Error" }	
	200 (Database Error)	{ "result_code": "1004",	



		<pre> "msg" : "Database Error" } </pre>
	401 (Unauthorized request)	<pre> {   "error_code": "000",   "msg": "Access Denied" } </pre>
	400 (Bad Request)	<pre> {   "error_code": "001",   "msg": "Access Denied" } </pre>
	400 (Parameter type not match)	<pre> {   "error_code": "002",   "error": "Bad Request - Parameter type not match" } </pre>
	400 (Parameter missing)	<pre> {   "error_code" : "003",   "msg" : "Bad Request - Parameter Missing" } </pre>

## 17. Check Email Unique API

### 17.1 Overview

This API is to check the unique of email

### 17.2 Specification

HTTP Request	https://{domain_name}/v1/checkemailunique		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	email	String	XXX@XXX.XX
Response	Status	Sample Response	
	200 (Successful response)	{ "result": "false", (false = not exists) "result_code": "0000", "message": "" }	
	200 (Successful response)	{ "result": "true", "result_code": "0000", "message": "Please enter a valid email address" }	
	200 (Successful response)	{ "result": "true", "result_code": "0000", "message": "This email has been verified by another member, if this is your email address, please email membership@hometeamns.sg" }	
	200 (server error)	{ "result_code": "1003", "msg": "Server Error" }	
	200 (Database Error)	{ "result_code": "1004", }	

		<pre> "msg" : "Database Error" } </pre>
	401 (Unauthorized request)	<pre> {   "error_code": "000",   "msg": "Access Denied" } </pre>
	400 (Bad Request)	<pre> {   "error_code": "001",   "msg": "Access Denied" } </pre>
	400 (Parameter type not match)	<pre> {   "error_code": "002",   "error": "Bad Request - Parameter type not match" } </pre>
	400 (Parameter missing)	<pre> {   "error_code" : "003",   "msg" : "Bad Request - Parameter Missing" } </pre>

## 18. Get MemberList By Filter

### 18.1 Overview

This API is to get member list by filter

### 18.2 Specification

HTTP Request	https://{domain_name}/v1/getmemberlistbyfilter		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	memberId	String	XXXXXXXX-XXXX-XXXX-XXXX-XXXXXXXXXXXX
	nric	String	X000000X / 000X
	name	String	xxx
	email	String	xx@xx.xx
	mobile	String	90909090
	membershipType	String	XXXXXXXX-XXXX-XXXX-XXXX-XXXXXXXXXXXX
	approvalStatus	String	0/1/2 (Pending/Approved/Rejected)
	status	String	0/1 (Active/Inactive)
	createdBy	String	XXXXXXXX-XXXX-XXXX-XXXX-XXXXXXXXXXXX
	pageno	int	1
	itemperpage	int	10
Response	Status	Sample Response	
	200 (Successful response)	{ "result": [ { "membershipType": "Associate Membership", "updatedBy": "CRM ADMINISTRATOR", "approval": "Approved", "mobile": "96164175", } ] }	

		<pre> "updatedAt": "2015-07-14 17:05:01.953", "nric": "XXXXX469W", "expiryDate": "2017-09-30 00:00:00.0", "createdDate": "2013-12-25 15:11:26.5", "registrationType": "Associate Membership - 5 Year (New Registration)", "createdBy": "CRM ADMINISTRATOR", "name": "AMIT GURUNG", "email": "NA@NA.com", "status": "Active", "memberId": "1EB3BE75-62BD-4334-9C37-76FB6A9125F0" }, { "membershipType": "Ordinary Membership", "updatedBy": "SYSTEM", "approval": "Approved", "mobile": "92329391", "updatedAt": "2020-09-30 23:26:05.153", "nric": "XXXXX001A", "expiryDate": "2027-10-31 23:59:59.0", "createdDate": "2013-12-25 15:38:45.163", "registrationType": "HomeTeamNS Family Scheme Ordinary Admin Fee (Auto-Extension)", "createdBy": "CRM ADMINISTRATOR", "name": "YEO CHIN HAN KEVIN", "email": "yeo79@hotmail.com", "status": "Active", "memberId": "C434173B-E6FC-4C7A-BAB4-006AE6DE9359" } ], "result_code": "0000", "totalrecords": "10" } </pre>
	200 (Empty Result)	<pre> { "result": [], "result_code": "0000", "totalrecords": "0" } </pre>
	200 (server error)	<pre> { "result_code": "1003", "msg": "Server Error" } </pre>
	200 (Database Error)	<pre> { "result_code": "1004", "msg": "Database Error" } </pre>
	401 (Unauthorized request)	<pre> { "error_code": "000", "msg": "Access Denied" } </pre>
	400 (Bad Request)	<pre> { "error_code": "001", "msg": "Access Denied" } </pre>

		}
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code": "003", "msg": "Bad Request - Parameter Missing" }

## 19. Get Transaction Detail By transaction ID

### 19.1 Overview

This API is to get transaction detail by transaction id.

### 19.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/gettransactiondetail		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	transactionId	String	XXXXXXXX-XXXX-XXXX-XXXX-XXXXXXXXXXXXX (BBB86249-140C-4878-A5C2-C2D1432B1D61)
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": [     {       "amount": "0.00",       "name": "LIM YEW CHUN",       "description": "desc",       "location": "HomeTeamNS",       "invoiceNo": "HTNS00028088",       "merchantRefNo": "20210507233721560",       "invoiceDate": "07-05-2021 23:37:22",       "nric": "XXXXX880C",       "onlineRefNo": "",       "remarks": "",       "paymentStatus": "Success",       "promotion": ""     }   ],   "result_code": "0000" }</pre>	
	200 (Empty Result)	<pre>{   "msg": "Database Error - Unable to find this record.",   "result_code": "1004" }</pre>	
	200 (server error)	<pre>{   "result_code": "1003",   "msg": "Server Error" }</pre>	

	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code" : "003", "msg" : "Bad Request - Parameter Missing" }



## 20. Get Invoice Detail By Invoice Number

### 20.1 Overview

This API is to get invoice detail by invoice number.

### 20.2 Specification

HTTP Request	https://{domain_name}/v1/getinvoicedetail		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	invoiceNumber	String	XXXXXXXXXXXXX (HTNS00027330)
Response	Status	Sample Response	
	200 (Successful response)	<pre>{   "result": [     {       "date": "2021-04-09 23:48:27.607",       "gstRate": 0.07,       "gstValue": "7",       "gst": "1.31",       "subTotal": "18.69",       "nric": "XXXXX187E",       "gstNumber": "M400055254",       "total": "20.00",       "invoiceItems": [         {           "total": "20.00",           "quantity": 1,           "price": "20.00",           "name": "UTHALUN WATCHARAPORN",           "particulars": "MBS - Family Membership - 2 Year (New Registration)",           "nric": "XXXXX033H"         }       ],       "englishAmt": "Twenty Dollar(s)",       "invoicePayments": [         {           "amount": "20.00",           "description": "Online Payment",           "paymentType": "Online Payment",           "serialNo": "1"         }       ]     }   ], }</pre>	

		<pre> "invoiceNumber": "HTNS00027330", "location": "HOMETEAMNS", "fullName": "TONG CHEE WAH" } ], "result_code": "0000" } </pre>
	200 (Empty Result)	<pre> {   "msg": "Database Error - Unable to find this record.",   "result_code": "1004" } </pre>
	200 (server error)	<pre> {   "result_code" : "1003",   "msg" : "Server Error" } </pre>
	200 (Database Error)	<pre> {   "result_code" : "1004",   "msg" : "Database Error" } </pre>
	401 (Unauthorized request)	<pre> {   "error_code": "000",   "msg": "Access Denied" } </pre>
	400 (Bad Request)	<pre> {   "error_code": "001",   "msg": "Access Denied" } </pre>
	400 (Parameter type not match)	<pre> {   "error_code": "002",   "error": "Bad Request - Parameter type not match" } </pre>
	400 (Parameter missing)	<pre> {   "error_code" : "003",   "msg" : "Bad Request - Parameter Missing" } </pre>

## 21. Get NRIC List API

### 21.1 Overview

This API is to get the nric list by main member id

### 21.2 Specification

HTTP Request	https://{domain_name}/v1/getnriclist		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	id	String	XXXXXXXX-XXXX-XXXX-XXXX-0000B6423AB
Response	Status	Sample Response	
	200 (Successful response)	{ "result": [ "S9773620J,t84Ve0/mq+E8rlvs1r2ObQ==" ], "result_code": "0000" }	
		(list of Nric + encoded nric)	
	200 (Empty Result)	{ "result": [], "result_code": "0000" }	
	200 (server error)	{ "result_code": "1003", "msg": "Server Error" }	
	200 (Database Error)	{ "result_code": "1004", "msg": "Database Error" }	

	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code": "003", "msg": "Bad Request - Parameter Missing" }

## 22. Upload Supporting Document API

### 22.1 Overview

This API is to upload the supporting document to the member.

### 22.2 Specification

HTTP Request	https://{domain_name}/v1/supportingdocument		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	memberId	String	XXXXXXXX-XXXX-XXXX-XXXX-0000B6423AB
	document	form-data	Png file
Response	Status	Sample Response	
	200 (Successful response)	{ "result": "Success", "result_code": "0000" }	
	200 (not support file format)	{ "result": "File Type Not Allow.", "result_code": "1000" }	
	200 (Upload Fail)	{ "result": "File Upload Fail.", "result_code": "1000" }	
	200 (Empty Result)	{ "msg": "Database Error - Unable to find this record.", "result_code": "1004" }	
	200 (server error)	{ "result_code": "1003", "msg": "Server Error" }	

		}
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code" : "003", "msg" : "Bad Request - Parameter Missing" }

## 23. Edit Family / Social API

### 23.1 Overview

This API is to edit family / social profile

### 23.2 Specification

HTTP Request	https://{domain_name}/v1/editfamilyorsocialprofile		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	userDetails	<div>member_id(string) status (string) approval_status(string) nric(string) email(string) full_name(string) hand_phone(string)  PA_CAN_Number(string) dob(string) gender(string) race(string)  residential_address(Map&lt;string,string&gt;) blk(string) street(string) unit(string) postal_code(string)  car_plate(string) car_IU(string)  communication_preference(Map&lt;string,string&gt;) handphone(string) postal_mail(string) email(string) frontline_magazine(string) )</div>	<pre>{   "userDetails":{     "member_id":"xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxxx",     "partial_update": 0,     "status": "",     "approval_status": "",     "nric": "",     "email": "",     "full_name": "",     "hand_phone": "",     "PA_CAN_Number": "",     "dob": "",     "gender": "",     "race": "",     "registration": "",     "relationship": "",     "residential_address":{       "blk": "",       "street": "",       "unit": "",       "postal_code": ""     },     "car_plate": "",     "car_IU": "",     "communication_preference":{       "isVoicecall": "",       "isHandphone": "",       "isPostal_mail": "", </pre>

			<pre>         "isEmail":"","         "isFrontline_magazine":"","         "isFrontline_magazine_digital": ""       }     }   }  //for partial update {   "userDetails": {     "member_id": "D449B8DA-D6E3-4B3D-A3A1-8751DDD7B5 53",     "email": "",     "hand_phone": "87126354",     "partial_update": 1,     "type":"family"   } } Type: family/social "partial_update": 0/1,  Note: all fields do not need to be filled, only member_id is compulsory and the field you want to change </pre>
Response	Status	Sample Response	
	200 (Successful response)	<pre> {   "result": {     "family_details": {       "family_member_id": "",       "status": "",       "approval_status": "",       "name": "",       "NRIC": "",       "relationship": "",       "gender": "",       "race": "",       "dob": "",       "email": "",       "hand_phone": "",       "registration_type": "",       "car_plate": "",       "car_IU": "",       "PA_CAN_Number": "",       "residential_address": {},       "communication_preference": {}     }   }, </pre>	



		<pre> "social_details": {   "social_member_id": "",   "status": "active",   "approval_status": "",   "name": "",   "NRIC": "",   "relationship": "",   "gender": "",   "race": "",   "dob": "",   "email": "",   "hand_phone": "",   "registration_type": "",   "residential_address": {     "blk": "",     "street": "",     "unit": "",     "postal_code": ""   },   "communication_preference": {     "handphone": "",     "postal_mail": "*",     "comm_email": "",     "frontline_magazine": ""   } }, "result_code": "0000" } </pre> <p>Note: information will be filled accordingly</p> <p><b>//For partial</b></p> <pre> {   "result": "Update success",   "result_code": "0000" } </pre>
	200 (server error)	<pre> {   "result_code" : "1003",   "msg" : "Server Error" } </pre>
	200 (Database Error)	<pre> {   "result_code" : "1004",   "msg" : "Database Error" } </pre>
	200 (Parameter	<pre> {   "result_code": "1005", </pre>

	empty)	"msg": "Missing required parameter data" }
	200 (wrong Member ID)	{ "result_code": "1007", "msg": "invalid member ID" }
	200 (wrong Status)	{ "result_code": "1008", "msg": "Only accept active or inactive" }
	200 (wrong Approval Status)	{ "result_code": "1008", "msg": "Only accept approved/pending approval/rejected" }
	200 (wrong nric format)	"result_code": "1008", "msg": "Invalid nric" }
	200 (wrong marital status format)	{ "result_code": "1008", "msg": "Only accept single/married/others" }
	200 (wrong contact number format)	{ "result_code": "1008", "msg": "Only accept numbers" }
	200 (wrong salutation format)	{ "result_code": "1008", "msg": "Only accept Dr/Mdm/Mr/Mrs/Ms/Prof/Miss" }
	200 (wrong email format)	{ "result_code": "1008", "msg": "Invalid email format" }
	200 (wrong name format)	{ "result_code": "1008", "msg": "Invalid name format" }
	200 (wrong mobile phone format)	{ "result_code": "1008", "msg": "Only accept numbers and numbers must start with 8 or 9" }

		}
	200 (wrong date of birth format)	{ "result_code": "1008", "msg": "Invalid Date of Birth format - dd/mm/yyyy" }
	200 (wrong gender)	{ "result_code": "1008", "msg": "Only accept male/female" }
	200 (wrong race)	{ "result_code": "1008", "msg": "Only accept Chinese/Malay/Indian/Others" }
	200 (wrong Communication Preferences)	{ "result_code": "1008", "msg": "invalid Communication Preference, only accept true/false" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 24. Create Member Account

### 24.1 Overview

This API is to create guest account or add user credential for other member

### 24.2 Specification

HTTP Request	https://{domain_name}/v1/create_account_credential		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	(string)	<b>Other member:</b> { "user_info":{ "type":"familymember", "username":"family", "password":"family",  "memberId":"57C32653-D84D-47E5-AC63-89271ACD4061" } }

			<p><b>Guest member:</b></p> <pre>{   "user_info":{     "type":"guestmember",     "username":"family",     "password":"family",     "email": "",     "Mobile": "",     "name": "",     "dob": ""   } }</pre> <p>Type :        guestmember, mainmember,        familymember, affiliatemember        For other member        Only username, password,        memberid and type is mandatory</p> <p>For guest member        Only username, password, mobile,        email, name, dob and type is        mandatory.</p>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result" : "Success",   "member_id": "57C32653-D84D-47E5-AC63-89271ACD4061"   "result_code" : "0000" }</pre>	
	200 (Fail Insert)	<pre>{   "result_code" : "1000",   "msg" : "Fail to insert guest info" }</pre>	
	200 (server error)	<pre>{   "result_code" : "1003",   "msg" : "Server Error" }</pre>	
	200 (Database Error)	<pre>{   "result_code" : "1004",   "msg" : "Database Error" }</pre>	

	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code": "003", "msg": "Bad Request - Parameter Missing" }

## 25. View Guest Account

### 25.1 Overview

This API is to view guest account by guestId

### 25.2 Specification

HTTP Request	https://{domain_name}/v1/viewguestaccount		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	guestId	String	E5D13F09-7D16-4E04-9289-AC2CA DBA4F11
Response	Status	Sample Response	
	200	{	

(Successful response)	<pre> "password": "//2yJY9oIRqzagC8+WajVg==", "modifiedOn": "2021-07-23 10:25:05.477", "dob": "15-08-1992", "mobile": "86840926", "name": "leo", "id": 1, "createdOn": "2021-07-23 10:19:27.593", "email": "ncw1121@hotmail.com", "username": "leo" </pre>
200 (Empty Result)	<pre> {   "msg": "Database Error - Unable to find this record.",   "result_code": "1004" } </pre>
200 (server error)	<pre> {   "result_code" : "1003",   "msg" : "Server Error" } </pre>
401 (Unauthorized request)	<pre> {   "error_code": "000",   "msg": "Access Denied" } </pre>
400 (Bad Request)	<pre> {   "error_code": "001",   "msg": "Access Denied" } </pre>
400 (Parameter type not match)	<pre> {   "error_code": "002",   "error": "Bad Request - Parameter type not match" } </pre>
400 (Parameter missing)	<pre> {   "error_code" : "003",   "msg" : "Bad Request - Parameter Missing" } </pre>

## 26. Edit Guest Account

### 26.1 Overview

This API is to edit guest account

### 26.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/editguestaccount		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	guestId	String	E5D13F09-7D16-4E04-9289-AC2CABDA4F11



	username	String	leonew
	password	String	leo1234
	name	String	Leo nam ah
	email	String	b@b.b
	mobile	String	12345678
	dob	String	16-08-1992
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	{ "result" : "Success", "result_code" : "0000" }	
	200 (Empty Result)	{ "msg": "Database Error - Unable to find this record.", "result_code": "1004" }	
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }	
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }	
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }	
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }	
	400 (Parameter missing)	{ "error_code" : "003", "msg" : "Bad Request - Parameter Missing" }	

## 27. List Guest Account

### 27.1 Overview

This API is to get the listing of guest account by filter

### 27.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/listguestaccount		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	pageno	Int	2

	itemperpage	int	10
	name	String	leo
	email	String	b@b.b
	mobile	String	6789 Note: Can insert 4 or 8 character
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": [     {       "password": "leo123",       "createdDate": "2021-07-23 10:19:27.593",       "dobStr": "Sat Aug 15 00:00:00 SGT 1992",       "mobile": "86840926",       "hashPassword": "//2yJY9oIRqzagC8+WajVg==",       "name": "leo",       "last4Mobile": "0926",       "modifiedDate": "2021-07-23 10:25:05.477",       "id": 1,       "email": "ncw1121@hotmail.com",       "username": "leo"     }   ],   "result_code": "0000",   "totalrecords": "1" }</pre>	
	200 (Empty Result)	<pre>{   "result": [],   "result_code": "0000",   "totalrecords": "0" }</pre>	
	200 (server error)	<pre>{   "result_code": "1003",   "msg": "Server Error" }</pre>	
	200 (Database Error)	<pre>{   "result_code": "1004",   "msg": "Database Error" }</pre>	
	401 (Unauthorized)	<pre>{   "error_code": "000", }</pre>	

	request)	"msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code": "003", "msg": "Bad Request - Parameter Missing" }

## 28. Guest Login

### 28.1 Overview

This API is to get guest login status

### 28.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/guestlogin		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
	<b>Key</b>	<b>Value</b>	<b>Example</b>

<b>Request Body</b>	Raw (application/json)	(string)	{ "user_info":{ "username":"user", "password":"pwd" } }
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	{ "result": { "member_id": "E5D13F09-7D16-4E04-9289-AC2CADBA4F11" }, "result_code": "0000" }	
	200 (Empty Result)	{ "msg":"Login fail, username not found", "result_code":"1000" }	
	200 (Password not match)	{ "msg":"Password not match", "result_code":"1000" }	
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }	
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }	
	401 (Unauthorized request)	{ "error_code":"000", "msg":"Access Denied" }	
	400 (Bad Request)	{ "eror_code":"001", "msg":"Access Denied" }	
	400 (Parameter type not match)	{ "error_code":"002",	

		<pre>"error": "Bad Request - Parameter type not match" }</pre>
	400 (Parameter missing)	<pre>{   "error_code": "003",   "msg": "Bad Request - Parameter Missing" }</pre>

## 29. Remove Family / Social from Main member API

### 29.1 Overview

This API is to remove main member family / social profile

### 29.2 Specification

HTTP Request	https://{domain_name}/v1/removefamilyorsocial		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	userDetails	family_id(string) social_id(string)	<pre>{   "userDetails":{     "family_id":"xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx",     "social_id":"xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx"   } }</pre> <p>Note: Either family_id or social_id must be fill</p>
Response	Status	Sample Response	
	200 (Successful response)	<pre>{   "result_code" : "1000",   "msg" : "Member: xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx has been successfully remove" }</pre>	
	200 (does not exist in database,	<pre>{   "result_code": "1000",   "result": "Member do not exist in database" }</pre>	

	social)	}
	200 (Successful response)	{ "result_code" : "1007", "msg" : "Invalid family member ID" }
	200 (Successful response)	{ "result_code" : "1007", "msg" : "Invalid social member ID" }
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }



## 30. Replacement Card Status API

### 30.1 Overview

Check if member is requesting replacement card

### 30.2 Specification

HTTP Request	https://{domain_name}/v1/isrequestingcardreplacement		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	member_id	(string)	"member_id": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxxx"
Response	Status	Sample Response	
	200 (Successful response)	{ "result_code": "1000", "result": "Active" }	
	200 (Successful response)	{ "result_code": "1000", "result": "Closed" }	
	200 (server error)	{ "result_code": "1003", "msg": "Server Error" }	
	200 (Database Error)	{ "result_code": "1004", "msg": "Database Error" }	
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }	

		}
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 31. Sign Up Form API

### 31.1 Overview

Get the signup form for registration

### 31.2 Specification

HTTP Request	https://{domain_name}/v1/signupform		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
Response	Status	Sample Response	
	200 (Successful response)	<pre>{   "result": [     {       "acknowledge": {         "min": -1,         "max": -1,         "format": "",         "name": "acknowledge",         "input_type": "Checkbox",         "disabled": false,         "onSelected": "",         "label": "I acknowledge that I have read and accept the above declarations.\nI agree and consent HomeTeamNS use of my personal data as part of my Membership Application",         "mandatory": true,         "info": ""       },       "normalFieldList": [         {           "min": -1,           "max": -1,           "format": "X0000000X",           "name": "nric",           "input_type": "Text field",           "disabled": false,</pre>	

		<pre> "onSelected": "check nric", "label": "* NRIC / FIN", "mandatory": true }, { "min": -1, "max": -1, "format": "Uppercase", "name": "name", "input_type": "Text field", "disabled": false, "onSelected": "", "label": "* Full Name (As on NRIC/FIN)", "mandatory": true }, { "min": -1, "answer": [ { "answer": "Male", "destination": "", "action": "" }, { "answer": "Female", "destination": "", "action": "" } ], "max": -1, "format": "capital", "name": "gender", "input_type": "Radio Button", "disabled": false, "onSelected": "", "label": "* Gender", "mandatory": true }, { "min": -1, "max": -1, "format": "dd-MM-yyyy", "name": "dob", "input_type": "Date", "disabled": false, "onSelected": "show available price in registrationtype", "label": "* Date Of Birth (DD-MM-YYYY)", "mandatory": true, "info": "To be eligible as a Main Member, you must be aged 16 and above" </pre>
--	--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre> }, {   "min": -1,   "max": -1,   "format": "a@a.a",   "name": "email",   "input_type": "Text Field",   "disabled": false,   "onSelected": "check dup, show confirm email",   "label": "* Email",   "mandatory": true }, {   "min": -1,   "max": -1,   "format": "a@a.a",   "name": "confirm email",   "input_type": "Text Field",   "disabled": false,   "onSelected": "check same as email",   "label": "* Confirm Email",   "mandatory": true }, {   "min": -1,   "max": -1,   "format": "00000000",   "name": "mobile",   "input_type": "Text Field",   "disabled": false,   "onSelected": "verify mobile, send otp, show otp",   "label": "* Hand Phone",   "mandatory": true }, {   "min": -1,   "max": -1,   "format": "000000",   "name": "otp",   "input_type": "Text Field",   "disabled": false,   "onSelected": "verify mobile, send otp",   "label": "* Hand Phone OTP",   "mandatory": true }, {   "min": -1,   "max": -1,   "format": "000000",   "name": "postalcode", </pre>
--	--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre> "input_type": "Text Field", "disabled": false, "onSelected": "show streetname, block, unit dropdownlist", "label": "* Postal Code", "mandatory": true }, {   "min": -1,   "max": -1,   "format": "",   "name": "streetname",   "input_type": "Text Field",   "disabled": true,   "onSelected": "",   "label": "* Street Name",   "mandatory": true }, {   "min": -1,   "max": -1,   "format": "",   "name": "block",   "input_type": "Text Field",   "disabled": true,   "onSelected": "",   "label": "* House No. / Block",   "mandatory": true }, {   "min": -1,   "max": -1,   "format": "#xx-xxx",   "name": "unit",   "input_type": "Drop Down List",   "disabled": false,   "onSelected": "",   "label": "* Floor - Unit No.",   "mandatory": true }, {   "min": -1,   "max": -1,   "format": "",   "name": "registrationtype",   "input_type": "Drop Down List",   "disabled": false,   "onSelected": "",   "label": "* Membership Registration Type:",   "mandatory": true,   "info": "'Ordinary Membership' - All NSmen who have </pre>
--	--	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



		<pre>"mandatory": true }, {   "min": -1,   "answer": [     {       "answer": "Yes",       "destination": "",       "action": ""     },     {       "answer": "No",       "destination": "",       "action": ""     }   ],   "max": -1,   "format": "",   "name": "promoemail",   "input_type": "Radio button",   "disabled": false,   "onSelected": "",   "label": "** Receive promotional email?",   "mandatory": true }, {   "min": -1,   "answer": [     {       "answer": "Yes",       "destination": "",       "action": ""     },     {       "answer": "No",       "destination": "",       "action": ""     }   ],   "max": -1,   "format": "",   "name": "magazine",   "input_type": "Radio Button",   "disabled": false,   "onSelected": "",   "label": "** Receive the digital copy of FRONTLINE Magazine?",   "mandatory": true }, ],</pre>
--	--	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



		<pre> "familyField": [   {     "min": -1,     "max": -1,     "format": "X00000000X",     "name": "familynric",     "input_type": "Text field",     "disabled": false,     "onSelected": "check nric",     "label": "* Family Member NRIC/Birth Cert No.",     "mandatory": true   },   {     "min": -1,     "max": -1,     "format": "Uppercase",     "name": "familyname",     "input_type": "Text field",     "disabled": false,     "onSelected": "",     "label": "* Family Member Name",     "mandatory": true   },   {     "min": -1,     "answer": [       {         "answer": "Spouse",         "destination": "",         "action": ""       },       {         "answer": "Parent",         "destination": "",         "action": ""       },       {         "answer": "Child",         "destination": "",         "action": ""       }     ],     "max": -1,     "format": "",     "name": "relationship",     "input_type": "Drop Down List",     "disabled": false,     "onSelected": "Spouse show spousedob   Parent show parentdob   Child show childdob",     "label": "* Relationship", </pre>
--	--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre> "mandatory": true }, {   "min": -1,   "answer": [     {       "answer": "Male",       "destination": "",       "action": ""     },     {       "answer": "Female",       "destination": "",       "action": ""     }   ],   "max": -1,   "format": "",   "name": "familygender",   "input_type": "Radio Button",   "disabled": false,   "onSelected": "",   "label": "* Gender",   "mandatory": true }, {   "min": -1,   "max": -1,   "format": "dd-MM-yyyy",   "name": "spousedob",   "input_type": "Date",   "disabled": false,   "onSelected": "show price registrationtype",   "label": "* Date Of Birth (DD-MM-YYYY)",   "mandatory": true,   "info": "To be eligible as a Spouse Member, he/she has to be aged 16 and above" }, {   "min": -1,   "max": -1,   "format": "dd-MM-yyyy",   "name": "parentdob",   "input_type": "Date",   "disabled": false,   "onSelected": "show price registrationtype",   "label": "* Date Of Birth (DD-MM-YYYY)",   "mandatory": true,   "info": "To be eligible as a Parent Member, he/she has to be aged 32 and above" } </pre>
--	--	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre> }, {   "min": -1,   "max": -1,   "format": "dd-MM-yyyy",   "name": "familydob",   "input_type": "Date",   "disabled": false,   "onSelected": "show price registrationtype   show sameasemail if age low than 14",   "label": "* Date Of Birth (DD-MM-YYYY)",   "mandatory": true,   "info": "To be eligible as a Child Member, he/she has to be aged between 0 and 19 years." }, {   "min": -1,   "max": -1,   "format": "",   "name": "familyregistrationtype",   "input_type": "Drop Down List",   "disabled": false,   "onSelected": "",   "label": "* Membership Registration Type",   "mandatory": true }, {   "min": -1,   "max": -1,   "format": "",   "name": "sameasemail",   "input_type": "Checkbox",   "disabled": false,   "onSelected": "disable familyemail   show email in familyemail",   "label": "Email same as Main Member",   "mandatory": false,   "info": "Email entered may be the same as Main Member only for child below 14 years old" }, {   "min": -1,   "max": -1,   "format": "a@a.a",   "name": "familyemail",   "input_type": "Text Field",   "disabled": false,   "onSelected": "check dup if not same as mainmember",   "label": "* Family Member Email",   "mandatory": true </pre>
--	--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre>     },     {       "min": -1,       "max": -1,       "format": "00000000",       "name": "familymobile",       "input_type": "Text Field",       "disabled": false,       "onSelected": "verify mobile, send otp, show otp, opt mandatory",       "label": "* Hand Phone",       "mandatory": false     },     {       "min": -1,       "max": -1,       "format": "000000",       "name": "otp",       "input_type": "Text Field",       "disabled": false,       "onSelected": "verify mobile, send otp",       "label": "* Hand Phone OTP",       "mandatory": true     },     {       "min": -1,       "max": -1,       "format": "",       "name": "sameasaddress",       "input_type": "Checkbox",       "disabled": false,       "onSelected": "show main member address and disable familypostalcode, familystreetname, familyblock, familyunit",       "label": "Address Same as Main Member",       "mandatory": false,       "info": ""     },     {       "min": -1,       "max": -1,       "format": "000000",       "name": "familypostalcode",       "input_type": "Text Field",       "disabled": false,       "onSelected": "show streetname, block, unit dropdownlist",       "label": "* Postal Code",       "mandatory": true     },     {       "min": -1, </pre>
--	--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre> "max": -1, "format": "", "name": "familystreetname", "input_type": "Text Field", "disabled": true, "onSelected": "", "label": "* Street Name", "mandatory": true }, {   "min": -1,   "max": -1,   "format": "",   "name": "familyblock",   "input_type": "Text Field",   "disabled": true,   "onSelected": "",   "label": "* House No. / Block",   "mandatory": true }, {   "min": -1,   "max": -1,   "format": "#xx-xxx",   "name": "familyunit",   "input_type": "Drop Down List",   "disabled": false,   "onSelected": "",   "label": "* Floor - Unit No.",   "mandatory": true }, {   "min": -1,   "answer": [     {       "answer": "Yes",       "destination": "",       "action": ""     },     {       "answer": "No",       "destination": "",       "action": ""     }   ],   "max": -1,   "format": "",   "name": "familymessage",   "input_type": "Radio Button",   "disabled": false, </pre>
--	--	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre> "onSelected": "", "label": "* Receive promotional messages to your hand phone?", "mandatory": true }, { "min": -1, "answer": [ { "answer": "Yes", "destination": "", "action": "" }, { "answer": "No", "destination": "", "action": "" } ], "max": -1, "format": "", "name": "familypostalemail", "input_type": "Radio Button", "disabled": false, "onSelected": "", "label": "* Receive promotional postal mail?", "mandatory": true }, { "min": -1, "answer": [ { "answer": "Yes", "destination": "", "action": "" }, { "answer": "No", "destination": "", "action": "" } ], "max": -1, "format": "", "name": "familypromoemail", "input_type": "Radio button", "disabled": false, "onSelected": "", "label": "* Receive promotional email?", "mandatory": true </pre>
--	--	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre>         }       ],       "declarations": "dec"     }   ],   "result_code": "0000" } </pre> <p>Note:</p> <p><b>check nric</b> is call checknric api to check dup</p> <p><b>show available price in registrationtype</b> is get the price list from getprice api depend on dob</p> <p><b>check dup, show confirm email</b> is call checkemail api to check dup and show confirm email field</p> <p><b>check same as email</b> is to check the confirm email same as email</p> <p><b>verify mobile, send otp, show otp</b> is to call checkmobileapi to check dup and verify otp</p> <p><b>show streetname, block, unit dropdownlist</b> is to get address from vendor and show in three field</p> <p><b>Spouse show spousedob   Parent show parentdob   Child show childdob</b> is when user choose spouse show spousedob, if user choose parent show parent dob, if user choose child show childdob</p> <p><b>show price registrationtype</b> is to show the price list depend on age</p> <p><b>show price registrationtype   show sameasemail if age low than 14</b> is to show the price list depend on age and show the sameasemail checkbox</p> <p><b>disable familyemail   show email in familyemail</b> is mark familyemail disabled and show the member email at the familyemail field</p> <p><b>check dup if not same as mainmember</b> is if user didnt tick sameasemail then call checkemail api to check email</p> <p><b>show main member address and disable familypostalcode, familystreetname, familyblock, familyunit</b> is if user tick, mark all 4 field to disabled, and copy main member addres to those field</p> <p><b>show streetname, block, unit dropdownlist</b> is to get address from vendor and show in three field</p> <p><b>Submit family detail to tplay API</b> to ask user is existing tplay member, If yes call api and get message at no.36 <b>checktplay</b></p>
--	--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }



## 32. Sign Up Member API

### 32.1 Overview

The api is to sign up the member and its family member

### 32.2 Specification

HTTP Request	https://{domain_name}/v1/signupmember		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	(string)	<pre>{   "nric": "G3820000A",   "name": "Ah Beng",   "gender": "0",   "dob": "15-08-1991",   "email": "ahbeng@ahbeng.com",   "mobile": "88889999",   "postal": "600123",   "street": "jurong east street 32",   "block": "602",   "unit": "01-111",   "type": "Associate Membership - 5 Year (New Registration - PCWF)",   "message": "0",   "postalmail": "0",   "promoemail": "0",   "megazine": "0",   "password": "qwerty",   "family": [     {       "familynric": "F1234567W",       "familygender": "1",       "familydob": "17-06-1996",       "familymobile": "98765432",       "familytype": "Family Membership - 5 Year for Child Aged Below 5 (New Registration)",       "familyemail": "ahseng@ahseng.com",       "familyrelationship": "Spouse",</pre>

			<pre> "familyblock": "602", "familyunit": "01-111", "familystreet": "jurong east street 32", "familypostal": "600123", "familyname": "Ah Seng", "message": "0", "postalmail": "0", "promoemail": "0", "tplay": "" }, { "familynric": "F7654321W", "familygender": "0", "familydob": "17-06-2001", "familymobile": "", "familytype": "Family Membership - 5 Year for Child Aged Below 5 (New Registration)", "familyemail": "ahgiao@ahgiao.com", "familyrelationship": "Child", "familyblock": "602", "familyunit": "01-111", "familystreet": "jurong east street 32", "familypostal": "600123", "familyname": "Ah Giao", "message": "0", "postalmail": "0", "promoemail": "0", "tplay": "" } ] } </pre> <p>Note:</p> <p>Dob format is dd-MM-yyyy  Gender 1 = Male 2 = Female  Nric format = X00000X  Mobile format = 00000000  Email format = X@x.x  Postal code format = 000000  Type is registration type get from price api</p> <p>Tplay is do when user add family to list, then ask user is exiting tplaymember, if yes then add his mobile to tplay mobile.</p>
	<b>Status</b>	<b>Sample Response</b>	

Response	200 (Successful response)	<pre>{   "result_code": "0000",   "result": {     "status": "Success",     "payableprice": 100,     "id": 12019   } }</pre> <p>Note: the <b>id</b> is temp member id for this member The payable is the price counted in backend and based on selection. <b>Price</b> = (mainmember price - promotion) + (family - promotion) + (family2 - promotion) + ...</p>
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid NRIC Format" }</pre>
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid Gender" }</pre>
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid dob Format" }</pre>
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid email Format" }</pre>
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid mobile Format" }</pre>
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid postal Format" }</pre>
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid street" }</pre>

	200 (Format Error)	{ "result_code" : "1000", "msg" : "Invalid block" }
	200 (Format Error)	{ "result_code" : "1000", "msg" : "Invalid unit" }
	200 (Format Error)	{ "result_code" : "1000", "msg" : "Registration type not found" }
	200 (Format Error)	{ "result_code" : "1000", "msg" : "Invalid message" }
	200 (Format Error)	{ "result_code" : "1000", "msg" : "Invalid postalemail" }
	200 (Format Error)	{ "result_code" : "1000", "msg" : "Invalid promoemail" }
	200 (Format Error)	{ "result_code" : "1000", "msg" : "Invalid megazine" }
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	401	{

	(Unauthorized request)	"error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 33. Add member API

### 33.1 Overview

This API is to add member

### 33.2 Specification

HTTP Request	https://{domain_name}/v1/addmember		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	(string)	<pre>{   "memberID":"73908130-48B4-4F9C-92CE-51A73ACF47AA",   "price":"60",   "enetsref":"20210818051422345",   "familyList": [{     "type":"family",     "sameemail":"1",     "sameaddress":"1",     "name":"GONE",     "nric":"G1122333G",     "gender":"1",     "relationship":"Child",     "email":"",     "dob":"15-08-2008",     "phone":"88998080",     "productNumber":"HTMRT000024",     "block":"",     "unit":"",     "street":"",     "postal":"",     "commmsg":"0",     "commpostal":"0",     "commemail":"0",     "tplay":"",     "username":"gone",     "password":"gone"   }], }</pre>

			<pre> "type":"social", "sameemail":"0", "sameaddress":"0", "name":"GTWO", "nric":"G3334455G", "gender":"1", "relationship":"", "email":"ncw1121@hotmail.com", "dob":"15-08-2008", "phone":"88998080", "productNumber":"HTMRT000086", "block":"315", "unit":"08-123", "street":"jurong east street 32", "postal":"600315", "commmsg":"0", "commpostal":"0", "commemail":"0", "tplay":"", "username":"gtwo", "password":"gtwo" }} } </pre> <p>Note:</p> <p>Price = social - promotion + family - promotion</p> <p>Enetsref : 17 digit</p> <p>Type: family/social</p> <p>Sameemail : 0 or 1 (1 only for child under 14)</p> <p>Sameaddress: 0 or 1 (1 only for child under 14)</p> <p>Nric : X0000000X</p> <p>Gender 0 = male 1 = female</p> <p>Relationship : Spouse/Parent/Child (social no relationship)</p> <p>Dob : dd-MM-yyyy</p> <p>ProductNumber: productNumber from registration type list</p> <p>Email : if same email is 1, email can be empty</p> <p>If same email is 0, email is mandatory</p> <p>block/unit/street/postal : if same address is 1, all field can be empty, if same address is 0, all field is mandatory</p> <p>Commmsg 0 or 1</p> <p>Commpostal 0 or 1</p> <p>Commemail 0 or 1</p> <p>Tplay is do when user add family to list, then ask user is exiting tplaymember, if yes then add his mobile to tplay mobile.</p>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200		

	(Successful response)	{ "result_code": "0000", "result": { "invoiceId": "6F885372-F085-4A12-80FB-7BB1AFEB558C", "status": "Success", "registrationId": [ "108", "109" ] } }
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	200 (Member ID empty)	{ "result_code": "1001", "msg": "Invalid memberID" }
	200 (Member ID not found)	{ "result_code": "1001", "msg": "Main member not found" }
	200 (Enetsref format error)	{ "result_code": "1001", "msg": "Invalid enetsref format" }
	200	{ "result_code": "1001", "msg": "Invalid type" }
	200	{ "result_code": "1001", "msg": "Invalid sameemail" }



	200	{ "result_code": "1001", "msg": "Invalid sameaddress" }
	200	{ "result_code": "1001", "msg": "Invalid NRIC format" }
	200	{ "result_code": "1001", "msg": "Invalid Gender" }
	200	{ "result_code": "1001", "msg": "Invalid Relationship" }
	200	{ "result_code": "1001", "msg": "Invalid email format" }
	200	{ "result_code": "1001", "msg": "Invalid dob format" }
	200	{ "result_code": "1001", "msg": "Invalid mobile format" }
	200	{ "result_code": "1001", "msg": "Membership not found" }
	200	{ "result_code": "1001", "msg": "Invalid block" }
	200	{ "result_code": "1001", "msg": "Invalid unit" }
	200	{

		<pre>"result_code": "1001", "msg": "Invalid street" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid postal format" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid message" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid postalemail" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid promoemail" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Price not match" }</pre>
	401 (Unauthorized request)	<pre>{ "error_code": "000", "msg": "Access Denied" }</pre>
	400 (Bad Request)	<pre>{ "error_code": "001", "msg": "Access Denied" }</pre>

## 34. Get Transaction History API

### 34.1 Overview

Get transaction history by memberid and filters

### 34.2 Specification

HTTP Request	https://{domain_name}/v1/gettransactionhistory		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	memberId	String	xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx
	invoice	String	XXXX00000000 Note: Can be empty
	paymentStatus	String	1 Note: 1 = success 2 = fail 3 = pending_payment 4 = pending_enets Can be empty
	pageno	int	1
	itemperpage	int	10
	datefrom	String	dd-MM-yyyy
	dateto	String	dd-MM-yyyy
Response	Status	Sample Response	
	200 (Successful response)	{ "result_code": "0000", "result": [ { "invoiceId": "A65B7D52-BF0A-4698-B3A6-290FA879492F", "invoiceNo": "NS50-4-250163", } ] }	

		<pre> "invoiceDate": "05-10-2017 11:23:13", "amount": "10.0", "paymentStatus": "Success", "description": "Ordinary Mship - 4 Year (NS50) Renew" }, { "invoiceId": "74557B61-F865-473A-AFA8-4C35891946A1", "merchantRef": "20210116134807711", "invoiceNo": "HTNS00024293", "invoiceDate": "16-01-2021 13:48:07", "amount": "50.0", "paymentStatus": "Success", "description": "XXXXX104G - MBS - Ordinary Membership - 2 Year Renewal" }, { "invoiceId": "F3AFE023-5949-4119-A364-4023A882727C", "invoiceNo": "PINV00253799", "invoiceDate": "02-12-2019 17:57:14", "amount": "0.0", "paymentStatus": "Success", "description": "MBS-(NEW) \$0 WIVES PROMO - 2-YEAR FAMILY MEMBERSHIP" }, { "invoiceId": "50A4C305-B1D8-4983-A9D9-000075051D6E", "invoiceNo": "PINV00278459", "invoiceDate": "23-01-2021 11:18:58", "amount": "14.0", "paymentStatus": "Success", "description": "KT - T-PLAY HTNS FAM MEMBER\nKT - T-PLAY SOCKS" } ] } </pre>
	200 (server error)	<pre> {   "result_code" : "1003",   "msg" : "Server Error" } </pre>
	200 (Database Error)	<pre> {   "result_code" : "1004",   "msg" : "Database Error - Unable to find this record." } </pre>
	200 (Parameter empty)	<pre> {   "result_code": "1005",   "msg": "Missing required parameter data" } </pre>

		}
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 35. Pay Membership Sign Up API

### 35.1 Overview

To make payment for membership sign up

### 35.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/paymembershipsignup		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	registrationId	int	Get from 32. Sign Up Member API
	onlinePaymentReference	String	20210804160517548
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	{ "result_code": "0000", "result": { "memberID": "667FE45C-6A03-477A-A2D8-DFAD2C97305D", "status": "Success" } }	
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }	
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error - Unable to find this record." }	
	200 (Parameter	{ "result_code": "1005",	

	empty)	"msg": "Missing required parameter data" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 36. Replacement Card API

### 36.1 Overview

To allow member to make card replacement

### 36.2 Specification

HTTP Request	https://{domain_name}/v1/replacementcard		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	(string)	<pre>{   "type": "1",   "name": "LEO",   "nric": "G3825469W",   "email": "leo.nam@techstudio.com.sg",   "mobile": "86840926",   "postal": "600315",   "street": "jurong east street 32",   "block": "315",   "unit": "01-123",   "can": "1029384756473829",   "est": "120",   "recoveryOption": "1",   "accountName": "aaa",   "accountNumber": "098765",   "bank": "POSB",   "ezlinkNumber": "0987654321234567",   "memberId": "D7ED92BE-B2E8-4A1A-B52B-FFFFE0B306F8",   "membership": "Associate Membership" }</pre> <p>Note: Type 0 = lost card (Physical) Type 1 = lost card (E-card) Type 2 = faulty card</p> <p>Can number can be empty</p>



			<p>Estimate cost can be empty  Recovery Option 0 = no option  Recovery Option 1 = Transfer to Bank Account  Recovery Option 2 = Transfer to another (Adult) EZ-Link Card</p> <p>Option 1  AccountName, accountNumber, bank is mandatory</p> <p>Option 2  EzlinkNumber is mandatory</p> <p>Bank - DBS/POSB</p>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": "Success",   "result_code": "0000" }</pre>	
	200 (server error)	<pre>{   "result_code": "1003",   "msg": "Server Error" }</pre>	
	200 (Database Error)	<pre>{   "result_code": "1004",   "msg": "Database Error - Unable to find this record." }</pre>	
	200 (Parameter empty)	<pre>{   "result_code": "1005",   "msg": "Missing required parameter data" }</pre>	
	401 (Unauthorized request)	<pre>{   "error_code": "000",   "msg": "Access Denied" }</pre>	
	400 (Bad Request)	<pre>{   "error_code": "001",   "msg": "Access Denied" }</pre>	

## 37. Check NRIC Eligible for Renew API

### 37.1 Overview

Check the nric eligible and get product list for renew.

### 37.2 Specification

HTTP Request	https://{domain_name}/v1/checkrenewnric		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	nric	(string)	A1234567B
Response	Status	Sample Response	
	200 (Successful response)	<pre>{   "result_code": "0000",   "result": {     "name": "LEO",     "membershipType": "Associate Membership",     "registrationType": "Associate Membership - 10 Year (New Registration)",     "expiryDate": "31-08-2031 ",     "productList": [       {         "productnumber": "HTMRT000008",         "productprice": 50,         "productname": "MBS - Associate Membership - 2 Year Renewal"       },       {         "productnumber": "TEST111111",         "productprice": 40,         "productname": "MBS - Testing Facility Membership Product"       },       {         "productnumber": "HTMRT000010",         "productprice": 100,         "productname": "MBS - Associate Membership - 5 Year</pre>	

		<pre> Renewal"     },     {         "productnumber": "HTMRT000006",         "productprice": 150,         "productname": "MBS - Associate Membership - 10 Year Renewal"     } ] } } </pre>
	200 (server error)	<pre> {   "result_code" : "1003",   "msg" : "Server Error" } </pre>
	200 (Database Error)	<pre> {   "result_code" : "1004",   "msg" : "Database Error - Unable to find this record." } </pre>
	200 (Parameter empty)	<pre> {   "result_code": "1005",   "msg": "Missing required parameter data" } </pre>
	401 (Unauthorized request)	<pre> {   "error_code": "000",   "msg": "Access Denied" } </pre>
	400 (Bad Request)	<pre> {   "error_code": "001",   "msg": "Access Denied" } </pre>

## 38. Check Promotion for Renew API

### 38.1 Overview

Check the promotion and get the price for renewal.

### 38.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/checkrenewpromotion		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	Raw (application/json)	(string)	<pre>{   "productNumber":"HTMRT000006",   "nric":"G3825469W",   "newExpiryDate":"31-08-2031",    "memberlist":[{"nric":"G1111111G"}, {"nric":"A1111111A"}] }</pre> <p>Note: productNumber get from api #37 newExpiryDate get from api #37</p> <p>Memberlist is all member nric from multiple renew</p>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result_code": "0000",   "result": {     "itemPrice": "140.19",     "gstPrice": "9.81",     "totalPrice": "150.00",     "newExpiryDateStr": "31-08-2041 ",     "allow": true,     "promotionId": 0,     "message": ""   } }</pre>	

		<pre> "isTPlayAvailable": false, "tplayNric": "", "tplayMobile": "", "tplayDob": "", "tplayRegType": "" } } </pre> <p>Note:</p> <p>Allow is means the member is available to renew  Message is to show the message to user when check eligible</p>
	200 (server error)	<pre> {   "result_code": "1003",   "msg": "Server Error" } </pre>
	200 (Database Error)	<pre> {   "result_code": "1004",   "msg": "Database Error - Unable to find this record." } </pre>
	200 (Parameter empty)	<pre> {   "result_code": "1005",   "msg": "Missing required parameter data" } </pre>
	401 (Unauthorized request)	<pre> {   "error_code": "000",   "msg": "Access Denied" } </pre>
	400 (Bad Request)	<pre> {   "error_code": "001",   "msg": "Access Denied" } </pre>

## 39. Renew Membership API

### 39.1 Overview

This API is to process user renewal.

### 39.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/renew		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	Raw (application/json)	(string)	<pre>{   "memberID":"73908130-48B4-4F9C-92CE-51A73ACF47AA",   "price":"150",   "enetsref":"20210820163701567",   "renewlist":[{"     "nric":"G3825469W",     "productnumber":"HTMRT000006",     "productprice":150,     "promocode":"",     "promotionId":0,     "tplay":""   }] }</pre> <p>Note: memberID is current login memberid productprice get from api #38 Enetsref format = 17 digit productnumber get from api #37 Promocode is future use, leave empty promotionId get from api #38 Tplay get from api #38 when isTplay = true</p>
	<b>Status</b>	<b>Sample Response</b>	

<b>Response</b>	200 (Successful response)	{ "result": "Success", "result_code": "0000" }
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error - Unable to find this record." }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 40. Add Transaction API (CRM)

### 40.1 Overview

This API is to add villa/facility transactions to the transaction list.

### 40.2 Specification

HTTP Request	https://{domain_name}/v1/addtransactioncrm		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	(string)	<pre>{   "memberID":"73908130-48B4-4F9C-92CE-51A73ACF47AA",   "price":"150",   "enetsref":"20210820163701567",   "prefixType":"villa",   "productlist":   [     {       "productname":"Product 1",       "productprice":20.00     },     {       "productname":"Product 2",       "productprice":40.00     }   ] }</pre> <p>Note: Enetsref format : 17 digits prefixType : villa/facility</p>



	Status	Sample Response
Response	200 (Successful response)	{ "result": "Add transaction successfully with price : 655.0", "result_code": "0000" }
	200 (Successful response)	{ "msg": "Invalid memberID", "result_code": "1000" }
	200 (Successful response)	{ "msg": "Main member not found", "result_code": "1000" }
	200 (Successful response)	{ "msg": "Invalid enetsref format", "result_code": "1000" }
	200 (Successful response)	{ "msg": "Invalid prefix Type", "result_code": "1000" }
	200 (Successful response)	{ "msg": "Product not found : 1819/08- 013", "result_code": "1000" }
	200 (Successful response)	{ "msg": "Price not match", "result_code": "1000" }
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error - Unable to find this record." }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }

	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 41. Check Username Unique API (CRM)

### 41.1 Overview

This API is to allow the user to check the unique for username.

### 41.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/checkusernameunique		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	username	(string)	testusername  Note: Not allowed for full digit username
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	{ "result": "true", "result_code": "0000" }	
	200 (Successful response)	{ "msg": "Invalid username format", "result_code": "1000" }	
	200 (server error)	{ "result_code": "1003", "msg": "Server Error" }	
	200 (Parameter empty)	{ "error_code": "003", "error": "Bad Request - Parameter Missing" }	
	401 (Unauthorized)	{ "error_code": "000", "error": "Unauthorized" }	

	request)	"msg":"Access Denied" }
	400 (Bad Request)	{ "error_code":"001", "msg":"Access Denied" }

## 42. Membership Validation API (CRM)

### 42.1 Overview

This API is to check the membership validation

### 42.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/membershipvalidation		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	Raw (application/json)	(string)	<pre>{   "user_info":{     "postal":"423687",     "mobile":"888888888",     "email":"email@email.com",     "dob":"2010-02-03",     "nricLast4":"111G"   } }</pre> <p>Note: All 4 field is mandatory Only check db for main member and family member Postal format : ##### Mobile format : ##### Email format : EE@EE.EE Dob format : yyyy-MM-dd nricLast4 : ###E</p>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": [     {       "type": "mainmember",       "memberId": "59482358-0EFD-46C0-A0F0-F229C36F4B66"     }   ],   "result_code": "0000" }</pre>	

	200 (Successful response)	{ "msg": "Member not found", "result_code": "1000" }
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 43. Update Username Password API (CRM)

### 43.1 Overview

This API is to update the username and password

### 43.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/updateusernamepassword		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	Raw (application/json)	(string)	<pre>{   "user_info":{     "username":"",     "password":"1",      "memberId":"E5D13F09-7D16-4E04-9289-AC2CADBA4F11"   } }</pre> <p>Note: Username and password can be empty. memberId can be guestid, main member id, family id and affiliate id</p>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": "success",   "result_code": "0000" }</pre>	
	200 (Successful response)	<pre>{   "msg": "Main member not found",   "result_code": "1000" }</pre>	

	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }



## 44. Retrieve Username API (CRM)

### 44.1 Overview

This API is to retrieve username by given info.

### 44.2 Specification

HTTP Request	https://{domain_name}/v1/retrieveusername		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	(string)	<pre>{   "user_info":{     "postal":"","     "mobile":"86840926",     "email":"leo.nam@techstudio.com.sg",     "dob":"1991-08-15",     "nricLast4":"469I"   } }</pre> <p>Note: Dob format : yyyy-MM-dd</p>
Response	Status	Sample Response	
	200 (Successful response)	<pre>{   "result": [     {       "username": "leo12345"     }   ],   "result_code": "0000" }</pre>	
	200 (Successful response)	<pre>{   "msg": "Member not found",   "result_code": "1000" }</pre>	

	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 45. Get Member By Type API (CRM)

### 45.1 Overview

This API is to get all memberid list by type

### 45.2 Specification

HTTP Request	https://{domain_name}/v1/getmemberidbytype		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	type	(string)	Family Membership / Associate Membership
	pageno	int	1
	itemperpage	int	5
Response	Status	Sample Response	
	200 (Successful response)	{ "result": [ "D192AB11-BBF9-4ECE-A6E5-0FB3BA8DC49E", "C910B385-AF2B-4DF3-B7DC-1014FA2E2B23", "B93DC802-7F1E-4941-B604-11218F000599", "11DB51E1-2857-4E41-B9E6-11702C28871A", "AE6CE3F9-9881-4C74-A45C-1210FCE143D9" ], "total": 1481, "result_code": "0000" }	
	200 (server error)	{ "result_code": "1003", "msg": "Server Error" }	
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }	

	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 46. Get Member By Expiry Duration API (CRM)

### 46.1 Overview

This API is to get all Member id by expiry duration

### 46.2 Specification

HTTP Request	https://{domain_name}/v1/getmemberidbyexpiryduration		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	type	(string)	Family Membership / Associate Membership
	pageno	int	1
	itemperpage	int	5
	frommonth	int	12
	tomonth	int	24
Response	Status	Sample Response	
	200 (Successful response)	{ "result": [ "D192AB11-BBF9-4ECE-A6E5-0FB3BA8DC49E", "C910B385-AF2B-4DF3-B7DC-1014FA2E2B23", "B93DC802-7F1E-4941-B604-11218F000599", "11DB51E1-2857-4E41-B9E6-11702C28871A", "AE6CE3F9-9881-4C74-A45C-1210FCE143D9" ], "total": 1481, "result_code": "0000" }	
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }	

	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 47. Add Member Pay (CRM)

### 47.1 Overview

This API is to make added family member as paid

### 47.2 Specification

HTTP Request	https://{domain_name}/v1/addmemberpay		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	(string)	<pre>{   "idList": [     "106",     "107"   ],   "invoice":     "5F8AC86E-4A23-482A-AAE6-C031C6F5D01C",   "enetsref": "83847465737383747" }</pre> <p>Notes: idList get from api no.33 registrationId Invoice get from api no.33 invoiceId</p>
Response	Status	Sample Response	
	200 (Successful response)	<pre>{   "result": "Success",   "result_code": "0000" }</pre>	
	200 (server error)	<pre>{   "result_code" : "1003",   "msg" : "Server Error" }</pre>	
	200 (Parameter	<pre>{   "result_code": "1005",</pre>	

	empty)	"msg": "Missing required parameter data" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }



## 48. Add member check price API

### 48.1 Overview

This API is to check price

### 48.2 Specification

HTTP Request	https://{domain_name}/v1/addmembercheckprice		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	(string)	<pre>{   "memberID":"73908130-48B4-4F9C-92CE-51A73ACF47AA",   "price":"60",   "enetsref":"20210818051422345",   "familyList": [{     "type":"family",     "sameemail":"1",     "sameaddress":"1",     "name":"GONE",     "nric":"G1122333G",     "gender":"1",     "relationship":"Child",     "email":"",     "dob":"15-08-2008",     "phone":"88998080",     "productNumber":"HTMRT000024",     "block":"",     "unit":"",     "street":"",     "postal":"",     "commmsg":"0",     "commpostal":"0",     "commemail":"0",     "tplay":""   }],   {     "type":"social",     "sameemail":"0",</pre>

			<pre> "sameaddress": "0", "name": "GTWO", "nric": "G3334455G", "gender": "1", "relationship": "", "email": "ncw1121@hotmail.com", "dob": "15-08-2008", "phone": "88998080", "productNumber": "HTMRT000086", "block": "315", "unit": "08-123", "street": "jurong east street 32", "postal": "600315", "commmsg": "0", "commpostal": "0", "commemail": "0", "tplay": "" } } </pre> <p>Note:</p> <p>Price = social - promotion + family - promotion  Enetsref : 17 digit  Type: family/social  Sameemail : 0 or 1 (1 only for child under 14)  Sameaddress: 0 or 1 (1 only for child under 14)  Nric : X0000000X  Gender 0 = male 1 = female  Relationship : Spouse/Parent/Child (social no relationship)  Dob : dd-MM-yyyy  ProductNumber: productNumber from registration type list  Email : if same email is 1, email can be empty  If same email is 0, email is mandatory  block/unit/street/postal : if same address is 1, all field can be empty, if same address is 0, all field is mandatory</p> <p>Commmsg 0 or 1  Commpostal 0 or 1  Commemail 0 or 1</p> <p>Tplay is do when user add family to list, then ask user is exiting tplaymember, if yes then add his mobile to tplay mobile.</p>
Response	Status	Sample Response	
	200 (Successful response)	<pre> {   "price": 60,   "result_code": "0000" } </pre>	

	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	200 (Member ID empty)	{ "result_code": "1001", "msg": "Invalid memberID" }
	200 (Member ID not found)	{ "result_code": "1001", "msg": "Main member not found" }
	200 (Enetsref format error)	{ "result_code": "1001", "msg": "Invalid enetsref format" }
	200	{ "result_code": "1001", "msg": "Invalid type" }
	200	{ "result_code": "1001", "msg": "Invalid sameemail" }
	200	{ "result_code": "1001", "msg": "Invalid sameaddress" }
	200	{ "result_code": "1001", "msg": "Invalid NRIC format" }
	200	{

		<pre>"result_code": "1001", "msg": "Invalid Gender" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid Relationship" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid email format" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid dob format" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid mobile format" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Membership not found" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid block" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid unit" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid street" }</pre>
	200	<pre>{ "result_code": "1001", "msg": "Invalid postal format" }</pre>
	200	<pre>{ "result_code": "1001", </pre>

		<pre>"msg": "Invalid message" }</pre>
	200	<pre>{   "result_code": "1001",   "msg": "Invalid postalemail" }</pre>
	200	<pre>{   "result_code": "1001",   "msg": "Invalid promoemail" }</pre>
	200	<pre>{   "result_code": "1001",   "msg": "Price not match" }</pre>
	401 (Unauthorized request)	<pre>{   "error_code": "000",   "msg": "Access Denied" }</pre>
	400 (Bad Request)	<pre>{   "error_code": "001",   "msg": "Access Denied" }</pre>

## 49. Get Member ID By Username And DOB API

### 49.1 Overview

This API is to get the memberid by username and dob

### 49.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/get_memberid_by_username_dob		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	Raw (application/json)	(string)	<pre>{   "user_info":{     "username":"main",     "dob":"15-08-1991"   } }</pre>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result_code": "0000",   "result": [     {       "id": "59482358-0EFD-46C0-A0F0-F229C36F4B66",       "type": "main"     },     {       "id": "59482358-0EFD-46C0-A0F0-F229C36F4B66",       "type": "family"     }   ] }</pre> <p>Type = main, family, affiliate, guest</p>	
	200 (server error)	<pre>{   "result_code" : "1003",   "msg" : "Server Error" }</pre>	

	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }
	200 (Member ID empty)	{ "result_code": "1001", "msg": "Invalid memberID" }
	200	{ "result_code": "1001", "msg": "Invalid dob format" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 50. Mark Email Verified API

### 50.1 Overview

This API is to mark the email to verified

### 50.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/mark_email_verified		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	Raw (application/json)	(string)	{ "user_info":{ "memberID":"57C32653-D84D-47E5-AC63-89271ACD4061" } }
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	{ "result": "Email Verified", "result_code": "0000" }	
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }	
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }	
	200 (Parameter empty)	{ "result_code": "1005", "msg": "Missing required parameter data" }	
	200	{	



	(Member ID empty)	"result_code": "1001", "msg": "Invalid memberID" }
	200	{ "result_code": "1001", "msg": "Invalid dob format" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }

## 51. Sign Up Member Check Price API

### 51.1 Overview

The api is to check the price when sign up member

### 51.2 Specification

HTTP Request	https://{domain_name}/v1/signupmembercheckprice		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	(string)	<pre>{   "nric": "G3820000A",   "name": "Ah Beng",   "gender": "0",   "dob": "15-08-1991",   "email": "ahbeng@ahbeng.com",   "mobile": "88889999",   "postal": "600123",   "street": "jurong east street 32",   "block": "602",   "unit": "01-111",   "type": "Associate Membership - 5 Year (New Registration - PCWF)",   "message": "0",   "postalmail": "0",   "promoemail": "0",   "megazine": "0",   "password": "qwerty",   "username": "ahbeng",   "family": [     {       "familynric": "F1234567W",       "familygender": "1",       "familydob": "17-06-1996",       "familymobile": "98765432",       "familytype": "Family Membership - 5 Year for Child Aged Below 5 (New Registration)",       "familyemail": "ahseng@ahseng.com",</pre>

			<pre> "familyrelationship":"Spouse", "familyblock":"602", "familyunit":"01-111", "familystreet":"jurong east street 32", "familypostal":"600123", "familyname":"Ah Seng", "message":"0", "postalmail":"0", "promoemail":"0", "tplay":"", "username":"ahgiao", "password":"ahgiao" }, { "familynric":"F7654321W", "familygender":"0", "familydob":"17-06-2001", "familymobile":"", "familytype":"Family Membership - 5 Year for Child Aged Below 5 (New Registration)", "familyemail":"ahgiao@ahgiao.com", "familyrelationship":"Child", "familyblock":"602", "familyunit":"01-111", "familystreet":"jurong east street 32", "familypostal":"600123", "familyname":"Ah Giao", "message":"0", "postalmail":"0", "promoemail":"0", "tplay":"", "username":"ahseng", "password":"ahseng" } ] } </pre> <p>Note:  Dob format is dd-MM-yyyy  Gender 1 = Male 2 = Female  Nric format = X00000X  Mobile format = 00000000  Email format = X@x.x  Postal code format = 000000  Type is registration type get from price api  Tplay is do when user add family to list, then</p>
--	--	--	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

			ask user is exiting tplaymember, if yes then add his mobile to tplay mobile.
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result_code": "0000",   "result": {     "status": "Success",     "payableprice": 100,     "id": 0   } }</pre>	
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid NRIC Format" }</pre>	
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid Gender" }</pre>	
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid dob Format" }</pre>	
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid email Format" }</pre>	
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid mobile Format" }</pre>	
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid postal Format" }</pre>	
	200 (Format Error)	<pre>{   "result_code" : "1000",   "msg" : "Invalid street" }</pre>	
	200	{	

	(Format Error)	<pre> “result_code” : “1000”, “msg” : “Invalid block” } </pre>
	200 (Format Error)	<pre> {   “result_code” : “1000”,   “msg” : “Invalid unit” } </pre>
	200 (Format Error)	<pre> {   “result_code” : “1000”,   “msg” : “Registration type not found” } </pre>
	200 (Format Error)	<pre> {   “result_code” : “1000”,   “msg” : “Invalid message” } </pre>
	200 (Format Error)	<pre> {   “result_code” : “1000”,   “msg” : “Invalid postalemail” } </pre>
	200 (Format Error)	<pre> {   “result_code” : “1000”,   “msg” : “Invalid promoemail” } </pre>
	200 (Format Error)	<pre> {   “result_code” : “1000”,   “msg” : “Invalid megazine” } </pre>
	200 (server error)	<pre> {   “result_code” : “1003”,   “msg” : “Server Error” } </pre>
	200 (Database Error)	<pre> {   “result_code” : “1004”,   “msg” : “Database Error” } </pre>
	200 (Parameter empty)	<pre> {   "result_code": "1005",   "msg": "Missing required parameter data" } </pre>
	401 (Unauthorized)	<pre> {   "error_code": "000", </pre>

	request)	"msg":"Access Denied" }
	400 (Bad Request)	{ "error_code":"001", "msg":"Access Denied" }

## 52. Get Member ID By Mobile And DOB API

### 52.1 Overview

This API is to get the memberid by mobile and dob

### 52.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/get_memberid_by_mobile_dob		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	Raw (application/json)	(string)	<pre>{   "user_info":{     "mobile":"9178710273",     "dob":"29-06-2005",     "type":"guest"   } }</pre>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result_code": "0000",   "result": {     "id": "F84F90D3-DDFA-48E5-84F2-29EA34079B18",     "type": "guest"   } }</pre> <p>Type = main, family, affiliate, guest</p>	
	200 (server error)	<pre>{   "result_code" : "1003",   "msg" : "Server Error" }</pre>	
	200 (Database Error)	<pre>{   "result_code" : "1004",   "msg" : "Database Error" }</pre>	
	200	{	

	(Parameter empty)	"result_code": "1005", "msg": "Missing required parameter data" }
	200 (Member ID empty)	{ "result_code": "1001", "msg": "Invalid memberID" }
	200	{ "result_code": "1001", "msg": "Invalid dob format" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }





# API Reference - Event

## 1. Get Event List API

### 1.1 Overview

This API is to get event list from database

### 1.2 Specification

HTTP Request	https://{domain_name}/v1/eventlist		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	pageno	Int	2
	itemperpage	int	10
	eventName	String	badminton  Notes: Event Name Sample: REAL® Run 2021 - Partners BB Courses - Taekwond HJC Courses - Yoga [2021] REAL® Run 2021
	eventStartDate	String	dd-MM-yyyy
	eventEndDate	String	dd-MM-yyyy
	updatedBy	int	1 (Default = 0)
	approveBy	int	24 (Default = 0)

	createdBy	int	26 (Default = 0)
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": [     {       "eventEndDate": "2021-12-31 00:00:00.0",       "registrationStartDate": "2018-08-21 00:00:00.0",       "registrationEndDate": "2021-12-31 00:00:00.0",       "name": "BB Courses - Zumba - Wednesday ",       "id": 38,       "eventStartDate": "2021-12-31 00:00:00.0"     },     {       "eventEndDate": "2022-02-01 00:00:00.0",       "registrationStartDate": "2021-01-31 00:00:00.0",       "registrationEndDate": "2022-01-01 00:00:00.0",       "name": "HJC Courses - Judo [2021] ",       "id": 308,       "eventStartDate": "2022-02-01 00:00:00.0"     }   ],   "result_code": "0000",   "totalrecords": "28" }</pre>	
	200 (Empty Result)	<pre>{   "result": [],   "result_code": "0000",   "totalrecords": "0" }</pre>	
	200 (server error)	<pre>{   "result_code": "1003",   "msg": "Server Error" }</pre>	
	200 (Database Error)	<pre>{   "result_code": "1004",   "msg": "Database Error" }</pre>	
	401 (Unauthorized request)	<pre>{   "error_code": "000",   "msg": "Access Denied" }</pre>	
	400 (Bad Request)	<pre>{   "error_code": "001", }</pre>	

		<pre>"msg": "Access Denied" }</pre>
	400 (Parameter type not match)	<pre>{   "error_code": "002",   "error": "Bad Request - Parameter type not match" }</pre>
	400 (Parameter missing)	<pre>{   "error_code": "003",   "msg": "Bad Request - Parameter Missing" }</pre>

## 2. Get Event Detail API

### 2.1 Overview

This API is to get event detail by event id from database

### 2.2 Specification

HTTP Request	https://{domain_name}/v1/eventdetail		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	eventId	Int	2
Response	Status	Sample Response	
	200 (Successful response)	<pre>{   "result": [     {       "eventEndDate": "2019-10-20 00:00:00.0",       "eventId": 200,       "registrationStartDate": "2019-10-10 00:00:00.0",       "termsConditions": "tnc",       "banner": "Terroween_ The Final Call_E-portal_ebb573e2-172a-47bd-a784-76f13dc0e0ea.png",       "maxCapacity": 50,       "maxPax": 2,       "eligibleMembershipList": [         {           "price": 8,           "membershipName": "Associate Membership"         },         {           "price": 8,           "membershipName": "Ordinary Membership"         },         {           "price": 8,           "membershipName": "Family Membership"         }       ]     }   ] }</pre>	

		<pre>         },         {             "price": 8,             "membershipName": "Social Membership"         },         {             "price": 8,             "membershipName": "Non-Member"         }     ],     "allowCategory": "1",     "registrationEndDate": "2019-10-19 00:00:00.0",     "eventStatus": "open",     "multipleCategory": [],     "eventName": "#TERROWEEN: The Final Call 20     Oct (Only) [Guest Room Promo - Child]",     "eventStartDate": "2019-10-19 00:00:00.0"     }     ],     "result_code": "0000"     } </pre>
	200 (Empty result)	<pre> {     "msg": "Database Error - Unable to find this record.",     "result_code": "1004" } </pre>
	200 (server error)	<pre> {     "result_code": "1003",     "msg": "Server Error" } </pre>
	200 (Database Error)	<pre> {     "result_code": "1004",     "msg": "Database Error" } </pre>
	401 (Unauthorized request)	<pre> {     "error_code": "000",     "msg": "Access Denied" } </pre>
	400 (Bad Request)	<pre> {     "error_code": "001",     "msg": "Access Denied" } </pre>
	400 (Parameter type not match)	<pre> {     "error_code": "002",     "error": "Bad Request - Parameter type not match" } </pre>

		}
	400 (Parameter missing)	{ "error_code" : "003", "msg" : "Bad Request - Parameter Missing" }

### 3. Event Booking List API

#### 3.1 Overview

This API is to get booking list by event id from database

#### 3.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/eventbookinglist		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	eventId	Int	2
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": [     {       "totalPax": 2,       "totalSession": 0,       "name": "AUDREY CHAU ",       "membershipTypeName": "Family Membership",       "mobile": "86841838",       "category": "-",       "email": "Poohbear7819@yahoo.com.sg"     },     {       "totalPax": 1,       "totalSession": 0,       "name": "CHENG XIN MEI MARIE",       "membershipTypeName": "Associate Membership",       "mobile": "91259303",       "category": "-",       "email": "lonewolf3333333@gmail.com"     }   ],   "result_code": "0000" }</pre>	

	200 (Empty Result)	{ "result": [], "result_code": "0000" }
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code" : "003", "msg" : "Bad Request - Parameter Missing" }



## 4. Get Booking Form API

### 4.1 Overview

This API is to get event detail by event id from database

### 4.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/bookingform		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	eventId	Int	326
	membershipType	String	Associate Membership
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": [     {       "categoryField": {         "item": [           {             "sessionPriceForCategory": 7.5,             "session": {               "min": 1,               "max": 1,               "format": "",               "name": "session",               "input_type": "Number",               "disabled": false,               "onSelected": "",               "label": "** Total Session",               "mandatory": false             },             "sessionChooser": {               "min": -1,               "answer": [                 {</pre>	

		<pre> "answer": "Yes", "destination": "session", "action": "show make mandatory" }, { "answer": "No", "destination": "session", "action": "hide remove mandatory" } ], "max": -1, "format": "", "name": "sessionchooser", "input_type": "Radio Button", "disabled": false, "onSelected": "", "label": "Register BySession", "mandatory": true }, "allowSession": true, "categoryName": "Hatha Yoga - (1 Session ONLY) [Master Ven Class]", "membershipPriceForCategory": -1 }, { "sessionPriceForCategory": -1, "allowSession": false, "categoryName": "Hatha or Vinyasa Yoga [Pauline Class][4 Session]", "membershipPriceForCategory": 35 } ], "name": "category", "input_type": "dropdownlist", "onSelected": "verify membership type", "label": "* Category", "mandatory": true }, "tnc": "tnc", "normalField": [ { "min": -1, "max": -1, "format": "String Capital", "name": "name", "input_type": "Text field", "disabled": false, "onSelected": "", "label": "* Full Name (As per NRIC)", "mandatory": true </pre>
--	--	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre>     },     {       "min": -1,       "max": -1,       "format": "x@x.x",       "name": "email",       "input_type": "Text field",       "disabled": false,       "onSelected": "",       "label": "** Email (receipt will be sent to this email address)",       "mandatory": true     },     {       "min": 1,       "max": 1,       "format": "x@x.x",       "name": "totalpax",       "input_type": "Text field",       "disabled": false,       "onSelected": "",       "label": "Total Pax",       "mandatory": true     },     {       "min": -1,       "max": -1,       "format": "",       "name": "promocode",       "input_type": "Text field",       "disabled": false,       "onSelected": "verify promocode",       "label": "Promo Code",       "mandatory": false     },     {       "min": -1,       "answer": [         {           "answer": ""         }       ],       "max": -1,       "format": "",       "name": "question",       "input_type": "Text field",       "disabled": false,       "onSelected": "",       "label": "Emergency Contact Name &amp; Number", </pre>
--	--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<pre> "mandatory": true }, { "min": -1, "answer": [ { "answer": "Hatha Yoga , Master Ven" }, { "answer": " Hatha Yoga, Pauline" }, { "answer": " Vinyasa Yoga, Pauline" } ], "max": -1, "format": "", "name": "question", "input_type": "Drop down list", "disabled": false, "onSelected": "", "label": "Class", "mandatory": true } ], "membershipPrice": 0, "title": "HJC Courses - Yoga [2021]", "category": true } ], "result_code": "0000" } </pre> <p>Note: Input type: Text field, Checkbox, Drop down list, date, number, Radio Button</p> <p><b>Term and conditions</b> to let registrant read and tick.</p> <p><b>onSelected</b> is make change of other field when selected or take some action.</p> <p><b>Max min</b> is to set maxmin of number field</p> <p><b>Mandatory</b> is to mark field as mandatory</p> <p><b>Format</b> is to format the input such as 00000000</p> <p><b>Category field</b> use when the <b>category</b> is true Each category have its own price The item category field is the dropdownlist item</p>
--	--	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

		<p><b>Session</b> radio button will show when category allow session. When user want to register by session must tick yes at radio button. After tick yes, a number field show to let user choose number of session.</p> <p><b>Price -1</b> for category, and session means that the category/session cannot be register for that membership type.</p>
	200 (Empty result)	{ "msg": "Database Error - Unable to find this record.", "result_code": "1004" }
	200 (Invalid Token)	{ "result_code" : "1001", "msg" : "Invalid Token" }
	200 (Expired Token)	{ "result_code" : "1002", "msg" : "Token Expired" }
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	200 (Parameter missing)	{ "result_code" : "1005", "msg" : "Parameter Missing" }
	401 (Unauthorized request)	{ "result_code": "001", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "002", "error": "Bad Request" }

## **5. Check PromoCode API**

### **5.1 Overview**

This API is to verify the promocode and return the status and price deducted.

## 5.2 Specification

HTTP Request	https://{domain_name}/v1/checkpromocode		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	eventId	Int	20291
	totalPax	Integer	2
	promocode	String	1D4VTGh
	membership	String	CE1188E9-956C-E311-9401-00155D0AB904
Response	Status	Sample Response	
	200 (Successful response)	<pre>{   "result": [     {       "msg": "promo_ended/valid_promocode/fully_redeemed/invalid_promocode",       "price": 0     }   ],   "result_code": "0000" }</pre>	
	200 (server error)	<pre>{   "result_code" : "1003",   "msg" : "Server Error" }</pre>	
	200 (Database Error)	<pre>{   "result_code" : "1004",   "msg" : "Database Error" }</pre>	
	401 (Unauthorized request)	<pre>{   "error_code":"000",   "msg":"Access Denied" }</pre>	

	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code" : "003", "msg" : "Baf Request - Parameter Missing" }

## 6. Check Available Capacity API

### 6.1 Overview

This API is to check the available capacity and return the result.

### 6.2 Specification

<b>HTTP</b>	<a href="https://{domain_name}/v1/checkavailablecapacity">https://{domain_name}/v1/checkavailablecapacity</a>
-------------	---------------------------------------------------------------------------------------------------------------



Request			
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	eventId	Int	20291
	category	String	Hero & Junior Bootcamp! - 9AM
Response	Status	Sample Response	
	200 (Successful response)	{ "result": "Available/Full", "result_code": "0000" }	
	200 (Empty Result)	{ "msg": "Database Error - Unable to find this record.", "result_code": "1004" }	
	200 (server error)	{ "result_code": "1003", "msg": "Server Error" }	
	200 (Database Error)	{ "result_code": "1004", "msg": "Database Error" }	
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }	
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }	
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }	

		}
	400 (Parameter missing)	{ "error_code" : "003", "msg" : "Baf Request - Parameter Missing" }

## 7. Get Booking Status API

### 7.1 Overview

This API is to get the current status of booking by id.

### 7.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/eventbookingstatus		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	registrationId	Int	43159
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	{ "result": "Cancelled", (Active/Cancelled) "result_code": "0000" }	
	200 (Empty Result)	{ "msg": "Database Error - Unable to find this record.", "result_code": "1004" }	
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }	
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }	
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }	

		}
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code": "003", "msg": "Bad Request - Parameter Missing" }

## 8. Cancel Booking API

### 8.1 Overview

This API is to cancel the booking by id

### 8.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/cancelbooking		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	registrationId	Int	43159
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	{ "result": "Success", (Success/Fail) "result_code": "0000" }	
	200 (Empty Result)	{ "msg": "Database Error - Unable to find this record.", "result_code": "1004" }	
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }	
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }	
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }	

		}
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code": "003", "msg": "Bad Request - Parameter Missing" }

## 9. Create Booking API

### 9.1 Overview

This API is to create the booking.

### 9.2 Specification

HTTP Request	https://{domain_name}/v1/createbooking		
Header Parameters	Key	Value	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
Request Body	Key	Value	Example
	Raw (application/json)	eventId int totalpax int category String mobile String membershipExpiryDate String membershipType String membershipStatus String  name String totalsession int promocode String  dob String email String  ans1 String ans2 String ans3 String ans4 String	{ "eventId": 20492, "totalpax":1, "category":"leo", "mobile":"86840926", "membershipExpiryDate":"15-08-2030", "membershipType":"Non-Member", "membershipStatus":"Active", "name":"leo name", "totalsession":"0", "promocode":""," "dob":"15-08-1991",  "email":"ncw1121@hotmail.com", "ans1":"aaa", "ans2":"a", "ans3":""," "ans4":""," "ans5":""," "ans6":""," "ans7":""," "ans8":""," "ans9":""," "ans10":""," "ans11":"","

		ans5 String ans6 String ans7 String ans8 String ans9 String ans10 String ans11 String ans12 String ans13 String ans14 String ans15 String ans16 String ans17 String ans18 String ans19 String ans20 String	<pre> "ans12":""," "ans13":""," "ans14":""," "ans15":""," "ans16":""," "ans17":""," "ans18":""," "ans19":""," "ans20":""," } </pre> <p>Note:  membershipType  membershipStatus  membershipExpiryDate  Is get from crm</p> <p>Category can be empty if event is without category</p> <p>Session can be 0 if no session</p> <p>Ans can be empty is no ans</p> <p>Totalpax must more than 0</p> <p>Promocode can be empty</p> <p>Dob must be string format dd-MM-yyyy</p>
Response	Status	Sample Response	
	200 (Successful response)	<pre> {   "result": "43163",   "result_code": "0000" } </pre> <p>Note:  This result is registrationId to be required in the add transaction API.</p>	
	200 (Add Fail)	<pre> {   "msg": "Unable to save registration",   "result_code": "1000" } </pre>	



	200 (Not allow Multiple register)	{ "msg": "This mobile has been registered.", "result_code": "1000" }
	200 (server error)	{ "result_code" : "1003", "msg" : "Server Error" }
	200 (Database Error)	{ "result_code" : "1004", "msg" : "Database Error" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code" : "003", "msg" : "Baf Request - Parameter Missing" }

## 10. Add Transaction API

### 10.1 Overview

This API is to add transaction.

### 10.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/addtransaction		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	Raw (application/json)	registrationId int payamount String redeemamount String unitprice String totalprice String paymentrefno String	<pre>{   "registrationId": 43163,   "payamount": "150",   "redeemamount": "0",   "unitprice": "150",   "totalprice": "150",   "paymentrefno": "20210715150209132" }</pre> <p>Note: The registrationId is get from event api No.9</p> <p><b>Paymentrefno</b> is enetsrefno</p> <p><b>Payamount</b> = totalprice - redeemamount</p> <p><b>Totalprice</b> = unitprice * totalsession * totalprice</p>
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful response)	<pre>{   "result": "Success",   "result_code": "0000" }</pre>	

		}
	200 (Add Fail)	{ "msg": "Couldn't not find this registration record", "result_code": "1000" }
	200 (Not allow Multiple register)	{ "msg": "Total price, RedeemAmount, PaymentAmount, unit price not match", "result_code": "1000" }
	200 (server error)	{ "result_code": "1003", "msg": "Server Error" }
	200 (Database Error)	{ "result_code": "1004", "msg": "Database Error" }
	401 (Unauthorized request)	{ "error_code": "000", "msg": "Access Denied" }
	400 (Bad Request)	{ "error_code": "001", "msg": "Access Denied" }
	400 (Parameter type not match)	{ "error_code": "002", "error": "Bad Request - Parameter type not match" }
	400 (Parameter missing)	{ "error_code": "003", "msg": "Baf Request - Parameter Missing" }

## 11. Get Booking By MemberID And Date Range API

### 11.1 Overview

This API is to get booking list by memberid and date range.

### 11.2 Specification

<b>HTTP Request</b>	https://{domain_name}/v1/getbookingbymemberidanddaterange		
<b>Header Parameters</b>	<b>Key</b>	<b>Value</b>	
	Authorization	string (Bearer {access_token})	
	Content-Type	string (application/json)	
<b>Request Body</b>	<b>Key</b>	<b>Value</b>	<b>Example</b>
	memberId	String	CE1188E9-956C-E311-9401-XXXXX XXXXXXX
	startDate	String	dd-MM-yyyy Cant be empty
	endDate	String	dd-MM-yyyy Cant be empty
<b>Response</b>	<b>Status</b>	<b>Sample Response</b>	
	200 (Successful	{	

response)	<pre> "result_code": "0000", "result": [   {     "registrationId": "47728",     "name": "ASD",     "membershipTypeName": "SAFRA Membership",     "category": "-",     "membershipDob1": "Nov 12, 1991 12:00:00 AM",     "email": "leo.nam@techstudio.com.sg",     "mobile": "93214654",     "totalPax": 1,     "totalSession": 0,     "status": "Success",     "eventName": "test",     "invoiceNumber": "HTEV00021434",     "merchantRefNo": "20210923163210226"   } ] } </pre>
200 (server error)	<pre> {   "result_code" : "1003",   "msg" : "Server Error" } </pre>
200 (Database Error)	<pre> {   "result_code" : "1004",   "msg" : "Database Error" } </pre>
401 (Unauthorized request)	<pre> {   "error_code": "000",   "msg": "Access Denied" } </pre>
400 (Bad Request)	<pre> {   "error_code": "001",   "msg": "Access Denied" } </pre>
400 (Parameter type not match)	<pre> {   "error_code": "002",   "error": "Bad Request - Parameter type not match" } </pre>
400 (Parameter missing)	<pre> {   "error_code" : "003",   "msg" : "Baf Request - Parameter Missing" } </pre>

		}
--	--	---