

# Project: Image Classification and Regression

## MVA - CentraleSupélec

Vincent Lepetit

- The goal of this project is to learn how to implement simple image classification and regression in Keras.
- You can refer to the introductory slides on Keras:  
[https://www.labri.fr/perso/vlepetit/teaching/deep\\_learning\\_mva/keras\\_intro.pdf](https://www.labri.fr/perso/vlepetit/teaching/deep_learning_mva/keras_intro.pdf)  
and of course the online documentation on Keras <https://keras.io/>.

### 1 Sending your Answers

1. Create an account on GitHub or equivalent if you don't have one;
2. Use jupyter to do the assignment. You should also add plain text to explain your solution. Put the jupyter file on your github account;
3. Send the link to your jupyter file on your github account by email to `vincent.lepetit@u-bordeaux.fr` with MVA-MP1, MVA-MP2, or MVA-MP3 and your last name and first name in the email subject. Example:

Subject: MVA-MP1 Doe, John  
Body: link\_to\_your\_jupyter\_file.ipynb

No exception! No .py, no .zip, no .pdf

4. No acknowledgment for receiving the email, sorry.

### 2 Getting Started

Download the code provided at

[https://www.labri.fr/perso/vlepetit/teaching/deep\\_learning\\_mva/mp1.py](https://www.labri.fr/perso/vlepetit/teaching/deep_learning_mva/mp1.py)

Take some time to read it and understand it.

### 3 Simple Classification

You can generate a training set of images of simple geometric shapes (rectangle, disk, triangle) centered in the images by calling the function:

```
[X_train, Y_train] = generate_dataset_classification(300, 20)
```

† Build and train a linear classifier in Keras to classify a image into one of the three possible categories (i.e. rectangle, disk, triangle). Try using the stochastic gradient descent optimizer, then the Adam optimizer.

Hints: You will have to use the following functions: `Sequential`, `add`, `Dense` (do not forget the activation), `compile`, `fit`, `np_utils.to_categorical`. For the Adam optimizer, I used a batch size of 32. You should use a small number of epochs when debugging to see if the optimization seems to converge correctly.

You can check your classifier using the following code (for example):

```
X_test = generate_a_disk()
X_test = X_test.reshape(1, X_test.shape[0])
model.predict(X_test)
```

## 4 Visualization of the Solution

We would like to visualize the weights of the linear classifier. Check the output of the function `model.get_weights()`: The first part corresponds to the matrix of the classifier. Its columns have the same size as the input images, because Keras uses vector-matrix multiplications instead of matrix-vector multiplications.

† Visualize the 3 columns as images.

Hint: Only two (short) lines of code are required to visualize one column.

## 5 A More Difficult Classification Problem

Now, the shapes are allowed to move within the images and change dimensions. You can generate the new training set with:

```
[X_train, Y_train] = generate_dataset_classification(300, 20, True)
```

Retrain your linear classifier on this new training set. Add the `metrics=['accuracy']` parameter when calling the `compile` function to get the classification error in addition to the loss value.

You can generate a test set by calling:

```
[X_test, Y_test] = generate_test_set_classification()
```

and evaluate your classifier on this test set by calling:

```
model.evaluate(X_test, Y_test)
```

† Train a convolutional (not-to-)deep network on this new dataset. What is the value of the loss function on this test set when using your deep network?

Hints: You can limit yourself to 1 convolutional layer with 16  $5\times 5$  filters, 1 pooling layer, and one fully connected layer, but you are free to use any other architecture. You are allowed to increase the number of training samples if you want to.

## 6 A Regression Problem

The task now is to predict the image locations of the vertices of a triangle, given an image of this triangle. You can generate a training set by calling:

```
[X_train, Y_train] = generate_dataset_regression(300, 20)
```

You can visualize a training sample (or a prediction) by calling the `visualize_prediction` function:

```
visualize_prediction(X_train[0], Y_train[0])
```

† Build and train a regressor on this data. Evaluate your solution on the test set generated by

```
[X_test, Y_test] = generate_test_set_regression()
```

Hint: You may have to normalize somehow the vertices in `Y_train` and `Y_test` before training and testing...

## 7 Image Denoising

Implement a hourglass network for denoising: Modifying the `generate_a_*` functions to generate pairs of images, where one image has noise with random amplitude, and the second image has the same content but without the noise. Train your network to predict a noise-free image given a noisy image as input.