## **Homework jQuery**

#### Get value text

## > In the file (html)

```
<!DOCTYPE html>
<html lang="en">
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
 <meta http-equiv="X-UA-Compatible" content="ie=edge">
 <title>Document</title>
<link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css"</pre>
 integrity="sha384-gg0yR0iXCbMQv3Xipma34MD+dH/1fQ784/j6cY/iJTQU0hcWr7x9JvoRxT2MZw1T"
crossorigin="anonymous">
 <div class="container mt-5">
   <div class="row">
     <div class="col-4"></div>
     <div class="col-4">
       <div class="card">
         <form class="form-group">
           <input type="text" class="form-control" id="text" placeholder="text....">
         <div class="alert alert-success"></div>
      <div class="col-4"></div>
<script src="js/jquery-3.4.1.min.js"></script>
<script src="js/practice.js"></script>
```

## > In the file (js)

```
> $(document).ready(function () {
> $('#text').on('keyup', function () {
> let text = $('#text').val();
> $('.alert-success').html(text);
> });
> });
```

# Get value password

## > In the file (html)

```
> <!DOCTYPE html>
> <html lang="en">
> <head>
> <meta charset="UTF-8">
> <meta name="viewport" content="width=device-width, initial-scale=1.0">
> <meta http-equiv="X-UA-Compatible" content="ie=edge">
> <title>Document</title>
> < rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css"</pre>
```

# ➤ In the file (Js)

```
$ $(document).ready(function () {

> $('#password').on('keyup', function () {

> let password = $('#password').val();

> $('.alert-info').html(password);

> });

> });
```

#### Get value Email

# > In the file (html)

## > In the file (Js)

```
> $(document).ready(function () {
> $('#email').on('keyup', function () {
> let password = $('#email').val();
> $('.alert-dark').html(password);
> });
> });
```

#### Get value radio

# ➤ In the file (html)

```
<!DOCTYPE html>
<html lang="en">
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<meta http-equiv="X-UA-Compatible" content="ie=edge">
<title>Document</title>
<link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css"</pre>
 integrity="sha384-gg0yR0iXCbMQv3Xipma34MD+dH/1fQ784/j6cY/iJTQU0hcWr7x9JvoRxT2MZw1T"
crossorigin="anonymous">
 <div class="container mt-5">
    <div class="row">
     <div class="col-4"></div>
     <div class="col-4">
       <div class="card">
         <form class="form-group">
                <input type="radio" name="gender" class="form-check-input gender" value="Female">Female
            <div class="form-check-inline">
                <input type="radio" name="gender" class="form-check-input gender" value="Male">Male
          <div class="alert alert-danger"></div>
      <div class="col-4"></div>
 <script src="js/jquery-3.4.1.min.js"></script>
 <script src="js/practice.js"></script>
```

## > In the file (Js)

```
> $(document).ready(function () {
> $('.gender').on('click', function () {
> let gender = $('.gender:checked').val();
> $('.alert-danger').html(gender);
```

```
>  });
> });
```

#### Get value checkbox

# > In the file (html)

```
<!DOCTYPE html>
<html lang="en">
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<meta http-equiv="X-UA-Compatible" content="ie=edge">
 <title>Document</title>
<link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css"</pre>
  integrity="sha384-gg0yR0iXCbMQv3Xipma34MD+dH/1fQ784/j6cY/iJTQU0hcWr7x9JvoRxT2MZw1T"
crossorigin="anonymous">
  <div class="container mt-5">
    <div class="row">
      <div class="col-4"></div>
      <div class="col-4">
        <div class="card">
          <form class="form-group">
            <div class="form-check-inline">
              <label class="form-check-inline">
                <input type="checkbox" class="form-check-input fruit" value="Apple">Apple
            <div class="form-check-inline">
              <label class="form-check-inline">
                <input type="checkbox" class="form-check-input fruit" value="Mengo">Mengo
      <div class="col-4"></div>
 <script src="js/jquery-3.4.1.min.js"></script>
 <script src="js/practice.js"></script>
```

## > In the file (Js)

```
> $(document).ready(function () {
> $('.fruit').on('click', function () {
> let fruit = "";
> $('.fruit:checked').each(function () {
> fruit += $(this).val() + "<br>";
> });
> $('.alert-primary').html(fruit);
> });
> });
```

### Get value select

➤ In the file (html)

```
> <!DOCTYPE html>
```

```
<html lang="en">
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<meta http-equiv="X-UA-Compatible" content="ie=edge">
<title>Document</title>
<link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css"</pre>
 integrity="sha384-gg0yR0iXCbM0v3Xipma34MD+dH/1f0784/j6cY/iJTQU0hcWr7x9JvoRxT2MZw1T"
crossorigin="anonymous">
 <div class="container mt-5">
   <div class="row">
     <div class="col-4"></div>
     <div class="col-4">
       <div class="card">
         <form class="form-group">
           <div class="form-group">
             <select class="form-control" id="select">
               <option value="desable selected">To select</option>
               <option value="jQuery">jQuery</option>
               <option value="Java programming">Java programming</option>
               <option value="Flutter">Flutter</option>
         <div class="alert alert-info"></div>
     <div class="col-4"></div>
 <script src="js/jquery-3.4.1.min.js"></script>
 <script src="js/practice.js"></script>
```

# In the file (Js)

```
$ $(document).ready(function () {

> $('#select').on('click', function () {

> let select = $('#select').val();

> $('.alert-info').html(select);

> })

> });
```

# **Thank You Teacher**