

FlakeAutoFind

Charles Yang

Last updates: October 24, 2020

Contents

1	Flattening	1
----------	-------------------	----------

1 Flattening

The symmetry of the background is assumed to that of an ellipse. Similar to a circle, where the radius is defined

$$s^2 = (x - x_c)^2 + (y - y_c)^2$$

we define a distance coordinate

$$s^2 = (x - x_c)^2 + r^2(y - y_c)^2$$

where r is the aspect ratio of the ellipse, given

$$r = \frac{\text{width}}{\text{height}}$$

In this way, we consider the background to be a function of the elliptical distance. To maintain smoothness, the background is modeled as the sum of even terms:

$$B_N(s) = \sum_{n=0}^N a_n s^{2n}$$

Clearly, the first n coefficients can be solved for using a system of linear equations generated by n samples of the background.

For simplicity, we consider only the lowest two orders,

$$B_2(s) = a_0 + a_1 s^2$$

Taking two samples,

$$B_2(s_1) = a_0 + a_1 s_1^2$$

$$B_2(s_2) = a_0 + a_1 s_2^2$$

$$B_2(s_2) - B_2(s_1) = a_1(s_2^2 - s_1^2)$$

$$a_1 = \frac{B_2(s_2) - B_2(s_1)}{s_2^2 - s_1^2}$$

$$a_0 = B_2(s_1) - a_1 s_1^2 = B_2(s_2) - a_1 s_2^2$$